

Rigid PVC Pressure Pipes and Fittings

IS:4985-2000



CML/1235335

... The most comprehensive range with a wide spectrum of fittings



The Supreme Industries Ltd., is an acknowledged leader of India's plastic industry. It is credited with pioneering several path-breaking products and has been a torch bearer in the transition from conventional to advanced plastic piping products in the country. Its customer-centric approach fuels its research for designing unmatched quality products to meet the aspirations of its quality conscious customers. The innovative product portfolio offered by Supreme is extensive in range and application and comprises variety of pipes and vast spectrum of fittings totaling over 8500 diverse products.

Supreme uPVC pressure piping system with a wide spectrum of pipes and fittings in different sizes and pressure classes is an ideal solution for water supply and irrigation. Supreme pressure piping system has become the prime choice of farmers, water supply bodies and different government institutions who have successfully replaced the conventional piping with our products.

Unique Features

- Odorless and hygienic
- High corrosion and chemical resistance
- Smooth bore
- Self extinguishing quality
- Maintenance free
- Long lasting
- Economical

The system

Supreme offers an exhaustive range of uPVC pressure pipes and fittings. Pressure pipes are manufactured as per IS:4985-2000 standards and are available in 20 to 450mm sizes in different pressure classes. Pipes with both types of joints, i.e., solvent cement type and rubber seal type are available. Varieties of moulded fittings and wide range of handmade fittings are also available. Moulded fittings are manufactured as per IS:7834 and fabricated fittings are manufactured as per IS:10124 and company standards. These pipes and fittings are used for a variety of applications like, in irrigation, water supply, industrial process lines, swimming pools, firefighting mains, etc. These pipes are superior to CI, DI or RCC pipes in terms of being light in weight, easier and quicker installation, excellent corrosion and chemical resistance properties, high flow rates, long life and economy. These pipes have the approval of MJP.

Features and benefits

Odorless and hygienic - These pipes are an excellent choice for carrying potable water as they do not allow contamination.

High corrosion resistance - Being immune to chemical, electrolytic and galvanic action, these pipes are free from corrosion which ensures a much longer and useful life.

High chemical resistance - Pipes offer excellent resistance to acids, oxidizing agents, alkalis, oils and domestic effluents.

Smooth bore - Pipes have a mirror smooth inner surface and hence better flow characteristics in comparison to AC, CI and GI pipes.

Self extinguishing quality - This feature eliminates the need for fire resistant coatings.

Maintenance free - Corrosion resistant property of the PVC pipes eliminates the need for repeated painting or coating like in the case of GI pipes.

Long lasting - As these pipes are free from weaknesses caused by scale formation, rusting, weathering and chemical action, they have a much longer effective life.

Economical - Despite being superior to conventional pipes, Supreme PVC pipes are very light in weight and last much longer than older piping systems offering a great economy in handling, transportation, installation and replacement.

Salient features

- General dimensions conform to IS:7834-87.
- Wall thickness is designed to meet required working pressure.
- Close to dimensional tolerance.
- Different working pressure ratings upto 16 kgf/cm² for different sizes

Properties

- Hazen Williams constant : 150 (remains constant)
- Specific gravity : 1.41 -1.46
- Coefficient of linear expansion : 5.4×10^{-5} mm/m/°C
- Combined flexural and compressive strength : 600 - 650 kgf/cm²
- Impact strength at 20°C : 3 Kgf/cm²
- Modulus of elasticity : $3 - 3.8 \times 10^4$ Kgf/cm²
- Vicat softening point : 80°C
- Electrical resistance : 10^{14} ohm-cm

Dimensions of uPVC Pressure Pipes as per IS:4985-2000

Nominal Outside Diameter (mm)	Tolerance on Outside Diameter	Wall Thickness (mm)													
		Class 1 (PN) 2.5 kgf/cm ²		Class 2 (PN) 4 kgf/cm ²		Class 3 (PN) 6 kgf/cm ²		Class 4 (PN) 8 kgf/cm ²		Class 5 (PN) 10 kgf/cm ²		Class 6 (PN) 12.5 kgf/cm ²		Plumbing Pipes	
		Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max
20	+ 0.3	-	-	-	-	-	-	-	-	1.1	1.5	1.4	1.8	2.8	3.3
25	+ 0.3	-	-	-	-	-	-	1.2	1.6	1.4	1.8	1.7	2.1	2.9	3.4
32	+ 0.3	-	-	-	-	-	-	1.5	1.9	1.8	2.2	2.2	2.7	3.4	3.9
40	+ 0.3	-	-	-	-	1.4	1.8	1.8	2.2	2.2	2.7	2.8	3.3	3.6	4.2
50	+ 0.3	-	-	-	-	1.7	2.1	2.3	2.8	2.8	3.3	3.4	4.0	3.7	4.3
63	+ 0.3	-	-	1.5	1.9	2.2	2.7	2.8	3.3	3.5	4.1	4.3	5.0		
75	+ 0.3	-	-	1.8	2.2	2.6	3.1	3.4	4.0	4.2	4.9	5.1	5.9		
90	+ 0.3	1.3	1.7	2.1	2.6	3.1	3.7	4.0	4.6	5.0	5.7	6.1	7.1		
110	+ 0.4	1.6	2.0	2.5	3.0	3.7	4.3	4.9	5.6	6.1	7.1	7.5	8.7		
125	+ 0.4	-	-	2.9	3.4	4.3	5.0	-	-	-	-	-	-		
140	+ 0.5	2.0	2.4	3.2	3.8	4.8	5.5	6.3	7.3	7.7	8.9	9.5	11.0		
160	+ 0.5	2.3	2.8	3.7	4.3	5.4	6.2	7.2	8.3	8.8	10.2	10.9	12.6		
180	+ 0.6	2.6	3.1	4.2	4.9	6.1	7.1	8.0	9.2	9.9	11.4	12.2	14.1		
200	+ 0.6	2.9	3.4	4.6	5.3	6.8	7.9	8.9	10.3	11.0	12.7	13.6	15.7		
225	+ 0.7	3.3	3.9	5.2	6.0	7.6	8.8	10.0	11.5	12.4	14.3	15.3	17.6		
250	+ 0.8	3.6	4.2	5.7	6.5	8.5	9.8	11.2	12.9	13.8	15.9	17.0	19.6		
280	+ 0.9	4.1	4.8	6.4	7.4	9.5	11.0	12.5	14.4	15.4	17.8	-	-		
315	+ 1.0	4.6	5.3	7.2	8.3	10.7	12.4	14.0	16.1	17.3	19.9	-	-		
355	+ 1.1	5.1	5.9	8.1	9.4	12.0	13.8	15.8	18.2	-	-	-	-		
400	+ 1.2	5.8	6.7	9.1	10.5	13.5	15.6	-	-	-	-	-	-		
450	+ 1.4	6.5	7.5	10.3	11.9	15.2	17.5	-	-	-	-	-	-		

Note: 1) Pipes are offered in Light Grey (LG) and/or Dark Grey (DG) colours in standard lengths of 6m. Pipes are offered plain or socketed, based on diameter and class of pipe. 2) Ringtight pipes with integral rubber ring socket (Elastomeric joint) are available from 63mm to 315mm in 4, 6 and 10 kgf/cm² pressure class. 3) Prefix "PN" indicates Nominal Pressure, i.e., working pressure.

	Size in mm	Available Pressure Rating in kgf/cm ² (PN)
	20	10, 16
	25	10, 16
	32	10, 16
	40	6, 10, 16
	50	3, 6, 10, 16
	63	1, 6, 10, 16
	75	1, 6, 10, 16
	90	1, 6, 10, 16
	110	1, 6, 10, 16
	140	3, 6
	160	6, 10
	200	6
	250	6

Coupler

Application/Special note: These are used for joining of two uPVC pipes. Fabricated couplers are also available in 20 to 400mm sizes in different pressure class.

	Size in mm	Available Pressure Rating in kgf/cm ² (PN)
	20	3, 10, 16
	25	3, 10, 12.5, 16
	32	3, 10, 16
	40	3, 6, 10, 16
	50	3, 4, 6, 10, 16
	63	1, 2, 3, 4, 6, 10, 16
	75	1, 2, 3, 4, 6, 10, 16
	90	1, 2, 3, 4, 6, 10, 16
	110	1, 2, 3, 4, 6, 10, 16
	140	4, 6
	160	3, 4, 6, 10
	180	6
	200	4, 6
	250	6
	315	4

Elbow 90°

Application/Special note: These are used for short turns of 90°. These are not advisable on large pipeline involving high pressure.

	Size in mm	Available Pressure Rating in kgf/cm ² (PN)
	20	16
	25	16
	32	16
	40	6, 16
	50	6, 16
	63	6, 16
	75	6, 16
	90	6, 16
	110	4, 6, 16
	140	4
	160	4, 6
200	4, 6	
250	6	

Elbow 45°

	Size in mm	Available Pressure Rating in kgf/cm ² (PN)
	32 x 25	10
	75 x 63	6
	90 x 50	6
	90 x 63	6
	90 x 75	6
	110 x 63	6
	110 x 75	6
110 x 90	6	

Reducing Elbow

	Size in mm	Available Pressure Rating in kgf/cm ² (PN)
	20 x 15	10
	25 x 15	10
	25 x 20	10
	50 x 40	16
	63 x 50	6, 16
	75 x 50	6
	75 x 65	6
	90 x 80	6
	110 x 100	6

Elbow 90°
One side threaded

Application/Special note: These are used for short turns of 90°. These are not advisable on large pipe lines.

	Size in mm	Available Pressure Rating in kgf/cm ² (PN)
	75	10
	90	10

Elbow 90°
Both side Threaded

	Size in mm	Available Pressure Rating in kgf/cm ² (PN)
	20 x 15	10
	25 x 15	10
	25 x 20	10
	63 x 50	6
	75 x 65	6
	90 x 80	6
	110 x 50	6
	110 x 65	6
	110 x 80	6
	110 x 100	6

One Side Threaded Tee

	Size in mm	Available Pressure Rating in kgf/cm ² (PN)
	20	3, 10, 16
	25	3, 10, 16
	32	3, 10, 16
	40	3, 6, 10, 16
	50	3, 4, 6, 10, 16
	63	1, 2, 3, 4, 6, 10, 16
	75	1, 2, 3, 4, 6, 10, 16
	90	1, 2, 3, 4, 6, 10, 16
	110	1, 2, 3, 4, 6, 10, 16
	140	4, 6
	160	3, 4, 6, 10
	180	6
	200	4, 6
	250	6
	315	4

Equal Tee

Application/Special note: These are used for bypass and taking equal size service line out of main line at 90°.

	Size in mm	Available Pressure Rating in kgf/cm ² (PN)
	25 x 20	10
	32 x 20	10
	32 x 25	10
	40 x 20	6
	40 x 25	10
	50 x 25	10
	50 x 32	6
	63 x 25	10
	63 x 32	10
	63 x 40	6
	63 x 50	6, 10
	75 x 40	6
	75 x 50	6
	75 x 63	4, 6
	90 x 63	4, 6
	90 x 75	4, 6
	110 x 50	6
	110 x 63	6
	110 x 75	4, 6
	110 x 90	4, 6
140 x 110	6	
160 x 75	4	
160 x 110	4, 6	
200 x 110	6	
200 x 160	6	

Reducing Tee

Application/Special note: These are used for by pass and taking lower diameter service line out of main line.

Note : 1) Fittings are offered in Light Grey (LG) and Dark Grey (DG) colours. All the fittings shown in dark grey colour are in 16kgf/cm² (PN) pressure class. 2) Prefix "PN" indicates nominal Pressure, i.e., working pressure. 3) * Marked fittings will be shortly introduced.

 <p>Enlarging Tee</p>	<table border="1"> <thead> <tr> <th>Size in mm</th> <th>Available Pressure Rating in kgf/cm² (PN)</th> </tr> </thead> <tbody> <tr> <td>63 x 75</td> <td>6</td> </tr> </tbody> </table> <p>Application/Special note: These are used for by pass and taking higher diameter service line out of main line.</p>	Size in mm	Available Pressure Rating in kgf/cm ² (PN)	63 x 75	6	<table border="1"> <thead> <tr> <th>Size in mm</th> <th>Available Pressure Rating in kgf/cm² (PN)</th> </tr> </thead> <tbody> <tr><td>25 x 15</td><td>10, 16</td></tr> <tr><td>32 x 15</td><td>10, 16</td></tr> <tr><td>32 x 20</td><td>10</td></tr> <tr><td>40 x 25</td><td>6</td></tr> <tr><td>50 x 32</td><td>6</td></tr> <tr><td>63 x 40</td><td>6</td></tr> <tr><td>75 x 50</td><td>6</td></tr> <tr><td>90 x 50</td><td>6</td></tr> <tr><td>90 x 65</td><td>6</td></tr> <tr><td>110 x 50</td><td>6</td></tr> <tr><td>110 x 80</td><td>6</td></tr> </tbody> </table> <p>Application/Special note: These are used to connect a uPVC pipeline directly to a metal pipe of over diameter or vice-versa.</p>	Size in mm	Available Pressure Rating in kgf/cm ² (PN)	25 x 15	10, 16	32 x 15	10, 16	32 x 20	10	40 x 25	6	50 x 32	6	63 x 40	6	75 x 50	6	90 x 50	6	90 x 65	6	110 x 50	6	110 x 80	6	 <p>Reducing Female Threaded Adaptor (R.F.T.A.)</p>																																												
Size in mm	Available Pressure Rating in kgf/cm ² (PN)																																																																										
63 x 75	6																																																																										
Size in mm	Available Pressure Rating in kgf/cm ² (PN)																																																																										
25 x 15	10, 16																																																																										
32 x 15	10, 16																																																																										
32 x 20	10																																																																										
40 x 25	6																																																																										
50 x 32	6																																																																										
63 x 40	6																																																																										
75 x 50	6																																																																										
90 x 50	6																																																																										
90 x 65	6																																																																										
110 x 50	6																																																																										
110 x 80	6																																																																										
 <p>Cross Tee</p>	<table border="1"> <tbody> <tr><td>63</td><td>6</td></tr> <tr><td>75</td><td>6</td></tr> <tr><td>90</td><td>6</td></tr> <tr><td>110</td><td>6</td></tr> </tbody> </table> <p>Application/Special note: These are used for by pass and taking equal size service line on both side of main line.</p>	63	6	75	6	90	6	110	6	<table border="1"> <tbody> <tr><td>25 x 20</td><td>10</td></tr> <tr><td>32 x 20</td><td>10</td></tr> <tr><td>32 x 25</td><td>10, 16</td></tr> <tr><td>40 x 25</td><td>6</td></tr> <tr><td>40 x 32</td><td>6, 16</td></tr> <tr><td>50 x 25</td><td>6</td></tr> <tr><td>50 x 32</td><td>6</td></tr> <tr><td>50 x 40</td><td>6, 16</td></tr> <tr><td>63 x 32</td><td>6</td></tr> <tr><td>63 x 40</td><td>6</td></tr> <tr><td>63 x 50</td><td>6, 16</td></tr> <tr><td>75 x 40</td><td>6</td></tr> <tr><td>75 x 50</td><td>6</td></tr> <tr><td>75 x 63</td><td>6</td></tr> <tr><td>90 x 50</td><td>6</td></tr> <tr><td>90 x 63</td><td>6</td></tr> <tr><td>90 x 75</td><td>6</td></tr> <tr><td>110 x 50</td><td>6</td></tr> <tr><td>110 x 63</td><td>6</td></tr> <tr><td>110 x 75</td><td>6</td></tr> <tr><td>110 x 90</td><td>6</td></tr> <tr><td>140 x 75</td><td>4</td></tr> <tr><td>140 x 90</td><td>4</td></tr> <tr><td>140 x 110</td><td>4, 6</td></tr> <tr><td>160 x 90</td><td>4</td></tr> <tr><td>160 x 110</td><td>4, 6</td></tr> <tr><td>160 x 140</td><td>4</td></tr> <tr><td>180 x 110</td><td>6</td></tr> <tr><td>200 x 110</td><td>4, 6</td></tr> <tr><td>200 x 160</td><td>4, 6</td></tr> <tr><td>200 x 180</td><td>6</td></tr> <tr><td>250 x 200</td><td>6</td></tr> </tbody> </table> <p>Application/Special note: These are used to convert the service line into small or extra small lines.</p>	25 x 20	10	32 x 20	10	32 x 25	10, 16	40 x 25	6	40 x 32	6, 16	50 x 25	6	50 x 32	6	50 x 40	6, 16	63 x 32	6	63 x 40	6	63 x 50	6, 16	75 x 40	6	75 x 50	6	75 x 63	6	90 x 50	6	90 x 63	6	90 x 75	6	110 x 50	6	110 x 63	6	110 x 75	6	110 x 90	6	140 x 75	4	140 x 90	4	140 x 110	4, 6	160 x 90	4	160 x 110	4, 6	160 x 140	4	180 x 110	6	200 x 110	4, 6	200 x 160	4, 6	200 x 180	6	250 x 200	6	 <p>Reducer</p>
63	6																																																																										
75	6																																																																										
90	6																																																																										
110	6																																																																										
25 x 20	10																																																																										
32 x 20	10																																																																										
32 x 25	10, 16																																																																										
40 x 25	6																																																																										
40 x 32	6, 16																																																																										
50 x 25	6																																																																										
50 x 32	6																																																																										
50 x 40	6, 16																																																																										
63 x 32	6																																																																										
63 x 40	6																																																																										
63 x 50	6, 16																																																																										
75 x 40	6																																																																										
75 x 50	6																																																																										
75 x 63	6																																																																										
90 x 50	6																																																																										
90 x 63	6																																																																										
90 x 75	6																																																																										
110 x 50	6																																																																										
110 x 63	6																																																																										
110 x 75	6																																																																										
110 x 90	6																																																																										
140 x 75	4																																																																										
140 x 90	4																																																																										
140 x 110	4, 6																																																																										
160 x 90	4																																																																										
160 x 110	4, 6																																																																										
160 x 140	4																																																																										
180 x 110	6																																																																										
200 x 110	4, 6																																																																										
200 x 160	4, 6																																																																										
200 x 180	6																																																																										
250 x 200	6																																																																										
 <p>Reducing Cross Tee</p>	<table border="1"> <tbody> <tr><td>40x20</td><td>6</td></tr> <tr><td>63x20</td><td>4</td></tr> <tr><td>63x25</td><td>4</td></tr> <tr><td>63x32</td><td>4</td></tr> <tr><td>63x40</td><td>6</td></tr> <tr><td>75x25</td><td>4</td></tr> </tbody> </table>	40x20	6	63x20	4	63x25	4	63x32	4	63x40	6	75x25	4	<table border="1"> <tbody> <tr><td>25 x 20</td><td>10</td></tr> <tr><td>32 x 20</td><td>10, 16</td></tr> <tr><td>32 x 25</td><td>10, 16</td></tr> <tr><td>40 x 25</td><td>16</td></tr> <tr><td>40 x 32</td><td>6, 16</td></tr> <tr><td>50 x 25</td><td>16</td></tr> <tr><td>50 x 32</td><td>6</td></tr> <tr><td>50 x 40</td><td>6, 16</td></tr> <tr><td>63 x 32</td><td>16</td></tr> <tr><td>63 x 40</td><td>6</td></tr> <tr><td>63 x 50</td><td>6, 16</td></tr> <tr><td>75 x 40</td><td>6</td></tr> <tr><td>75 x 50</td><td>6, 16</td></tr> <tr><td>75 x 63</td><td>6, 16</td></tr> <tr><td>90 x 50</td><td>6</td></tr> <tr><td>90 x 63</td><td>6</td></tr> <tr><td>90 x 75</td><td>6, 16</td></tr> <tr><td>110 x 63</td><td>6</td></tr> </tbody> </table>	25 x 20	10	32 x 20	10, 16	32 x 25	10, 16	40 x 25	16	40 x 32	6, 16	50 x 25	16	50 x 32	6	50 x 40	6, 16	63 x 32	16	63 x 40	6	63 x 50	6, 16	75 x 40	6	75 x 50	6, 16	75 x 63	6, 16	90 x 50	6	90 x 63	6	90 x 75	6, 16	110 x 63	6	 <p>Reducing Bush</p>																								
40x20	6																																																																										
63x20	4																																																																										
63x25	4																																																																										
63x32	4																																																																										
63x40	6																																																																										
75x25	4																																																																										
25 x 20	10																																																																										
32 x 20	10, 16																																																																										
32 x 25	10, 16																																																																										
40 x 25	16																																																																										
40 x 32	6, 16																																																																										
50 x 25	16																																																																										
50 x 32	6																																																																										
50 x 40	6, 16																																																																										
63 x 32	16																																																																										
63 x 40	6																																																																										
63 x 50	6, 16																																																																										
75 x 40	6																																																																										
75 x 50	6, 16																																																																										
75 x 63	6, 16																																																																										
90 x 50	6																																																																										
90 x 63	6																																																																										
90 x 75	6, 16																																																																										
110 x 63	6																																																																										
 <p>Male Threaded Adaptor (M.T.A.)</p>	<table border="1"> <tbody> <tr><td>20</td><td>10, 16</td></tr> <tr><td>25</td><td>10, 16</td></tr> <tr><td>32</td><td>10, 16</td></tr> <tr><td>40</td><td>6, 16</td></tr> <tr><td>50</td><td>6, 16</td></tr> <tr><td>63</td><td>6, 10, 16</td></tr> <tr><td>75</td><td>6, 10, 16</td></tr> <tr><td>90</td><td>6, 10, 16</td></tr> <tr><td>110</td><td>6, 10, 16</td></tr> <tr><td>140</td><td>6</td></tr> <tr><td>160</td><td>6</td></tr> </tbody> </table> <p>Application/Special note: These are used to connect a uPVC pipeline directly to a female threaded metal pipe and all types of valves, taps, pumps etc. through a male portion.</p>	20	10, 16	25	10, 16	32	10, 16	40	6, 16	50	6, 16	63	6, 10, 16	75	6, 10, 16	90	6, 10, 16	110	6, 10, 16	140	6	160	6	<p>Application/Special note: These are used to convert the service line into small or extra small lines.</p>																																																			
20	10, 16																																																																										
25	10, 16																																																																										
32	10, 16																																																																										
40	6, 16																																																																										
50	6, 16																																																																										
63	6, 10, 16																																																																										
75	6, 10, 16																																																																										
90	6, 10, 16																																																																										
110	6, 10, 16																																																																										
140	6																																																																										
160	6																																																																										
 <p>Reducing Male Threaded Adaptor (R.M.T.A.)</p>	<table border="1"> <tbody> <tr><td>75 x 50</td><td>6</td></tr> <tr><td>90 x 50</td><td>6</td></tr> <tr><td>90 x 65</td><td>6</td></tr> </tbody> </table> <p>Application/Special note: These are used to connect a uPVC pipeline directly to a female threaded metal pipe.</p>	75 x 50	6	90 x 50	6	90 x 65	6																																																																				
75 x 50	6																																																																										
90 x 50	6																																																																										
90 x 65	6																																																																										
 <p>Female Threaded Adaptor (F.T.A.)</p>	<table border="1"> <tbody> <tr><td>20</td><td>3, 10, 16</td></tr> <tr><td>25</td><td>10, 16</td></tr> <tr><td>32</td><td>10, 16</td></tr> <tr><td>40</td><td>6, 16</td></tr> <tr><td>50</td><td>6, 16</td></tr> <tr><td>63</td><td>6, 10, 16</td></tr> <tr><td>75</td><td>6, 10, 16</td></tr> <tr><td>90</td><td>6, 10, 16</td></tr> <tr><td>110</td><td>6, 10, 16</td></tr> <tr><td>160</td><td>6</td></tr> </tbody> </table> <p>Application/Special note: These are used to connect a uPVC pipeline directly to a male threaded metal pipe.</p>	20	3, 10, 16	25	10, 16	32	10, 16	40	6, 16	50	6, 16	63	6, 10, 16	75	6, 10, 16	90	6, 10, 16	110	6, 10, 16	160	6																																																						
20	3, 10, 16																																																																										
25	10, 16																																																																										
32	10, 16																																																																										
40	6, 16																																																																										
50	6, 16																																																																										
63	6, 10, 16																																																																										
75	6, 10, 16																																																																										
90	6, 10, 16																																																																										
110	6, 10, 16																																																																										
160	6																																																																										

Note : 1) Fittings are offered in Light Grey (LG) and Dark Grey (DG) colours. All the fittings shown in dark grey colour are in 16kgf/cm² (PN) pressure class. 2) Prefix "PN" indicates nominal Pressure, i.e., working pressure.

 Reducing Bush	Size in mm	Available Pressure Rating in kgf/cm ² (PN)	 Service Saddle		
		110 x 75		6	
		110 x 90		6, 16	
		140 x 75		6	
		140 x 90		6	
		140 x 110		6	
		160 x 90		6	
		160 x 110		6	
		200 x 160		6	
		250 x 160		6	
	250 x 200	6			
Application/Special note: These are used along with Coupler, Elbow, Tee, MTA, FTA to convert service line or fitting to smaller line.					
 Threaded Reducing Bush		75 x 50	6	 End Cap (Plain)	
		90 x 65	6		
 Tail Piece		63	6, 16		
		75	6, 16		
		90	6, 16		
		110	6, 16		
		140	6		
		160	6, 16		
	200	6, 16			
Application/Special note: These are used for connecting an air release valve/water fill way valve (CI/MS etc.) and any other flanged fitting (like strainer) Non-return valve, pumps etc with the pipe.					
 Flange		63	6		
		75	6		
		90	6		
		110	6		
Application/Special note: These are used along with Tail piece for connecting an air release valve, Non-return valve, pumps and metal pipes etc with the pipe.					
 Flange Adapter		63	10		
		75	6		
		90	6		
		110	10		
		160	10		
Application/Special note: These are used for connecting an air release valve, Non-return valve, pumps and metal pipes etc with the pipe.					
 Blind Flange		63	10	 Single Y	
		75	10		
		90	10		
		110	10		
	Application/Special note: These are used for to close the end of pipeline for various application.				
	 Service Saddle		40 x 15		6
			50 x 15		6
			50 x 20		6
			50 x 25		6
			63 x 15		6
		63 x 20	6		
		63 x 25	6		
		75 x 15	6		
	75 x 20	6			
Application/Special note: These are used for tapping the large service main line into small feeder line for house hold purpose and for connecting air release valves.					
		20	10	 End Cap (Threaded)	
		25	10		
		32	10		
		40	6		
		50	6		
		63	4, 6		
		75	4, 6		
		90	4, 6		
		110	4, 6		
		140	4		
		160	6		
		180	4, 6		
		200	6		
		250	6		
		315	6		
Application/Special note: These are used to close the end of pipe line.					
		20 x 15	10	 End Cap (Threaded)	
		25 x 20	10		
		32 x 25	10		
		40 x 32	6		
		50 x 40	6		
		63 x 50	6		
		75 x 65	6		
		90 x 80	6		
		110 x 100	6		
		140 x 125	6		
Application/Special note: Threaded end cap with inside threads (BSP threads) are used to close the end of pipe line. Note: In case of threaded fittings avoid overtightening the joint with wrench as it may damage the uPVC threads.					
		63	6	 Reducing Y	
		75	6		
		90	6		
		110	6		
		140	6		
		160	6		
		200	6		
		250	4		
Application/Special note: These are used for by pass and taking equal size service line out of main line at 45°.					
		110 x 63	6		
		160 x 110	6		
		200 x 110	4		
		200 x 160	4		

Note : 1) Fittings are offered in Light Grey (LG) and Dark Grey (DG) colours. All the fittings shown in dark grey colour are in 16kgf/cm² (PN) pressure class. 2) Prefix "PN" indicates nominal Pressure, i.e., working pressure.

	Size in mm	Available Pressure Rating in kgf/cm ² (PN)
 Female Threaded Tee	25 x 15 32 x 15	10, 16 10
 Female Threaded Elbow	25 x 15 32 x 15	10, 16 10
 Female Threaded Joint	25 x 15 32 x 15	16 10
 Male Threaded Joint	25 x 15 25 x 20	10 16
 Ball Valve	20 25 32 40 50 63 75	10 10 10 6 6 6 6
 Ball Valve	25 32 40 50 63	16 16 16 16 16
 Ball Valve	75 90 110	10 10 10
 Threaded Ball Valve (Union Type)	25	16
 Non Return Valve (NRV)	63 75 90 110	16 10 10 10
 Non Return Valve (Female Threaded)	63 75 90 110	16 10 10 10

Size in mm	Available Pressure Rating in kgf/cm ² (PN)	
¾" 1" 1¼" 1½" 2"	10 10 10 10 10	 Air Release Valve
75 90 110 160	10 10 10 10	 Butterfly Valve
25 32 40 50 63	10 10 10 10 10	 Union
25 32 40 50 63 75 90	10 10 6 6 6 6 6	 Bend
63 75 90 110 140 160 180 200	6 6 6 6 6 6 6 6	 Leakage Coupler (F)
63 75 90 110 140 160 180 200 225 250 280 315	6, 10 4, 6, 10	 Repair Coupler Long (with elastomeric rubber seal)
63 75 90 110 140 160 180 200 225 250 280	10 10 10 10 10 10 10 10 10 10 10	 Repair Coupler (F)

Special note: All the leakage couplers are available in 6", 9" and 12" standard length.

Note: 63 to 160mm Repair Coupler Short (with elastomeric rubber seal) is also made available in 4 & 6 kgf/cm².

Note: 1) Fittings are offered in Light Grey (LG) and Dark Grey (DG) colours. All the fittings shown in dark grey colour are in 16kgf/cm² (PN) pressure class. 2) Prefix "PN" indicates nominal Pressure, i.e., working pressure. ● All the dimensions unless otherwise specified are in mm



Solvent Cement

Size	Box qty
50 ml	100
100 ml	50
250 ml	80
500 ml	50
1000 ml	24
5000 ml	4

Note: Recommended for smaller sizes and lower pressure class, upto 75mm size - any pressure class, upto 110mm size in 4 and 6 kgf/cm², upto 200mm size - 2.5 kgf/cm²



Solvent Cement Heavy Duty

100 ml	24
250 ml	24
500 ml	24
1000 ml	6
5000 ml	4

Note: Recommended for larger sizes and higher pressure class, 90mm and 110mm in 10 and 12.5 kgf/cm², 140mm and above sizes in 4,6,10 and 12.5 kgf/cm²



Solvent Cement Super Heavy Duty

100 ml	24
250 ml	24
500 ml	24
1000 ml	6
5000 ml	4

Size in mm
110-175x15
110-175x20
110-175x40
200-300x40
200-300x50
300-400x50



Strap Saddle

Handmade Fittings:

Besides a vast range of moulded fittings, an exhaustive range of handmade fitting is also available from Supreme. This range of products includes couplers, bends, short bends, tee's, reducing tee's, cross tee's, tail pieces, reducers, single or reducing Y's, end caps, leakage couplers etc. in 20 to 450mm sizes in different pressure classes.

Handmade division of the Company is equipped to make any tailor-made product as per customer requirements. This implies a complete system solution made of the same material eliminating the dependence of the customer on any other conventional product.

Handling Instructions: Pipes should be kept on an even surface while storing. They should be properly supported and should not be stacked for more than 1.5 m height for a long duration.

While laying big pipelines, provision should be made for expansion of joints, air venting and proper anchorage.

Pipes or fittings should not be cleaned with solvent cement. Quality of solvent cement plays an important role. It is, therefore, recommended that good quality solvent cement be used.

For large diameter and higher class pipes (6 Kgf/cm² and above), always use heavy duty solvent cement. Very old, hard, semi-fluid solvent cement should not be used.




Installation of Supreme pipeline in the field

Consumption of Solvent Cement

Diameter of pipe (mm)	20	25	32	40	50	63	75	90	110	140	160	180	200	225	250	280	315	355	400	450
Approx no of joints which can be made per litre of solvent cement	354	270	225	180	130	125	103	79	54	36	27	25	15	12	9	7	5	3	2	2


Jointing Instructions:



Cut the pipe as square as possible. Ensure that fitting of the pipe with socket of fitting is correct.


Total length of socket should be marked on pipe. In most cases, the pipe inserted should be up to the marked line and in no case should it be less than 2/3rd of pipe end.

The pipe and the socket should be clean and dry. Dust, oil, water, grease etc. should be wiped off with dry cloth or a cleaner from the surfaces to be coated with solvent cement






Roughen the outer surface of the pipe and the inner surface of the socket using sand paper or piece of hacksaw blade up to the entry mark. Stir solvent cement thoroughly.

Apply a thick coat of solvent cement using a flat clean brush evenly on the inner surface of the socket for full length of insertion and then on the outer surface of the pipe end up to the marked line.



After application of solvent cement, insert the pipe within one minute of application into the socket. Hold the joint for a few seconds and ensure that the pipe does not come out the fitting. Wipe off extra cement. Let it dry. Within 24 hours, your Supreme rigid PVC pipes are ready for use.

In case of big pipeline projects, it is recommended to refer to our installation guide.




Ringtight Rigid PVC Pipes with Sealing Rings

Ringtight advantages

These pipes are specially designed and suitable to overcome difficulties experienced while jointing higher diameter pipes using solvent cement and offer the following advantages:-


- As elastomeric sealing rings are used, requirements and precautions associated with quality and quantity of solvent cement are eliminated.
- Unlike solvent type joints, curing period is not required which allows the pipelines to be tested and brought in use immediately after jointing.
- Pipe laying and jointing is very easy, quicker and more reliable. Pipes up to 140mm size can be jointed by hand but large diameter pipes require a jack.
- Joints are stable, watertight and can resist loads from horizontal and vertical tractive forces.
- Joints can accommodate angular deflection up to 2° and axial displacement resulting from thermal expansion and contraction which eliminates the need of expansion joints as required in solvent type joints.
- Joints can be made in any climatic condition.



About Elastomeric sealing ring

Unique design of sealing ring supplied with the pipe is made from high quality EPDM rubber to meet the practical requirements of sites, which add to installation efficiency. This seal can be safely and easily fitted in wet, cold and muddy conditions. These sealing rings offer the following advantages:-

- Very low assembling force is required for joint.
- It has large operational life (minimum life is about 50 years).
- These rings give greater reliability and joint tightness and can withstand pressures beyond that of specified testing pressure of the pipes.
- Specially suitable for underground applications.
- It is resistant to salt water, organic vegetable oils, dilute acids and alkalis normally found in waste water. It is also resistant to ultra violet radiations, bacteria, fungus and termites. In short, Supreme ringtight pipes are designed to give long term satisfaction to the customers.



Jointing instructions

1. Clean the inside of the socket. Remove all traces of mud, dirt, grease, gravel and clean the elastomeric sealing ring.
2. Shape the ring into a heart shape by pinching a portion of ring from inside. Insert it into the socket and release to seat it into the groove.
3. Factory supplied pipes are provided with a 15° chamfer. Mark the insertion depth on spigot of pipe. Clean and apply lubricant to the pipe insertion depth before pushing it into the socket.
4. If pipe needs to be cut, it should be cut perpendicular to the axis of the pipe after which it should be chamfered properly.
5. Align the socket and spigot correctly in the horizontal and

- vertical planes. Before insertion, ensure that no sand or dirt adheres to the lubricated surface of the pipe. Care should be taken that the spigot end is inserted in the socket at the correct angle.
6. Push the spigot into the socket until it reaches the depth of entry mark. Do not over insert. This must be done manually. Use a steel crow bar, if necessary. Protect the pipe with a wooden block. Insertion of spigot end inside the socket should be at the correct angle.
7. In case of large diameter pipes, if the crow bar does not give sufficient leverage, use of a jointing jack may be helpful.



• Any specification may change without prior notice. • All information contained in this literature is given in good faith and believed to be accurate and reliable. Because of many factors which may be outside our knowledge or control and affect the use of the product, no warranty is given or implied with respect to such information, nor do we offer any warranty of immunity against patent infringement. No responsibility can be accepted for any error, omissions or incorrect assumptions.

The Supreme Industries Ltd. (Plastic Piping Division)

Corporate Office: 1161/1162, Solitair Corporate Park, Building No. 11,167, Guru Hargovindji Marg, Chakala, Andheri Ghatkopar Link Road, Andheri (East) Mumbai - 400 093. India. Tel: 91-22-3084 0000, 4043 0000

Regd. Office: 612 Raheja Chambers, Nariman Point, Mumbai 400 021. India. Tel.: (022) 2285 1656, 2282 0072

Export Division: Tel: (022) 4043 0125, 3084 0125

Overseas Office: Sharjah, UAE. Tel# +971 6 557 4484; Fax# +971 6 557 4485

CIN: L35920MH1942PLC003554

Branch Offices Tel.

- Ahmedabad** : 079-30028371
- Bangalore** : 080-30913715
- Chennai** : 044-39811182
- Cochin** : 0484-2385346
- Hyderabad** : 040-23221130
- Indore** : 0731-2432684
- Jaipur** : 09910995853
- Jalgaon Gadgegaon** : 0257-3050541,42
- Kanpur** : 0512-2332280
- Kolkata** : 033-66190000
- Noida (Delhi)** : 0120-6660000

Authorised Distributor



I & T SIL Gadgegaon, Dist-Jalgaon • PC/AG/MKG/01 • REV.18-01/2020