

TECHNICAL DATA SHEET

Anticorr Bitumen Primer:

Anticorr Bitumen Primer is Bituminous air curing ready mixed Acid & Alkali resistant special primer.

Application:

Concrete surface must be clean, dry and rough. No primer should be applied over smooth and wet surface.

After cleaning the concrete surface, one coat of Anticorr Bitumen Primer should be applied with brush and allow to dry thoroughly.

The drying time will depend upon the temperature.

Storage Life: 24 Month at the temperature 30°C ($\pm 2^{\circ}\text{C}$)

Packing: Anticorr Bitumen Primer: 25 Liter Drum

Export packing(As per customer's requirement)

Note:

Anticorr Bitumen Primer contains volatile and slightly toxic solvent. Keep away from spark and open flames at working area.

All recommendations for use of our products, whether given by us in writing, verbally, or to be implied from the results of tests carried out by us are based on the current state of our knowledge. Although the information contained in this sheet is accurate to the best of our knowledge, no liability can be accepted in respect of such information and no warranty or conditions are intended in respect of the product described as the conditions of application are beyond our control.

For Technical/Trade Inquiry

ZEOCHEM ANTICORR

Regd. Office: B/5, Rameshwar Flat, Dafnala Road, Shahibaug, Ahmedabad-380004, Gujarat, India

Admin Office: A-402/403, 4th Floor, Abhishek-I, Near Vishwavidhyalay School, Asarwa, Ahmedabad-380016, Gujarat, India

Contact : +91-7600 3535 01/02 E: zeochem@hotmail.com