



**AIR FLUSHING CONTINUOUS BAND SEALER**

<b>Model</b>	<b>Model PPCS 900AF (AIR FLUSHING)</b>
Voltage (V / Hz)	220 / 50
Power(W)	835
Heat Sealing Power (W)	40 x 2
Sealing Speed (m/min.)	0-12 (0-16)
Sealing Width (mm)	8 ~ 10
Temperature range (Deg.C)	0 ~ 300
Distance from the sealing center to the conveying table (mm)	10 ~ 40
Conveyor size (LxW) mm	930 x 153
Film Thickness (mm)	0.08
Single Conveyor Loading (Kg)	1
Overall conveyor Loading (Kg)	3
Overall Dimension (LxWxH) mm	1050 x 560 x 900
Net Weight (Kg)	62



**LIQUID POUCH PACKING MACHINE**

<b>Model</b>	<b>PPLP 1000</b>
Voltage (V/Hz)	220 / 50
Power (W)	1750
Product Capacity (bag/min)	1000
Packing Capacity (ml)	200-1000
Size of bag (mm) (LxW)	(L) 50-210 (W) 50-170
Dimension (LxWxH) (mm)	1050 x 850 x 1920
Weight (kg)	450

**HEAVY DUTY CONTINUOUS BAND SEALER**

<b>Model</b>	<b>Model PPCS 1100</b>
Voltage (V / Hz)	220 / 50
Power(Kw)	1.5
Heat Sealing Power (W)	300 x 4
Sealing Speed (m/min.)	0-10
Sealing Width (mm)	8 ~ 10
Temperature range (Deg.C)	0 ~ 300
Conveyor size (LxW) mm	1400 x 2500
Film Thickness (mm)	0.12 ~ 0.18
Single Conveyor Loading (Kg)	5
Overall conveyor Loading (Kg)	15
Overall Dimension (LxWxH) mm	1450 x 680 x 1480
Net Weight (Kg)	107



**BOX STRETCH WRAPPING MACHINE**

<b>Model</b>	<b>PPBW 600</b>
Max. Wrapping Size (LxWxH)(Max)(mm)	600x600x600
Wrapping Efficiency(loads/hour)	20~40
Turntable Speed (rpm/min)	3~20
Turntable Diameter (mm)	H : 600
Turntable Loading (max)(mm)	50
Electrical Requirement (V/Hz)	220/50
Power (kw)	Turntable : 0.75 Film, Carriage : 0.4, Steel Tower : 0.37
Film Carriage	Pre-Stretch Type
Control System	PLC
Top Plate Device	Pneumatic Type Top Plate
Machine Dimension (mm)	600x4170x1800
Weight (kg)	260 kg

