

ZYDEX 2400

PRODUCT ATTRIBUTES

- Ideal for finer counts and denser sorts
- Better penetration and providing strength to the yarn
- Provides high abrasion resistance
- Very high flexibility
- Minimum loss of elongation
- Compatible with starch and other binders
- Lesser effluent load because of lower dosage

TECHNICAL DATA

FORM	
Colour	Pale yellow transparent liquid
Solid content	25 ± 1.5 %
pH	6.5-7.5
Viscosity	5-50 CPs

APPLICATION

- It is recommended for cotton/ PC/ PV finer and denser sorts.
- Higher dosage with the increase of fineness and density of sorts.

APPLICATION GUIDELINES

- Take desired level of water and add starch with stirring.
- Add ZYDEX 2400 along with other ingredients and transfer to pressure cooker.
- Heat till the starch is completely cooked.
- Add softener to the above mixture and transfer to the sizing box.

COMPLIMENTARY PRODUCTS

- **SIZOL AQ:** Modified starch
- **ZYDEX 2300:** Acrylic based binder.
- **ZYDEX 2501:** Softener for spun yarn sizing.

STORAGE & SHELF LIFE

- Keep carboys of in cool shade. Do not store above 45 °C or under direct sun.
- Minimum shelf life is 12 months.

DISCLAIMER

The information & data contained herein are given in good faith but without warranty. We recommend that before using our products, the customer should make his/her own tests to determine the suitability of the products for his/her own purpose under his/her operating conditions. As the circumstances under which our products are stored, handled and used are beyond our control, we cannot assume any responsibility for their use by the customers.

ZYDEX HOUSE, 61, Gotri-Sevasi Road, Vadodara - 390 021. Gujarat. INDIA
Tel : +91 265 3312000 E-mail: info@zydexindustries.com Web: www.zydexindustries.com