


# SAC3000S

SAC3000S ALL-TERRAIN CRANE  
300 TONS LIFTING CAPACITY

Quality Changes the World



**SANY**


SANY Automobile Hoisting Machinery is one of the core business unit of Sany Heavy Industry, mainly engaged in the research and development of high end, mid to large tonnage crane series, including mobile crane, crawler crane, tower crane and loader crane. It has two industrial parks in Ningxiang and Huzhou, since entering the market, the products of Sany Automobile Hoisting Machinery have received worldwide recognition with advanced technology, lean manufacturing, high reliability and excellent service.



# SANY ALL-TERRAIN CRANE

## CONTENT

- 04 Icon
- 05 Selling points
- 06 Introduction
- 09 Dimension
- 10 Technical Parameter
- 11 Operation Condition
- 12 Load Chart
- 33 Wheel Crane Family Map



### Excellent and stable chassis performance

The use of innovative 6-axle chassis design with six driving modes and four braking modes can provide more reliable traveling performance. High stability and safety are guaranteed with tipping over early-warning technology.



### Ultra long Boom for Wide Working Radius

Fully-extended boom is 73m and luffing jib is 43m respectively, which ensures Max. lifting height of 112m with working radius of 86m. 0°~40° automatic infinite variable luffing jib is applied to ensure conveniently switching over between all operation with high efficiency.



### Highly efficient, energy-saving and unique hydraulic control technology

Self-developed dual-pump converging / diversion main valve is used. Converging flow of the single-action dual-pump ensures fast operation and high work efficiency, combined-action dual-pump diversion system is applied to ensure stable controllability. Electric proportional variable piston pump is used to ensure high-accurate flow control and higher efficiency and energy saving.



### Safe, stable, advanced, and intelligent electronic control technology

The adoption of internationally advanced distributed integration bus data communication network and configuration of the abundant sensing elements can achieve timely feedback of data information and monitor the overall working status in real-time. The human-computer interaction interface is used to fully meet customer's individual requirements.

## Superstructure

**Cab**

- It is made of safety glass and anti-corrosion steel plate with ergonomic design such as full-coverage soften interior, panoramic sunroof and adjustable seats etc., and humanized design providing more comfortable and relaxing operation experience. The display of load moment limiter integrates main console and operation display system, which clearly show the data of all operating superstructure conditions for lifting operation.

**Engine**

- Type: Inline six-cylinder, water cooled, supercharged and inter-cooling diesel engine
- Rated power: 205kw/2200r/min
- Environment-protection: Emission complies with EurolIII standard
- Capacity of fuel tank: 280L

**Hydraulic system**

- High-quality hydraulic components such as main pump, slewing pump, main valve, winch motor, balance valve etc., are equipped to ensure the stability and reliability of the system. Precise parameter matching makes the control performance excellent. The electrical proportion variable piston pump is adopted and the oil flow is controlled by the electrical joystick to achieve real-time flow control and prevent energy waste. The dual-pump confluent/separate mode is designed by SANY itself and dual-pump confluent is more efficient for combined operations and dual-pump separate for single operation.
- The use of dead-weight lowering compensation hydraulic system ensures excellent lowering micro-mobility and stability.
- Single-cylinder pin telescopic system is used for boom.
- Jib is equipped with luffing cylinder to achieve 0°~40°infinitely luffing.
- Closed slewing system is used with flow and direction changed through adjusting the angle of the swash plate of the variable pump, thus ensuring the excellent micro-mobility and stable rotation.
- Capacity of hydraulic oil tank: 1050L.

**Control system**

- With 24V DC power supply, the PLC integrated programmable controller and CAN-bus control network can be used to achieve logic control and electro proportional control of the system through combining with the common electricity.
- With real-time monitoring and fault self-diagnosis system.
- Lifting, slewing, and luffing can be controlled by two auto-reset multidirectional electro proportional handles. Lifting of counterweight, shifting of cab, and locking of rotating bed can be controlled through the keys on the control panel.
- Display can be connected with the controller via CAN-bus with main functions as follows: digital adjustment and display of the electro proportional control parameters, display of fault code of the electro proportional system, and real-time data display by the hydraulic system.

**Luffing system**

- The top single-cylinder luffing is applied with luffing angle ranging from -0.4° to 82°. Hydraulic system adopts the dual-pump converging open hydraulic circuit to achieve large-angle fast lowering and small-angle stable and slow lowering operations combining with electro proportional control, power lowering and self-weight luffing.

**Telescopic system**

- It consists of six section booms welded with bended fine-grain high-strong steel plate, with oval section applied to ensure good buckling resistance performance. With single-cylinder automatic pin system, a dual-action cylinder can control telescopic operation of all booms and achieve a variety of boom combinations.
- Basic boom length is 15.65m and full length of boom is 73m. Max. lifting height is 73.5m.

**Lattice jibs**

- The fixed jib is variable from 12.2m to 43m according to the combination and it is luffing free from 0-40°according to the actual working condition. The max. lifting height is 112m.

## Superstructure

**Slewing system**

- It consists of constant displacement motor and slewing reducer with mature technology. 360° full-rotation can be achieved through external gearing with slewing ring, with slewing speed of 0-1.6rpm and with infinitely variable speed adjustment. Slewing hydraulic system adopts the closed system, which not only avoids throttling loss of the open system but also ensures a high efficiency. Emergency brake can be achieved through electro proportional brake pedal.

**Hoisting system**

- Planet-gear speed reducer and special groove winch drum are driven by hydraulic motor with brake installed internally.
- Wire rope lock: High-quality wire rope lock with casting at end is applied. It is installed in the lock sleeve directly, which improves the replacement speed of the lifting rate.
- Spec. of wire rope: φ24-2160, non-rotating.
- Length: About 400m.
- Max. single rope speed (outer layer): about 130m/min.

**Safety system**

- Load moment limiter: With analytical mechanics method, the load moment limiter calculation system is established based on the load mechanical model. Therefore, the rated hoisting accurate can be up to ±3% through on-line non-load calibration.
- Hydraulic system is configured with the balance valve, overflow valve, and two-way hydraulic lock etc. ensuring stable and reliable operation of the hydraulic system.
- Main and auxiliary winches are configured with 3-wraps protectors to prevent over roll-out of wire rope.
- Boom and jib are configured with height limiter at end to prevent over-hoist of the wire rope.
- Boom head is equipped with anemometer to detect whether the high-altitude wind speed is within the allowable range.

**Counterweight**

- Combined variable counterweights are used with 0t, 12.5t, 27t, 41.5t, 56t, 80t, 100t seven combinations to meet requirements of different operating conditions and maximize structural parts performance , which can be self-assembled and disassembled remotely with good micro-mobility.

## Chassis

**Cab**

- Cab is made of new steel structure self-developed by SANY, featuring excellent shock absorption and tightness, which is configured with swing-out doors at both sides, pneumatically suspended driver's seat and passenger seat, adjustable steering wheel, large rearview mirror, comfortable driver chair with a headrest, anti-fog fan, air conditioner, stereo radio, and complete control instruments and meters, providing more comfortable and safe operation experience.

**Carrier frame**

- Designed and manufactured by SANY, anti-torsion box structure is welded by fine-grain high-strength steel plate to provide strong load bearing capacity.

**Axles**

- Full-axle steering is applied with axles 1, 3, 5 and 6 used for drive operation and with axles 1, 3, 5 and 6 equipped with differential locks for planetary transmission. Axles 1 and 2 adopt the bar-feedback hydraulic power steering systems and axles 3, 4, 5 and 6 adopt the electrohydraulic control steering system with assist in speed control and special steering mode optional applied, thus ensuring easy steering and flexible operation.

## Chassis

### Engine

- Type: Electric controlled, V- type eight-cylinder, water cooled, supercharged and inter-cooling diesel engine.
- Rated power: 440kw/1800r/min
- Max torque: 2800Nm/1300rpm
- Environment-protection: Emission complies with EuroIV standard
- Capacity of fuel tank: 550L

### Transmission system

- Gearbox: Manual / Automatic gearbox is adopted with 12-gear and large speed ratio range applied, which meets the requirements of low gradeability speed and high speed traveling.
- Transfer case: Transfer case with a large input torque is used with rated torque up to 30000N.m and with differential lock cylinder configured.
- Transmission shaft: With optimized arrangement of the transmission shaft, the transmission is more stable and reliable. For most optimized transmission, face-tooth coupling transmission shaft is used with large transmission torque.

### Brakes system

- Brakes system includes traveling brake, parking brake, emergency brake, and auxiliary brake.
- Traveling brake: All wheels use the air servo brakes and dual-circuit brake system and are equipped with disk brakes.
- Parking brake: Force driven by accumulator is applied on the second to sixth axle.
- Emergency brake: Accumulator is used not only for cutting-off brake but also for emergency brake.
- Auxiliary brake consists of engine brake and exhaust brake etc. There are double brakes for the engine, hydraulic power retarder brake for reducer and eddy current retarder brake for four axle which ensure high safety and reliability of the travelling.

### Suspension system

- Axle suspension devices adopt the height-adjustable oil-gas suspension devices equipped with the hydraulic lock, with stroke of suspension cylinder of +160/-130mm to achieve suspension, rigid locking, automatic leveling, overall lifting and lowering, single-point lifting and lowering modes. Load applied on each axle is no more than 12t. With good trafficability and adaptability of a variety of severe operating conditions and road, smooth and comfortable travelling and side stability of the vehicle are guaranteed.

### Steering system

- Servo power steering gear and dual-circuit system hydraulic steering device are used with emergency steering pump equipped. Steering can be adjusted through regulating the speed. Axles 3 and 4 steering will stop from 30km/h and from 60km/h for axles 5 and 6.
- Six types steering modes: 1) Road running mode (default mode). 2) Full-wheel steering mode. 3) Crab-type mode; 4) Steering mode without deflection. 5) Independent rear-axle steering mode. 6) Steering mode with rear axle locked.

### Outriggers


- Four-point supporting of the H-shaped outriggers ensures easy operation and strong stability with Max. span up to 8.95m×8.6m. Outrigger telescopic hydraulic system adopts the electro proportional control technology with wireless remote control configured. Outrigger control panel can display all loads with automatic level function to ensure high control precision and simple operation.

### Tyres


- 12\*16.00R25

### Electrical system


- With 24V DC power supply, cutting off power of the undercarriage can be achieved. Automotive lighting system is equipped. Vehicle actions such as throttle and outrigger control can be electrically controlled. Electrical system has strong detection, logic, and calculation capacity with fault self-diagnosis, centralized display and self-protection function.
- Chassis adopts CAN-bus system. Multifunctional centralized display system is used. Power consumption is small with maximum value of only 5w. Four functional keys are provided on the user interface. LCD display is used with adjustable contrast ratio.



Dimension(mm)						
Tyre Size	A	B	C	D	E	F
14.00 R25	3940	3720	1955	2564	14°	12°
16.00 R25	4000	3780	2015	2552	16°	18°



Type	Item	Parameter
Capacity	Max. lifting capacity	300 t
	Overall length	18200 mm
	Overall width	3000 mm
	Overall height	4000 mm
Dimensions	Axle-1, 2	1650 mm
	Axle-2, 3	3170 mm
	Axle-3, 4	1650 mm
	Axle-4, 5	2440mm
	Axle-5, 6	1650 mm
Weight	Overall weight	72000 kg
	Axle load	12000 kg
	Axle load-1, 2, 3	12000 kg
	Axle load-4, 5, 6	12000 kg
	Rated power	440 kW/1800 rpm
	Rated torque	2800 N.m/ 1300 rpm
Traveling	Rated power	205kw/2200rpm
	Rated torque	1100N.m/1200-1600rpm
	Max.traveling speed	80 km/h
	Turning radius	12 m
	Min.turning radius of boom head	14.4 m
	Wheel formula	12 × 8
Main Performance Data	Min.ground clearance	360 mm
	Approach angle	16 °
	Departure angle	18 °
	Max.gradeability	49%
	Fuel consumption per 100km	≤ 114 L
	Temperature range	- 20 ° ~ + 50 °
Working speed	Min.rated range	3 m
	Tail slewing radius of swingtable	5735 mm
	Boom section	6
	Boom shape	U-shaped
	Max.lifting moment	8800 kN·m
	Base boom	3640 kN·m
	Full-extend boom	884 kN·m
	Boom length	15.65 m
	Full-extend boom	73 m
	Full-extend boom+jib	115 m
	Outrigger span (Longitudinal×Transversal)	8.95 × 8.6 m
	Jib offset	0°\20°\40°
Aircondition	Max.single rope lifting speed of main winch (no load)	130 m/min
	Max.single rope lifting speed of auxiliary winch (no load)	130 m/min
	Full extension/retraction time of boom	600 / 600 s
	Full lifting/descending time of boom	65 / 90 s
	Slewing speed	1.7 r/min
	Aircondition in up cab	Cooling / Heating
	Aircondition in low cab	Cooling / Heating




**SAC3000S ALL-TERRAIN CRANE  
LOAD CHART**

**Prerequisites:**

- ① Boom operating conditions: from 15.65m to 73m
- ② The span of outriggers is 8.95mx8.6m
- ③ 360°rotation is applied
- ④ Counterweight is 100T

Radius (m)	Main Boom (m)												Radius (m)
	15.65	20.93	26.2	31.48	36.75	42.03	47.31	52.58	57.86	63.14	68.41	73	
2.5	300.0*												2.5
3	260.0*												3
4	185.0	152.0	138.0										4
5	164.0	140.0	130.0	118.0									5
6	140.0	135.0	122.0	110.0	92.0								6
7	125.0	118.0	115.0	105.0	88.0	70.0							7
8	110.0	110.0	110.0	95.0	82.0	68.0	55.0						8
9	97.0	95.0	95.0	87.0	80.0	66.0	52.0	48.0					9
10	88.0	87.0	85.0	81.0	76.0	64.0	51.0	47.0	40.0				10
11	80.0	78.0	75.0	75.0	72.0	62.0	50.0	45.0	38.0				11
12	67.0	70.0	70.0	70.0	68.0	59.0	49.0	43.0	36.0	27.0			12
14		60.0	60.0	65.0	60.0	55.0	46.0	37.5	34.0	26.0	21.0	17.5	14
16		50.0	52.0	55.0	50.0	50.0	43.0	34.5	32.0	24.5	20.0	17.0	16
18		42.0	45.0	45.0	45.0	45.0	40.0	32.0	28.0	23.0	19.0	16.5	18
20		39.0	40.0	40.0	40.0	36.0	29.0	25.5	22.5	18.0	16.0	16.0	20
22		33.0	36.0	35.0	35.0	33.0	25.0	23.0	21.5	17.0	15.5	15.5	22
24			32.0	32.0	30.0	30.0	24.0	21.0	20.0	16.0	15.0	15.0	24
26			26.0	29.0	28.0	26.0	22.0	19.0	18.0	14.5	14.0	14.0	26
28			21.0	26.0	25.0	23.0	20.5	17.0	16.5	13.5	13.0	13.0	28
30			24.0	23.0	21.0	18.5	16.0	15.1	12.5	12.0	12.0	12.0	30
32			22.0	21.0	19.0	17.0	15.0	14.0	11.5	10.5	10.5	10.5	32
34				19.0	17.5	16.0	13.5	13.0	10.5	10.0	10.0	10.0	34
36				17.5	17.0	15.0	13.0	12.0	10.0	9.5	9.5	9.5	36
38				15.0	16.5	14.5	12.0	11.0	9.5	8.5	8.5	8.5	38
40					15.5	13.5	11.0	10.5	9.0	8.0	8.0	8.0	40
42						14.5	12.5	10.5	9.5	8.5	7.5	7.5	42
44						8.0	11.5	10.0	9.0	8.0	7.0	7.0	44
46							10.5	9.0	8.5	7.5	6.5	6.5	46
48							9.0	8.5	8.0	7.0	6.0	6.0	48
50								8.0	7.5	6.5	5.5	5.5	50
52								7.5	7.0	6.0	5.2	5.2	52
54								7.0	6.5	5.6	5.0	5.0	54
56									6.1	5.2	4.8	4.8	56
58									6.0	5.0	4.5	4.5	58
60										4.5	4.0	4.0	60
62										4.0	3.8	3.8	62
64										3.0	3.6	3.6	64
66											3.2	6.6	66
Parts of line	16	16	16	16	13	10	6	5	4	3	2	2	Parts of line
Telescopic Condition (%)													
1	0	0	0	0	0	0	0	0	0	0	0	0	1
2	0	46	46	46	46	46	92	92	92	92	92	100	2
3	0	0	46	46	46	46	46	92	92	92	92	100	3
4	0	0	0	46	46	46	46	46	92	92	92	100	4
5	0	0	0	0	46	46	46	46	46	92	92	100	5
6	0	0	0	0	0	46	46	46	46	46	92	100	6

Notes: The item with \* should be operated at rear side with additional equipment.


**SAC3000S ALL-TERRAIN CRANE  
OPERATION CONDITION**




**Prerequisites:**

- ① Jib Length:12.2m
- ② The span of outriggers is 8.95mx8.6m
- ③ 360°rotation is applied
- ④ Counterweight is 100T
- ⑤ Jib offset is 40°

Radius (m)	Main Boom (m)										Radius (m)
	36.8	42.0	47.3	52.6	57.9	57.9	63.1	63.1	68.4	73.0	
10											10
12											12
14											14
16											16
18	9.2	9.4									18
20	8.9	9.1	9.2								20
22	8.7	8.8	8.9	8.9	9.1						22
24	8.6	8.7	8.7	8.8	9	8.9					24
26	8.4	8.6	8.7	8.7	8.8	8.7	8.9	8.8			26
28	8.2	8.4	8.4	8.6	8.7	8.7	8.8	8.7	8.7	8.0	28
30	8.1	8.2	8.2	8.4	8.7	8.5	8.7	8.5	8.6	7.7	30
32	7.7	8.0	7.9	8.1	8.5	8.3	8.7	8.2	8.3	7.4	32
34	7.3	7.8	7.5	7.8	8.4	7.9	8.6	8.0	7.9	7.1	34
36	6.9	7.4	7.1	7.5	8.3	7.6	8.3	7.7	7.7	6.9	36
38	6.5	7.1	6.8	7.1	8	7.2	8	7.3	7.3	6.6	38
40	5.5	6.9	6.4	6.8	7.7	6.9	7.8	7.0	7.0	6.2	40
42	5.0	6.5	6.0	6.5	7.3	6.4	7.4	6.7	6.8	6.0	42
44		6.2	5.8	6.2	6.9	6.1	7.1	6.4	6.5	5.7	44
46		5.5	5.6	6.0	6.6	5.8	6.8	6.0	6.2	5.4	46
48		4.8	5.2	5.7	6.2	5.5	6.2	5.8	6.0	5.2	48
50			4.5	5.0	6	5.4	5.7	5.5	5.7	5.2	50
52			4.0	4.5	5.5	5.1	5.1	5.3	5.3	4.9	52
54				3.5	4.5	4.0	4.9	5.3	5.1	4.8	54
56				3.0	4.0	3.5	4.4	5.0	4.7	4.6	56
58					3.5	3.0	4.0	4.5	4.2	4.2	58
60					3.2	2.5	3.5	4.1	3.8	3.8	60
62					2.5		2.8	3.5	3.3	3.3	62
64							2.0	2.8	3.0	3.0	64
66							2.0	2.4	2.5	2.5	66
68											68
70											70
72											72
74											74
76											76
78											78
80											80
82											82
84											84
86											86
n	1	1	1	1	1	1	1	1	1	1	n
1	0+	0+	0+	0+	46+	0+	92+	46+	92+	100+	1
2	0+	0+	0+	46+	92+	92+	92+	92+	92+	100+	2
3	0+	46+	92+	92+	92+	92+	92+	92+	92+	100+	3
4	92+	92+	92+	92+	92+	92+	92+	92+	92+	100+	4
5	92+	92+	92+	92+	46+	92+	46+	92+	92+	100+	5
m/s	9	9	9	9	9	9	9	9	9	9	m/s



**SAC3000S ALL-TERRAIN CRANE  
LOAD CHART**


**Prerequisites:**  
 ① Jib Length:22m  
 ② The span of outriggers is 8.95mx8.6m  
 ③ 360°rotation is applied  
 ④ Counterweight is 100T  
 ⑤ Jib offset is 0°

Radius (m)	Main Boom (m)										Radius (m)
	36.8	42.0	47.3	52.6	57.9	57.9	63.1	63.1	68.4	73.0	
5											5
6											6
7											7
8											8
9											9
10	8.5	8.5	8.5	8.0							10
11	8.3	8.4	8.5	8.0							11
12	7.9	8.2	8.0	7.7	8.1	7.8	7.7	7.5			12
14	7.8	8.0	7.9	7.7	8.1	7.8	7.7	7.5			14
16	7.5	7.4	7.8	7.6	7.6	7.7	7.7	7.4	6.5		16
18	7.2	7.2	7.6	7.5	7.5	7.6	7.4	6.5	5.8	18	
20	7.0	6.9	7.5	7.4	7.4	7.0	7.4	7.3	6.4	5.8	20
22	6.8	6.8	7.0	7.2	7.2	6.9	6.9	7.2	6.3	5.8	22
24	6.5	6.6	6.5	6.9	7.0	6.7	6.8	7.0	6.2	5.7	24
26	6.2	6.3	6.2	6.7	6.8	6.1	6.6	6.8	6.1	5.7	26
28	6.0	6.0	6.0	6.5	6.6	6.0	6.5	6.4	5.9	5.6	28
30	5.8	5.9	5.9	6.4	6.2	5.8	5.9	5.7	5.8	5.5	30
32	5.5	5.7	5.7	6.2	6.0	5.7	5.7	5.6	5.7	5.4	32
34	5.3	5.5	5.5	5.9	5.7	5.5	5.6	5.4	5.6	5.3	34
36	5.1	5.2	5.3	5.3	5.5	5.3	5.4	5.3	5.4	5.2	36
38	4.9	5.1	5.1	5.2	5.3	5.2	5.3	5.1	5.3	5.1	38
40	4.7	4.9	5.0	5.1	5.2	5.1	5.1	5.2	5	40	
42	4.5	4.7	4.9	5.0	5.1	5.0	5.1	5.0	4.9	42	
44	4.2	4.5	4.7	4.8	5.0	4.9	5	4.9	5	44	
46	4.1	4.4	4.5	4.7	4.8	4.7	4.8	4.9	4.7	46	
48	3.9	4.2	4.4	4.5	4.7	4.6	4.7	4.6	4.9	48	
50	3.8	4.1	4.2	4.4	4.6	4.4	4.6	4.5	4.4	50	
52	3.6	3.9	4.1	4.2	4.5	4.5	4.5	4.7	4.2	52	
54	3.2	3.8	4.0	4.2	4.4	4.3	4.4	4.5	4.6	54	
56	2.5	3.5	3.8	4.2	4.2	4.1	4.3	4.3	4.5	56	
58	2.0	3.0	3.7	4.0	4.2	3.9	4.2	4.2	3.6	58	
60		2.4	3.3	3.8	4.2	3.7	3.9	4.0	4.0	60	
62		2.0	3.0	3.7	4.0	3.5	3.5	3.8	3.6	62	
64			2.5	3.0	3.7	3.3	3.2	3.6	3.3	64	
66				2.0	2.5	3.5	3.0	2.9	3.5	66	
68					2.0	3.0	2.5	2.7	2.8	68	
70						2.5	2.0	2.4	2.5	70	
72							2.0	2.0	2.3	72	
74								2.0	1.9	74	
76									1.7	76	
78										78	
80										80	
82										82	
84										84	
86										86	
n	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	n	
1	0+	0+	0+	0+	92+	0+	92+	46+	92+	100+	1
2	0+	0+	0+	46+	92+	92+	92+	92+	92+	100+	2
3	0+	46+	92+	92+	92+	92+	92+	92+	92+	100+	3
4	92+	92+	92+	92+	46+	92+	92+	92+	92+	100+	4
5	92+	92+	92+	92+	46+	92+	92+	92+	92+	100+	5
m/s	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	m/s	

Radius (m)	Main Boom (m)										Radius (m)
	36.8	42.0	47.3	52.6	57.9	57.9	63.1	63.1	68.4	73.0	
12											12
14											14
16											16
18											18
20	5.9										20
22	5.7	5.7	5.7	5.6							22
24	5.5	5.5	5.5	5.5	5.4	5.5	5.5	5.4	5.4	5.3	24
26	5.3	5.3	5.3	5.3	5.3	5.4	5.4	5.4	5.4	5.3	26
28	5.1	5.1	5.1	5.2	5.2	5.2	5.3	5.3	5.3	5.2	28
30	5.0	5.1	5.1	5.1	5.1	5.1	5.2	5.2	5.2	5.2	30
32	4.8	4.9	4.9	4.9	5.0	5.0	5.1	5.1	5.1	5.0	32
34	4.7	4.8	4.8	4.9	4.9	5.0	5.0	5.0	5.0	5.0	34
36	4.6	4.7	4.7	4.8	4.8	4.8	4.9	4.9	4.9	4.9	36
38	4.5	4.6	4.6	4.7	4.7	4.7	4.8	4.8	4.8	4.8	38
40	4.4	4.3	4.3	4.4	4.4	4.4	4.5	4.5	4.5	4.5	40
42	4.3	4.4	4.4	4.5	4.5	4.5	4.6	4.6	4.6	4.6	42
44	4.2	4.3	4.3	4.4	4.4	4.4	4.5	4.5	4.5	4.5	44
46	4.1	4.2	4.2	4.3	4.3	4.3	4.4	4.4	4.4	4.4	46
48	4.0	4.1	4.1	4.2	4.2	4.2	4.3	4.3	4.3	4.3	48
50	4.0	4.2	4.2	4.4	4.4	4.4	4.5	4.5	4.5	4.5	50
52	3.5	4.2	4.2	4.4	4.4	4.4	4.5	4.5	4.5	4.5	52
54	3.0	4.0	4.0	4.2	4.3	4.4	4.5	4.6	4.6	4.6	54
56	3.0	3.5	3.8	4.2	4.1	4.3	4.5	4.5	4.5	4.5	

**Prerequisites:**  
 ① Jib Length:22m  
 ② The span of outriggers is 8.95m×8.6m  
 ③ 360°rotation is applied  
 ④ Counterweight is 100T  
 ⑤ Jib offset is 40°

Radius (m)	Main Boom (m)										Radius (m)
	36.8	42.0	47.3	52.6	57.9	57.9	63.1	63.1	68.4	73.0	
18											18
20											20
22											22
24											24
26	4.6										26
28	4.5	4.5	4.4	4.4	4.3	4.3					28
30	4.4	4.4	4.4	4.3	4.3	4.3					30
32	4.3	4.3	4.3	4.3	4.3	4.3	4.3	4.2	4.2		32
34	4.3	4.3	4.3	4.3	4.3	4.2	4.2	4.2	4.2		34
36	4.3	4.2	4.2	4.2	4.2	4.2	4.2	4.2	4.1		36
38	4.3	4.2	4.2	4.2	4.2	4.2	4.2	4.2	4.1		38
40	4.3	4.2	4.2	4.2	4.2	4.2	4.2	4.2	4.1		40
42	4.3	4.2	4.2	4.2	4.2	4.2	4.2	4.2	4.1		42
44	4.3	4.2	4.2	4.2	4.2	4.2	4.2	4.1	4.1		44
46	4.3	4.2	4.2	4.2	4.2	4.2	4.2	4.1	4.1		46
48	4.0	4.2	4.2	4.2	4.2	4.2	4.2	4.1	4.1		48
50	3.8	4.2	4.2	4.2	4.2	4.2	4.2	4.1	4.0		50
52	3.5	4.0	4.2	4.2	4.2	4.2	4.2	4.1	4.0		52
54	3.8	4.0	4.2	4.2	4.2	4.2	4.2	4.1	3.9		54
56	3.2	3.8	4.1	4.2	4.0	4.2	4.2	4.1	3.8		56
58		3.5	4.0	4.2	3.8	4.2	4.1	4.1	3.7		58
60		3.0	3.8	4.2	3.8	4.2	3.9	4.1	3.7		60
62		2.5	3.2	4.0	3.5	3.7	3.7	3.9	3.5		62
64			2.5	3.8	3.2	3.5	3.7	3.8	3.3		64
66			2.0	3.5	2.8	3.0	3.5	3.3	3.2		66
68				3.0	2.2	2.8	3.1	3.0	3.0		68
70						2.0	2.5	2.7	2.7		70
72							2.0	2.3	2.3		72
74								1.8	2		74
76									1.5		76
78											78
80											80
82											82
84											84
n	1	1	1	1	1	1	1	1	1	n	
1	0+	0+	0+	0+	46+	0+	92+	46+	92+	100+	1
2	0+	0+	0+	46+	92+	92+	92+	92+	92+	100+	2
3	0+	46+	92+	92+	92+	92+	92+	92+	92+	100+	3
4	92+	92+	92+	92+	92+	92+	92+	92+	92+	100+	4
5	92+	92+	92+	92+	46+	92+	46+	92+	92+	100+	5
m/s	9	9	9	9	9	9	9	9	9	9	m/s






**Prerequisites:**

- ① Jib Length:29m
- ② The span of outriggers is 8.95m×8.6m
- ③ 360°rotation is applied
- ④ Counterweight is 100T
- ⑤ Jib offset is 40°

Radius (m)	Main Boom (m)										Radius (m)
	36.8	42.0	47.3	52.6	57.9	57.9	63.1	63.1	68.4	73.0	
24											24
26											26
28											28
30											30
32	2.8	2.8									32
34	2.7	2.7	2.7								34
36	2.7	2.7	2.7	2.6	2.7	2.6	2.6	2.5	2.7		36
38	2.6	2.6	2.6	2.6	2.6	2.6	2.5	2.5	2.6		38
40	2.6	2.6	2.6	2.6	2.6	2.5	2.5	2.5	2.6		40
42	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.6		42
44	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.4	2.4		44
46	2.5	2.5	2.5	2.5	2.4	2.4	2.4	2.4	2.5		46
48	2.5	2.5	2.4	2.4	2.4	2.4	2.4	2.4	2.4		48
50	2.5	2.5	2.4	2.4	2.4	2.4	2.4	2.4	2.4		50
52	2.5	2.5	2.4	2.4	2.4	2.4	2.4	2.4	2.4		52
54	2.3	2.5	2.4	2.4	2.4	2.4	2.4	2.4	2.4		54
56	2.0	2.5	2.4	2.4	2.4	2.4	2.4	2.4	2.4		56
58	1.5	2.4	2.4	2.4	2.4	2.4	2.4	2.4	2.4		58
60		2.0	2.4	2.4	2.4	2.4	2.4	2.4	2.4		60
62		1.5	2.3	2.4	2.4	2.4	2.4	2.4	2.4		62
64			2.0	2.4	2.4	2.4	2.4	2.4	2.4		64
66			1.6	2.3	2.4	2.4	2.4	2.4	2.4		66
68			1.0	2.0	2.3	2.3	2.4	2.4	2.4		68
70				1.6	2.0	2.0	2.4	2.4	2.4		70
72				1.0	1.8	1.8	2.4	2.4	2.4		72
74					1.2	1.4	2.3	2.3	2.3		74
76						1.0	2.0	2.0	2.1		76
78							1.5	1.5	2.0		78
80							1.0	1.0	1.5		80
82								1.0	1.0		82
84											84
86											86
88											88
90											90
n	1	1	1	1	1	1	1	1	1	n	
1	0+	0+	0+	0+	46+	0+	92+	46+	92+	100+	1
2	0+	0+	0+	46+	92+	92+	92+	92+	92+	100+	2
3	0+	46+	92+	92+	92+	92+	92+	92+	92+	100+	3
4	92+	92+	92+	92+	92+	92+	92+	92+	92+	100+	4
5	92+	92+	92+	92+	46+	92+	46+	92+	92+	100+	5
m/s	9	9	9	9	9	9	9	9	9	9	m/s






**Prerequisites:**

- ① Jib Length:36m
- ② The span of outriggers is 8.95mx8.6m
- ③ 360°rotation is applied
- ④ Counterweight is 100T
- ⑤ Jib offset is 40°

Radius (m)	Main Boom (m)										Radius (m)
	36.8	42.0	47.3	52.6	57.9	57.9	63.1	63.1	68.4	73.0	
30											30
32											32
34											34
36											36
38	1.7	1.7									38
40	1.6	1.6	1.6								40
42	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.5	1.5		42
44	1.6	1.6	1.6	1.6	1.6	1.6	1.5	1.5	1.5		44
46	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5		46
48	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5		48
50	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5		50
52	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5		52
54	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5		54
56	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5		56
58	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5		58
60	1.3	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5		60
62	1.1	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5		62
64		1.3	1.5	1.5	1.5	1.5	1.5	1.5	1.5		64
66		1.1	1.5	1.5	1.5	1.5	1.5	1.5	1.5		66
68			1.3	1.5	1.5	1.5	1.5	1.5	1.4		68
70				1.2	1.5	1.5	1.5	1.5	1.4		70
72					1.0	1.3	1.5	1.5	1.4		72
74						1.2	1.5	1.5	1.4		74
76						1.0	1.3	1.3	1.4		76
78							1.2	1.2	1.4		78
80							1.0	1.0	1.4		80
82								1.2	1.2		82
84								1.0	1.0		84
86									1.2		86
88									1.0		88
90											90
92											92
94											94
96											96
98											98
100											100
n	1	1	1	1	1	1	1	1	1	n	
1	0+	0+	0+	0+	46+	0+	92+	46+	92+	100+	1
2	0+	0+	0+	46+	92+	92+	92+	92+	100+	2	
3	0+	46+	92+	92+	92+	92+	92+	92+	100+	3	
4	92+	92+	92+	92+	92+	92+	92+	92+	100+	4	
5	92+	92+	92+	92+	46+	92+	46+	92+	100+	5	
m/s	9	9	9	9	9	9	9	9	9	m/s	



**SAC3000S ALL-TERRAIN CRANE  
LOAD CHART**

**Prerequisites:**  
 ① Jib Length:43m  
 ② The span of outriggers is 8.95mx8.6m  
 ③ 360°rotation is applied  
 ④ Counterweight is 100T  
 ⑤ Jib offset is 0°

Radius (m)	Main boom (m) + Extension										Radius (m)
	36.8	42	47.3	52.6	57.9	57.9	63.1	63.1	68.4	72	
9											9
10											10
11	3.6										11
12	3.6	3.4									12
14	3.6	3.4	3.1	3	2.8	2.7	2.4	2.3			14
16	3.6	3.4	3.1	3	2.8	2.7	2.4	2.3			16
18	3.6	3.4	3.1	3	2.8	2.8	2.4	2.3	2.2		18
20	3.5	3.4	3.1	3	2.8	2.8	2.4	2.3	2.2	1.7	20
22	3.4	3.3	3.1	3	2.8	2.8	2.4	2.3	2.2	1.7	22
24	3.2	3.2	3.1	3	2.8	2.7	2.4	2.3	2.2	1.7	24
26	3.2	3.1	3	2.9	2.7	2.5	2.4	2.3	2.2	1.7	26
28	3	3	2.9	2.8	2.6	2.4	2.4	2.3	2.2	1.7	28
30	2.9	2.9	2.8	2.7	2.6	2.4	2.4	2.3	2.2	1.7	30
32	2.8	2.8	2.7	2.6	2.5	2.4	2.4	2.3	2.2	1.7	32
34	2.6	2.6	2.6	2.5	2.4	2.3	2.3	2.3	2.2	1.7	34
36	2.5	2.5	2.5	2.4	2.3	2.2	2.3	2.2	2.2	1.7	36
38	2.4	2.4	2.4	2.3	2.3	2.2	2.3	2.2	2.1	1.7	38
40	2.3	2.3	2.3	2.3	2.3	2.2	2.2	2.1	2.1	1.7	40
42	2.2	2.3	2.3	2.2	2.2	2.1	2.1	2	2	1.7	42
44	2.1	2.2	2.2	2.2	2.1	2	2.1	2	2	1.7	44
46	2	2.1	2.1	2.1	2	1.9	2	1.9	1.9	1.7	46
48	1.9	2	2	2	2	1.9	1.9	1.8	1.9	1.7	48
50	1.8	1.9	1.9	1.9	1.9	1.8	1.9	1.8	1.8	1.7	50
52	1.8	1.8	1.8	1.8	1.8	1.7	1.8	1.7	1.8	1.7	52
54	1.7	1.7	1.8	1.8	1.8	1.8	1.8	1.7	1.6	1.6	54
56	1.6	1.7	1.7	1.7	1.7	1.7	1.7	1.6	1.6	1.6	56
58	1.6	1.6	1.6	1.6	1.7	1.7	1.6	1.5	1.6	1.5	58
60	1.5	1.5	1.6	1.6	1.6	1.6	1.6	1.6	1.5	1.5	60
62	1.4	1.5	1.5	1.5	1.6	1.6	1.5	1.5	1.5	1.4	62
64	1.4	1.4	1.5	1.5	1.5	1.5	1.5	1.5	1.4	1.4	64
66	1.4	1.4	1.4	1.4	1.5	1.5	1.4	1.4	1.4	1.3	66
68	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.3	68
70	1.3	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.3	1.3	70
72	1.3	1.3	1.4	1.4	1.4	1.4	1.4	1.4	1.2	1.2	72
74	1.3	1.2	1.3	1.4	1.4	1.4	1.4	1.4	1.1	1.1	74
76		1.2	1.3	1.3	1.3	1.3	1.3	1.3	1	1	76
78			1.2	1.2	1.1	1.3	1.3	1.3	0.9	0.9	78
80				1.2	1.1	1.3	1.4	1.1		0.8	80
82				1.1	1.1	1.2	1.4			0.8	82
84					1	1.1				0.8	84
86						1				1.1	86
n	1	1	1	1	1	1	1	1	1	1	n
1	0+	0+	0+	0+	92+	0+	92+	46+	92+	92+	1
2	0+	0+	0+	46+	92+	92+	92+	92+	100+	2	
3	0+	46+	92+	92+	92+	92+	92+	92+	100+	3	
4	92+	92+	92+	92+	46+	92+	92+	92+	100+	4	
5	92+	92+	92+	92+	46+	92+	92+	92+	100+	5	
m/s	9	9	9	9	9	9	9	9	9	m/s	


**Prerequisites:**  
 ① Jib Length:43m  
 ② The span of outriggers is 8.95mx8.6m  
 ③ 360°rotation is applied  
 ④ Counterweight is 100T  
 ⑤ Jib offset is 20°

Radius (m)	Main boom (m) + Extension										Radius (m)
	36.8	42	47.3	52.6	57.9	57.9	63.1	63.1	68.4	72	
22											22
24											24
26	2.5										26
28	2.4	2.3									28
30	2.3	2.3									30
32	2.2	2.2									32
34	2.1	2.1									34
36	2	2									36
38	1.9	1.9									38
40	1.9	1.9									40
42	1.8	1.8									42
44	1.7	1.7									44
46	1.6	1.6									46
48	1.6	1.6									48
50	1.6	1.6									50
52	1.5	1.5									52
54	1.5	1.5									54
56	1.4	1.4									56
58	1.4	1.4									58
60	1.4	1.4									60
62	1.4	1.4									62
64	1.4	1.4									64
66	1.4	1.4									66
68	1.4	1.4									68
70	1.3	1.4									70
72	1.3	1.3									72
74	1.2	1.3									74
76	1.2	1.3									76
78	1.2	1.2									78
80	1.2	1.1									80
82	1.1	1.1									

**SAC3000S ALL-TERRAIN CRANE  
LOAD CHART**

**Prerequisites:**  
 ① Jib Length:43m  
 ② The span of outriggers is 8.95m×8.6m  
 ③ 360°rotation is applied  
 ④ Counterweight is 100T  
 ⑤ Jib offset is 40°

Radius (m)	Main boom (m) + Extension											Radius (m)
	36.8	42	47.3	52.6	57.9	57.9	63.1	63.1	68.4	72		
32												32
34												34
36	1.6											36
38	1.6	1.6	1.5	1.5	1.4	1.4						38
40	1.5	1.5	1.5	1.5	1.4	1.4	1.4	1.4				40
42	1.5	1.5	1.5	1.5	1.4	1.4	1.4	1.4	1.4			42
44	1.5	1.5	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.3		44
46	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.3		46
48	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.3		48
50	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.3		50
52	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.3		52
54	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.3		54
56	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.3	1.3		56
58	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.3	1.3		58
60	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.3	1.3		60
62	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.3	1.3		62
64		1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.3	1.3		64
66		1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.3	1.3		66
68		1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.3	1.3		68
70			1.4	1.4	1.4	1.4	1.4	1.4	1.3	1.3		70
72			1.4	1.4	1.4	1.4	1.4	1.4	1.3	1.3		72
74			1.4	1.4	1.4	1.4	1.4	1.4	1.3	1.2		74
76				1.4	1.4	1.4	1.4	1.4	1.3	1.2		76
78				1.4	1.4	1.4	1.4	1.4	1.3	1.2		78
80					1.4	1.3	1.3	1.3	1.1			80
82						1.3	1.3	1.3	1.1			82
84									1.2	0.9		84
86										0.9		86
n	1	1	1	1	1	1	1	1	1	1		n
1	0+	0+	0+	0+	46+	0+	92+	46+	92+	92+		1
2	0+	0+	0+	46+	92+	92+	92+	92+	92+	100+		2
3	0+	46+	92+	92+	92+	92+	92+	92+	92+	100+		3
4	92+	92+	92+	92+	92+	92+	92+	92+	92+	100+		4
5	92+	92+	92+	92+	46+	92+	46+	92+	92+	100+		5
m/s	9	9	9	9	9	9	9	9	9	9		m/s

**SAC3000S ALL-TERRAIN CRANE  
WHEEL CRANE FAMILY MAP**
**■ TRUCK CRANE**

**■ ALL TERRAIN CRANE**

**■ ROUGH-TERRAIN CRANE**




Quality Changes the World

## SANY AUTOMOBILE HOISTING MACHINERY

Address: SANY Industrial Park, Jinzhou Development Zone,  
Changsha, Hunan, China.

Service Hotline: 4006098318

Email: crd@sany.com.cn

For more information, please visit: [www.sanygroup.com](http://www.sanygroup.com)

For our consistent improvement in technology, specifications may change without notice.  
The machines illustrated may show optional equipment which can be supplied at additional cost.

Version: 2016.1

Distributed By: