



AN ISO 9001:2008 CERTIFIED COMPANY

OUR MISSION SERVICE WITHIN 24 HOURS CALL:180030003377 (9.30 AM TO 5.30 PM ON WORKING DAYS) | FOR PRODUCT ENQUIRY CALL: 1800 3001 8383



FOR PRODUCT ENQUIRY CALL  
**1800 3001 8383**



### Hand operated sealing machines

Ideal for sealing heat sealable poly pouches | Hand operated Impulse (instant) sealing | Hot bar sealers for laminated pouches | Adjustable electronic timer | Audio visual sealing indicators | Suitable for packing solids, granules and powders | Round element option for simultaneous sealing and cutting

#### Technical specifications

Model	Seal (mm)		Power		Dimension (mm)			Weight Kg.
	Length	Width	V	VA	L	B	H	
<b>Impulse Sealers</b>								
190 HW	190	3	240	345	305	85	155	2.80
190 HP	190	1.6 x 2	240	335	305	85	155	2.80
200 D V2	200	1.6	240	215	305	85	155	2.60
200 HB	200	1.6	240	245	305	85	155	2.80
250 Delta	250	1.6	240	320	350	85	155	2.70
300 Delta	300	1.6	240	340	405	85	155	3.10
300 HB	300	1.6	240	390	405	85	155	4.40
300 HW	300	3	240	500	405	85	155	4.60
400 D	400	1.6	240	340	535	85	155	4.40
400 HB	400	1.6	240	380	535	85	155	5.10
400 HW	400	3	240	380	535	85	155	5.10
500 HB	500	1.6	240	440	630	85	155	6.3
600 HB	600	1.6	240	500	720	85	155	6.6
<b>Hotbar Sealers</b>								
200 HH	200	11	240	190	340	85	155	2.6
300 HH	300	11	240	290	410	85	155	3.0

\*Indicated dimensions are without packing

### Foot operated sealing machines

Adjustable electronic timer  
Tiltable sealing jaw  
Adjustable bag rest  
Ease of operation  
High productivity  
Visual indication during sealing  
Audio indication at the end of sealing  
Hot bar sealer with energy regulator for sealing laminated pouches



#### Technical specifications

Model	Seal (mm)		Power		Dimensions (mm)			Weight (kg)
	Length	Width	V	W	L	B	H	
<b>Impulse Sealers</b>								
QS 200 F	200	1.6	240	280	660	620	1050	17
QS 200 FE	200	5	240	470	660	620	1050	18
QS 200 FP	200	3x2	240	750	660	620	1050	22
QS 300 F	300	1.6	240	400	660	620	1050	19
QS 300 FE	300	5	240	800	660	620	1050	22
QS 300 FP	300	3x2	240	800	660	620	1050	24
QS 400 F	400	1.6	240	470	660	620	1050	20
QS 400 FE	400	5	240	720	660	620	1050	23
QS 500 F	500	1.6	240	560	660	620	1050	20
QS 500 FE	500	5	240	750	660	620	1050	23
QS 600 F	600	1.6	240	650	700	620	1050	23
QS 600 FE	600	5	240	920	700	620	1050	26
QS 900 F	900	1.6	240	950	1000	620	1050	30
<b>Hotbar Sealers</b>								
200 FH	200	12	240	200	660	620	1050	24
300 FH	300	12	240	270	660	620	1050	26
400 FH	400	12	240	350	660	620	1050	28

### Delta series (Economy)

No tilting facility; F D- Standard model, FE D-5mm sealing Width, FP D- Two parallel 3mm wide seals, FHE D- Hot bar sealers



#### Technical specifications

Model	Seal (mm)		Power		Dimensions (mm)			Weight (kg)
	Length	Width	V	W	L	B	H	
<b>Impulse sealers</b>								
300 FD	300	1.6	240	400	500	500	1000	17
300 FE D	300	5	240	600	500	500	1000	18
300 FP D	300	3x2	240	800	500	500	1000	19
400 F D	400	1.6	240	470	500	500	1000	22
400 FE D	400	5	240	720	500	500	1000	24
<b>Hot bar sealers</b>								
200 FHE D	200	12	240	130	500	530	930	14
300 FHE D	300	12	240	200	500	530	930	17
400 FHE D	400	12	240	200	500	530	930	20





## Sepack Impulse Sealers

Eliminating the errors of manual process, Sepack presents a digitally intelligent range of automatic impulse sealing machines with state-of-art features. Like microprocessor control for accurate timing, electro-magnetic jaw for perfect sealing pressure. Automatic or foot switch operated process control and more. An automatic impulse sealer for fast and perfect packaging of a wide range of products. Excellent for supermarkets and FMCG sectors.

### FEATURES

- | Sealing width: 5 mm | Sealing speed: 20 pouches/min
- | Dual operation modes: Automatic: Continuous operation with pre-set timer. Manual-Foot- switch based operation control.

Models available - AIS 350, AIS 450 & AIS 600

\*Pouch used for testing:10 micron thickness multilayer pouch, pouch placing time not included.



## Mobile sealer

- | For packing heavy bags
- | Ideal for tea sacks, chemicals, spices etc.
- | A mobile machine can reach to the filled bag
- | Height adjustability 0.3 to 1.3m

### Technical specifications

Model	Seal (mm)		Power		Dimensions (mm)			Weight (Kg)
	Length	Width	V	W	L	B	H	
900 MSE	900 mm	5mm	240	1.04 kw	1150	305	1500	60



## Bed sealer

- | can seal up to a length of six feet 5mm sealing width
- | Reverse bend rocker arm for uniform- sealing from one end to the other | Equipped with bearing mounted lever to achieve maximum pressure during sealing

### Technical specifications

Model	Seal		Power	
	Length	Width	V	W
1800 TM	1800 mm	5	240	2.7 Kw
1200 TM	1200 mm	5	240	1.5 Kw

## Foil sealers

- | For pilfer evident and leak proof sealing of aluminum foils on cups, cans, bottles, plastic containers and trays | Height adjustability and provision for heat control

Strong cups, cans and bottles can be sealed without extra attachments. Flimsy Cups and trays require extra support at the bottom of the neck, otherwise the cup/neck may be crushed during sealing operation. The support has to be matched with the shape of the cup to be sealed. (Provide dimensional sketches or samples for design of appropriate support)

### Technical specifications

Model	Height of the Containers	Sealing Dia Max	Power Watts	Voltage	L B H (mm)			Weight Kg
					L	B	H	
FS 1045	0 to 450mm	90mm	200	AC 240	560	250	650	8.5
FS 1545	0 to 450mm	140mm	300	AC 240	560	250	650	11
FS 2045	0 to 450mm	190mm	450	AC 240	560	250	650	13.5
FSD 1045	0 to 170 mm	90mm	200	AC 240	460	170	250	4
FSD 1545	0 to 170 mm	140mm	300	AC 240	460	170	250	4.5



Foil Sealer (FS)



Foil Sealer Delta



## Hand wrapper HW 450

- | Ideal for wrapping cling film | Suitable for super markets, fruit stalls, Bakeries, frozen foods etc | Enhanced display on the shelf

### Technical specifications

Model	Hand wrapper - HW 450
Voltage	240 V 1Phase
Power	50W
Film width	up to 450mm



## Hot air gun

The Stylish Hot Air Gun from Sepack is generally used for shrink wrapping of objects like bottles, containers, tray, hardware items & spare parts. Shrink wrapping provides an attractive pilfer proof shape hugging protection.

### Technical specifications

Air flow :	250/500LPM
Temp :	400°C/550°C
Voltage :	240V/50Hz
Power :	1600W



## Carton sealer

A hand held tool for dispensing BOPP adhesive tapes over boxes, containers etc.

Sepack Clip master & Strap master makes an ideal combination of hand tools for 'crimping the seal into place' effortlessly. Used for steel sealing clips.

### SEPACK CLIPMASTER STRAPPING SEALER



### SEPACK STRAPMASTER STRAPPING TENSIONER



Clip sizes: 0.6mm to 0.9mm Thick Steel Clip, 14mm - 19mm Width  
Straps size: 0.6mm to 0.9mm Thick, PP Strap - 13mm - 19mm Width  
Sealing type: Double Notch



## Sepack SmartCode 4L

Offers smart economical coding solution for pouches, labels etc.  
Supported letter types: Polymer (4mm)  
Max No of Lines: 4  
Max Print Height: 55mm  
Ink Type: Anti Freeze 2R Grade(Black)