


PINKTO CHEMICALS



A CRISIL Certified Company
410001301153

Q.C. Laboratory

Technical Data Sheet

Zinc Chloride (ZnCl₂)

CAS No.: 7646-85-7
HSN Code: 28273990

(Synonym: Zinc Chloride Powder)

Molecular Formula: ZnCl₂

Molecular Weight: 136.30


Grade: CG - 82

PARTICULARS	SPECIFICATIONS
Appearance	White, Deliquescent Crystalline Powder
Assay	82% (min)
Zinc (Zn)	39.4% (min)

Note: All the afore-mentioned specifications are standard. Specifications can be tailor-made as per requirement.

PINKTO CHEMICALS

A CRISIL Certified Company
410001301153



Q.C. Laboratory

Properties

Appearance	White powder of granule in solid state. Colorless and transparent water-solution in liquid state
Melting point	283°C
Boiling point	732°C
Flash point	-19°C
Toxicology Information	Highly Hygroscopic
Limit of ox chloride	Dissolve 1.0 g in 20 ml of water; add 20 ml of alcohol, and mix. To 10 ml of the mixture add 0.30 ml of 1.0 N hydrochloric acid: the solution becomes perfectly clear.
Relative Density	2.91 (25°C / 4 °c)
Solubility	High solubility in water, deliquescent
Identification	A solution of it responds to the tests for Zinc and for Chloride.
Organic volatile impurities	meets the requirements

Storage & Transportation


- Should be stored in ventilated, dry coffer
- Bags must be sealed to prevent moisture.
- Not to be kept with the consumable goods and feed during storage or shipment.
- Transportation should be covered to prevent rain and sun.
- To be handled gently, to prevent the packaging rupture.

Packaging

- 25kg/ 50kg HDPE Marked Bags with double poly-line inside
- 50kg HDPE/Galvanized Drums (from inside)

PINKTO CHEMICALS

A CRISIL Certified Company
410001301153



Q.C. Laboratory

Application/Uses:

Dry Cell or Batteries: Zinc chloride is commonly used in dry cell batteries as an electrolyte.

Electroplating

Galvanizing, Soldering and Tinning Fluxes: Zinc chloride is used in fluxes for galvanizing, soldering and tinning.

Agriculture

Petroleum: It is an excellent emulsion breaker and is used to separate oil from water

Water Treatment: It is used in specialty corrosion inhibitors in cooling towers, potable water, and in gas and oil wells.

Resins: It is used in Ion - Exchange resins production.

Paints: It is used in for the production of lithopone and as pigment for zinc chromate.

Rubber: It is used as accelerator in the vulcanizing process of rubber.

Glue, Wood work: Zinc chloride is used in for the preservation of glue, and for the impregnation of timber.

Textile Printing: It is used in Mordant dyeing industry, mercerizing agent and sizing agent

Odor Control: It reacts with sulfide to minimize release of H₂S gas in waste treatment facilities.

Oil-Gas Wells: High-density solutions of Zinc Chloride and calcium chloride give good performance in well completion and work-over operations.

Herbicide: It is used to control lichen and moss growing on the roofs of houses and other domestic dwellings.

Pharmaceuticals

Chemical Synthesis: It is also used in organic synthesis industry and as dehydrating agent. Zinc Chloride Anhydrous is used for Friedel Craft Reaction, Azotropic or Azeotropic Distillation.

DISCLAIMER: For R&D and Industrial use only. Not for drug or household uses.

WARRANTY: All the technical information given in this document is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Pinkto Chemicals shall not be held liable for any damage resulting from handling or from contact with the above product.