



Brilliant Engineering Works

ISO 9001:2008 Certified Company



www.brilliantengineering.in

www.brilliantengineering.net

email: marketing@brilliantengineering.in

FAST ATTACK PORTABLE WATER MONITOR. 1000 TO 2000@7 KG.



WEIGHT. BODY ASSY. 12.30 KG

NOZZLE WT. 1.44 KG.
TOTAL WT. = 13.74 KG

Technical detail of Fast Attack water monitor

- Monitor : Portable light weight
- Flow rate : 2000 LPM @ 7 kg/cm²
- MOC : Aluminum alloy Hard anodized
- Inlet connection : Double Inlet 2.5" swivel Male INST.
- Monitor outlet : 2.5" NH MALE (65 MM)
- Horizontal movement : 20` PLUS 20` MINUS. Degree 40`
- Vertical movement : 65 degree
- Vertical flow height . Approx. 25 MTR
- Horizontal flow length ; approx 45 MTR.
- Finishing : powder coating.

Brilliant Engineering Works

ISO 9001:2008 Certified Company



www.brilliantengineering.in

www.brilliantengineering.net

email: marketing@brilliantengineering.in

FAST ATTACK NOZZLE DETAIL



- FLOW RATE : 2000 LPM @ 7 BAR , 525 GPM}
- INLET COUPLING SIZE : 2 ½" NH (FEMALE INST. SWIVEL)
- PRESSURE : APPROX 7 to 12 KG / CM 2
- Throw : Approx. 45 MTR.
- MOC : HARD ANNODIZE ALUMINIUM ALLOY
- FLOW PATTERN METHOD : JET AND SPRAY
- OPERATION : MANUAL
- FLOW : Manual controls.

Brilliant Engineering Works

ISO 9001:2008 Certified Company



www.brilliantengineering.in

www.brilliantengineering.net

email: marketing@brilliantengineering.in

FAST ATTACK WATER MONITOR,S PARTS DETAIL AS.



Brilliant Engineering Works

ISO 9001:2008 Certified Company



www.brilliantengineering.in

www.brilliantengineering.net

email: marketing@brilliantengineering.in