



Product Name : - Remote Control Fire Water Monitor

Product Description

- FLOW RATE : 1000/4500LPM @ 7 BAR
- MINIMUM FLOW : 450 LPM @ 7 BAR
- MAXIMUM FLOW : 4500 LPM @ 7 BAR
- INLET FLANGE SIZE : 100 MM FLANGE 150 CLASS/80 MM.
- WORKING PRESSURE : APPROX 7 KG / CM² (7 BAR).
- TESTING PRESSURE : ON 21 kg/cm² (21 BAR) AT 15 MINUTS.
- THROW : Approx. 45 MTR.
- MOC : Stainless Steel 304/316.
- FLOW PATTERN METHOD : JET AND SPRAY BY LINIER ACTATURE/24 VOLT DC.
- HORJONTAL ROTATION : MIN. 30 DEGREE TO 260 DEGREE BY R.C. MOTOR 1/4 HP AC/DC /24 VOLT

- VERTICAL ROTATION. : MINUS 35 DEGREE AND + 85 DEGREE BY R.C MOTOR 1/4 HP AC/DC .24 V.
- REMOTE CONTROL : YES ALL THREE DIMENTIONS BY ELECTICAL PANNAL AND MAUAL SWITCHS.
- COLOR PAINT : NATURAL / FIRE RED.



