

# FRIABILITY TEST APPARATUS MODEL: VFT-DV



### **SPECIFICATIONS**

• No. of drums: 2

Fixed RPM: 25 RPMAccuracy: ±1 rotation

• Timer: Settable upto 11 hrs 59min 59sec

Rotation: 1 to 9999 rotations
Display: 2 Line LCD Display
Input: 4 x 4 Matrix Keyboard
Power: 220/230 VA C 50/60Hz

less than 25 VA.

Unit FABRICATED IN S.S. CABINET is also available.

## FRIABILITY TEST APPARATUS MODEL: VFT-2D

### FEATURES - ECONOMICAL VERSION

- Micro-controller based friability test apparatus.
- Equipped with two lines LCD display screen.
- · Audio signal indicates Test over.

Unit FABRICATED IN S.S. CABINET is also available.

#### **FEATURES**

- · Front loading system.
- Interlocking mechanism to ensure correct drum position.
- · User friendly operation.
- 4x4 matrix Alpha numerical splash proof keyboard for entries like sample name, batch number.
- · Programmable modes for timer or rotation.
- · Automatic discharge facility
- Total number of drum rotations can be set in the range of 1 to 9999.
- Instrument complies with USP, BP, and IP specifications.
- Instrument can tilt 10 Degree as per specification.
- It supports regular friability drum & abrasion drum.
- Balance interface for sample weight transfer.
- Parallel port for test report print.

