



Article Name: Harvey

Operative Standard	Meets IS 15298:2011 Part II & EN 20345
Description	Black Plastic Eyelet safety Derby Shoe, Single Density Slip resistant Direct Injected PU Sole. Nail less. As per design A , SRC
Marking	As per IS 15298 (Part 2):2011 or EN 20345 CE
Electrical Properties	Electrical. Resistance between 12 to 15KV
Upper leather	Buff Grain Apolo Textured Black Leather
Vamp lining	Non woven Polyester
Tongue & Collar	Padded Syn. Lin PU coated Codura
Quarter Lining	Black Mesh with cushion laminated
Quarter Fashion	Silver Reflector
Eyelets	Plastic Round Black eyelet
Heel Stiffener	Molded stiffener for additional support.
Steel Toecap	Composite 200 Joule Broader Toe cap EN marked
Insole	Biogiolic Non Woven Antistatic sheet
Sole	PU Single Density Black for High Durability and Flexibility, Electrical , Oil resistant, Slip resistant and shock absorbing heel, and open cleats for higher grip and self cleaning effect with better water dispersion
Sole fixation	Direct injection process on DESMA Machines
Other	Nail less construction
Lace	Round Double Colored Nylon
Socks	Full EVA padded for Extra comfort
Protection Level	S1
Size	5 - 11
Sizes	UK (Range 5-11)

