



Article Name: Marvin Low

Operative Standard	Meets IS 15298:2011 Part II & EN 20345
Description	Black 2 D-ring Sporty Safety Shoe, Single Density Slip resistant Direct Injected PU Sole. Nail less. As per design A ,
Marking	As per IS 15298 (Part 2):2011 or EN 20345
Electrical Properties	Antistatic. Resistance between 100 Kilo Ohms & 1000 mega ohms
Upper leather	Buff Suede Blue Leather
Tongue & Collar Upper	Padded Syn. Lin PU coated Codura. Tongue Bellow
Lining other than vamp	Breathable cushion laminated Grey Mesh
Eyelet	2 Rust Resistant Metal Black D-ring with PP Tape
Steel Toecap	200 Joule Broader Steel Toe cap EN marked
Insole	Biogiolic Non Woven Antistatic sheet
Sole	PU Single Density Black for High Durability and Flexibility, Antistatic, Oil resistant, Slip resistant and shock absorbing heel, and open cleats for higher grip and self cleaning effect with better water dispersion
Sole fixation	Direct injection process on DESMA Machines
Other	Nail less construction
Lace	Round Double Colored Nylon
Socks	Full EVA padded for Extra comfort
Protection Level	S1
Sizes	UK ( Range 5-11)

