

WELCOME

# Nozzle Separator

Get the Best Price.

[More Info](#)



SPFX series nozzle separator is a kind of high speed, high precision and high efficiency continuous discharge separator. Several nozzles are installed outside of the bowl wall, insoluble solids which deposit in the sediment chamber will be discharged out continuously under the centrifugal force formed by high rotation speed of bowl. This separator is suitable for solid liquid two phase separation and concentration which content high solid content ( max30%), such as fermentation liquor, sludge, Koolmic and so on.



[Send Inquiry](#)



[Send Inquiry](#)

Model	Treatment Capacity (m <sup>3</sup> /h)	Inlet Pressure (MPa)	Outlet Pressure (MPa)	Motor Power (Kw)	Weight (kg)	Outline Dimension (mm)
SPFX430	5-20	0.2	≤0.2	15	1250	1519x962x1484
SPFX445	5-25	0.1	≤0.2	30	1300	1386x1265x1484
SPFX470	7.5-30	0.2	≤0.2	30	1720	1780x1154x1710
SPFX550	25-50	0.2	≤0.2	45	2500	1860x1300x1860
SPFX630	30-70	0.1	≤0.2	75	3000	2130x1595x2242
SPFX720	45-90	0.2	≤0.2	75, 90	3200	2130x1595x2242

SARTHAK ENGINEERING  
GST : 08APP160Q1Z4

- No. No. 41-117, Kumbhari, Sarpat - 431002, Nagpur, India
- Phone : 0804381644
- Mr. Mishra (Marketing Manager)
- Mobile : 9304886424 ( Please Add Another Number ) - 91 8948 5699

[Send Inquiry](#)

[Send SMS](#)

[Call Me Free](#)

- Home Page
- Company Profile
- Our Products
- Contact Us
- Site Map

