

# MILK VENDING MACHINE

Capacity 300 LTR & 500 LTR.



**BOOTH TYPE**



**MOBILE TYPE**  
(Suitable for Vehicle Mounted)



**SERVING IN MORE THAN 35 COUNTRIES FOR MORE THAN 35 YEARS**

## Salient Features :

- Weighing based technique .
- Dispensing by Calibrated RFID Panel.
- Dispensing in both Rupee & Litre Selectable Mode.
- 12 V DC & 220V AC Operating System.
- Password Facility to change data, time & date.
- Effortless Data maintaining system
- Faster cooling owing to direct expansion
- Blue tooth Connectivity to machine available.
- Password facility for protection from frauds.
- Online Power Back up System.

**Capacity 300 LTR & 500 LTR.**

*W*orldwide Dairy Equipments

- MILK CANS
- MILK COOLING TANKS
- CREAM SEPARATOR
- BUTTER CHURNER
- DAIRY INSTALLATION
- ALL SORTS OF DAIRY EQUIPMENTS
- AUTOMATIC MILK VENDING MACHINE

## MAJOR SPECIFICATIONS OF MILK VENDING MACHINE

Particulars	300 LTR.	500 LTR.	500 LTR. (MOBILE)
Model No.	BI-DX-SVM-300	BI-DX-SVM-500	BI-DX-MVM-500
Rated Capacity	300	500	500
Thermo Plate	Laser Welded	Laser Welded	Laser Welded
Construction Material	AISI 304 SS	AISI 304 SS	AISI 304 SS
Type of tank	Rectangular	Rectangular	Horizontal Cylindrical
CIP Facility	Manually	Manually	Manually
Insulation Thickness	50mm	50mm	50mm
MAKE OF COMPRESSOR	EMERSON COPELAND / DANFOSS	EMERSON COPELAND / DANFOSS	NA
COOLING CAPACITY	2250 Kcal / Hr.	4500 Kcal / Hr.	NA
TYPE OF REFRIGERENT	R-22 / R-404	R-22 / R-404	NA
MAX. COOLING TIME	3 Hours	3 Hours	NA
TEMP. RANGE CONSIDERED	18->4 C	18->4 C	NA
POWER REQUIREMENT	Single Phase	Single Phase	Single Phase
CONNECTING LOAD	2.5 KW	6 KW	NA
BATTERY -UPS BACK UP	12 V/ 100 AH	12 V/ 100 AH	12 V/ 100 AH
	700VA, INPUT : 230VAC / 50HZ	700VA, INPUT : 230VAC / 50HZ	700VA, INPUT : 230VAC / 50HZ
DISPENSING TECHNOLOGY	RFID Panel	RFID Panel	RFID Panel
DISPENSING MEDIUM	Smart Cards	Smart Cards	Smart Cards
VENDING OPTIONS	250mL, 500mL, 1000mL, 2000mL, 5000mL, Rs. 5, Rs. 10, Rs. 50, Rs. 100	250mL, 500mL, 1000mL, 2000mL, 5000mL, Rs. 5, Rs. 10, Rs. 50, Rs. 100	250mL, 500mL, 1000mL, 2000mL, 5000mL, Rs. 5, Rs. 10, Rs. 50, Rs. 100
ACCURACY	±1 %	±1 %	±1 %
OVERALL DIMENSION	1165 X 905 X 1970 MM	1565 X 1100 X 1970 MM	1450 X 1100 X 1170 MM
POWER BACK UP TIME	24Hr	24Hr	24Hr

**MANUFACTURERS & EXPORTERS**

**BIMAL ALUMINIUM PVT. LTD.**

35, Industrial Estate, Phase II,  
Yamuna Nagar - 135 001, HARYANA, INDIA

Ph.: +91-1732-250131

e-mail : [info@bimalindia.com](mailto:info@bimalindia.com), website : [www.bimalindia.net](http://www.bimalindia.net)