



Xchange Color Model 1279



20 MP Images
¼ sec Trigger Speed
Xchange Flash System



Cuddeback's Xchange Black Flash® is a totally new concept in trail cameras. Interchangeable flash modules allow the camera to become a color, IR or Black Flash. Xchange LED modules feature 30 LEDs for maximum performance. Xchange strobe features a 1.5" strobe with 370uF capacitors.

Featuring an industry leading ¼ second trigger speed that captures the deer that so many other cameras would miss. Then add a Super-Fast Recovery Speed that is ready for the next picture within 1 second of taking the first, and the result is Cuddeback can capture 2 photos before many cameras can capture the first.

And the pictures are incredible. 20MP images with stunning daylight color and color night images.

On top of the performance, we added a ton of cool and innovative features, such as Zone Control, separate day/night delays, fully customizable time lapse and many more.

We even reinvented the mounting system to make it easier and more versatile to deploy the camera. With Genius Mount the user does not bang the camera around while strapping it to a tree, he simply straps (or screws) the mount to the tree then slides the camera on and off as needed. Plus, optional mounts allow panning, tilting, and locking.

Cuddeback Xchange – versatility and performance.

Model 1279 includes a color strobe module. Other flash modules sold separately.





Xchange Color Model 1279

20 MP Images
¼ second trigger speed
Strobe flash for 100 foot range

Feature	Setting	Advantage
Flash Technology	Color Strobe	Color strobe with 570uF capacitors & 1 inch tube
Flash Power		Flash range is highly dependent upon the setting, but in a forest deer can be identified to 100 feet.
Trigger Speed	¼ second	Fast trigger speeds allows the camera to capture moving animals before they move beyond the view of the camera.
Recovery Speed	1 to 2 seconds	The camera can be ready for the 2 nd shot 1 to 2 seconds after the first allowing the camera to capture a second animal following the first.
Battery System	AA battery, quantity 8	AA batteries allows the camera to be very small.
Battery Life	Up to 12 months Over 10,000 images	Battery life is dependent on battery quality, run days, number of images taken, temperature, and other factors.
Day Images	Full Color	5MP or 20MP color images with stunning clarity.
Night Images	IR Black and White	5MP or 20MP properly exposed b/w images with good black and white definition. No-glow images are not good as IR, but still very good image quality.
Image Imprint	Date, Time, Moon Phase, CAM ID	Black bar provides clear identification.
Zone Control	Yes (Select wide/narrow)	Set the animal detector to wide view or narrow view as required by the situation.
Time Lapse	10 seconds to 24 hours	Allows different settings for day and night.
Camera Delays	1 second to 60 minutes	Provide versatility for trails, scrapes, food plots and feeders.
Burst Mode	1 to 5 images	Select to trigger multiple images per event.
Day & Night Modes	Separate day and night	Separate delays, time lapse, images, video, & burst for day and night.
No Card Mode	Yes	Camera will continue to record images without an SD card.
Operating Modes	EZ & Advanced	Use EZ mode for simple setup and use. Use Advanced Mode for more control over the camera settings.
Video with sound	Yes – 10, 20, 30 seconds	Can record an image with video.
HD Size Images	Yes (16:9)	Select for wide format images.
Full Size Images	Yes (4:3)	Select for full sized images.
Genius Mount	Yes	Easier to deploy a camera when the mount is separated from the camera. Optional pan, tilt, lock sold separately.
Conformal Coated Electronics	Yes	Waterproof coating on all electronics provides enhanced protection from humidity and water.
Warranty Tracker	Yes	No receipt required to validate warranty.
5:2:1 Warranty	Yes	1 year standard warranty. 2 years with online registration. 5 year reduced cost replacement program.

Learn more at www.cuddeback.com

Non Typical, Inc. - PO Box 10447 - Green Bay, WI 54307

Since 1989 – the World’s Oldest Trail Camera Company