

TORQUE WRENCHES

NEW

NORTRONIC® WRENCH

Wireless and traceable electronic torque and angle control

- Supplied with traceable calibration certificate for torque and certificate of angle calibration
- Accurate to $\pm 1\%$ from 20% to 100% of full scale. $\pm 2\%$ from 10% to 19% of full scale
- Angle accurate to $\pm 1\%$ plus one digit (clockwise)
- Supplied with a robust ratchet and compatible with Norbar's huge range of spanner end fittings
- Test results are time and date stamped
- Performs to IP44 for resistance to dust and water ingress
- Displays torque only or torque and angle
- Two full colour OLED displays positioned at 90° for great visibility
- Colour indicator on display changes when target torque/angle has been reached
- Audible and vibration feedback when set target of torque/angle has been reached
- TDS (Torque Data System) software included
- Torque and angle readings can be sent to TDS in real time (or downloaded) via the USB and wireless interfaces
- Wireless PC adapter available separately. Each adapter can register up to 8 NorTronic® wrenches
- NorTronic® can be set up either on the wrench or via the TDS software. Settings can be locked from the TDS software

Range N·m	Model
NorTronic Wrench	
5-50	50
20-200	200
30-330	330

ELECTRONIC TORQUE TOOLS

EVOTORQUE®

Norbar's Electronic Torque Tool utilises patent pending motor technology to give unprecedented joint control.

- Each tool is factory calibrated to $\pm 3\%$
- Dual torque units, N-m or lbf-ft can be set by the operator
- Performs to IP44 for resistance to dust and water ingress
- Correct torque output from hard through to soft joints
- Can safely be used on pre-tightened bolts as part of a joint verification process
- Torque Control or Angle Control is selected by the operator on the tool
- Clear signalling on the tool that correct torque and angle has been achieved
- Easily removable secondary handle for balanced handling of tool
- Reaction spline arrangement is identical to corresponding PneuTorque®
- 110v and 230v versions available





NEW

Range N·m	Model
 200-1000	ET-72-1000-B
 270-1350	ET-72-1350-B
 400-2000	ET-72-2000-B
 800-4000	ET-92-4000-B
 1200-6000	ET-119-6000-B

