



## SCREW SUPPORT MOUNTS, Series DLC



**Dynemech** DLC Series Mounts are simple and effective vibration dampers for machines with respective holes in the base. These mounts offer both low frequency attenuation and stable machine levelling.

| Model  | Load Kg/pc | Model  | Load Kg/pc | Model   | Load Kg/pc | Model   | Load Kg/pc | Model  | Load Kg/pc | Bolt Size | Dia (D) mm | H u/m/p1 | H s2/i | Adj. mm |
|--------|------------|--------|------------|---------|------------|---------|------------|--------|------------|-----------|------------|----------|--------|---------|
| DLC1-u | 150        | DLC1-m | 190        | DLC1-p1 | 75         | DLC1-s2 | 125        | DLC1-i | 250        | M 12x100  | 65         | 30       | 40     | 6       |
| DLC2-u | 350        | DLC2-m | 450        | DLC2-p1 | 175        | DLC2-s2 | 300        | DLC2-i | 575        | M 12x100  | 98         | 37       | 47     | 8       |
| DLC3-u | 600        | DLC3-m | 800        | DLC3-p1 | 300        | DLC3-s2 | 550        | DLC3-i | 1000       | M 16x100  | 125        | 44       | 54     | 8       |
| DLC4-u | 900        | DLC4-m | 1150       | DLC4-p1 | 500        | DLC4-s2 | 850        | DLC4-i | 1600       | M 16x100  | 150        | 46       | 56     | 10      |
| DLC5-u | 1400       | DLC5-m | 1750       | DLC5-p1 | 700        | DLC5-s2 | 1250       | DLC5-i | 2300       | M 18x150  | 180        | 48       | 58     | 10      |
| DLC6-u | 1900       | DLC6-m | 2400       | DLC6-p1 | 950        | DLC6-s2 | 1700       | DLC6-i | 3100       | M 20x150  | 204        | 52       | 62     | 12      |
| DLC7-u | 2500       | DLC7-m | 3200       | DLC7-p1 | 1250       | DLC7-s2 | 2200       | DLC7-i | 4000       | M 20x150  | 235        | 57       | 67     | 12      |
| DLC8-u | 3500       | DLC8-m | 4000       | DLC8-p1 | 1500       | DLC8-s2 | 2800       | DLC8-i | 5200       | M 24x200  | 270        | 72       | 82     | 18      |
| DLC9-u | 4200       | DLC9-m | 5000       | DLC9-p1 | 1900       | DLC9-s2 | 3500       | DLC9-i | 6500       | M 24x200  | 302        | 84       | 94     | 18      |

## SCREW SUPPORT MOUNTS, Series DL



**Dynemech** DL Series is used for light to medium weight machines suited to levelling screw support or having tapped hole in the base.

**Dynemech** DLS Series Mounts, developed in stainless steel finds application in pharmaceutical, food and beverages processing and packaging units, medical equipment manufacturing and chemical processing industries. Provide vibration isolation with complete hygienic seal and corrosion resistance.

| Model | Load Kg/pc | Model | Load Kg/pc | Model  | Load Kg/pc | Model  | Load Kg/pc | Model  | Load Kg/pc | Dia (D) mm | H u/m/p1 | H s1 | H s2 |
|-------|------------|-------|------------|--------|------------|--------|------------|--------|------------|------------|----------|------|------|
| DL1-u | 150        | DL1-m | 190        | DL1-p1 | 75         | DL1-s1 | 80         | DL1-s2 | 125        | 55         | 21       | 26   | 31   |
| DL2-u | 350        | DL2-m | 450        | DL2-p1 | 175        | DL2-s1 | 200        | DL2-s2 | 300        | 85         | 25       | 30   | 35   |
| DL3-u | 600        | DL3-m | 800        | DL3-p1 | 300        | DL3-s1 | 375        | DL3-s2 | 550        | 112        | 28       | 33   | 38   |
| DL4-u | 900        | DL4-m | 1150       | DL4-p1 | 500        | DL4-s1 | 575        | DL4-s2 | 850        | 135        | 30       | 35   | 40   |
| DL5-u | 1400       | DL5-m | 1750       | DL5-p1 | 700        | DL5-s1 | 800        | DL5-s2 | 1250       | 160        | 30       | 35   | 40   |
| DL6-u | 1900       | DL6-m | 2400       | DL6-p1 | 950        | DL6-s1 | 1100       | DL6-s2 | 1700       | 185        | 34       | 39   | 44   |
| DL7-u | 2500       | DL7-m | 3200       | DL7-p1 | 1250       | DL7-s1 | 1500       | DL7-s2 | 2200       | 215        | 37       | 42   | 47   |
| DL8-u | 3500       | DL8-m | 4000       | DL8-p1 | 1500       | DL8-s1 | 1900       | DL8-s2 | 2800       | 249        | 44       | 49   | 54   |
| DL9-u | 4200       | DL9-m | 5000       | DL9-p1 | 1900       | DL9-s1 | 2400       | DL9-s2 | 3500       | 276        | 43       | 48   | 53   |