





Cable Ties & Accessories

(An ISO 9001:2015; 14001:2015;
45001:2018 & CE Certified Company, UL Approved)



Correspondence Address :

Nirupam Co-operative Society
Langalpotta, Bishnupur, Rajarhat
(Near 211A Bus Stand, Opp. Merlin Rise)
Kolkata - 700 135, West Bengal, INDIA
Mobile : +91 89105 93201, 78118 24435
E-mail : yashsyndpltd@gmail.com
Website : www.yashsyndicate.com

Registered Office :

194/4, Bangur Avenue, Block - B, 2nd Floor, Kolkata - 700 055

ABOUT US

Established in 2003, Yash Syndicate Pvt Ltd, is acknowledged as one of the most respected manufacturers of Nylon Cable Ties, Push Mount Ties, Security Ties, Marker Ties and other wiring accessories to cater the needs of industrial and OEM Customers all over the world.

Located in Kolkata, West Bengal, India, the plant has a total carpet area of 45000 sqft., divided equally for raw material storage and machinery. We also have separate area for storage with capacity of holding approximately 1,000 tons of raw material, 100 tons of finished goods and nearly 15,000 cartons of goods. We have invested abundant resources in both R&D and employment training programs. The company took the lead in applying ISO9001 Quality Management System, ISO14001 Environment Management System, and ISO45001 in health and safety at work. Also our products are UL and CE Certified.

We are fully aware of the fact that that only “Versatile Staff, Distinctive Quality and Advanced Technology” can help us survive and succeed in today's intensively competitive market. Hence, along with High-Speed World-Class injection Moulding Technology sourced directly from Japan and United States, we reassure TRUST to our customers with quality products.

Enquiries from both domestic and overseas customers are cordially welcomed.

MATERIAL SPECIALITY

Polyamide 66 (Nylon 66) / Polyamide 6 (Nylon 6)	STANDARD	<ol style="list-style-type: none"> 1. High Water absorption. 2. Good surface lubricity, abrasion resistance. 3. Good mechanical Properties. 4. Good insulation. 5. UL94 Flammability Rating V-2. 6. Good resistance to chemicals, especially for alkali. 7. Compare with Nylon 6, Nylon 66 has better toughness and better resistance to abrasion, heat and fatigue.
Polyamide 66 (Nylon 66) / Polyamide 6 (Nylon 6)	UV RESISTANCE (W)	<ol style="list-style-type: none"> 1. High Water absorption. 2. Good surface lubricity, abrasion resistance. 3. Good mechanical Properties. 4. Good insulation. 5. UL94 Flammability Rating V-2. 6. Good resistance to chemicals, especially for alkali. 7. Compare with standard Nylon 6, Nylon 66-W has better UV resistant.
Polyamide 66 (Nylon 66)	HEAT RESISTANCE (HS)	<ol style="list-style-type: none"> 1. High Water absorption. 2. Good surface lubricity, abrasion resistance. 3. Good mechanical Properties. 4. Good insulation. 5. UL94 Flammability Rating V-2. 6. Good resistance to chemicals, especially for alkali. 7. Compare with standard Nylon 6, Nylon 66-HS has better high temperature resistant.
Polyamide 66 (Nylon 66)	FLAME RESISTANCE (V0)	<ol style="list-style-type: none"> 1. High Water absorption. 2. Good surface lubricity, abrasion resistance. 3. Good mechanical Properties. 4. Good insulation. 5. UL94 Flammability Rating V0. 6. Good resistance to chemicals, especially for alkali. 7. Compare with standard Nylon 6, Nylon 66-V0 has better flammability rating.

ORDERING INFORMATION

Material	Color	Suffix	Item No.
STANDARD	Natural / Black	—	YT-100 / YT100B
UV RESISTANCE	Black	W	YT-100W
HEAT STABILIZED	Light Green	HS	YT-100HS
FLAME RESISTANCE	White	V0	YT-100V0

CERTIFICATES

The image displays several certification documents for Yash Syndicate Pvt. Ltd. The primary certificates are ISO 9001:2015, ISO 14001:2015, and ISO 45001:2018, all issued by Bureau Veritas Certification. Additionally, there are PAIR Certification Services certificates for CE, UL, and RoHS compliance. The certificates include company details, accreditation logos, and specific product or process information.

NYLON CABLE TIES

UL Number : E532506



Model No.	Cable Length		Cable Tie Width		Max. Bundle Diameter		Tensile Strength	
	MM	INCH	MM	INCH	MM	INCH	KGF	LBS

YT-100L x 1.8	100	4	1.8	0.07	20	0.79	8	18
YT-100M x 2.2	100	6	2.2	0.09	22	0.87	8	18
YT-150L x 2.0	150	6	2	0.078	35	1.38	8	18
YT-200L x 2.2	150	6	2.2	0.09	35	1.38	8	18
YT-250L x 2.8	250	10.6	2.8	0.11	65	2.9	14	31
YT-300L x 2.8	300	12	2.8	0.11	75	2.95	14	31

YT-100 x 2.5	100	4	2.5	0.1	20	0.79	8	18
YT-150 x 2.5	150	6	2.5	0.1	35	1.38	8	18
YT-200M x 2.5	200	8	2.5	0.1	45	1.77	8	18
YT-150S x 3.2	150	6	3.2	0.12	35	1.38	18	40
YT-200M x 3.2	200	6	3.2	0.12	45	1.77	18	40
YT-250M x 3.2	250	10.6	3.2	0.12	68	2.67	18	40
YT-300M x 3.2	300	12	3.2	0.12	82	3.23	18	40
YT-368M x 3.2	368	14.5	3.2	0.12	105	4.13	18	40

YT-150M x 3.6	150	6	3.6	0.14	35	1.38	18	40
YT-200 x 3.6	200	8	3.6	0.14	45	1.77	18	40
YT-250D x 3.6	250	10	3.6	0.14	65	2.9	18	40
YT-300D x 3.6	300	12	3.6	0.14	75	2.95	18	40
YT-350 x 3.6	350	14	3.6	0.14	90	3.54	18	40
YT-400 x 3.6	400	16	3.6	0.14	100	3.94	18	40

YT-250S x 4.2	250	10	4.2	0.17	68	2.68	22.7	50
YT-300S x 4.2	300	12	4.2	0.17	82	3.23	22.7	50
YT-200H x 4.6	200	8	4.6	0.19	45	1.77	22.7	50
YT-250H x 4.8	250	10	4.8	0.19	65	2.9	22.7	50
YT-300 x 4.8	300	12	4.8	0.19	75	2.95	22.7	50
YT-368 x 4.8	368	14.5	4.8	0.19	95	3.94	22.7	50
YT-450 x 4.8	450	18	4.8	0.19	115	4.52	22.7	50
YT-500 x 4.8	500	20	4.8	0.19	130	5.11	22.7	50

YT-300H x 7.6	300	12	7.6	0.29	75	2.95	54.4	120
YT-380 x 7.6	380	15	7.6	0.29	95	3.94	54.4	120
YT-450 x 7.6	450	18	7.6	0.29	110	4.33	54.4	120
YT-550 x 7.6	550	21.7	7.6	0.29	140	5.551	54.4	120
YT-610 x 7.6	610	24	7.6	0.29	180	7.1	54.4	120
YT-710 x 7.6	710	28	7.6	0.29	220	8.66	54.4	120

- Material : UL approved NYLON 66, 94V-2
- Colour : Natural, Black & Other Colours on request
- UV resistant Black for all sizes available
- Max Operating Temperature upto 85°C

PG THREAD CABLE GLANDS



Item No.	Thread Size	Cable Range (mm)	Thread O. D. L2 (mm)	Thread Length L1 (mm)	Spanner Size A&E (mm)
PG-7	PG-7	3-6.5	12.5	9	18/16
PG-9	PG-9	4-8	15.2	9	22/19
PG-11	PG-11	5-10	18.6	9	24/22
PG-13.5	PG-13.5	6-11	20.4	10	27/24
PG-16	PG-16	10-13	22.5	10	30/27
PG-19	PG-19	12-15	24	10	30/28
PG-21	PG-21	13-18	28.3	12	35/33
PG-25	PG-25	16-21	30	12	37/35
PG-29	PG-29	18-25	37	12	45/42
PG-36	PG-36	22-32	47	15	58/52
PG-42	PG-42	32-38	54	18	62/58
PG-48	PG-48	37-44	59.3	18	70/64
PG-63	PG-63	42-50	71	30	83/77

M THREAD CABLE GLANDS



Item No.	Thread Size	Cable Range (mm)	Thread O. D. L2 (mm)	Thread Length L1 (mm)	Spanner Size A&E (mm)
M-12	M12x1.5	3-6.5	12	9	18/16
M-15	M15x1.5	4-8	15	9	22/19
M-18	M18x1.5	5-10	18	9	24/22
M-20	M20x1.5	6-11	20	10	27/24
M-25	M25x1.5	13-18	25	11	31/28
M-32	M32x1.5	18-25	32	12	38/35
M-40	M40x1.5	22-32	40	15	52/52
M-50	M50x1.5	37-44	50	18	62/58
M-53	M53x1.5	37-44	53	18	64/61

- Material : Polyamide 66 (Nylon 66)
- Color : Black, available in other colors.
- Suit a variety of applications, and diverse industries.
- Function : Mount gland to pre-drilled panel hole, use locknut to fix gland on board, insert the cables in the seal, and then tighten up the nut to hold cables in position.


SCREW MOUNTING TIE



Item No.	L	W	A	Max. Bundle Dia (MM)	Min. Loop Tensile Strength	
					LBS	KGS
SMT-155	171.5	3.7	5.2	40	40	18
SMT-205	219	4.2	5.2	60	50	22

- Material : UL approved NYLON 66, 94V-2
- The cable tie can be secured to panel with a single bolt.

MARKER TIES



Item No.	Length		Width (MM)	Bundle Dia (MM)	Min. Loop Tensile Strength		Marking Pad Size
	INCH	MM			LBS	KGS	
YMT-100	4	100	2.5	22	18	8.0	25x8
YMT-110	4 1/3	110	2.5	22	18	8.0	21x10
YMT-200	8	200	2.5	22	18	8	25x8

- Material : Nylon 66 94V-2, Acid-control and not easy to age.
- Write markings on the black tag at the entrance of cable ties.


CABLE TIE MOUNT



Item No.	Length (MM)	Width (MM)	Height (MM)	Mounting Hole	T
YTM-19	19	19	4.5	3.4	4
YTM-25	26.1	26.1	6	4.3	8

- Material : UL approved NYLON 66, 94V-2 with adhesive tape.
- Colour : Natural, available in other colours.
- To apply, simply peel off liner, and apply mount to surface. After that cable ties can be inserted to secure wire bundles

PUSH MOUNT TIES



Item No.	Length (MM)	Width (MM)	Bundle Dia (MM)	Chasis	Mounting Hole	Min. Loop Tensile Strength	
						LBS	KGS
YPMT-157	168	3.8	40	4.8	3	40	18

- Material : UL Approved Nylon - 66, 94V-2
- Press the tie into a pre-drilled hole and bind the cord by securing the tie

NAIL CLIP



Item No.	W	H1	H	Marking Pad
NC-0.35N	3.5	3.7	5.9	2x15
NC-0.4N	4	4.2	6.6	2.5x18
NC-0.5N	5	5	7.6	2.5x18
NC-1N	6	6.6	9.6	2.5x18
NC-1.5N	7	7.5	11	2.5x22
NC-2N	8	8.2	12.9	2.5x22
NC-3N	10	10.4	13.8	2.5x25
NC-4N	12	12.3	16	2.5x27
NC-6N	14	15.6	20	3x35

- Material : PE
- With nail inserted, Steel nail for Masonry
- Color: White/Grey/Black (other available upon request)

SECURITY TIES



Item No.	Length (MM)	Width (MM)	Max. Bundle Dia (MM)
YST-250	250	3.5	55

- Material : UL Approved Nylon - 66, 94V-2
- Flame Rated : UL94V-2
- Marking : Laser marking for company logo, custom text, and custom numbering.

CLOSE END WIRE CONNECTORS



Item No.	Dimension (MM)			Wire Range	
	A	B	C	A.W.G.	mm ²
CE-1	2.6	7.8	18	22-16	0.5-1.5
CE-2	3.1	9.5	19.7	16-14	1.5-2.5
CE-5	4.4	12.5	25.5	18	4-6
CE-8	5.3	14.6	27.7	8	6-10

- Material : Polyamide, UL94V-2 flame-retardant shell.

TIE GUN & DUCT CUTTER



Item No.	For Tie Width	Weight
TG-3	2.2~4.8	300 g
TG-5	2.2~4.8	333 g
TG-6	2.5~5.0	60 g
TG-7	2.5~5.0	275 g
TG-9	2.5~10.0	275 g
TG-10	4.8~13.0	320 g
TG-20	4.5~7.9	554 g
TG-21	4.6~7.9	556 g

- Economical, Pocket Use
- Twist to cut surplus tie end after tightening cable (TG-6)
- Tie gun for stainless steel tie (TG-20, TG-21)

STRAIN RELIEF BUSHING



Item No.	Wire Accomodate		Mounting Hole		Part Length	Max. Chassis Thickness
	UL Wire Size	Size	A	B		
SR-6P1 (R)	SJT 3C#18	∅7.4~∅8.2	15.9	14.0	14.8	0.5-1.6

- Material : UL approved NYLON 66, 94V-2 (Black)