

PRODUCT CATALOG

SS ENGINEERING WORKS

TABLE OF CONTENTS_____



| ABOUT US | 03 |
|---|-----|
| CERITIFICATIONS | 0 4 |
| OIL EXPELLERS | 0 5 |
| OIL FILTERS | 0 5 |
| OIL EXPELLERS | 10 |
| ROTARY GHANI | 11 |
| HYDRAULIC OILPRESS | 14 |
| ELECTRIC FRYING MACHINE | 21 |
| ROLLER FRYING MACHINE | 23 |
| CONTINUOUS FRYING MACHINE | 25 |
| CENTRIFUGAL OIL FILTER | 27 |
| VACCUME OIL FILTER | 28 |
| AIR PRESSURE OIL FILTER | 29 |
| REFINING MACHINE | 30 |
| HYDRATION MACHINE | 31 |
| OIL COOLER | 32 |
| ENVIRONMENTAL DUST REMOVAL SEPERATING MACHINE | 33 |
| CONTACT US | 34 |

ABOUT US____

Established in 2019, **SS Engineering Works** has quickly emerged as a trusted name in the machinery manufacturing sector, operating out of Indore, Madhya Pradesh, India. As a dedicated manufacturer, supplier, and service provider, the company specializes in producing a diverse range of robust industrial equipment, including Filter Presses, Hydraulic Presses, Oil Expellers, Rice Mills, Sortex Grading Machines, Rotary Ghanis, and more. With a focus on precision engineering and superior build quality, S S Engineering Works ensures that each machine delivers reliable performance and long-lasting durability, making them an ideal choice for businesses across multiple industries.

Certified under GST Number **23CHHPB6108C1Z2**, the company stands out for its transparent business practices and adherence to stringent quality standards. Backed by a skilled team of 20 employees, SS Engineering Works combines technical expertise with modern manufacturing techniques to cater to the evolving needs of its clients. The company proudly operates under the brand name S S Engineering Works, which has become synonymous with trust, quality, and innovation in the field.

The company maintains its commitment to excellence not only through product manufacturing but also through comprehensive installation and repair services, ensuring complete customer satisfaction from start to finish.

Driven by a passion for engineering excellence and a customer-first approach, S S Engineering Works continues to expand its footprint across India, offering certified, dependable, and competitively priced machinery solutions designed to support the growth and efficiency of its clients' operations.



CERTIFICATIONS


Sonu Vishwakarma



We are a trusted manufacturer and supplier of precision-engineered machinery, dedicated to delivering consistent quality and reliable performance. Backed by years of expertise and certified to meet stringent international standards, our products are built to last and designed to enhance productivity across industries. Every machine undergoes thorough quality checks and adheres to strict safety guidelines, reflecting our commitment to excellence and customer satisfaction. With a reputation grounded in integrity and innovation, we partner closely with clients to provide tailored solutions that meet diverse operational needs. Our certified processes and transparent business practices ensure not only high performance but also peace of mind, making us a preferred choice for businesses seeking durable and efficient machinery. Trust us to power your growth with technology you can rely on.









OIL EXPELERS



A 95-10, 120, 130, 150

Automatic Combined Oil Press With Vaccume Oil Press



A 95-10, 120, 130, 150

Automatic Combined Oil Press With Air Press Oil Press

OIL EXPELERS.



A 95-10, 120, 130, 150

Intelligent Temprature Controlled Oil Press



85

Automatic Combined Oil Press With Vaccume Oil Press

OIL EXPELERS_



▲ 60, 85 Single Oil Press




▲ 95-10, 120, 130, 150 Single Oil Press

TECHNICAL PARAMETER DETAIL _____

| Product Detail | | | | | | |
|----------------|------------------------|------------------------------|---------------------------|--------|----------------|-------------|
| MODEL | Processing Capacity | Press Screw Speed (r/min) | Measurement mm (L*W*H) | Weight | Motor Power KW | Motor Model |
| SS_60 | 1 | 38 | 1020x400x1180 | 150 | 3 | 100L-4 |
| SS_85 | 1.8 | 42 | 1085x500x1130 | 250 | 5.5 | 132L-4 |
| SS_95-10 | 4.5 | 30 | 1650x500x1320 | 500 | 7.5-11 | 160M-6 |
| SS_120 | 6.5 | 30 | 1800x500x1400 | 600 | 11 | 160L-6 |
| SS_130 | 10 | 34 | 1900x650x1600 | 800 | 18.5 | 180M-4 |
| SS_150 | 12 | 34 | 2100x650x1600 | 900 | 22 | 200L2-4 |

AUTOMATIC COMBINED OIL PRESS WITH VACCUME OIL FILTER

| Technical Parameter | | |
|---------------------|--------|--|
| MODEL | SS_150 | |
| HOST POWER(KW) | 22 | |
| OIL FILTER POWER | 2.2 | |





COLD PRESS OIL FILTER MACHINE

| MODEL | CAPACITY (l/h) |
|-------|----------------|
| 12x12 | 100 |
| 14×14 | 120-140 |
| 16x16 | 150-180 |
| 18x18 | 200-240 |
| 24x24 | 300-320 |



WOODEN GHANI COLD PRESS OIL EXTRACTION MACHINE

| MODEL | WOODEN LATEST 3HP-5HP |
|--------------------------|-----------------------|
| HOST POWER(KW) | 2.2-4.3 |
| CAPACITY | 0.6T/Day |
| PRESS SHAFT SPEED (Kg/h) | 20-25 |
| MEASEREMENT (MM)(L*W*H) | 800x1000x1800 |
| WEIGHT (KG) | 550 |



ROTARY GHANI COLD PRESS OIL EXTRACTION MACHINE

| MODEL | DOLPHIN – 7.5HP/10HP |
|--------------------------|----------------------|
| HOST POWER(KW) | 5.5 |
| CAPACITY | 1.1T/Day |
| PRESS SHAFT SPEED (Kg/h) | 35-40 |
| MEASEREMENT (MM)(L*W*H) | 1200x400x1200 |
| WEIGHT (KG) | 650 |



ROTARY GHANI COLD PRESS OIL EXTRACTION MACHINE

| MODEL | PORTABLE – 3HP/5HP |
|--------------------------|--------------------|
| HOST POWER(KW) | 2.2 |
| CAPACITY | 0.48T/Day |
| PRESS SHAFT SPEED (Kg/h) | 15-20 |
| MEASEREMENT (MM)(L*W*H) | 900x400x900 |
| WEIGHT (KG) | 350 |



AUTOMATIC HYDRAULIC OIL PRESSER150 TON

| Technical Parameter | | |
|-------------------------|--------------------------|--|
| MODEL | SS150TB | |
| MOTOR POWER(KW) | 1.5kw | |
| CAPACITY | 5.5kg/batch 33kg/Hour | |
| VOLTAGE | 220V/50hz | |
| MEASEREMENT (CM)(L*W*H) | 110*67*142 | |
| WEIGHT (KG) | 730 | |



AUTOMATIC HYDRAULIC OIL PRESSER SS320

| MODEL | SS2320 |
|-------------------------|----------------------------------|
| MOTOR POWER(KW) | 4kw |
| CAPACITY | 1.10-15kg/Batch 2-4 time/Hour |
| VOLTAGE | 220V |
| MEASEREMENT (CM)(L*W*H) | 81*185*100 |
| WEIGHT (KG) | 2500 |



AUTOMATIC HYDRAULIC OIL PRESSER SS320

| Technical Parameter | | |
|-------------------------|-----------------------------|--|
| MODEL | SS4320 | |
| MOTOR POWER(KW) | 4kw | |
| CAPACITY | 15kg/Batch 2-4 time/Hour | |
| VOLTAGE | 380V | |
| MEASEREMENT (CM)(L*W*H) | 81*185*100 | |
| WEIGHT (KG) | 2500 | |



AUTOMATIC HYDRAULIC OIL PRESSER80 TON

| MODEL | SS80TB |
|-------------------------|-----------------------------|
| MOTOR POWER(KW) | 1.5kw |
| CAPACITY | 2.25kg/batch 13.5kg/Hour |
| VOLTAGE | 220V/50hz |
| MEASEREMENT (CM)(L*W*H) | 95*60*120 |
| WEIGHT (KG) | 380kg |



SEMI-AUTO HYDRAULIC OIL PRESSER 80 TON

| MODEL | SS80TB SEMI-AUTO |
|-------------------------|-----------------------------|
| MOTOR POWER(KW) | 1.5kw |
| CAPACITY | 2.25kg/batch 13.5kg/Hour |
| VOLTAGE | 220V/50hz |
| MEASEREMENT (CM)(L*W*H) | 95*60*120 |
| WEIGHT (KG) | 350kg |



MANUAL HYDRAULIC OIL PRESSER 80 TON

| MODEL | SS80TB MANUAL |
|-------------------------|-----------------------------|
| MOTOR POWER(KW) | 1.5kw |
| CAPACITY | 2.25kg/batch 13.5kg/Hour |
| VOLTAGE | 220V |
| MEASEREMENT (CM)(L*W*H) | 85*60*110 |
| WEIGHT (KG) | 305kg |



MANUAL HYDRAULIC OIL PRESSER 32 TON

| Tec | hnical | Param | neter |
|-----|--------|-------|-------|
| | | | |

| MODEL | SS32TB MANUAL |
|-------------------------|------------------------|
| MOTOR POWER(KW) | 1kw |
| CAPACITY | 500g/batch 3kg/Hour |
| VOLTAGE | 220V |
| MEASEREMENT (CM)(L*W*H) | 55*30*74 |
| WEIGHT (KG) | 93kg |



ELECTRIC FRYING MACHINE



ELECTRIC FRYING MACHINE

| Technical Paramet | ter | | | |
|-----------------------------|------------------------------|------------------------------|------------------------------|------------------------------|
| MODEL | SS_50 | SS_100 | SS_200 | SS_300 |
| CAPACITY (KG/H) | 50 | 100 | 200 | 300 |
| MOTOR POWER (KW) | 1.1 | 1.1 | 1.1 | 1.1 |
| HEATING POWER (KW) | 9 | 15 | 24 | 28 |
| BEARING | UCP205(2PSC) UCP209(2PSC) | UCP205(2PSC) UCP209(2PSC) | UCP205(2PSC) UCP209(2PSC) | UCP205(2PSC) UCP209(2PSC) |
| MEASEREMENT (MM) (L*W*H) | 1300X750X1000 | 1850X950X1150 | 2000X1000X1250 | 2500X1000X1250 |
| V-BELT | B1280(2PSC) | B1250(4PSC) | B1250(2PSC) B1321(2PSC) | B1250(2PSC) B1321(2PSC) |
| WEIGHT (KG) | 220 | 310 | 380 | 450 |

ROLLER FRYING MACHINE




ROLLER FRYING MACHINE

| Technical Parameter | | | | | | |
|-------------------------|---|--|------------------------------|------------------------------|--|--|
| MODEL | SS_50 | SS_80 | SS_180 | SS_250 | | |
| CAPACITY (KG/H) | 50 | 80 | 180 | 250 | | |
| MOTOR POWER (KW) | 0.75 | 1.1 | 1.1 | 1.1 | | |
| BEARING | 305(2PSC) 1506 bearing box(2PSC) UCP205(2PSC) | UCP205(2PSC) UCP209(2PSC) 205 (2PSC) 205 bearing box(2PSC) | UCP205(2PSC) UCP209(2PSC) | UCP205(2PSC) UCP209(2PSC) | | |
| MEASEREMENT (MM)(L*W*H) | 1500x700x1000 | 1600x850x1200 | 2000x900x1200 | 2100x1000x1400 | | |
| V-BELT | A1549(1PCS) | A1727(2PCS) | A1727(2PCS) | A1956(2PCS) | | |
| WEIGHT (KG) | 110 | 150 | 220 | 260 | | |

CONTINUOUS FRYING MACHINE

| Technical Parameter | | | | |
|-----------------------------|----------------|--|--|--|
| MODEL | SS_500 | | | |
| CAPACITY (KG/H) | 200-500 | | | |
| MOTOR POWER (KW) | 50-80 | | | |
| MEASEREMENT (MM) (L*W*H) | 9000x1000x1500 | | | |
| WEIGHT (KG) | 1100 | | | |



CONTINUOUS FRYING MACHINE

| Technical Parameter | | | | | | |
|-------------------------|---|--|------------------------------|------------------------------|--|--|
| MODEL | SS_50 | SS_80 | SS_180 | SS_250 | | |
| CAPACITY (KG/H) | 50 | 80 | 180 | 250 | | |
| MOTOR POWER (KW) | 0.75 | 1.1 | 1.1 | 1.1 | | |
| BEARING | 305(2PSC) 1506 bearing box(2PSC) UCP205(2PSC) | UCP205(2PSC) UCP209(2PSC) 205 (2PSC) 205 bearing box(2PSC) | UCP205(2PSC) UCP209(2PSC) | UCP205(2PSC) UCP209(2PSC) | | |
| MEASEREMENT (MM)(L*W*H) | 1500x700x1000 | 1600x850x1200 | 2000x900x1200 | 2100x1000x1400 | | |
| V-BELT | A1549(1PCS) | A1727(2PCS) | A1727(2PCS) | A1956(2PCS) | | |
| WEIGHT (KG) | 110 | 150 | 220 | 260 | | |

CENTRIFUGAL OIL FILTER

| Technical Parameter | | | | | | | |
|---------------------|--------------------|------------------|---------|-------------|-----------|----------------------------|-------------|
| MODEL | CAPACITY (kg/time) | MOTOR POWER (kw) | BEARING | V-BELT | OIL SEAL | MEASEREMENT (MM)(L*W*H) | WEIGHT (kg) |
| 20 | 10 | 1.5 | 7206AC | A800(2PCS) | 40*55*8 | 640x460x850 | 100 |
| 100 | 50 | 3 | 7215AC | B1250(2PCS) | 85*110*12 | 910x610x1250 | 100 |



▲ SS_20
Centrifugal Oil Filter



▲SS_100 Centrifugal Oil Filter



Hydration Machine Is Combined With Centrifugal Oil Filter

CENTRIFUGAL OIL FILTER

| Technical Parameter | | | | | | |
|---------------------|--------------------|------------------|---------|----------------------------|-------------|--|
| MODEL | CAPACITY (kg/hour) | MOTOR POWER (kw) | VOLTAGE | MEASEREMENT (MM)(L*W*H) | WEIGHT (kg) | |
| SS50 | 150-180 | 2.2 | 220V | 750x500x850 | 120 | |







VACCUME OIL FILTER

| Technical Parameter | | | | | | |
|---------------------|----------------------|----------------|------------------|------------------|----------------------------|--|
| MODEL | BARREL DIAMETER (mm) | WEIGHT (kg) | MOTOR POWER (kw) | VACCUME BUMP (L) | MEASEREMENT (MM)(L*W*H) | |
| SS_80 | 800 (SINGLE BARREL) | 245 | 2.2 | 15 | 1700x900x8000 | |
| SS_65 | 650 (DOUBLE BARREL) | 300 | 1.1 | 10 | 2000x850x800 | |
| SS_35 | 350 (DOUBLE BARREL) | 150 | 0.75 | 5 | 1700x550x700 | |







VACCUME OIL FILTER

| Technical Parameter | | | | | |
|---------------------|--------|----------------|------------------|-----------|----------------------------|
| MODEL | Votage | WEIGHT (kg) | MOTOR POWER (kw) | CAPCITY | MEASEREMENT (MM)(L*W*H) |
| SS_50 | 220V | 40 | 0.75 | 10kg/hour | 490x570x600 |







AIR PRESSURE OIL FILTER

| Technical Parameter | | | | | |
|---------------------|---|----------------|--------------------|-----------------------------|--|
| MODEL | CAPACITY | WEIGHT (kg) | MOTOR POWER (kw) | MEASEREMENT (MM) (L*W*H) | |
| SS_SINGLE | 20 kg/time | 80 | 600w 30 lift press | 550x550x700 | |
| SS_DOUBLE | 20 kg/time DOUBLE DRUM FOR ALTERNATE USE | 180 | 600w 30 lift press | 1550x1100x700 | |
| SS_CONTINUOUS | 40-1000 kg/day | 300 | 9kw | 1700x750x1200 | |











▲ Continuous
Air Pressure Oil Filter

AIR PRESSURE OIL FILTER SS_SPECIAL







REFINING MACHINE

| MODEL | SS_500 | SS_2000 |
|-----------------------------|----------------|----------------|
| CAPACITY (kg/day) | 800 | 3000 |
| POWER (KW) | 50 | 130 |
| MEASEREMENT (MM) (L*W*H) | 3500x1000x2400 | 5000x1900x3500 |
| WEIGHT (KG) | 500 | 1200 |



HYDRATION MACHINE

| MODEL | SS_500 |
|-------------------------|----------------|
| CAPACITY (kg/day) | 800 |
| POWER (KW) | 50 |
| MEASEREMENT (MM)(L*W*H) | 3500x1000x2400 |
| WEIGHT (KG) | 500 |



OIL COOLER

| MODEL | SS_180 |
|-------------------------|-------------|
| CAPACITY (kg/day) | 150 |
| POWER (KW) | 1 |
| MEASEREMENT (MM)(L*W*H) | 880x570x980 |
| WEIGHT (KG) | 30 |



ENVIRONMENTAL DUST REMOVAL SEPERATING MACHINE

| MODEL | SS_90 |
|-------------------------|---------------|
| CAPACITY (kg/day) | 600 |
| POWER (KW) | 1.7 |
| MEASEREMENT (MM)(L*W*H) | 1400x900x1150 |
| WEIGHT (KG) | 500 |











CONTACT US

PHONE/WHATSAPP: +91-9724100312 || +91-9685786883

EMAIL: SSWORKSENGINEERING@GMAIL.COM | WEBSITE: WWW.SSENGINEERINGWORKS.COM

B-23, SAMPAT HILLS BICHOLI MARDANA, INDORE 452016

NAME OF A/C. - SS ENGINEERING WORKS || BANK A/C. NO. - 259724100312 || INDUSIND BANK LTD || IFSC: INDB0000850

GSTIN: 23CHHPB6108C1Z2 | PAN NO: CHHPB6108C