

TECHNICAL SPECIFICATIONS:

MODEL	AE-VSM 20"	AE-VSM 30"	AE-VSM 36"	AE-VSM 48"	AE-VSM 60"	AE-VSM 72"
Screens	SS 304 (SS 316 / 316 L Optional) Also Available in Contact Part – SS -304. Or Non-Contact Part Mild Steel (M.S.) Powder Coated.					
Screen Dia.	500 mm.	750 mm.	914 mm.	1220 mm.	1520 mm.	1820 mm.
Capacity/Hour *	20 to 200 Kg.	30 to 300 Kg.	30 to 325 Kg.	40 to 410 Kg.	60 to 700 Kg.	100 to 1000 Kg.
Charging height	800 mm without Lid 1000 mm with Lid	900 mm without Lid 1220 mm with Lid	900 5 mm without Lid 1220 mm with Lid	1000 5 mm without Lid 1350 5 mm with Lid	1100 5 mm without Lid 1420 mm with Lid	1100 5 mm without Lid 1420 mm with Lid
Discharging height	720 mm.	735 mm.	735 mm.	780 mm.	935 mm.	965 mm.
Electric Motor	0.25 HP / 1440 RPM / 3 Ph.	0.5 HP / 1440 RPM / 3 Ph.	0.5 HP / 1440 RPM / 3 Ph.	1.5 HP / 1440 RPM 3 Ph.	3.0 HP / 1440 RPM / 3 Ph.	5.0 HP / 1440 RPM 3 Ph.