

- Chain Link Fence fabric is a fencing material made of steel wire helically wound and inter woven in such a manner as to provide a continuous mesh without knots or ties except in the form of knuckling or twisting the ends of the wires to form the selvage of the fabric.
- It is the latest in fencing material and is most economical concept in modern fencing. It lasts a lifetime and can be easily installed and reinstalled by securely affixing it to reinforced cement poles, angle iron poles, pipe poles or wooden poles.



## CHAIN LINK MESH



Chainlink fences can be easily erected on any ups and downs and uneven ground.



Chainlink fabric is packed in compacted rolls, which makes it easy to transport

### Available coatings:

- GI - Normal environment
- PVC - for coastal areas



### Available in 3 types depending on the security requirements:

Knuckled-Knuckled, Twisted-Twisted and Knuckled Twisted



## Sizes & Specification

- Available in 1.60 mm to 4.00 mm of Gi Wire 40 to 270 GSM ZINC COATING.
- Made from prime QUALITY HOT DIP GALVANIZED WIRE as per IS Specifications.

Wire Thickness	Aperture (pitch)	Width	Length
1.60 MM	25MM TO 34MM	Upto 2 Mtrs.	Upto 15 Mtrs.
2.00 MM	38MM TO 50MM	Upto 2 Mtrs.	Upto 15 Mtrs.
2.50 MM	50MM TO 100MM	Upto 4 Mtrs.	Upto 15 Mtrs.
3.00 MM	50MM TO 100MM	Upto 4 Mtrs.	Upto 15 Mtrs.
4.00 MM	50MM TO 100MM	Upto 4 Mtrs.	Upto 15 Mtrs.

We manufacture & supply according to CUSTOMER NEEDS & SPECIFICATIONS  
Also, available in PVC COATED Wire