

Galvanized Steel Wire

- **Galvanized steel wire** is used in applications which are Farming, Poultry Cages, Gabions, Chain Link Fence, Barbed Wire, Concertina Wires, Stay Wire & Earth Wire. GI Wire is also used in making Stitching Wire, Tle Wire for grass as well as yarns.
- **Galvanized Wires** are coated with different levels of Zinc and are generally sold as commercial, light coated, medium coated and heavy coated categories. Amount of Zinc coating offered by HDWPL is as given below.

Specification

Diameter	: 0.80 mm to 6.00 mm
Zinc Coating	: 60 to 300 gsm
Tensile Range	: 300 to 900 MPa
Coil Weight	: 40 to 1500 kg
Standard	: IS 280:2006/As per customer specification



Applications

- Farming Sector
- Poultry
- Fencing Purpose
- General Engineering Sector
- Cable Armouring



Binding wire (GI & MS)

- **Binding Wire** is used in construction industry to tie the TMT Bars and ensure that the spacing between bars is proper and they do not get displaced while concreting.

Specification

0.80 mm to 3.00 mm	:	Diameter
ISI/Commercial	:	Zinc Coating
500 MPa Max	:	Tensile Range
As Per Required Length	:	Coil Weight
5 / 10 / 15 / 25 / 30 kg	:	
IS 280:2006 / As per customer specification	:	Standard

Applications

- Concrete Construction
- Tying Rebars at Joint
- Install Fence/Barrier