

MONOBLOCK TYPE AIR SOURCE HEAT PUMP			
Sr. No.	Model		SC-H-60M
	Parameter	Unit	
#	Power Supply		Voltage 230V $\pm$ 10% Frequency 50Hz $\pm$ 5%
#	Ambient Temp	$^{\circ}$ C	0 to 46 $^{\circ}$ C
1.	Rated Heating Output	W	5500
2.	Rated Produce Water Capacity	L/h	118
3.	Rated Power	W	1340
4.	Rated Current	A	6.4
5.	Max. Power	W	1664
6.	Max. Current	A	7.59
7.	Cop	W/W	4.10
8.	Water Circulating Pump		In – Built
9.	Rated Outlet Hot Water Temp.	$^{\circ}$ C	55
10.	Max. Outlet Hot Water Temp.	$^{\circ}$ C	60
11.	Compressor		Fully closed rotor type
12.	Waterproof Grade		IPx4
13.	Electric Shock Protection Type		Grade 1
14.	Noise	dB(A)	$\leq$ 54
15.	Net Weight	kg	62
16.	Unit Dimension ( L X W X H )	mm	960 x 360 x 555

**Testing Conditions:**

1. Use side initial water temp.: 15 $^{\circ}$ C, Setting water temp. 55 $^{\circ}$ C, Max. temp.: 60 $^{\circ}$ C
2. Dry bulb temp. 20 $^{\circ}$ C, Wet bulb temp. 15 $^{\circ}$ C

**Working Condition:**

1. Working Ambient temp. 0 to 46 $^{\circ}$ C



Above Snap is only for your reference.