

MONOBLOCK TYPE AIRSOURCE HEAT PUMP			
Sr. No.	Model		SC-H-75M
	Parameter	Unit	
#	Power supply		Voltage 230V ±10% Frequency 50Hz ±5%
#	Ambient temp	°C	0 to 46°C
1.	Rated heating output	W	7500
2.	Rated produce water capacity	L/h	161
3.	Rated Input power	W	1840
4.	Rated Input current	A	8.8
5.	Max. Input power	W	2000
6.	Max. Input current	A	10.5
7.	COP	W/W	4.08
8.	Water Circulating Pump		In – Built
9.	Rated outlet hot water temp.	°C	55
10.	Max. Outlet hot water temp.	°C	60
11.	Compressor		Fully closed rotor type
12.	Waterproof grade		IPx4
13.	Electric shock protection type		Grade 1
14.	Noise	dB(A)	≤55
15.	Net weight	kg	69
16.	Unit dimension (L x W x H)	mm	1005 x 400 x 587

Testing Conditions:

1. Use side initial water temp.: 15°C, Setting water temp. 55°C, Max. temp.: 60°C
2. Dry bulb temp. 20°C, Wet bulb temp. 15°C

Working Condition:

1. Working Ambient temp. 0 to 46°C



Above Snap is only for your reference.