




CNC ROUTER
LTM 1325

CNC ROUTER

LTM 1325



AIR COOLED SPINDLE
FOR MORE STAMINA



GEAR BOX
FOR MORE CORRECTNESS



DSP CONTROLLER
FOR EASY WORK



HELICAL RACK
FOR MORE QUICKNESS

TECHNICAL SPECIFICATION

TECHNICAL SPECIFIC	LTM 1325 GOLDEN JAGUAR 	LTM 1225 BLACK PANTHER 
X-Y-Z AXIS MOVEMENT	1300MM X 2500MM X 200MM	1300MM X 2500MM X 200MM
REPOSITIONING ACCURACY	(+/-0.5MM)	(+/-0.5MM)
X-Y MOVEMENT	HELICAL RACK & PINION	HELICAL RACK & PINION
Y TRANSMISSION	TIMUNG PULLEY WITH BELT	TIMUNG PULLEY WITH BELT
Z MOVEMENT	BALL SCREW WITH COUPLING	BALL SCREW WITH COUPLING
OVERALL MACHINE DIMENSION	3100MM X 2100MM X 1700MM	3100MM X 2100MM X 1700MM
MAX IDLING SPEED	25000MM/MIN	15000 MM/MIN
MAX CUTTING SPEED	15000 MM/MIN	10000 MM/MIN
WORKING VOLTAGE	3PHASE 415V 50 HZ	1PHASE 230V 50HZ
SPINDLE (AIR /WATER COOLED)	6HP (4.5KW) 0-24000 RPM	4.5HP (3KW) 0-24000 RPM
DRIVE MOTOR	STEPPER SYSTEM (YAKO)	STEPPER SYSTEM
COMMAND	G CODE	G CODE
COMPUTER INTERFACE	USB	USB
CABLE GUIDE	IGUS CABLE CHAIN	IGUS CABLE CHAIN
CONTROLLER	DSP (RICH AUTO A11)	DSP (RICH AUTO 0501)
COLLET TYPE & SIZE	ER32/25	ER25/20
WORK PIECE HOLDING	MANUAL T SLOT CLAMPING	MANUAL T SLOT CLAMPING
WEIGHT	1000 KG APPROX	800 KG APPROX

OTHER ACCESSORIES REQUIRED :



SERVO STABILIZER



DOUBLE BAG DUST COLLECTOR



VACUUM TABLE

SALIENT FEATURES :



AIR COOL SPINDLE



SPINDLE DRIVE



DSP SET



STEPPER MOTOR



STEPPER DRIVE



RAIL & BLOCK



HELICAL RACK



BODY STRUCTURE

APPLICATION :



Contact No. :

Inquiry No. : +91 98258 32834

 www.laxmitechnoworld.com

 laxmithechologyc.v@gmail.com

Connect with us on:



LAXMI TECHNO WORLD  93288 18413



VACUUM MEMBRANE PRESS

**SMALL SIZE
MACHINE 2 TROLLY**

EASY WORK



TECHNICAL SPECIFICATION

OTHER ACCESSORIES REQUIRED

Air Compressor

Spray Gun



DESCRIPTION	UNIT	LTM - 4550
Machine Length-Width-Height	MM	2955x2930x1070
Table Size (L x B)	MM/Inch	1380x2295 (54"x102")
Working Table Size (L x B)	MM/Inch	2470x1300 (97"x51")
No of Working Table	Nos	1 or 2
Type of Press	-	Door/Furniture
Vacuum	MMHHG	-700
Max. Thickness of Work Piece	MM	50
Max. Connecting Load	HP/K	15/10
Average Cycle Time	Min.	0-5/3
Heating System		Through Heaters
Voltage		415 W/3 Phase 50Hz
Heater		Easy Movable- 2 Trolley
Controls		Manual/Auto
Application/Material	MM	MDF/HDF
PVC Foil Thickness	MM	0.15 to 2
Approx Dimension(LxBxH)	Nos	5300x1700x1600
MCB	Nos	L&T MAKE
Cable		RR MAKE
Approx Weight	KG	900

**SPECIALLY DESIGNED WITH
NON MAINTENANCE
HEATER**

TECHNICAL FEATURES

TROLLEY

DIFFERENT PANEL BOARD


SILICONE SHEET



EASY TO USE



POWER SAVER
ELECTRIC
HEATER



INCREASE
PRODUCTION
QUALITY

APPLICATION



LAMINATION DOOR



MEMBRANE DOOR



LAMINATE DOOR

CNC MULTIHEAD GLASS CUTTING MACHINE

TECHNICAL SPECIFICATIONS

DESCRIPTION	LTM
X-Y-Z Axis Movement	1200mm X 1200mm x 50mm
Repositioning Accuracy	(+ - 0.2mm)
X-Y Movement	German Rack & Pinion Transmission
Z Movement	Hiwin Ball Screw
Table Size	1550mm x 1550mm
Max Idling Speed	20000mm/min
Max Cutting Speed	15000mm/min
Working Voltage	380 w / 50 Hz
Drive Motor	Stepper System (yako)
Command	G Code (*.mmg, *.tap, *.plt)
Computer Interface	USB
Cable Guide	"IGUS" Germany
Controls	DSP (RICH AUTO)/ NC Studio
Application	Glass
Servo Stabilizer	Optional



APPLICATION



STONE
CUTTING




STREET LIGHT
GLASS CUTTING



CLOCK
GLASS CUTTING

SALIENT FEATURES



HEAD CUTTER



RAIL & BLOCK



HELICAL RACK



STEPPER MOTOR



BODY STRUCTURE



HIWIN BALL SCREW



DRIVE



NC STUDIO

OTHER ACCESSORIES REQUIRED



OIL PUMP



VACUUM TABLE

Contact No. :

Inquiry No. : +91 93288 18413, +91 98258 32834

www.laxmitechnoworld.com
laxmithechologyc.v@gmail.com

Connect with us on:

   LAXMI TECHNO WORLD



TERMS & CONDITION

DELIVERY	Delivery will be done in 5-6 weeks (20-25 working days) after the purchase order.
FREIGHT	Transportation cost will be charged extra or will be managed by the buyers' side.
PRODUCTS WITH THE MACHINE	The machine will be given with the same specification as mention in above column in the machine detail CNC ROUTER MACHINE WITH PANEL BOX TOOL KIT (7 NOS TOOLS, 3NOS COLLET, 8NOS CLAMP, SPENER SET, V.PAID) DUST COLLECTOR, SERVO STABILIZER, VACCUM PUMP (if order) VACUUM PRESS MACHINE WITH SILICON SHEET AIR COMPRESSOR & SPRAY GUN (if order)
TEXES	GST @ 18% Extra.
PAYMENT TERM	60% Payment will be done at the time of purchase order. Rest payment will be done before dispatch of machine from the factory.
INSTALLATION & TRAINING	The installation facility will be available only for the first time after that it's chargeable. The customer should book the train tickets for both ways. Accommodation and food facility should be provide by the customer to the installation engineer.
WARRANTY	1 Year manufacturing defect warranty from the date of sale. It should be clearly understood that this warranty is against any manufacturing defects, if any. The warranty should not be applicable on the following parts: Rail Block, Timing Belt, DSP (keypad, USB Pot, and Cable), All Switches of panel box, Silicon Sheet, Solenoid valve. The warranty should not be given on the accident or damaged condition.
AFTER SALES SERVICE	The sales service will be only given to the manufacture defects and will be free of cost along with transportation cost rest all the service will be chargeable with food, accommodation and transport.
JURISDICTION	All disputes are subject to INDIA laws and are covered by Surat, India jurisdiction
VALIDITY	The quoted prices are valid for next 10 days and there after subject to our written confirmation.

SIGNATUTE OF PURCHASER

FOR Laxmi Techno World
