

# RUN FLAT (RFT) TYRE CHANGER

## FS 850 + RH 750

### FEATURES:

- » With lifting column, pneumatic locked at optional position.
- » Inside and outside clamped totally protected by plastic guard to prevent damage to the most delicate rims.
- » Turn table with two pneumatic cylinders.
- » Manually operated lifting arms support column with tensional rigidity in all working positions.
- » M/D Head with interchangeable plastic parts to protect rims.
- » Bead breaking unit with pneumatic cylinder.
- » Electronic pedal control unit to make the working procedure quicker and safer.
- » Manometer for inflating pressure control equipped with deflating push button.
- » High pressure jets on wheel clamps to inflate tubeless tyre effortlessly. (optional)

### TECHNICAL SPECIFICATIONS :

Power Supply	220 V, 50 Hz
Motor Power	0.75 - 1.1 KW
Bead-Remove Cylinder	2,500 Kg
Operating Pressure	0.8 - 1 Mpa
Rim Diameter	255 - 560 mm (10" - 22")
Rim Width	76 - 410 mm (3" - 16")
Max. Wheel Diameter	1,000 mm
Noise	< 70 db



# Naman



### OUR SALES & SERVICE NETWORK

- Ahmedabad
- Bangalore
- Chandigarh
- Cochin
- Hyderabad
- Indore
- Jaipur
- Kolkatta
- Lucknow
- Mumbai
- New Delhi
- Patna
- Pune