

# TYRE CHANGER

## FS-812



### FEATURES:

- » Semi-automatic style.
- » Operate the mounting / de mounting work manually.
- » Plastic front cover.
- » Strong pneumatic bead breaker.
- » ATV and motor cycle adaptor is optional to handle tyre from 6" to 26".
- » Modern appearance and excellent performance.
- » Manufactured with Latest Technology, High Quality material and good workmanship

### TECHNICAL SPECIFICATIONS :

Power Supply	230 V, 50 Hz
Motor Power	0.75 - 1.1 KW
Bead-Remove Cylinder	2,500 Kg
Operating Pressure	0.8 - 1 Mpa
Rim Diameter	255 - 560 mm (10" - 22")
Rim Width	76 - 410 mm (3" - 16")
Max. Wheel Diameter	1,125 mm
Noise	< 70 db
Average Rotate speed	5 to 10 RPM
Compressor Air Req.	6 to 12 Bars
Foot valve adopts stainless steel valve rod	



# Naman

An ISO 9001 : 2008 CERTIFIED COMPANY

Professional Solution For Modern Garage Under One Roof



Plot No. 504, Road No. 13, Phase-II, G.I.D.C., Kathwada, Ahmedabad - 382 430.  
M.: + 91 - 93277 99995, 98981 46824, Tele Fax : + 91 - 79 - 22900186  
E-mail : namanautomotive@hotmail.com , spramani30@hotmail.com  
www.namanautomotive.com