



DIESEL EXHAUST FLUID

PRODUCT TECHNICAL DATA SHEET

	Min	Max	% by weight	Our Results
Urea Content	31.8	33.2	%(m/m)	32.60
Density at 20°C	1.0870	1.0930	g/cm ³	1.0946
Refracting Index at 20°C	1.3814	1.3843		1.3841
Alkalinity as NH ₃		0.2	%	0.002
Biuret		0.3	%	0.29
Aldehyde		5	mg/kg	2.01
Insolubles		20	mg/kg	18.00
Phosphate (PO ₄)		0.5	mg/kg	0.10
Calcium		0.5	mg/kg	0.4
Iron		0.5	mg/kg	0.02
Copper		0.2	mg/kg	0.01
Zinc		0.2	mg/kg	0.03
Chromium		0.2	mg/kg	0.09
Nickel		0.2	mg/kg	0.05
Aluminium		0.5	mg/kg	0.02
Magnesium		0.5	mg/kg	0.09
Sodium		0.5	mg/kg	0.49
Potassium		0.5	mg/kg	0.01

EuroDeF Diesel Exhaust Fluid (DEF) has a shelf life of two years. However, this may be reduced if the fluid is exposed to direct sunlight or if the temperature of the DEF remains above 86°F (30°C) for sustained periods.

EuroDeF Features

- Meets ISO22241-1 and AUS32 Specifications
- Meets or Exceeds OEM specifications
- Formulated for SCR System Protection.
- Reduces SCR Component Wear
- Extends SCR Catalyst Life
- Ready to Use formula.

Marketed By

Turbo
Intertrade
Company India Pvt. Ltd.

No.42/2150-A, Providence Road
Cochin-682018, Kerala, India
Ph : +91-484-4015465.
Email : info@tic.net.in, www.tic.net.in