

Portable Surface Texture Measuring Instruments

# HANDYSURF<sup>+</sup>



# New HANDYSURF reborn with sophisticated design

## Portable surface texture measuring instrument for global use to diverse needs

# HANDYSURF<sup>+</sup> **NEW!**

### Display changeable in 20 languages

### Multi-language support available worldwide

20 Asian and European languages including Japanese, English and German are provided as standard. Display language can be easily changed by operating the buttons.



### High resolution with wide measuring range

### No need to set up measuring range

The previous HANDYSURF required setting of a narrow measuring range when measuring with a high resolution, but HANDYSURF<sup>+</sup> does not have such a requirement.

The instrument has the Z direction measuring range of 370  $\mu\text{m}$ , which is the widest in class, and achieved a resolution as high as 0.0007  $\mu\text{m}$  over the entire range.



### Handy drive unit selectable from 3 types according to workpiece and measurement location



#### 35 (Standard type)

The standard-type measurable with different attitudes including horizontal, inclined, vertical and ceiling surfaces.



#### 40 (Retract type)

Retract-type that reduces damage to the stylus and pickup by raising the pickup while waiting for measurement or at ending. It can be used as a detector incorporated into an automatic machine.



#### 45 (transverse trace-type)


The transverse trace-type where the pickup moves sideways. Narrow areas, such as crankshaft pins and journals, that were difficult to measure before can now be measured.

### Connectable to small printer, USB memory stick and PC with built-in USB connector

With the USB connector, it is possible to generate measurement results from the optional compact printer, save measurement conditions and results in USB memory sticks and recharge the instrument from the USB port of a PC or with a USB battery.



Compact Printer (Option)



By connecting to the USB memory stick (option), it is possible to save and read measurement conditions and results.

se responding



## Superior Operability

2.4 inch color LCD has significantly improved the visibility.

Moreover, 6 buttons and newly developed UI have achieved simple and intuitive operations.



Home screen




Menu screen



Measurement condition setting display

## Multiple analysis functions


Graphic representation of measurement results enables their on-site verification with parameter and waveform. Moreover, despite being a portable instrument, it is capable of a variety of analyses including analyses of BAC, ADC, peak count and motifs. By setting the conditions in advance, OK/NG judgment can be performed automatically.




Example of surface roughness (Ra) measurement



Example of OK/NG judgment of measurement result



Example of BAC analysis



Example of ADC analysis



## Specifications

Model			HANDYSURF <sup>+</sup>				
			35		40		45
			Tip radius 5 μm	Tip radius 2 μm	Tip radius 5 μm	Tip radius 2 μm	Tip radius 5 μm
Measurement range	Z direction		-210 to +160 μm				
	Drive axis		X direction 16 mm				Y direction 16 mm
Tracing Driver	Movement type		Standard type		Retraction type		Horizontal tracing type
	Evaluation Length		0.2 to 16 mm				0.2 mm to 4.0 mm
	Measurement speed		0.5, 0.6, 0.75, 1.0 mm/s				0.6 mm/s
Pickup	Sensing type		Differential inductance				
	Measurement Method		Skid				
	Z direction resolution		0.0007 μm/-210 to +160 μm				
	Model		E-DT-SM10A	E-DT-SM49A	E-DT-SM10A	E-DT-SM49A	E-DT-SM39A
	Stylus	Measurement force	4 mN	0.75 mN	4 mN	0.75 mN	4 mN
		Tip radius	r <sub>tip</sub> = 5 μm	r <sub>tip</sub> = 2 μm	r <sub>tip</sub> = 5 μm	r <sub>tip</sub> = 2 μm	r <sub>tip</sub> = 5 μm
		Tip angle	90°cone	60°cone	90°cone	60°cone	90°cone
		tip material	Diamond				
Analysis item	Calculation Standards		Comply with JIS2013/2001, JIS1994, JIS1982, ISO1997/2009, ISO13565, DIN1990, ASME2002/2009, ASME1995, CNOMO				
	parameter	Profile Curve	Pt, Rmax, Rz, Rk, Rpk, Rvk, Mr1, Mr2, Vo, K, tp				
		Roughness Curve	Ra, Rq, Rz, Rv, Rc, Rt, RSm, RΔq, Rsk, Rku, Rmr(c), Rmr, Rδc, Rz94, R3z, RΔa, Ry, Sm, S, tp, PC, R <sub>PC</sub> JIS, R <sub>PC</sub> ISO, R <sub>PC</sub> EN, Pc, PPI, Rp, Rmax, Mr1, Mr2, Rpk, Rvk, Rk, Vo, K, A1, A2, Rpm, Δa, Δq, Htp				
		Motif	R, Rx, AR, W, Wx, AW, Rke, Rpk, Rvke, NCRX, NR, CPM, SR, SAR, Wte, NW, SAW, SW, Mr1e, Mr2e, Vo, K				
	Evaluation Curve		Profile Curve, Roughness Curve, ISO13565Special Roughness Curve, Roughness motif curve, Waviness motif curve, Upper envelope waviness curve				
Filter	Characteristics graph		Bearing area curve, Amplitude distribution curve				
	Filter type		Gaussian, 2RC (phase compensation), 2RC (non-phase compensation)				
	Cutoff value	λc λs	0.08, 0.25, 0.8, 2.5 mm None, 2.5, 8 μm				
Amplification indicator	Display		2.4-inch color liquid crystal panel				
	Data output		USB connectors for USB memory/printer connection x 1, Micro USB connector for USB communication x 1				
	Print output		Optional (external printer unit) / Thermal recording paper width: 58 mm (recording width: 48 mm)				
	Language		Japanese, English, Chinese (Traditional Chinese/Simplified Chinese), Korean, Thai, Malay, Vietnamese, Indonesian, German, French, Italian, Czech, Polish, Hungarian, Turkish, Swedish, Dutch, Spanish, Portuguese				
Specifications	Power Supply	Charging	Built-in battery (to be charged using AC adaptor, PC USB port, USB battery), charging period: 4 hours (about 1000 measurements can be take when fully charged)				
		Voltage, frequency	AC100 to 240 V ±10%, 50/60 Hz, Single phase (Included AC adapter)				
		Power consumption	Maximum 10 W				
External dimensions (W x D x H) / Weight			Amplification indicator: 184.5 x 68 x 57.4 mm/about 500 g for the entire system				

## ACCRETECH

### World wide Sales and Service Offices

#### Head Office

2968-2, Ishikawa-machi, Hachioji-shi,  
Tokyo 192-8515, Japan  
TEL: +81(0)42-642-1701  
FAX: +81(0)42-642-1798

#### International Sales and Marketing

4, Higashi-Nakanuki-machi,  
Tsuchiura-shi, Ibaraki 300-0006, Japan  
TEL: +81(0)29-831-1240  
FAX: +81(0)29-831-1461

#### Germany

##### Accretech (Europe) GmbH

Head Office  
TEL: +49(0)89-546788-0  
FAX: +49(0)89-546788-10

##### Dresden Office

TEL: +49(0)351-89024-11  
FAX: +49(0)351-89024-12

#### France

##### Accretech (Europe) GmbH

TEL: +33(0)4-76-04-40-80  
FAX: +33(0)4-76-04-07-30

#### Italy

##### Accretech (Europe) GmbH

TEL: +39-02-2316-3291  
FAX: +39-02-2316-3099

#### Hungary

##### Accretech-Tosei Hungary Kft.

TEL: +36(0)23-232-224  
FAX: +36(0)23-232-224

#### Korea

##### Accretech Korea Co., Ltd.

Head Office / Seongnam  
TEL: +82(0)31-786-4000  
FAX: +82(0)31-786-4090

##### Ulsan Office

TEL: +82(0)52-268-2136  
FAX: +82(0)52-268-2137

#### China

##### Accretech (China) Co., Ltd.

Head Office / Shanghai  
TEL: +86(0)21-3887-0801  
FAX: +86(0)21-3887-0805

#### Thailand

##### Accretech (Thailand) Co., Ltd.

HQ & Metrology  
TEL: +66(2)751-9573, 9574  
FAX: +66(2)751-9575

#### Malaysia

##### Accretech (Malaysia) Sdn. Bhd.

Head Office  
TEL: +60(3)5632-7488  
FAX: +60(3)5632-7489

##### Johor Bahru Office

TEL: +60(7)361-4388

#### Vietnam

##### Accretech Vietnam Co., Ltd.

Head Office / Hanoi  
TEL: +84(24)3941-3309  
FAX: +84(24)3941-3310

##### Ho Chi Minh Office

TEL: +84(28)3512-6760  
FAX: +84(24)3941-3310

#### Indonesia

##### PT Accretech Indonesia

TEL: +62(0)21-2961-2375  
FAX: +62(0)21-2961-2376

#### Taiwan

##### Accretech Taiwan Co., Ltd.

TEL: +886(0)3-553-1300  
FAX: +886(0)3-553-1319

#### Brasil

##### Accretech-Tosei do Brasil Ltda.

TEL: +55(0)11-3360-9531  
FAX: +55(0)11-3360-9531



ISO 9001 and ISO 14001 awarded to the Hachioji and Tsuchiura Plants

We reserve the right to change the contents of this catalog, including product specifications, without notice when products are updated.

Some of our products shall be controlled by the Foreign Exchange and Foreign Trade Act, and required an export license by the Japanese Government. Regarding exporting the products and/or providing a non-resident with technologies, please consult Tokyo Seimitsu.

<http://www.accretech.jp/>