

Technical Specification

L-SEALER WITH SHRINK TUNNEL COMBO MACHINE HEAVY DUTY MODEL JSHL-01+JSH 01

L-Bar Sealer

✚ POWER SUPPLY	1 Ø, 220 V AC, 50 HZ
✚ SEALING AREA	400 MM(W) X 500 MM (L)
✚ MAXIMUM PRODUCT HEIGHT	150 MM
✚ IMPULSE SEALING SYSTEM	Bottom Blade
✚ WORKING PLATE HEIGHT (ON STAND)	820 MM
✚ APPLICABLE FILM	POF / PVC
✚ CONVEYOR SPEED	8 – 12 Meter / Minute
✚ DIMENSION	1570 MM(L) X 720 MM(W) X 1025 MM(H)
✚ MACHINE WEIGHT	120 KGS APPROXIMATELY
✚ ELECTRICAL PARTS	Schneider make Relay, Contactor , Switches Temperature controller, time relay & motor are Meiwa, Japan make

SHRINK TUNNEL

✚ POWER SUPPLY	3 Ø, 380 V AC, 50 HZ 11 KW
✚ WINDOW SIZE	400 MM X 250 MM (WXH)
✚ TUNNEL LENGTH	1000 MM
✚ WORKING PLATE HEIGHT (ON STAND)	800MM
✚ PACKING SPEED	20 PACKET / MINUTE
✚ FILM TYPE	POF / PE / PVC
✚ ELECTRICAL PARTS	VFD, Contactor & switches Schneider make Temperature Controller, relay are omron make, Motor Meiwa make
✚ SENSORS	Proximity Switch P & F Make
✚ TUNNEL DIMENSION	1320 MM(L) X 760 MM(W) X 1480 MM(H)
✚ MACHINE WEIGHT	250 kg aprox
✚ TOTAL DIMENSION	2900mm(L) X 760mm(W)X 1480MM(H)

For Video Press YouTube link ➡ <https://www.youtube.com/watch?v=1vp6w835J18>

MACHINE IMAGES

