



Making Packaging Simple & Strong

## MODEL JS-1 IMBT + TP FPR: FULLY AUTOMATIC POWER ROLLER BOX STRAPPING MACHINE WITH CARTON SEALING



- JS-1 IMBT + TP -102 FPR makes your Strapping Sealing easier & increase your packaging production with very low cost automation.
- Automatic Power roller driven machine accepts wide range of products, efficiently strapping operation will increase your production speed.

Before Strapping



After Strapping



### Features:

- Auto load & retracting of Strap.
- Sensors for product detection & strapping operation.
- PLC Control operation.
- Auto / manual option.
- Easily incorporate with in feed & out feed conveyor.
- Gear BOX: In line clutch mechanism, there is no pulley & belt so, zero transmission loss & setting not required. Low maintenance.
- Feeding Unit: Not tricky settings.
- Heater: Heavy duty Stainless steel single piece, So long life operation.

Email : [info@jpackengineers.com](mailto:info@jpackengineers.com)  
Tel :93764 90009  
Website : [WWW.jpackengineers.com](http://WWW.jpackengineers.com)

**Jpack Engineers Pvt Ltd.**  
32, Devraj Industrial Park,  
Piplaj-Pirana Road, Piplaj,  
Ahmedabad – 382 405





Making Packaging Simple & Strong

Specification	JS – 1 IMBT + TP – 102 FPR
<b>Mechanical Specification</b>	
<b>Arch Size</b>	800 mm (W) x 600 mm (H) (Standard)
<b>Machine Tension</b>	10-70 Kgs
<b>Strap Width</b>	12 mm
<b>Strapping operation Speed</b>	2 Sec / Cycle
<b>Power Roller Speed</b>	19 Meters / Min
<b>Tape Width</b>	48 mm – 72 mm
<b>Weight Capacity</b>	30Kgs
<b>Strap Joint</b>	Heat Sealed
<b>Electrical Specification</b>	
<b>PLC Control</b>	Siemens, or Equivalent
<b>Sensors</b>	P&F, Germany
<b>Power supply</b>	415 – 440 VAC, Three Phase, 50 hz
<b>Power consumption</b>	1.66 KW

