



MODEL: JSW – 01 RING

RING STRETCH WRAPPING MACHINE



TECHNICAL SPECIFICATION

BELT DRIVEN ROTATION UNIT

- ❖ **Max rpm:** 70RPM
 - Continuous operating cycle by foot-control.
 - Constant film tensioning.
 - Rotating speed available adjustment.
- ❖ **Std. Voltage:** 220V, 1 phase, 50 Hz cycles.
- ❖ **Installed Power:** 1KW
- ❖ **Air consumption:** 0.1cmf
- ❖ **Air pressure:** 5 bar
- ❖ **Ring Open Dia:** 300MM
- ❖ **Working Width:** 250MM

FILM SPECIFICATIONS

- ❖ Film width: 8" ~ 18"
- ❖ Film Thickness: 23 micron to 35 micron
- ❖ Max. Spool diameter: 8" (200mm)
- ❖ Core Diameter: 3" (76mm)





OPTION

- ❖ Power Conveying systems/Pneumatically pressure/safety guide
- ❖ Conveying systems.
- ❖ The Ring Stretch Wrapping machine can bundle and protect produces of various shapes and size.
- ❖ Ring Stretch Wrapping machine use stretch wrap film to provide secure protection against dirt, dust and dampness during transport and storage. There are applications as fellow: Wood products/Pipe Tubing/Paper/Building materials Windows Door/products Motor, Sink, Lamp/ Cartons/ Products traditionally unitized with string, strap and tape.
- ❖ All machines feature friendly and simplicity of operation with onecon stant roller for tensioning, fim simple threading, low maintenance costs.
- ❖ A range of size to suit most need

