



Sealing Size :- 500 mm

Seal Bar Up :- 150 mm

Conveyor Length :- 1500 mm , Max Conveyor Speed :- 15 Mtrs / Min

Packing Speed :- 8 -10 Packing

Compressed Air Request :- 8 – 10 Kgs / Cm2

Power Supply :-3 Phase 440 V 50/60 hz , 3 Kw

Machine Size :- 2475 mm (L) X 1370 mm (W) x 1800 mm (H)

Gross Weight :- 650 Kgs

Shrink Tunnel :-

Tunnel Passage :- 500 mm (W) x 300 (H) , Tunnel length :- 2400 mm Net Chamber Length :- 1400 mm

Max Product Size :- W + H <= 500 mm , L :- No Limit , Height <= 250 mm

Power Supply :- 3 Phase 440 V 50/60 Hz , 18 Kw

Machine Size :- 2400 mm (L) x 900 mm (W) x 1720 mm (H) , Gross Weight :- 750 Kgs

Main Electric Fittings: -

1. PLC (Controller) :- **Mitsubishi / Equivalent**
2. Temperature Controller :- **Omron / Equivalent**
3. Sensor :- **Banner / Leuze / Equivalent**
4. Pneumatic System :- **Shanko / Equivalent**
5. Conveyor Motor :- **CPG / GPG / Equivalent**
6. Blowing Motor :- **ESPA / Bonfigoli / Bolvario / Equivalent**
7. Timer / Relay :- **Schneider / Siemens / Equivalent**
8. Main Power Switch / Switch / :- **Fuji / Siemens / Equivalent**
9. Speed Controller :- **Siemens / Equivalent**

“ Grouping With Shrinking Machine (Flameproof Motor and Body Struture – SS 304) “

Main Features of JSH – 02

- 1. Wrapper Imported Advance Technology to ensure the Machine's Stability and Reliability**
- 2. Use Mitsubishi / Siemens / PLC Realized The Integration with Mechanical , Electrical and Pneumatic**
- 3. Adopts the Worm Gear Reducer to Ensure the Stability Conveying and Film Feeding**
- 4. Inline Feed, No limit no Length of Products and Speed is much Faster than Traditional Design**
- 5. Speed of Conveyor is adjustable by Freq inverter for Different Request ,**

**Shrink Tunnel Adopts Blowing of Motor Assures the Hot air inside the Tunnel even , shrink is perfectly
The Adjustable Hot air Guide flows Frame inside the tunnel Makes More Energy Saving
Used Solid Steel Rollers covered with Silicon Gel Pipe , Chain Conveyor and Durable
The Colling System With large Winds Blowing Ensures the Quick Coiling and Forming With Shrink
SS mesh Net Conveyor
High Density Conveyor Rollers for Bottles or Small Products**