



## JS - 1 IMBT

### TOP & BOTTOM DRIVE TYPE- CARTON SEALING MACHINE



Note: Product specifications are subject to change without notification.

|                                                          |                                                                                                            |
|----------------------------------------------------------|------------------------------------------------------------------------------------------------------------|
| Tap Width                                                | 48mm - 72mm   1.88" - 2.83"                                                                                |
| Speed                                                    | 20 Cartons / Min.                                                                                          |
| Package Size                                             | L(150 - INFINITE) x W(150 - 500) x H(150 - 500)mm   L(5.9" - INFINITE) x W(5.9" - 19.7") x H(5.9" x 19.7") |
| Weight Capacity                                          | 30 Kg.   66.13lbs.                                                                                         |
| Motors                                                   | 2 Nos. (3/4 HP)                                                                                            |
| Power Supply                                             | 230 V AC   1   50 Hz                                                                                       |
| Power Requirement                                        | 400 Watt                                                                                                   |
| Machine Dimension                                        | 1700mm (L) x 760mm (W) x 1600mm (H)   66.92" x 29.92" x 62.99" (L x W x H)                                 |
| Machine Weight                                           | 145 Kg.   319.67 lbs.                                                                                      |
| (Length includes 0.5 Mtr. in feed and out feed conveyor) |                                                                                                            |

#### Features:

Compact & Rugged Design | In-feed & Out-feed Free Roller Conveyor | Interchangeable Top & Bottom Tapping Head | Adjustable Tape Tension Unit for Accurate Tapping | PP - Rough Top For Long Life & Smooth Operation

#### Benefits:

Uniform Tapping | Saving of Tapping Material | Increase in Speed of Packing |  
Reduce Packing Material Cost

### J - PACK ENGINEERS PVT. LTD.

32, Devraj Industrial Park, Piplaj - Pirana Road, Piplaj, Ahmedabad - 382 405,  
Gujarat, INDIA.

Tel: +91 93764 90009 | +91 73594 60003, e-mail: info@jpackengineers.com

[www.jpackengineers.com](http://www.jpackengineers.com)

Distributor: