



Construction

Double walled construction inner chamber made of Mild Steel / Stainless Steel and exterior made of Galvanized sheets powder coated. The gap between the two walls filled with glasswool insulation. Double door inner door made of Acrylic to see through the chamber and exterior metal door with magnetic gasket and Lock. Supplied with G.I. wiremesh shelves.

Heating Elements

Made from best quality Nichrome wire.

Temperature Control

Temperature Controlled by Electronic Digital Temperature Controller with sensor.

Temp Range : 5°C above ambient to 60°C

Resolution : 0.1°C

Accuracy : ±0.5°C

Optional Accessories

- Stainless Steel Wiremesh Shelves.
- Forced Air Circulating System with fan for better uniformity of Temperature.

All instruments work on 230 V. A.C. 50 Hz Single Phase

Chamber Size	Rating	No of shelves	Exterior dimension	Weight
12"X12"X12"	200W	2 Nos	19"x19"x26"	28 Kgs
14"X14"X14"	250W	2 Nos	21"x21"x28"	33 Kgs
18"X18"X18"	500W	3 Nos	25"x25"x32"	51 Kgs
18"X18"X24"	600W	4 Nos	25"x25"x39"	66 Kgs
24"X24"X24"	750W	4 Nos	32"x31"x39"	77 Kgs
24"X24"X36"	1000W	5 Nos	32"x31"x53"	85 Kgs

Also available in GMP Model

Manufactured by :



Scientific Industries Mumbai

Distributor :