
LARGE FORMAT PRINTER SURECOLOR™ SC-S80670

Authorised Distributor:



Jl. Tongkol No. 6 BI, Jakarta Utara 14430 T. +62 21 691 0072 F. +62 21 691 0073 www.muliamandiri.com





The Epson SureColor $^{\text{TM}}$ SC-S80670 is Epson's next generation, high-performance, eco-solvent signage printer. It incorporates the latest printing technologies, which include precision media feeding system and dual-performance PrecisionCore™ TFP printheads, to confidently meet the most demanding jobs. Equipped with the widest colour gamut in the new S-Series range, the SC-S80670 is set to astound with true-to-life colours in every brilliant printout.











700ML*





Foson UltraChrome™ GS3 ink is Greenquard Gold certified and meets the French-VOC A+ Class criteria for low chemical emissions.







Print exceedingly vivid colours in outstanding

quality with PrecisionCore technology and a

Outstanding Performance

64"

Steadfast Reliability

DUAL

Tackle high-volume printing with ease through the newly developed precision media feeding system that allows you to print uninterrupted.

26.8

Optimised Design

Enjoy hassle-free operations and maintenance with automatic media alignment and setup, along with automated printhead cleaning technology.

ENGINEERED FOR BUSINESS



wide colour gamut.





13.2

^{* 700}ml for all colours. 600ml for white, 350ml for metallic silver

ed on 8-pass printing for high quality and 4-pass printing for production, on banner media



MODEL NUMBER		SC-S80670		
SKU No.		C11CE45402		
Printer Width		64 "		
Printing Tec	hnology			
Print Head		PrecisionCore™ TFP® Printhead		
Nozzle Configuration		360 x 1 x 2 nozzles each colour (x10)		
Maximum Resolution		1440 x 1440 dpi		
Minimum Ink Droplet Volume		4.2 pl		
Print Speed				
1 Layer	Colour	Max Speed - 1 pass	Up to 95.1 m ² /h (360 x 720 dpi)	
		High Speed - 2 pass (Billboard)	Up to 52.3 m ² /h (720 x 720 dpi)	
		Production 1 - 4 pass	Up to 26.8 m²/h (720 x 720 dpi)	
		Production 2 - 6 pass	Up to 18.2 m ² /h (720 x 720 dpi)	
	Colour, Colour + White	High Quality - 8 pass	Up to 13.2 m ² /h (720 x 720 dpi)	
	•	Max Quality 1 - 12 pass	Up to 8.8 m²/h (720 x 1440 dpi)	
		Max Quality 2 - 16 pass	Up to 6.8 m ² /h (720 x 1440 dpi)	
		Max Quality 3 - 30 pass	Up to 3.7 m ² /h (720 x 1440 dpi)	
		Max Quality 4 - 48 pass	Up to 2.4 m ² /h (1440 x 1440 dpi)	
	Colour + Metallic Silver	Production - 20 pass	Up to 4.2 m ² /h (720 x 1440 dpi)	
	CO.CON I MICRONICO CHIVEI	High Quality - 36 pass	Up to 2.3 m²/h (1440 x 1440 dpi)	
2 Layer	Colour + White	Speed - 18 pass	Up to 6.4 m²/h (720 x 720 dpi)	
∠ ∟ayer	Ocioui + Wille	Production - 32 pass	Up to 3.5 m²/h (720 x 1440 dpi)	
		High Quality - 48 pass	Up to 2.4 m ² /h (1440 x 1440 dpi)	
	Colour + Metallic Silver	Production - 40 pass	Up to 1.9 m²/h (720 x 1440 dpi)	
	COIDUI T WIELZIIIC SIIVEF	High Quality - 72 pass	Up to 1.5 m// (720 x 1440 dpi)	
B Layer	Colour + White	Speed - 27 pass	Up to 3.2 m ² /h (720 x 720 dpi)	
Layer	Colour + Writte	Production - 48 pass	Up to 1.7 m²/h (720 x 720 dpi)	
		High Quality - 72 pass	Up to 1.7 m /m (/20 x 1440 dpi)	
nk System		I light Quality = 12 pass	Op to 1.1 111/11 (1440 x 1440 upi)	
-		Francia I Iltra Chrama IM CCO Int. Tanhanta	over the Dood	
Ink Type Colours		Epson UltraChrome™ GS3 Ink Technolo		
		10 colours - Cyan, Magenta, Yellow, Black, Light Cyan, Light Magenta, Light Black, Orange, Red,		
		White or Metallic Silver		
Ink Capacity		700 ml (all colours except White and Metallic Silver), 600 ml (White), 350 ml (Metallic Silver)		
Paper Handling		Rear roll feed (2 " / 3 " core with max 250 mm diameter and up to 45 kg); Auto take-up reel		
Media Type				
Printable Area		Max printing width: 1616 mm; Side Margin: 5 mm both sides, 10 mm with media holding plates		
Media Width		300 to 1626 mm		
Media Thickness		Up to 1 mm		
Heaters		Pre- and Platen- Heater (30 to 50 °C); After-Heater (30 to 55 °C)		
Control Par		2.7 " Colour LCD		
Connectivit				
Printer Interfa		Hi-Speed USB 2.0, 100BASE-TX / 1000BASE-T		
Printer Langu	-	Standard: ESC/P raster		
Printer Driver	'S	<u> </u>		
Memory		512 MB main + 128 MB network		
Software		Standard: CD Installer, Communication Driver, EPSON Manuals Launcher, Operators Guides, General		
		Information, Epson Control Dashboard, EpsonNet Config, EpsonNet Setup, EpsonNet Print, Epson		
		Software Updater, Onyx RIPCenter		
Other Features		Auto Head Alignment Technology (Media feed and Bi-directional), Auto Nozzle Check System, Mail		
		Report System, Custom Paper Backup		
Power and	Operating Requirements			
Power Requirements		Input voltage AC 100 - 240 V 50/60 Hz / 10 - 5 A		
Power Cons		Operating: Approx. 745 W; Standby: Approx. 445 W w/ heater ON; Sleep: Approx. 13 W;		
		Power Off: Less than 1.8 W		
Recommend	led Operating			
Recommended Operating Temperature & Humidity		15 - 35 °C; 20 - 80 % RH (non-condensing)		
Temperature		33 3, 23 30 /0111 (1011 001100110	····•oi	
Printer Dim	ensions	2 620 x 880 x 1 338 mm (M/ v D v H) (ct	orage)	
Printer Dim Dimensions	ensions	2,620 x 880 x 1,338 mm (W x D x H) (st	orage)	
Temperature Printer Dim Dimensions Weight Bundled Ite		284 kg (without ink)	orage) 1), SC-S80670 Printer Starter Kit (include Onyx RIPCenter)	

Dimensions & Weight -S80670

eight: 284 kg (without ink)



Cartridge Compatibility

 Black (700 ml) 	C13T892100
 Cyan (700 ml) 	C13T892200
Magenta (700 ml)	C13T892300
Yellow (700 ml)	C13T892400
Light Cyan (700 ml)	C13T892500
Light Magenta (700 ml)	C13T892600
 Light Black (700 ml) 	C13T892700
 Orange (700 ml) 	C13T892800
 Red (700 ml) 	C13T892900
O White (600 ml)	C13T892A00
 Metallic Silver (350 ml) 	C13T892B00

pplies & Optional Accessories

350 ml Cleaning Cartridge	C13T696000
Maintenance Parts Kit	C13S210044
Ink Cleaner	C13T699300
Cleaning Stick	C13S090013
Clean Room Wiper	C13S090016
Waste Ink Bottle	C13T724000
Additional Print Drying System	C12C932381
Media Holding Guide	C12C932411

2016 Epson Singapore Pte Ltd. All Rights Reserved. production in part or in whole, without the written mission from Epson, is strictly prohibited. EPSON and CEED YOUR VISION are registered trademarks of Selko son Corporation. All other products names and other mpany names used herein are for identification purposes y and are the trademarks or registered trademarks of iir respective owners. Epson disclaims any and all rights hose marks. Print samples shown are simulations only. edicitations and product availability are subject to change hout notice and may vary between countries. Please sck with local Epson offices for more information.

Dealer's Stamp

Information correct at time of printing Printed April 2016

Authorised Distributor: PT. Mulia Mandiri Supply

Jl. Tongkol No. 6 BI, Jakarta Utara 14430 T. +62 21 691 0072 F. +62 21 691 0073 www.muliamandiri.com

Sales Enquiries 800 120 5564







To find out more, visit www.epson.com.sg/s-series or call 800 120 5564