PRECURED TREAD RUBBER MOLDING PRESS

TECHNICAL SPECIFICATIONS:

MODELS	STP - 360	STP - 650	STP - 800	STP - 1000	STP - 1200	STP - 2000
Clamping Force (T)	360	650	800	1000	1200	2000
Table Size (mm)	305 x 3650	305 x 8000	400 x 8000	350 x 5500	625x4500	400 x 11000
Daylight (MM)	125 each	125 each	125 each	125 each	150 each	150 each
No. of Daylight / Layers	4 Nos.	5 Nos.	5 Nos.	4 Nos.	6 Nos.	5 Nos.
Stroke of Main Cylinder	500 mm	600 mm	550 mm	500 mm	900 mm.	750 mm
No. of Cylinders	6 Nos.	12 Nos.	8 Nos.	10 Nos.	8 Nos.	20 Nos.
Piston dia of each cylinders	Ø 200 mm	Ø 200 mm	Ø 250 mm	Ø 250 mm	Ø 300 mm	Ø 250 mm
Electric Motor (H.P.)	10 H.P.	20 H.P.	25 H.P.	25 H.P.	30 H.P.	40 H.P.
Working Pressure (Bar)	200 Bar	200 Bar	200 Bar	200 Bar	200 Bar	200 Bar
Weight (approx)	35 Tons	75- 80 Tons	80 - 85 Tons	50 tons	50-60 Tons	130 tons
Specific Pressure	40 to 45 Kg/cm2	40 to 45 Kg/cm2	40 to 45 Kg/cm2	45 to 50 Kg/cm2	45 to 50 Kg./cm2	45 to 50 Kg/cm2
Heating Method	Steam / Thermic Oil	Steam / Thermic Oil	Steam / Thermic Oil	Steam / Thermic Oil	Steam / Thermic Oil	Steam / Thermic Oil