



ISO 9001:2015  
Certified Company



**SYPTONE**  
IMPEX



[www.syptoneimpex.com](http://www.syptoneimpex.com)



## **Welcome to SYPTONE IMPEX,**

SYPTONE IMPEX, The Universal pharma exporter deal in Broad range of pharmaceutical formulation, Surgical disposable, Hospital Products, Medical Devices, Ophthalmic Products, Bulk Drugs, Herbal Products & Ayurvedic Medicines, Herbal Food Products, Veterinary Products, cosmetics etc. according to GMP, WHO, and ISO 9001:2015 standards.

Export Company started operations to Provide high quality product & formulations.

We are committed to applying our expertise and resources for the improvement of health and well-being of people. We strive to provide access to high quality, effective and affordable health care products to the people across the world.

Our focus is to provide a wide range of high quality pharmaceutical products to our valued customer at best rates and quality By creating long term business value.

Syptone Impex's mission is to become the worldwide supplier of wide range of therapeutic categories and prescription drugs that are manufactured at WHO GMP approved world class facility with modern infrastructure and technology.

Pharmaceuticals product like, Tablets, Capsules, Oral Liquids, Powders, Injectables and others, Herbal product & Ayurvedic products etc. Our medicines bear the true symbol of quality and trust.

**Commitment** : We stand by our words and our promises. We offer timely deliveries according to the needs of our customer.

**Persistent** : Our highly efficient team makes sure that our customer gets up to date product efficacy from first supply to every supply. We possess strong expertise in managing the regulatory, logistics and supply chain challenges of sourcing, storing and distributing pharmaceuticals.

**Performance** : The highly skilled and efficient team at SYPTONE IMPEX believes in delivering unmatched performance.

**Quality** : We assure to maintain conscious approach truthfully & serve you better than your expectation.

**Mission** : To provide All life saving medicines & pharma related product at affordable and sensible price.

# SUPPLY OF GENERAL GOODS

## COVID-19 ITEMS

We have the expertise of procuring and supplying all forms of materials and equipment for Pharmaceutical, surgical and hospital items like,

- ◆ **AED DEFIBRILLATOR**
- ◆ **AUDIOMETER DIGIO2**
- ◆ **PULSE OXIMETER**
- ◆ **NEBULIZER**
- ◆ **ECG MACHINE**
- ◆ **FIRST AID**
  - I. FIRST AID KIT
  - II. AUTOMATIC LOADING STRETCHER FOR AMBULANCE
  - III. EMERGENCY CHAIR STRETCHER
  - IV. SPINE BOARD
  - V. ALUMINIUM ALLOY SCOOP STRETCHER
  - VI. STAIR STRETCHER
- ◆ **HOME NURSING**
  - I. NURSING BED
  - II. OXYGEN THERAPY
  - III. PATIENT LIFTING HOIST
  - IV. RIPPLE MATTRESS
  - V. MAIDESITE BED
- ◆ **MEDICAL DEVICES**
  - I. TENS AND EMS DEVICES
  - II. DOPPLER\_HANDHELD
  - III. STETHOSCOPE AND DIAGNOSTIC TOOL
  - IV. PATIENT BED SIDE MONITOR
  - V. HEARING AID
  - VI. BREATH ALCOHOL ANALYSER
  - VII. EQUIPMENT CART
    - S SMEDICAL TROLLEY
    - MEDICAL TROLLEY WITH DRAWER
  - VIII. ANGIOGRAPHIC PRODUCT
- ◆ **WEEL CHAIR**
  - I. SWING WHEELCHAIR
  - II. ELECTRIC POWER WHEELCHAIR
- ◆ **FREEZERS**
  - I. ULTRA LOW DEEP FREEZER
  - II. ULTRA LOW TEMPERATURE CABINET/ DEEP FREEZER
  - III. BLOOD BANK REFRIGERATOR
- ◆ **INFUSION PUMP**
- ◆ **HIGH SPEED CENTRIFUGE**
- ◆ **OXYGEN CONCENTRATOR**
- ◆ **THERMOMETER**
  - I. CLINICAL MERCURY THERMOMETER
  - II. DIGITAL THERMOMETER
  - III. CONTACTLESS INFRARED THERMOMETER
- ◆ **VITAL SIGN MONITER**
- ◆ **WEIGHING SCALE**
  - I. WEIGHING BALANCE
  - II. HOSPITAL WEIGHING SCALE
  - III. HOSPITAL BABY WEIGHING SCALE
- ◆ **SYRINGES**
- ◆ **SWAB GAUZE**
- ◆ **DESINFECTION TABLET**
- ◆ **DISPOSABLE PRODUCTS**
  - I. SURGICAL MASK
  - II. N95 FACE MASK
  - III. DISPOSABLE APRON
    - NON WOVEN APRON
    - DISPOSABLE SURGICAL GOWN
    - DISPOSABLE COVERALL
  - IV. DISPOSABLE BIO HAZARD MEDICAL BAG
  - V. FACE SHIELD
    - NON DISPOSABLE POLYCARBONATE FACE SHIELD
    - GOGGLE FACE SHIELD (FRAME TYPE)
- ◆ **GLOVES**
  - I. NITRILE GLOVE (POWER FREE)
  - II. LATEX GLOVE
- ◆ **MICROSCOPE BINOCULARS AND TRINOCULAR**
  - I. BINOCULAR MICROSCOPE
  - II. DIGITAL MICROSCOPE
  - III. TRINOCULA MICROSCOPE

# 1. AED DEFIBRILLATOR

## KEY FEATURES :

Simple Operation LED Status Indicators, Automatic Self-testing CPR coaching Especially designed for public usage Economic Standard Package.

## Product Specification

Types	Automatic External Defibrillators
Usage/Application	Home & Public Place
Accuracy	1-2 BPM
Resolution	1 BPM
Weight	6.5 Kgls
Application	Hospital
Display Area	120 X 90 mml
Range	30-250 BPM

## Automated And User-

### Activated Self-Tests

#### **Daily Self Tests :**

Tests internal circuitry, waveform delivery system, battery capacity and software

#### **Battery Insertion Test :**

Upon battery insertion, extensive automatic selftests and user-interactive test check device readiness

### DATA RECORDING AND TRANSMISSION

#### **Infrared :**

Wireless transmission of event data to personal computer using the IrDA protocol

#### **Data Stored :**

First 40 minutes of ECG an the entire incident's events and analysis decisions.

## TECHNICAL SPECIFICATIONS DEFIBRILLATOR

**Waveform Biphasic :** Truncated Exponential

**Shock-to-Shock CycleTime :** Typically less than 20 seconds

**Protocol :** Voice prompts and indicators guide user through protocol

**Voice Instructions :** Detailed voice messages guide responder through use of the defibrillator

**Controls :** Shock Button, i-Button, On/Off Button

**Indicators :** 4 LED's (different colours), i-Button

## ENVIRONMENTAL / PHYSICAL REQUIREMENTS

Temperature Operating : 32° ~ 110°F [0° ~ 43°C]

Standby : 32° ~ 110°F [0° ~ 43°C]

Humidity : Operating - 0% to 60% relative, non-condensing, Standby - 0% to 95% relative, non-condensing


Vibration : Meets EN1789 random and swept sine, road ambulance specification in operating and standby states.

EMI [Radiated/Immunity] : Meets EN55011 Group 1 Level B Class B and EN61000-4-3

Sealing : Meets IEC60529 class IP43 with battery installed

Battery Type : 12 Volt DC, 4.2 Ah, lithium manganese dioxide, disposable long-life primary cell

Capacity : Minimum 200 shocks or 4 hours of operating time [25°C]



# AUDIOMETER DIGI O2



## PRODUCT SPECIFICATION

Type Of Audiometer	Clinical
Grade	Medical Grade
Usage/Application	Hospital
Model Name/Number	Proton Sx3
Weight	900g
Display	LCD, 2 rows of 16 characters
Brand	Arphi
Screen Dimensios	155 x 16mm
Distortion	Less than 1% (T.H.D)
Frequency	Better than +- 2%
Hearing Level	Within +-1%dB of indication
Acoustical	Within +- 3db of indication



# PULSE OXIMETER



## PRODUCT SPECIFICATION

Parameter Measures	SpO2 + Pulse Rate
Display Type	Dual Color LED
Display Mode	3 Display Modes
Features	Digital, Auto power off, Low battery indication
Usage/Application	Home Use
Pulse Rate Range	30- 235 BPM
DeviceColor	Blue

# NEBULIZER

## PRODUCT SPECIFICATION

Usage/Application	Hospital, Clinic
Operation Mode	Table Top, Portable
Size	188 mm x Dia 136 mm
Noise Level	52 Dba
Weight	1.5 kg
Nebulization Rate	0.4 ml/min
Operating Temperature	100 - 600 degree C
Age Group	Adult
Power Supply	230VAC 50 Hz
Minimum Filling Volume	2 ml
Maximum Filling Volume	8 ml
Maximum Pressure	2.2 bar
Expected Service life	1000 hours
Humidity	10% RH - 95% RH
Atmospheric pressure	700 hPa - 1060 hPa

## PRODUCT DESCRIPTION

Key Features :

1. You can carry it with you as it is light in weight and handy.
2. The nebulizer has an open/ close vent for user selectable control of medication rate as per the age of the patient.
3. Easy to use and convenient to carry, the portable nebulizer is your relief from respiratory problems.
4. It has a powerful compressor which ensures medication is atomised into fine particles faster and has immediate effect.
5. It is extremely easy to clean and maintain.



# ECG MACHINE



## PRODUCT DESCRIPTION

The offered machine is developed in compliance with set standards by our skilled professionals using high quality material and modern techniques.

This machine has digital filters to remove baseline drift, AC & EMG interference.

We are giving this machine after checking it properly in order to assure its excellence.

## PRODUCT SPECIFICATION

<b>Type</b>	Digital, Portable, Manual, Automatic
<b>Application</b>	Hospital, Clinical
<b>Types</b>	12-Lead
<b>LCD Display</b>	2.7 inch
<b>Mode of Printing</b>	Multiply Printing Modes
<b>Memory</b>	Built-in memory, SD Cards
<b>Battery Type</b>	Rechargeable Lithium Battery
<b>Battery Life</b>	8 hrs
<b>Printing Mode</b>	Manual, AutoInterface
<b>Language</b>	Chinese, English



## FEATURES:

2.7" LCD, accurate and clear ECG waveform and working state display

Economical to save recording paper.

## FUNCTIONS:

Sync collection for 12-lead ECG, adopt digital signal processing technology to get high-quality ECG waveforms via AC filter, baseline filter and EMG filter of ECG signal.

Display of 1/2/3-lead ECG, print mode, sensitivity, paper speed and filter state, etc. on one screen, convenient for contrastively diagnosing.

Multiply printing modes and formats, including manual, auto 4\*3, auto 3\*4 1, auto 3\*4, auto 2\*6 1, auto 2\*6, etc.

Waveform length printed can be adjusted, and with timing print function, which meets different requirements.

# III. EMERGENCY CHAIR STRETCHER



## Product Specification

<b>Material</b>	CRCA
<b>Brand</b>	SCARE
<b>Size</b>	190 L x 59 W x 85 H cm
<b>Usage/Application</b>	MEDICAL

## Product Description

Manufactured using excellent quality material, these products are highly appreciated by customers. To ensure that these are free from defects, we thoroughly inspect these on certain parameters of quality.

## Specifications:

Automatic wheelchair type stretcher is mainly used to transport the sick, wooded outdoor. It's a necessary accessory on ambulance and could be folded as wheelchair in narrow stairs or elevators.

This model is made of high quality aluminium alloy, with characteristics such as light weight , good appearance, reasonable configuration, convenience operation, antiseptis.

## Technical Parameter :

Product Size	190 L x 59 W x 85 H cm
Net Weight	45 Kg
The bearing pressure	159 Kg
Packing box dimension	200 x 60 x 27 cm

## Features :

Durable,  
Tough construction,  
High material strength



# IV. SPINE BOARD

## Product Specification

<b>Color</b>	Red
<b>Material</b>	Plastic
<b>Dimension</b>	900 x 570 x 65 mm
<b>Application</b>	Hospital

## Product Description

Made under strict quality control system, our folding short spine board in large quantity products are of stable performance and high quality.

## Features:

- Allow X-ray through. It is a good choice for rescue or rough-terrain operations.
- With plastic structure, this folding backboard is easy to disinfect.
- With aluminum alloy mechanical pivot makes it easy to use.
- Edge of this folding backboard is reflective for easier visibility.
- Extremely durable, easy to carry.



# FIRST AID



## I. FIRST AID KIT

### Product Specification

<b>Packaging Type</b>	Box
<b>Categories</b>	Home First Aid Boxes
<b>Brand</b>	SypeCare
<b>Material</b>	Plastic
<b>Color</b>	White

### Product Description

1. Rolled Bandage: 7.5 Cm x 2 MTR (1Nos)
2. Rolled Bandage: 5 Cm x 2 MTR (1Nos)
3. Gauze Swab (Sterilized) 7.5 CM X 7.5 CM, 8 ply (2 Nos)
4. Medicated First Aid Dressing Strip (5 Nos)
5. Provodinelodine Ointment U.S.P 20 gm (1 Nos)
6. Absorbent Cotton Wool 15 Gm (1 Nos)
7. Antiseptic Liquid 100 Ml. 1 Nos
8. Clinical Thermometer 1 Nos
9. Elastic Adhesive Bandage 6 CM x 10 CM (1 Nos)
10. Antiseptic Pre injection alcoholswab (5 Nos)
11. Scissor (1 Nos)



## II. AUTOMATIC LOADING STRETCHER FOR AMBULANCE

(Size: 190L x 55W x 90Hcms)

### Product Specification

<b>Type</b>	Automatic stretcher
<b>Size</b>	190L x 55W x 90Hcms
<b>Color</b>	Orange
<b>Handles</b>	Yes
<b>Design</b>	Light weight, durable, and easy for sterilization
<b>Load Bearing (kg)</b>	159kg
<b>Weight (kg)</b>	40kg
<b>Number of Wheels</b>	8
<b>Foldable Type</b>	Foldable
<b>Load Limit (kg)</b>	159kg
<b>Castors Diameter</b>	150mm
<b>Folded Size (cm)</b>	190 x 60 x 26cms
<b>Coating</b>	Aluminium
<b>Wheel Material</b>	Mild Steel
<b>Style</b>	Stretcher
<b>Shape</b>	Rectangle
<b>Packaging Type</b>	Box Packing
<b>Tube Material</b>	Aluminium alloy thick-wall pipes
<b>Mattress Material</b>	Foamed
<b>Back-Rest Lifting</b>	60 degree angle
<b>Brand</b>	SCARE

### Product Description

#### Salient Features


- This is made of high-strength aluminium alloy thick-wall pipes. It is supplied with foamed cushion and the adjustable back making the wounded feel comfortable.
- This machine is very convenient; one person is enough to send the patient (with this stretcher) to the ambulance car.
- The mechanical foldaway legs are controlled by the handles on the both ends of the stretcher and the legs can be folded under the stretcher automatically when loading into the vehicle. Also the stretcher can be locked by the fixing devices when on the ambulance car.
- This type of stretcher is characterized by its light weight, durable, safe usage and easy for sterilization.



## V. ALUMINIUM ALLOY SCOOP STRETCHER

### Product Specification

Type	Hospital
Material	Aluminum
Length	Up to 6 Feet
Color	Silver
Loading Capacity	Up to 150 kg



## VI. STAIR STRETCHER

Size	90 x 51 x 91cm
Color	Red
Brand	SSTAIR

### Specifications:

Model	YXH-5A
Product Size	90 X 51 X 91 CM
Folder Size	90 X 17 X 59 CM
Load Bearing	< 159 kg
N.W.	8 kg
G.W.	9.2 kg



# HOME NURSING



## I. NURSING BED

### Product Specification

Type	Hospital
BedSize	2150x950x380-720 mm (LxWxH)
No. Of Wheels	4 Wheels
Load Capacity (kg)	150 Kg Approx
Material	Stainless Steel



## II. OXYGEN THERAPY

### Technical Specification

Model	HiFent(HUMID-BM)
Dimensions (mm)	291W x 186H x 162D
Weight (kg)	1.7 Kg
Display	LCD 3.5 inch HD colourDisplay
Flow Setting Range	2 -25 L/min (Junior Mode) 10 -80 L/min (HiflowMode)
Heat Temp. Range	31 / 34 / 37 °C
Heating Element	Metal Heater Plate
Max. Oxygen Input	80 L/min
Oxygen Concentration	21 % ~ 100
Classification	Class II a
Certification/Standard	CE, IEC, EN & ISO
Power	100 240 V
Power Consumption	≤ 350 watts
Disinfection procedure	Ozone Technology
Disinfection Time	30 min
Accessories	Pole Stand, Pole Mounting Tray & Braket , Hiflow Meter,Disinfection Device, HME Filter ,Connecting O 2 tube.



## III. PATIENT LIFTING HOIST

### Product Specification

Brand	Syplean
Maximum Load	180 Kg
Maximum Lifting Height(m)	5 ft
Number of Stops	0-5
Machine Room	Required
Maximum Lifting Speed	12 (m/s)
Loading Capacity	180 Kg

### Product Description

-We hold expertise in offering our clients a qualitative range of SYPLEAN Patient Lifting Hoistat a very nominal price.

### Features:

- Excellent load bearing capacity
- Elevated durability
- Sturdiness



## IV. RIPPLE MATTRESS

### Product Specification

<b>Power Source</b>	Electric
<b>Voltage</b>	180 V
<b>Frequency</b>	50 Hz
<b>Phase</b>	Single Phase

### Features:

- Sturdy construction
- Fine quality
- Excellent service life

### Product Description

- We are a prominent provider of Pneumatic Ripple Beds to our clients.
- These beds are noted for their robust construction and excellent quality.
- These offer most comfort to bed ridden patient, prevention of bed sore, hospital bed size pattern, hot air circulation.
- We are offering these beds after thorough




## V. MAIDESITE BED (Hospital Bed, Mild Steel)

### Product Specification

<b>Type</b>	Semi Electric Beds
<b>Usage/Application</b>	Hospitals
<b>Frame Material</b>	Mild Steel
<b>Folded</b>	Yes

### Product Description

- Back rest adjustable on lever mechanism.
- Overall size : 203L x 90W x 60H cms.
- Frame work of mild steel rectangular CRC tubes.
- Mounted on PVC stumps.
- Head and leg bow of M.S. tubular pipes, epoxy coated with vertical supports on either side.
- Provision for saline / IV rod at four locations.
- Pre-treated epoxy powder coated finish.
- Knockdown construction.



# MEDICAL DEVICES



## I. TENS AND EMS DEVICES

### Product Specification

<b>Channels</b>	4 Channel
<b>Usage</b>	Clinical/Hospital
<b>Voltage</b>	50 Hz
<b>Color</b>	White
<b>Material</b>	Mild Steel
<b>Country of Origin</b>	Made in India
<b>Surface Finishing</b>	Powder Coated



### Product Description

- TENS stands for Transcutaneous Electrical Nerve Stimulation.
- It is a method of pain relief.
- The placement of the TENS electrode pads is carefully selected to target the problematic areas which are causing pain.
- The theory is that the electrical impulses from the machine modify the pain signals which are transmitted to the brain via the nerves.
- You should experience a slight tingling sensation when the machine is in use.
- Many users find that they may have to wait a few weeks before obtaining effective results.

## II. DOPPLER HANDHELD

### Product Specification

<b>Number Of Transducer Sockets</b>	2
<b>Connectivity</b>	DICOM
<b>Weight</b>	500 g
<b>Is It Portable</b>	Portable
<b>Display Type</b>	Digital
<b>Material</b>	ABS
<b>Probe Frequency</b>	2 MHZ
<b>Features</b>	With Heart-Rate Monitor



## III. STETHOSCOPE AND DIAGNOSTIC TOOL

### Product Specification

<b>Color</b>	Black
<b>Chest Piece Material</b>	Aluminium
<b>Usage/Application</b>	Hospitals, Clinics and Medical Collages
<b>Chestpiece</b>	Double Sided
<b>Diaphragm</b>	Tunable
<b>Features</b>	Powder Coating
<b>Weight</b>	180 gram

### Product Description

- Accessories - Pair of Soft Ear tips, diaphragm
  - Application - Professional Practitioners, Medical Students & Cardiologist
  - Key Features - Stethoscope Super Soft & Sealing Ear Knob Stunning Looks . Excellent Acoustic Level Available tubing color are Ash, Red, blue, Yellow.
- Package include:  
1 x Professional Stethoscope 2 x Eartips 1 x Diaphragm



## IV. PATIENT BED SIDE MONITOR

### Product Specification

NIBP Measurement range	10-270mmHg
Brand	CREATIVES
PO2 Measurement Range	0-50%
Model	CMS-104
Pulse Rate Range	20-200bpm
Number Of Parameters	5
Charging Time	4 Hours
Parameters	ECG,SPO2,NIBP,RESP,TEMP
Screen Size	12. 1"
Display Type	TFT
ECG Lead Mode	5 lead
Handling Option	Portable
Heart Rate Range	15-300 bpm
Suitable For	Neonatal, Pediatric, Adult
NIBP Mode	Manual, Auto, Continuous



## VI. BREATH ALCOHOL ANALYSER

### Product Specification

Application	Law Enforcement Agencies
Warning Signal	Beep
Display	LCD Display
Type of Mouthpiece	Replaceable
Model Number/Name	Fuel-Cells Sensor
ModelsAnalyzingtime	3 s

### Product Description

- Advance NM Hot Wire Alcohol sensorQuickResponse.
- Smart MCU ControldirectTesting Process LCD Indication.
- Digital LCD display with Light Blue Backup.
- Portable, Audio Warning Beyond Pre-set Limit.
- Sensor Fault Self checking, Battery Saved Design.
- Low Voltage Indication
- Application to Driving and Dangerous Work.



## - STAINLESS STEEL MEDICINE TROLLEY

### Product Specification

Usage/Application	Hospital
Material	Stainless Steel
Size	24 X 48 72 (L,W,H) Inch
Color	Silver
Capacity	150 Kg
No. Of Wheels	4
No. Of Drawers	2



## V. HEARING AID

### Product Specification

No. Of Channels	3-4
Brand	PhonakAid
Placement	Behind The Ear
Type	BTE
Battery Life	45-55 Hr



## VII. EQUIPMENT ART - SS MEDICAL TROLLEY

### Product Specification

Usage/Application	Hospital
Material	Stainless Steel
Finishing	Polished
Number Of Shelve	3
Steel Grade	Ss304
Height	750 MMN
No. Of Wheel	4

### Product Specification

Product Type	Crash Cart
Usage/Application	Hospital
Material	Stainless Steel
Size	760 mm L x 380 mm W x 1500 mm H
No. Of Wheels	4
No. Of Drawers	Multy Drawer



# ANGIOGRAPHIC PRODUCT

A. HVA – Hemostasis Valve Adapter



B. Guide Wire Insertion Device



C. PTA CATHETERS



D. DRAINAGE ACCESS (INTRODUCER SYSTEM)



E. WATER SEALED DRAINAGE BAG



F. ANGIOGRAPHIC NEEDLES



# WHEEL CHAIR

## I. SWING INVALID WHEELCHAIR

### Product Specification

Type	Wheelchair
Seat Width	46 cm
Seat Depth	46.5cm
Weight Carrying Capacity	150 kg. (approx.)
Front Swivel Castors	20cm
Rear Solid Tyres	60 cm with brakes

### Product Description

- Folding Type, Self Propelling
- Stainless Steel Frame Work
- Foldable Aluminium Foot Rests, Swing-out & Detachable Leg Rests
- With Swing Back, comfortable Arm Rests.
- Strong Washable Seat & Back



## II. ELECTRIC POWER WHEELCHAIR

### Product Specification

Type Of Wheelchairs	Ergonomic Wheelchairs
Frame Color	Black
Max Speed	8-10 km/h
Color	Black
Brand	Easy Move
Dimension (h*w*l)	97*65*85cm
Seat width-depth-height	45cm-45cm-52cm
Wheels Front	10' solid tire
Rear	18' air tire
Weight Capacity	100 KGS
Motor	24V DC 250W*2
Battery Capacity	12V 12Ah*2
weight	4.5kg*2
Dimension	19.5*13*18cm*2
Charger	24V x 5AMP
Recharge time	6-8hrs
Incline capability	12 degrees
Net weight(with batteries)	44KG
Net weight	35KG (without batteries)
Flip-up armrest	Yes
Swing-away footrest	Yes



# INFUSION PUMP



## Product Specification

<b>Type</b>	Infusion Pump
<b>Power Supply</b>	12V DC (1A) Adaptor
<b>Battery / Backup</b>	7.2V NIMH 800mAh
<b>Back up time</b>	8 -10 hrs @ 10 drop/min
<b>Power Consumption</b>	3VA
<b>Pumping Mechanism</b>	Gravity
<b>Drop Sensor</b>	Internal Applicable IV Set
<b>Compatible with</b>	all brand IV set
<b>Display</b>	7- Segment (4nos) & LED
<b>Flow rate Range (Dr/min)</b>	1 to 150 drop/min for Adults 1 to 100 drop/min for Micro 1 to 350 ml/hr for Adults 1 to 100 ml/hr for Micro
<b>Flow rate Range (ml/hr)</b>	1 to 100 ml/hr for Micro
<b>Drop Rate Resolution</b>	1 drop/min (Adult & Micro) 1 ml/hr (Adult & Micro)
<b>MI Rate Resolution</b>	1 ml/hr (Adult & Micro)
<b>Infused Volume</b>	0.1 – 9999 ml
<b>Elapsed Time</b>	00:01 to 99:59 hrs
<b>V Set ml Conversion</b>	Adult :12 to 26 dr/ml in steps of 0.1 drop Micro :50 to 85 dr/ml in steps of 1drop
<b>Accuracy</b>	± 5%
<b>KVO</b>	0.5 drop/min
<b>Modes</b>	Drops/min, Target volume, Target time
<b>Dimension in mm &amp; Weight</b>	106(L) x 121(H) x 55(B) & 450 g
<b>Cabinet</b>	ABS Plastic
<b>Coating</b>	Rust proof durable
<b>Target Volume</b>	0.1 to 999.9ml
<b>Target Time</b>	1min to 200 hr 59 min
<b>Target Volume Steps</b>	Adult 0.1 to 100 ml step 0.1 ml 100 to 999.9 ml steps 10 ml Micro: 0.1 to 10 ml step 0.1 ml 10 to 100 ml steps 1 ml 100 to 999.9ml steps 10 ml
<b>Display Type</b>	LED DISPLAY
<b>Certification</b>	ISO 13485:2003, CE



# HIGH SPEED CENTRIFUGE

## Product Specification

<b>Usage/Application</b>	Laboratory
<b>Size</b>	36,48 Inch
<b>Material</b>	Stainless Steel
<b>Type</b>	Laboratory Centrifuge
<b>Maximum speed</b>	20000 rpm
<b>Display</b>	Digital LCD with Set & Working Parameters
<b>Digital countdown timer</b>	0-99 minutes
<b>Model Number</b>	TC 4815 D
<b>Control</b>	Microprocessor
<b>Max. Speed</b>	16000 RPM
<b>Max. Rcf</b>	17500 x g Max
<b>Capacity</b>	48 ml
<b>Program Memory</b>	Last Used Program Memory
<b>Acceleration</b>	30 - 300 Secs
<b>Timer</b>	1 - 99 Min
<b>Safety</b>	Sturdy Cabinet, Lid Lock & Imbalance Protection
<b>Choice of Rotor Heads (Angle)</b>	10
<b>Power Supply</b>	230V, 50 Hz



# OXYGEN CONCENTRATOR



## SINGLE FLOW OXYGEN CONCENTRATOR WITH NEBULIZER

### Product Specification

<b>Brand</b>	Nareena
<b>Model Name/Number</b>	NLS-OCSF-10 L
<b>Oxygen Concentration</b>	1-10 LPM, 93 % + -3 %
<b>Usage/Application</b>	Hospital
<b>Warranty</b>	2 Year
<b>Voltage</b>	220 V +- 22 V/110 V+-10 V
<b>Frequency</b>	50/60 Hz
<b>Output Pressure</b>	58.6 +-6 kPa
<b>Input Power</b>	720 Va
<b>Operating Environmental Temperature</b>	5-40 Degree C
<b>Atmospheric Pressure</b>	86 kPa-106 kPa
<b>Weight Of Machine</b>	22.6 Kg

### Product Description

#### Features

- 24 hours work continuously, Nebulizer Function
- Three alarm systems ( power off alarm pressure circulation fault alarm and compressor fault alarm)
- AVG oxygen purity:93%±3%
- Low sound level: less than 55dB (A)



# THERMOMETER

## I. CLINICAL MERCURY THERMOMETER

### Product Specification

<b>Type</b>	Mercury
<b>Temperature Range</b>	36-42 C
<b>Response Time</b>	60 Seconds
<b>Usage / Application</b>	Oral Rectal & Underarm
<b>Country of Origin</b>	Made in India



## II. DIGITAL THERMOMETER

### Product Specification

<b>Type</b>	Digital Temperature
<b>Range</b>	-10 To 45 Degree C
<b>Response Time</b>	6 Sec.
<b>Warranty</b>	12 Months
<b>Country of Origin</b>	Made in India
<b>Weight</b>	9.8 gm
<b>Dimension</b>	125 mm x 19 mm x 11 mm
<b>Life Of Battery</b>	2 years or 2500 times
<b>Auto Power Off</b>	8 minute, +-2 minute



# III. CONTACTLESS INFRARED THERMOMETER



## Product Specification

<b>Feature</b>	Contactless
<b>Type</b>	Infrared
<b>Range</b>	-30 Degree C to +350 Degree C
<b>Material</b>	ABS
<b>Accuracy</b>	3 to 15
<b>Display</b>	Digital
<b>Auto Off</b>	In 1 min
<b>Usage/Application</b>	Medical, Personal
<b>Warranty</b>	1 Year



# VITAL SIGN MONITOR

## Product Specification

<b>Power Source</b>	Electricity
<b>Display Type</b>	Digital
<b>Voltage</b>	240 V
<b>Suitable for</b>	Neonatal, Infant, Pediatric
<b>Type of Product</b>	Patient Monitor Parameters
<b>Parameters</b>	Pulse Rate, SPO2
<b>CO2 Measuring parameters</b>	Respiration Rate, EtCO2, InsCO2 EtCO2
<b>EtCO2 Measurement Range</b>	0-150 mmHg
<b>InsCO2 Measurement Range</b>	3-50 mmHg
<b>Respiration Range</b>	0-150 bpm
<b>CO2 Resolution</b>	0.1mmHg, 0.25mmHg



# WEIGHING SCALE

## I. WEIGHING BALANCE

### Product Specification

<b>Type</b>	Weighing Balance
<b>Balance Capacity</b>	150Kg
<b>Graduation</b>	500 gm
<b>Dimension</b>	26.7 x 26.8 x 5.0 cm of the scale
<b>Use</b>	Home, Clinical
<b>Warranty</b>	1 year



## II. HOSPITAL WEIGHING SCALE

### Product Specification

<b>Type</b>	Weighing Balance
<b>Use</b>	Hospital and Medical
<b>Weighing Capacity</b>	Above 100
<b>Accuracy</b>	100 GM
<b>Configuration</b>	Handrail for support
<b>MOC</b>	SS Top Plate - 202 or 304

## III. HOSPITAL BABY WEIGHING SCALE



### Product Specification

<b>Usage/Application</b>	Hospital
<b>Brand</b>	Korridda Medical System
<b>Material</b>	ABS plastic
<b>Battery</b>	6V/4Ah
<b>Display Type</b>	LED
<b>Size</b>	40 Cms x 15 Cms x 15 Cms
<b>Capacity</b>	30 kg
<b>Bowel Size</b>	550 X 300 mm
<b>Accuracy</b>	10. g



## SYRINGES

### Product Specification

<b>Usage</b>	Hospital
<b>Size</b>	2-10 ml
<b>Material</b>	PlasticWall
<b>Type</b>	Regular
<b>WallTipType</b>	Slip-Tip'

### SYRINGE TYPE

- 1) 2ml syringes with needle : Blister pack
- 2) 3ml syringes with needle : Blister pack
- 3) 5ml syringes with needle : Blister pack
- 4) 10ml syringes with needle : Blister pack

### PACKING DETAILS

- All our syringes are 3 Pc. (with black rubber gasket)  
(NEEDLE 24GX1" or 23GX1" or 21GX1.5")
- Packing style : Blister pack



## SWAB GAUZE

### Features list :

- High absorption capacity.
- Swabs have Folding Edge, so there is no chance of loose thread.
- Made from Cotton Gauze fabric.

### Packing Details

- Good Sterile pack, there indicates the coformsterility.
- Individual Gauze Swab packed in single pouch.
- 20/50/100 Pouch pack in box pack.

### Size Availability :

- 5cm X 5cm X 8ply / 12ply / 16ply
- 7.5 X 7.5cm X 8ply / 12ply/ 16ply
- 10cm X 10cm X 8ply / 12ply/ 16ply
- 40cm X 40cm X 8ply / 12ply/ 16ply
- Number of thread 24 X 18



# DESINFECTATION TABLET



## Certification :

- WHO approved
- ISO 9001:2015.
- COA Available
- FDA recommended
- HAFFKINE Certified

## Usage:

- 1 tablet to be dissolved in 10 litres of water and then it can be used for disinfection of all surfaces, areas, walls, doors, cars, wheels, vegetables etc
- Let us save ourselves from getting Infected.



# DISPOSABLE PRODUCTS

## I. SURGICAL MASK

<b>Materials</b>	<b>Mask Body</b>	Outer Material	Polypropylene Spunbond nonwoven
		Filter Layer	Meltblown Nonwoven
		Inner Material	Polypropylene Spunbond nonwoven
	<b>Nose-piece</b>		PE wire (Metal Free)
	<b>Earloop</b>		Flat elastic or round elastic (latex Free)
<b>Dimension</b>	<b>Body Size</b>	Length	90 mm +/-2mm
		Width	175 mm +/-2mm
	<b>Depth pleated</b>		90mm +/-2mm
	<b>Depth full</b>		175 mm +/-2mm
	<b>Loop size</b>		155 mm +/-2mm



### Additional Information

Store under cool, clean, and dry conditions. Avoid excessive heat (over 40°C or 104°F)  
INDIA  
50 Mask in Single Pack, 2500 Mask in master pack  
Blue

## II. N95 FACE MASK

**N95 MASK (HS CODE : 90189099) – Level 5 Barrier Protection**

### Characteristic

- High Bacterial Filtration Efficiency (BFE)
- Fluid Resistance
- High Particulate Filtration Efficiency (PFE)
- Textile Flammability

### Characteristic Specification

<b>Materials</b>	<b>Mask Body</b>	Filter Layer	Meltblownfilter (25GSM)
		Filter Layer	Meltblownfilter (25GSM)
		Filter Layer	Meltblownfilter (25GSM)
		Inner Material	Polypropylene Spunbondnonwoven (20GSM)
		Outer Material	Polypropylene Spunbond nonwoven (60GSM)
	<b>Nose-piece</b>		Flexible metal Nose piece
	<b>Earloop Round</b>		Soft Elastic
	<b>Respirator</b>		Plastic Round Shape respirator Round half oval shape
<b>Dimension</b>	<b>Body Size</b>	Length	<b>15.5 cm +/-0.1cm</b>
		Width	10.0 cm +/-0.1cm
		Loop size	<b>16.5 cm +/-0.1cm</b>



### Additional Information

**Storage Condition** Store under cool, clean, and dry conditions. Avoid excessive h  
**Country of Origin** INDIA  
**Packaging Information** 50 Mask in Single Pack, 2500 Mask in master pack  
**Colour** WHITE, GRAY, PINK, YELLOW



# III. DISPOSABLE APRON

## - NON WOVEN APRON

<b>Colour</b>	Blue, White
<b>Material</b>	Non Woven
<b>Mode</b>	Disposable
<b>Size</b>	Free/Customize
<b>Packing</b>	individual APRON



## APRON SPECIFICATION

- Latex Free
- Non Sterile, Single use
- One size fits all, High level fluid protection
- Blue/white colour non woven fabric with 2% Antibacterial hydrophobic
- Shelf Life : 5 Year
- Mode : Disposable Non woven
- Quality compliant with following standard
- a. ISO/IEC 17025 : 2017 NABL ACCREDITED With SITRA (The South Indian Research Association) (Physical, Chemical & Biological Testing Report)
- b. ISO/IEC 17025 : 2017 NABL ACCREDITED With ATRIA (Ahmedabad Textile Industry's Research Association) Approval

## - DISPOSABLE SURGICAL GOWN

<b>Colour</b>	Blue, White
<b>Material</b>	SMS Nonwoven/PP Spun bond
<b>Mode</b>	Disposable
<b>Size</b>	Free/Customize
<b>Packing</b>	individual APRON

## GOWN SPECIFICATION

- Impermeable to blood and body fluids and single use.
- Material : SMS Nonwoven/ PP Spun bond
- Avoid culturally unacceptable colour. Example. Blue and White
- Blue/white colour non-woven fabric with 2% Antibacterial hydrophobic (90GSM)
- Packing : Individual
- Mode : Disposable
- Test parameters pass having ATIRA test report (ISO/IEC 17025 : 2017 NABL ACCREDITED) & SITRA (THE SOUTH INDIA TEXTILE RESEARCH ASSOCIATION) Pass all test attached below.



## DISPOSABLE COVERALL/BOILER SUIT

<b>Colour</b>	Blue, White
<b>Material</b>	SMS Nonwoven/PP Spun bond
<b>Mode</b>	Disposable
<b>Size</b>	Customize
<b>Packing</b>	indivial

## COVERALL SPECIFICATION

- Coverall 90 GSM ETO sterilized (70 GSM fabric + 20 GSM ETO plastic layer = 90 GSM )
- Impermeable to blood and body fluids and single use.
- Fabric weight 83.4 g/m<sup>3</sup>(ASTM D 3776 Option C Test method)
- Avoid culturally unacceptable colour. Example. Blue and White
- Blue/white colour non-woven fabric with 2% Antibacterial hydrophobic (90GSM ETO Sterilized)
- Same fabric full size coverall one pair.
- Water repellency by spray test. Water resistance by hydrostatic pressure 60 mbar. Water Absorbency.
- Air permeability, Flame Retardency(Flammability), Pore Size this all Test parameters pass having ATIRA test report (ISO/IEC 17025 : 2017 NABL ACCREDITED) & SITRA (THE SOUTH INDIA TEXTILE RESEARCH ASSOCIATION) Pass all test attached below.



## IV. DISPOSABLE BIO HAZARD BAG MEDICAL



### Product Description :

- These translucent bags are manufactured using high molecular weight, high-density polyethylene which is of 0.03-mm wall thickness.
- Imprinted with standard orange-red bio hazard warning label.
- Bags can be autoclaved at a maximum of 121 C.
- Sterilization indicator patch darkens when subjected to steam sterilization.
- These are perfect for safe disposal of used pipets, Petri dishes, culture plates, and more.

### Product Specification

<b>Color</b>	Red
<b>Size</b>	25 X 30 inches
<b>Capacity</b>	30-60 liter
<b>Material</b>	Plastic

- Used in hospitals and surgery centers to collect potentially infectious waste
- Biohazard emblem and warnings in English
- High density polyethylene (HDPE) construction
- Case of 500 and 1000 piece
- Latex free -Smooth surface finish



## V. FACE SHIELD

### - NON-DISPOSABLE POLYCARBONATE FACE SHIELD

#### Product Specification

<b>Material</b>	Polycarbonate
<b>Disposability</b>	Non-Disposable
<b>Thickness</b>	1-2 mm
<b>Color</b>	Transparent
<b>Country of Origin</b>	Made in India

#### Product Description

- Optical Clarity
- High Impact Resistance
- Unbreakable
- Washable
- Movable Visor
- Scratch Resistant
- Can be Sterilized And Sanitized



### - GOGGLE FACE SHIELD (FRAME TYPE)

#### Product Specification

<b>Material</b>	Polycarbonate
	Frame, APET Visor
<b>Frame Type</b>	PC Poly Carbonate
<b>Standards</b>	CE,ISO
<b>Size</b>	265mm x 208mm

**Products in the Kit Frame and Visor**

**Country of Origin Made in India**



# GLOVES



## I. NITRILE GLOVE (POWER FREE)

### Product Specification

Brand	SYPNILE
Category	Non-Sterile
Color	BLUE, WHITE
Sizes	6 inches
Material	Rubber, Latex
Type	Disposable
Gender	Unisex
Usage	Hospital, Clinic, Medical Centre, Dental
Packaging Size	100 piece in box or 2000 piece in loss



## II. LATEX GLOVE

### Product Specification

Material	Latex
Brand	SYPCARE
Size	S M L XL
Sleeve Length	240 MM
Standard	ISO 9001:2015
Glove Type	UPTO WRIST
Usage	Hospital, Clinic, Medical Centre
Packaging	Size100 piece in box or 2000 piece in loose bag



# MICROSCOPE

## I. BINOCULAR MICROSCOPE

### Product Specification

Model Number/Name	MLXiPlus LED
Brand	Magnus
Optical Tube	Binocular
Illumination	6v 20W Halogen
Power	100V-240V 50/60Hz
Warranty	1 year
Nose Piece	Quadruple
Accessories	Dust Cover
Voltage	220V
Eyepiece	10x WF Fn20
Objective	4x, 10x, 40x, 100x
Mechanical Stage Size	125 x 145mm
Fine Focus Ragne	0.2 mm
Mechanical Stage	Co-axial low drive mechanical Stage (125mmx145mm) with traverse area of 50mmx76mm (+/-5mm)
Battery Backup	6 to 8 hrs back-up on full charge
Lamp	6V 20W halogen lamp (x2)L
Power Supply	100-240 V
long Life	30000 hrs
Working Distance	108 mm
Portable	Yes
Color	White



### Product Description

**Features:** Plan Infinity Optics with Field of view 20mm  
Parfocaland Centered Optics  
Optics with Multi-layer Coating & Anti-Fungus treated  
Choice of Halogen and LED Illumination  
Easy Access for Lamp Replacement  
Siedentophead. Hard-Coated Stage  
Double Slide Holder. Inward Nosepiece  
Universal Power Supply

## II. DIGITAL MICROSCOPE



### Product Specification

<b>Magnification</b>	40X to 1000X
<b>Brand</b>	QUASMO
<b>Light Source</b>	LED
<b>Color</b>	White and Blue
<b>Power Supply</b>	220 V
<b>Lens Type</b>	Achromatic/ Semi-plan/ Plan Objectives
<b>Country of Origin</b>	Made in India

### Product Description

**Optical System** : High Contrast Infinity corrected Optical System.

**Observation Head** : Binocular / Trinocular head inclined at 30° with Interpupillary distance of 50-75mm with dioptic adjustment.

**Nose-piece** : Inward, Quintuple revolving nose-piece ball bearing type with proper click stops.

**Eyepieces** : Wide Field 10x eye-piece with 22mm F.O.V, anti-fungal & anti-reflection hard coated.

**Mechanical Stage** : Rackless & Scratchless Double plate stage size 180mm X160mm. X/Y travel range 75mm X 50mm.

**Division** : 0.1mm Low drive right side movement.

**Objectives** : High Contrast Infinity corrected iQVST series Plan Achromatic objectives 4x (N.A. 0.10, W.D. 25mm), 10x (N.A. 0.25, W.D. 6.7mm), 40x (SL, N.A. 0.65, W.D. 0.6mm) and 100x (SL, Oil, N.A. 1.25, W.D. 0.17mm) antifungal, anti-reflection hard coated.

**Condenser** : Abbe condenser NA 1.25 with aspheric lens. Iris diaphragm with Frosted white filter, antifungal & antireflection coated. Rack and pinion movements on stainless steel guides Focusing.

**Control** : Co-axial coarse and fine focusing on gear systems for smooth operation. Fine adjustment 0.2mm / rotation with maximum 2 microns scale increment.

**Illumination** : Q-LED 3.5W 3V illumination with variable control. Up to 100,000 hours of LED life.

**Electronics** : Koehler Universal input 110V/240V AC, 50/60 Hz.

**Certifications** : BIS (ISI), ISO 9001, ISO 13485, EuCe.

**Optional Attachment** : Monocular Head, QVST series DIN Infinity Plan objectives 20x, 60x SL, WF 15x, WF 20x, Pointers & Micrometer Reticules, Phase contrast, Polarizing, Fluorescence and Dark Field attachments, Digital USB Cameras (1.3MP, 3MP, 5MP, 14MP) with in-built adaptors, Digital Cameras and DSLR Cameras with adaptors, Illumination System Halogen 6V 20W.



# III. TRINOCULAR RESEARCH MICROSCOPE



## PRODUCT SPECIFICATION

<b>Light Source</b>	LED
<b>Model Name/Number</b>	LXL-DG
<b>Brand</b>	LABAPPARAMagnification1000x
<b>Usage/Application</b>	Laboratory, Clinical, medical , Pathology
<b>Draw Tube</b>	Trinocular
<b>Power</b>	100 V To 240 V,ac50-60 Hz
<b>Color</b>	Off White & Black
<b>Power Supply</b>	Universal Power Supply

## PRODUCT DESCRIPTION

### Trinocular Research Microscope (Model: LXL-DG)

#### Trinocular Observation Head :

Siedentopf Observation head inclined at 30° rotatable at 360°. Vertical phototube for photomicrography. Diopter adjustment ring on ocular tube. ( $\pm 5$ ). Inter-pupillary distance from 48mm to 75mm.

**Eyepiece (Anti fungus coated) :** Wide Field 10X (paired) F.O.V 20mm.

#### Objectives (Anti fungus coated) :

E-Plan Achromatic 4X

E-Plan Achromatic 10X

E-Plan Achromatic 40X(S.L.)

E-Plan Achromatic 100X Oil(S.L.)

**Mechanical Body :** Double plate mechanical stage size 140mm X 132mm having low positioned co-axial controls.

Cross movement 76mm X 50mm.

**Focusing :** co-axial focusing system. pre-focusing lever & tension adjustment ring. The slow motion has 1Div=0.002mm.

**Nosepiece :** Quadruple nosepiece revolves on ball bearing.

**Sub Stage Condenser :** Abbe condenser N.A.1.25 swing out filter holder, iris diaphragm.

**Illumination System :** The built-in-base illumination system with Ultra high brightness single 3W LED cold light source. Brightness control knob.

**Standard Accessories :** Operating manual, dust cover, guarantee card and Styrofoam molded pack. Warranty 2 years.





**SYPTONE**  
IMPEX



ISO 9001:2015  
Certified Company

**SYPTONE IMPEX**



**Email :** [office.syptoneimpex@gmail.com](mailto:office.syptoneimpex@gmail.com)

**Contact :** +91 79848 67516, +91 96624 03702

**Office :** FF-102, Khushi Arcade, Nr. Khodiyar Temple, Nikol-Odhav Road, Nikol,  
Ahmedabad-50, Gujarat, India.