



ISO 9001 : 2015 (QMS)
Certified Company



ISO 14001 : 2015 (EMS)
Certified Company

Leepol™ Carbomers | Leepol™ Coats | Leepol™ HCO
Acids | Chemicals | Solvents | Dyes | Pigments | APIs
Hazardous Waste Management



MATERIAL SAFETY DATA SHEET
LEEPOL™ 940 POLYMER

THE LEELA CORPORATION
Page 1 of 7

Section 1 | Chemical Product and Company Identification

THE LEELA CORPORATION

F2, Mangalam Nirwana 2,
B/h Umiya Campus, Sola,
Ahmedabad – 380060
Gujarat, India

| | |
|--------------------------|--|
| Product Trade Name | LEEPOL™ CARBOMER 940 POLYMER |
| Generic Chemical Name | Polyacrylic acid |
| Ingredients | Acrylic Polymer (>98%) |
| Synonyms | Carbomer 940, Carboxyvinyl Polymer |
| CAS Number | 9003-01-4 |
| H.S. CODE | 39069090 |
| Product Type | Not applicable |
| Transportation Emergency | FOR TRANSPORT EMERGENCY call Mr. Ujas Patel Phone No. +91 9724216384 |
| MSDS No. | MSDS/TLC/940/21-22 |

Section 2 | Hazards Identification

| | |
|-------------------|--|
| Appearance | White powders |
| Odor | Slight acetic |
| Principal Hazards | Caution Dusts may be harmful if inhaled |

See Section 11 for complete health hazard information.

Section 3 | Composition / Information on ingredients

| Chemical Name | CAS Number | Percent by Weight |
|--------------------|------------|-------------------|
| Acrylic Acid Resin | 9003-01-4 | 0.1-0.5% |

THE LEELA HOUSE

F/2 Mangalam Nirvana- 2, Behind Umiya Campus, Sola, S. G Highway, Ahmedabad-380060, Gujarat, INDIA



+91 972 421 6384



info@leelacorp.com



www.leelacorp.com

| | |
|------------------|---------------------------|
| Section 4 | First Aid Measures |
|------------------|---------------------------|

| | | |
|------------------------|---|--|
| Eyes | : | Immediately flush eyes with plenty of one percent (1%) physiological saline solution for five (5) minutes while holding eyelids open. If no saline is available, flush with plenty of clean water for fifteen (15) minutes. See a physician. Water (Moisture) swells this product into a gelatinous film which may be difficult to remove from the eye using only water. |
| Skin | : | Wash with soap and water. Get medical attention if irritation develops. Launder contaminated clothing before reuse. |
| Inhalation | : | Remove exposed person to fresh air if adverse effects are observed. If Breathing is labored, administer oxygen. If breathing has stopped, apply artificial respiration. If irritation persists or if toxic symptoms are observed, get medical attention. |
| Oral | : | Treat symptomatically. Get medical attention. |
| Additional Information | : | Note to physician: Treat symptomatically |

| | |
|------------------|-------------------------------|
| Section 5 | Fire Fighting Measures |
|------------------|-------------------------------|

| | | |
|------------------------|---|---|
| Flammability class | : | Not Applicable |
| Flash Point | : | Not Applicable |
| Extinguishing Media | : | CO2, dry chemical, foam, water spray, water fog. Carbon dioxide may be ineffective on larger fires due to a lack of cooling capacity which may result in re-ignition. Avoid hose stream or any method which will create dust clouds. |
| Firefighting Procedure | : | Wear full protective fire-gear including self-containing breathing apparatus operated in the positive pressure mode with full face-piece, coat, pants, gloves and boots. |
| Unusual Fire | : | Solid does not readily release flammable vapors. Material can & Explosion Hazards form an explosive organic dust air mixture. |



The Leela Corporation

ISO 9001 : 2015 (QMS)
Certified Company



ISO 14001 : 2015 (EMS)
Certified Company

Leepol™ Carbomers | Leepol™ Coats | Leepol™ HCO
Acids | Chemicals | Solvents | Dyes | Pigments | APIs
Hazardous Waste Management



See section 10 for additional information.

Fire and Explosive Properties

| | | |
|------------------------------------|---|---------------------------------|
| Min. Explosive Concentration | : | 130 g/m ³ |
| Minimum ignition energy | : | > 0.03 joules |
| Deflagration Index, Kst (estimate) | : | 130 bar m/sec |
| Volume resistivity | : | 3.24 x 10+15 ohm-cm |
| Maximum rate of pressure rise | : | 380 bars @ 500 g/m ³ |
| Maximum explosion pressure | : | 4.8 bars @ 500 g/m ³ |
| Explosion severity | : | 2.02 (Severe) |
| Ignition temperature of dust cloud | : | 520°C (968°F) |

Section 6 Accidental Release Measures

| | | |
|------------------|---|--|
| Spill Procedures | : | Personal Protective Equipment must be worn. Take precautions to avoid release to the environment. Prevent entry into sewers and waterways. Dispose of in accordance with all federal, state and local environmental regulation. Avoid raising a dust. Wash spill area with detergent. Material is slippery when wet. |
|------------------|---|--|

Section 7 Handling and Storage

| | | |
|------------------------------|---|---|
| Pumping Temperature | : | Not applicable |
| Maximum Handling Temperature | : | Not determined |
| Handling Procedures | : | Maintain good housekeeping practices. Do not discharge into drains or the environment; dispose to an authorized waste collection point. Use appropriate containment to avoid environmental contamination. Avoid drinking, tasting, swallowing or ingesting this product. Avoid inhalation of dust, aerosol, mist, spray, fume, or vapor. Use with appropriate and adequate ventilation. Avoid contact with eyes, skin and clothing. Ground and bond containers when transferring material. Avoid prolonged skin contact. Launder contaminated clothing before reuse. Dispose of packaging or containers in accordance with local, regional, national and international regulations. |
| Maximum Storage Temperature | : | Not determined |
| Storage Procedures | : | Take precautions to avoid release to the environment. Store in a cool, dry, well-ventilated area. Keep container closed when not in use. |

THE LEELA HOUSE

F/2 Mangalam Nirvana- 2, Behind Umiya Campus, Sola, S. G Highway, Ahmedabad-380060, Gujarat, INDIA

+91 972 421 6384 info@leelacorp.com www.leelacorp.com



The Leela Corporation

ISO 9001 : 2015 (QMS)
Certified Company



ISO 14001 : 2015 (EMS)
Certified Company

Leepol™ Carbomers | Leepol™ Coats | Leepol™ HCO
Acids | Chemicals | Solvents | Dyes | Pigments | APIs
Hazardous Waste Management



See section 10 for incompatible materials.

Maximum Loading : Not determined
Temperature

| | |
|------------------|---|
| Section 8 | Exposure Controls/ Personal Protection |
|------------------|---|

Exposure Limits : None established
Other exposure limit : The industry-recommended permissible exposure limit for respirable polyacrylate dusts is 0.05 mg/m3
Engineering control : If use generates a dust, local exhaust ventilation is recommended. Prevent inhalation by providing effective general and, when necessary, local exhaust ventilation to draw dust away from workers. Avoid high concentrations of dust in air and accumulation of dust on equipment.
Gloves Procedures : Use good industrial hygiene practices to avoid skin contact. If contact with the material may occur wear chemically protective gloves.
Eye Protection : Safety glasses or goggles
Respiratory protection : Use dust masks and depending upon your specific use, appropriate respirator can be used with all applicable regulations.
Clothing recommendation : Long sleeve shirt is recommended.

| | |
|------------------|---|
| Section 9 | Physical and chemical Properties |
|------------------|---|

Flash Point : Not applicable
Upper Flammable limit : Not determined
Lower Flammable limit : Not determined
Auto-ignition Point : 520°C, 968°F
Explosion Data : Dust can form explosive mixtures in the air.
Vapor pressure : Not determined
pH : 2.5 – 3.5 at 1% in water
Specific Gravity : 1.4 (20°C)
Bulk Density : < 0.24 Kg/L, < 2
Lb/gal Water solubility : Material will swell in water Percent
Solid : Not determined
Percent volatile : > 2% By Weight
Volatile Organic Compound : Not determined
Vapor density : Not determined
Evaporation rate : Not determined
Odor : Slight acetic
Appearance : White powder
Viscosity : Not determined

THE LEELA HOUSE

F/2 Mangalam Nirvana- 2, Behind Umiya Campus, Sola, S. G Highway, Ahmedabad-380060, Gujarat, INDIA

+91 972 421 6384

info@leelacorp.com

www.leelacorp.com



The Leela Corporation

ISO 9001 : 2015 (QMS)
Certified Company



ISO 14001 : 2015 (EMS)
Certified Company

Leepol™ Carbomers | Leepol™ Coats | Leepol™ HCO
Acids | Chemicals | Solvents | Dyes | Pigments | APIs
Hazardous Waste Management



| | | |
|--------------------------|---|----------------|
| Odor Threshold | : | Not determined |
| Boiling Point | : | Not determined |
| Pour Point Temperature | : | Not determined |
| Melting / Freezing Point | : | Not determined |

| | |
|-------------------|---------------------------------|
| Section 10 | Stability and Reactivity |
|-------------------|---------------------------------|

| | | |
|-----------------------|---|--|
| Stability | : | Material is normally stable at moderately elevated temperature and pressures. |
| Decomposition | : | Not determined Temperature |
| Incompatibility | : | Heat may be generated if polymer comes in contact with strong basic materials like ammonia, sodium hydroxide or strong basic amines. |
| Polymerization | : | will not occur |
| Thermal decomposition | : | Smoke, carbon monoxide, carbon dioxide, aldehydes and other products of incomplete combustion. |
| Conditions to Avoid | : | Not Determined |

| | |
|-------------------|----------------------------------|
| Section 11 | Toxicological Information |
|-------------------|----------------------------------|

-- ACUTE EXPOSURE -

| | | |
|--------------------------|---|--|
| Eyes Irritation | : | Not expected to cause eye irritation. Based on data from components or similar materials. Particulates may cause mechanical irritation. Solid particles (powder or dust) on the eye may cause pain and irritation. |
| Skin Irritation | : | Not expected to be a primary skin irritant. Based on data from components or similar materials. |
| Respiratory Irritation | : | Breathing of dust may cause coughing, mucous production, and shortness of breath. |
| Dermal Toxicity | : | Rabbit LD50>5000 mg/kg. Based on data from components or similar materials. |
| Inhalation Toxicity | : | Avoid inhalation of dust. Animal studies indicate the inhalation of respirable polyacrylate dust may cause inflammatory changes in the lung. |
| Oral Toxicity | : | Rat LD50>5000 mg/kg. Based on data from components or similar materials. |
| Dermal Sensitization | : | Not expected to cause skin sensitization. Based on data from components or similar materials. |
| Inhalation Sensitization | : | No data available to indicate product or components may be respiratory sensitizers. |

THE LEELA HOUSE

F/2 Mangalam Nirvana- 2, Behind Umiya Campus, Sola, S. G Highway, Ahmedabad-380060, Gujarat, INDIA

+91 972 421 6384 info@leelacorp.com www.leelacorp.com

--CHRONIC EXPOSURE--

| | | |
|-----------------------|---|--|
| Chronic Toxicity | : | There were no observed adverse effects at exposures of 0.05 mg/m ³ . However, the inhalation of respirable dusts should be avoided by implementing respiratory protection measures and observing the recommended permissible exposure limit of 0.05 mg/m ³ . |
| Carcinogenicity | : | Not listed as a carcinogen or suspect carcinogen by OSHA. |
| Mutagenicity | : | No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic. |
| Reproductive Toxicity | : | No data available to indicate either product or components present at greater than 0.1% that may cause reproductive toxicity. |
| Teratogenicity | : | No data available to indicate product or any components contained at greater than 0.1% may cause birth defects. |

--ADDITIONAL INFORMATION--

| | | |
|-------|---|---|
| Other | : | Pre-existing skin conditions may be aggravated by prolonged or repeated exposure. Persons with sensitive airways (e.g. asthmatics) may react to vapors. This material readily absorbs moisture and may become thick and gelatinous upon contact with mucous membranes of the eye, or upon inhalation into the nasal passages. |
|-------|---|---|

| | |
|-------------------|-------------------------------|
| Section 12 | Ecological Information |
|-------------------|-------------------------------|

| | | |
|----------------------------------|---|--|
| Freshwater Fish Toxicity | : | The acute LC ₅₀ is 100-1000 mg/L based on literature. |
| Freshwater Invertebrate Toxicity | : | The acute EC ₅₀ is 100-1000 mg/L based on literature. |

This product is not biodegradable; do not inhibit waste treatment bacteria; and do not pass through typical waste water treatment to the environment.

| | |
|-------------------|--------------------------------|
| Section 13 | Disposal Considerations |
|-------------------|--------------------------------|

| | | |
|----------------|---|---|
| Waste Disposal | : | This material if discarded, is a hazardous waste under RCRA Regulation 40 CFR 261. Treatment, storage, transportation, and disposal must be in accordance with applicable federal, state/provincial, and local regulations. |
|----------------|---|---|



The Leela Corporation

ISO 9001 : 2015 (QMS)
Certified Company



ISO 14001 : 2015 (EMS)
Certified Company

Leepol™ Carbomers | Leepol™ Coats | Leepol™ HCO
Acids | Chemicals | Solvents | Dyes | Pigments | APIs
Hazardous Waste Management



TM

Section 14 | Transport Information

Pack Size: 20 kg & 5 kg.

Not a dangerous good within the meaning of transportation regulations.

Section 15 | Regulatory Information

SARA Ext. Haz. Subst. : This product does not contain greater than 1.0% of any Chemical substances on the SARA Extremely Hazardous substance list.

SARA Section 313 : This product does not contain greater than 1.0% (greater than 0.1% for carcinogenic substance) of any chemical substances listed under SARA section 313.

SARA 311 Classifications :

| | |
|-------------------|----|
| Acute Hazard | No |
| Chronic Hazard | No |
| Fire Hazard | No |
| Reactivity Hazard | No |

Section 16 | OTHER INFORMATION

The information set forth herein has been gathered from standard reference materials and / or **THE LEELA CORPORATION** test data. The information containing herein is based on the present state of our knowledge and is intended to describe our product from the view of safety requirements. It should not therefore be construed as guaranteeing specific properties.

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation. Safe handling and use remain the responsibility of the user.

THE LEELA HOUSE

F/2 Mangalam Nirvana- 2, Behind Umiya Campus, Sola, S. G Highway, Ahmedabad-380060, Gujarat, INDIA



+91 972 421 6384



info@leelacorp.com



www.leelacorp.com