

HORIZONTAL LAMINAR AIR FLOW

This system is designed to provide product protection. It ensures ISO 5 cleanliness level and maintains unidirectional airflow within workspace.



Model	Internal dimension (mm)			External dimension (mm)		
	W	D	Н	W	D	Н
ST-HLAF-36X24	875	610	570	1035	910	1440
ST-HLAF-48X24	1180	610	570	1340	910	1440
ST-HLAF-72X24	1800	610	570	1960	910	1440

Note: Customised dimensions as per requirement



Features:

- MOC: SS304, SS316 and SS316L or customized execution
- > SS worktable
- Cabinet support stand with leveling pads
- Side glass panel
- > Pre-filter:EU-7
- > Final Filter:H-14
- > PAO port.
- Mechanical differential gauge across final filter.
- Ventilator
- ➤ LED Light
- Standard electrical control system with push button and indicators
- Switch socket

Optional Features:

- Microprocessor based control system
- > EC ventilator
- ➤ GEL seal HEPA
- U.V light with hour meter

Performance:

- > Air cleanliness level: ISO 5
- Air Velocity: 0.45mps (± 0.05mps)
- Air Flow: Vertical
- > Noise Level: Less than 70db A when ambient is not more than 55db A
- ➤ Light Intensity: 250-300 lux