



BATTERY OPERATED STRAPPING TOOLS

FEATURES

LATEST TECHNOLOGY

- Brushless motor patented single motor design provides extremely long service life.
- Li-Ion battery- 18V 3000mAh high capacity rechargeable battery and Bosch 30 minutes charger.



POWERFUL & SPEEDY

- Max. tension 420 KGS (4000N) – 96A standard duty model.
- Max. tension 270 KGS (2500N) – 92A standard duty model.
- Patented strap grippers design contributes to high tension ability.
- Single-handed operation performs automatic tensioning, friction welding and cutting efficiently.

SMART & EASY

- Pre-programmed touch panel with digital signal to suit different operation needs instinctively.
- Lightest model in same class of tools less than 3.5kg (7.7lbs incl. battery) relieves operation fatigue.
- Special tool retreating device ensures smooth and easy removal of tool.
- Unique rear-end roller design prevents scratches or worn out damages on strapping objects.
- User self-adjustable strap widths guiders and self-changeable wearing parts.
- Optional hanger reduces operation fatigue.
- Soft mode device facilitates lighter strapping tension force for light packages or fragile objects.

SAFETY

- Single-handed operation conforms to CE safety directive and meets RoHS requirements.
- Li-Ion battery complies with UN38.3 safety requirements.
- Bosch charger A/C voltage 100V, 115V, 230V, 240V available for different markets demand.
- Sealing time adjustment: 0.4 ~ 2.0 seconds. (0.2 second / increment)
- Li-Ion battery life is up to 2000 charges with proper charging and discharging habits.
- A Fully charged Li-Ion battery supports approx. 650 cycles with regular specification & quality of PP straps.
- Cycle number varies based on strap quality, specifications, tension force and sealing time settings etc.

REMARKS

- Tension performance and sealing efficiency varies based on battery capacity, strap specifications & quality.
- Please select cutter based on your strap type. Both PET cutter and PP cutter are available to suit your demand.



SPECIFICATIONS

Model No.	Fits Poly strap	Strap Width		Strap Thickness		Tension Range	Sealing Efficiency	Dimension & weight
		mm	inch	mm	inch			
ZP92A	PP	9-16	3/8~5/8	0.55 ~1.35	0.022 ~ 0.053	10 ~ 270 kgs (22~550 lbs)	85+-5%	Approx. 33*15*12.5 cm (13*6*5)
	PET							Tool Weight
ZP96A	PP	16 & 19	5/8 & 3/4	0.75 ~1.35	0.029~ 0.053	10 ~ 270 kgs (88~880 lbs)	85+-5%	Approx. 2.80 kgs (61.6 lbs)
	PET			0.65 ~1.35	0.026 ~ 0.053			Battery Weight