

AGRICULTURAL TRACTOR FRONT TYRES



BLACKING TYRES®



BLK002



BLK003



BLK004



BLK103



BLK005



BLK104

Tyre Size	Ply Rating	Pattern	Rim width(inch)	Unloaded Inflation Dimension +/-2%		Static Loaded Radius (mm) +/-2%	Rolling Circumference +/-2.5% (mm)	Type	IP BAR
				CSW (mm)	OD (mm)				
4.00-8	8	BLK104	3	110	415			TT	4.25
5.00-15	4	BLK002	4	142	659	307	1951	TT	2.8
6.50/8-12/6.00-12	6	BLK104							
4.50-16	4	BLK002	3	124	657	311	1952	TT	3.1
5.00-16	6	BLK002	4	142	682	322	2025	TT	4.2
5.50-16	6	BLK002	4	156	722	340	2145	TT	3.7
5.50-16	6	BLK004	4	156	722	340	2145	TT	3.7
5.50-16	6	BLK005	4	156	722	340	2145	TT	3.7
6.00-16	8	BLK002	5.5	203	819	383	2220	TT	2.8
6.00-16	8	BLK004	5.5	203	819	383	2220	TT	2.8
6.00-16	8	BLK005	5.5	203	819	383	2220	TT	2.8
6.00-16	8	BLK103	5.5	203	819	383	2220	TT	2.8
6.50-16	6	BLK005	4.5	182	767	359	2280	TT	3.1
7.50-16	8	BLK002	6	214	803	372	2393	TT	4.15
7.50-16	8	BLK004	6	214	803	372	2393	TT	4.15
7.50-16	8	BLK005	6	214	803	372	2393	TT	4.15
7.50-16	8	BLK103	6	214	803	372	2393	TT	4.15
9.00-16	10	BLK002	8	239	857	398	2548	TT	3.9
10.00-16	8	BLK003	8	275	900	418	2682	TT	2.8
11.00-16	8	BLK003	10	320	970	448	2890	TT	2.5
7.50-18	8	BLK103	5.5	210	862	408	2650	TT	3.7
4.00-19	4	BLK002	3	117	717	343	2145	TT	2.4
6.00-19	6	BLK002	4.5	169	817	386	2445	TT	3.3
6.50-20	6	BLK005	4.5	177	867	409	2578	TT	3.1
7.50-20	8	BLK002	5.5	207	918	431	2745	TT	3.4

Email: export@blackingtyres.com | Mob: +91 84484 01214