GC202D series

INTEGRATED DIRECT-DRIVE BOTTOM FEED LOCKSTITCH SEWING MACHINE WITH THREAD TRIMMER

- Direct drive motor, fast start, energy saving, environmental protection
- Integrated control system, easy to install
- Link rod feeding and feeding stable
- Gear pump for lubrication
- Simple system control, the display is simple and easy to operate
- Equipped with LED lighting to decrease operator's visual fatigue

Function may be different according to models

GC202D	Integrated direct drive lockstitch sewing machine
GC202DCX	Integrated direct drive lockstitch sewing machine (thick thread)
GC202	High speed lockstitch sewing machine (with clutch motor)

GC202D

GC	202D	•	3,200	•	8	DPx17 20-23#	37	•	8/16	20/3			M	260x120
	202DCX	•	2,800	•	12	DPx17 20-25#	37	•	8/16	4#/3#			M	260x120
	202	•	3,200	•	8	DPx17 20-23#	37	•	8/16	20/3			M	260x120

GC202D3 series

INTEGRATED DIRECT-DRIVE BOTTOM FEED LOCKSTITCH SEWING MACHINE WITH THREAD TRIMMER

- Direct drive motor, fast start, energy saving, environmental protection
- Integrated control system, easy to install
- With automatic thread nipper, automatic back tack, automatic thread trimmer and other automation functions
- Pneumatic or electromagnet foot lifter is optional

Function may be different according to models

GC202D3	Integrated direct-drive bottom feed lockstitch with thread trimmer
GC202D3T2	Integrated direct-drive bottom feed lockstitch with thread trimmer and AFL

GC202D3

GC202D3	•	3,200	•	8	DPx17 20-23#	37	•	8/16	20/3	•	•	M	260x120
GC202D3T2	•	3,200	•	8	DPx17 20-23#	37	•	8/16	20/3	•	•	M	260x120

TW1/TW2-898/899/999L14-D2T3 series

ONE/TWO-NEEDLE COMPOUND FEED LOCKSTITCH SEWING MACHINE WITH THREAD TRIMMER

- Taiwan Ho hsing standard multi-functional hanging system i70m-4-ds-220
- Standard size interactive switch, needle gauge switch, automatic presser foot, automatic back tack, automatic thread cutting device
- Using a new type of closed cycle lubrication system, the oil from oil pan through the filtering system automatically into the inner circulation, which reduces oil consumption, and convenient to the operator.
- Automatic presser foot lift 16mm, easy sewing thick material.
- The top type large spin lock button can be easily adjusted and set foot interaction.
- Equipped with new thread pass plate, makes the thread pass more stable.
- Large operation space: 355mmx120mm

Double needle gauge:
E type presser foot: standard 10; optional 3/4/6/8/12 mm

S presser foot: Standard 3/8˝;optional 1/8˝,3/16˝,1/4˝,5./16˝,1/2˝

Function may be different according to models

TW1-899SL14-D2T3

TW1/TW2-898L14-D2T3	Single / double needle E type presser foot, 1.6 times hook has excellent track.
TW1/TW2-899L14-D2T3	Single / double needle E type presser foot, 2 times hook, suitable for straight sewing.
TW1/TW2-899SL14-D2T3	Single / double needle E type presser foot, 2 times hook.
TW1/TW2-999L14-D2T3	single / double needle E type presser foot, 2.5 times large hook.

TW-1	898L14-D2T3	•	3,500	•	9	DPx17 19-23#	34	•	9/16	20/3		•	•	•	•	M/H	355x120
	899L14-D2T3	•	2,800	•	9	DPx17 19-23#	37	•	9/16	20/3		•	•	•	•	M/H	355x120
	899SL14-D2T3	•	2,800	•	9	DPx17 19-23#	37	•	9/16	20/3		•	•	•	•	M/H	355x120
	999L14-D2T3	•	2,800	•	9	DPx17 19-23#	34	•	9/16	20/3		•	•	•	•	M/H	355x120
TW-2	898L14-D2T3	•	2,800	•	9	DPx17 19-23#	34	•	9/16	20/3	•	•	•	•	•	M/H	355x120
	899L14-D2T3	•	2,800	•	9	DPx17 19-23#	37	•	9/16	20/3	•	•	•	•	•	M/H	355x120
	899SL14-D2T3	•	2,800	•	9	DPx17 19-23#	37	•	9/16	20/3	•	•	•	•	•	M/H	355x120
	999L14-D2T3	•	2,800	•	9	DPx17 19-23#	34	•	9/16	20/3	•	•	•	•	•	M/H	355x120