

MAGAFIX Tile Adhesive

CHEMLAND CHEMICAL TECHNICAL DATA SHEET



CHEMLAND CHEMICAL

JHOTWARA INDUSTRIAL AREA, JAIPUR

Tile Adhesive

1. Fixing of ceramic and clay tiles in dry indoor applications

Advantages :

- Excellent grab
- Easy to mix and spread
- Pot life >50 minutes

Area of applications:

- ceramic tiles
- clay tiles

application instructions:

Mixing

- Chemland Mega Fix should be mixed with clean potable water in the ratio of 4:1 by weight (4 part powder : 1 water)
- A slow speed drill fitted with a mixing paddle is recommended for mixing.
- Add powder to water and mix until a uniform, lump – free consistency is achieved.

Application :

- Mixed material should be spread on the substrate up to a uniform thickness of 3-4mm, and then combed horizontally with a serrated trowel.
- Place tiles firmly into adhesive bed, ensuring good contact with a twisting motion and without leaving any voids.
- Suitable spacers should be placed around the tiles.
- Do not disturb fixed tile up to 24 hrs.

Packing :

- Available in 20 kg bags

2. High performance tile adhesive

Advantages:

- High adhesion strength
- Suitable for submerge condition
- Good slip resistance

Areas of application:

- Kitchens and bathrooms
- Tile claddings
- Bigger size tiles
- Interior stone
- Fixing of ceramic and vitrified tiles

Application instructions

Mixing

- Chemland Mega Fix should be mixed with clean potable water in the ratio of 3:1 by weight (3 part powder : 1 water)
- A slow speed drill fitted with a mixing paddle is recommended for mixing.
- Add powder to water and mix until a uniform, lump – free consistency is achieved.

Application :

- Mixed material should be spread on the substrate up to a uniform thickness of 3-4mm, and then combed horizontally with a serrated trowel.
- Place tiles firmly into adhesive bed, ensuring good contact with a twisting motion and without leaving any voids.
- Suitable spacers should be placed around the tiles.
- Do not disturb fixed tile up to 24 hrs.

Packing :

- Available in 20 kg bags

3. Fixing Granite, marble, stone, jumbo tiles for both interior and exterior cladding applications

Advantage:

- High bond strength
- Good grab for heavy duty stone cladding
- Quick fixing

Area of application

- Granite
- Marble
- Stone
- Jumbo tiles
- Swimming pool tiles

Application instructions:

Mixing

- Chemland Mega Fix should be mixed with clean potable water in the ration of 4:1 by weight (4 part powder : 1 water)
- A slow speed drill fitted with a mixing paddle is recommended for mixing.
- Add powder to water and mix until a uniform, lump – free consistency is achieved.

Application :

- Mixed material should be spread on the substrate up to a uniform thickness of 4-6mm, and then combed horizontally with a serrated trowel.
- Place tiles firmly into adhesive bed, ensuring good contact with a twisting motion and without leaving any voids.
- Suitable spacers should be placed around the tiles.
- Do not disturb fixed tile up to 24 hrs.

Packing :

- Available in 20 kg bags

CHEMLAND CHEMICALS

Jhotwara Industrial Area, Jaipur 302019

Web : www.chemlandchemicals.com / E-mail : chemlandchemical@gmail.com
www.chemlandchemicals.in /