

Nominal volume	Series	Max. operating pressure				Eff. gas volume	A max.	B	C	Ø D max.	J Thread	Ø E	AF	Q max. ²⁾	Weight				
		CC U		CC S															
		[bar]	Part no. ¹⁾	[bar]	Part no. ¹⁾											[l]	[mm]	[mm]	[mm]
0.5	SB400	400	3047163	—	—	0.5	270	57	33.5	96	G 3/4	50	32	4	4				
1	SB330	330	3047162	—	—	1	316	57	56	115	G 3/4	50	32	4	7				
	SB550 ⁴⁾	550	3110531	—	—		343	67		123	G 1	67	45	6	10				
2.5	SB330	330	3047165	—	—	2.4	528	64	56	115	G 1 1/4	67	50	10	11				
	SB550 ⁴⁾	550	3068916	—	—	2.5	550	67		123	G 1		45	6	14				
4	SB330	330	3047166	—	—	3.7	412	65	56	170	G 1 1/4	67	50	10	15				
	SB400 ⁴⁾	400	3107905	—	—														
5	SB550 ⁴⁾	550	3090654	—	—	4.9	876	64	56	123	G 1	67	45	6	27				
6	SB330	330	3047168	—	—	5.7	534	65	56	170	G 1 1/4	67	50	10	18				
10 ³⁾	SB330	330	3047170	—	—	9.3	810	65	56	170	G 1 1/4	67	50	10	31				
10	SB330	330	3047172	262	3141237	9.3	582	101	56	229	G 2	100	70	15	33				
	SB330N		3156632	—	—									25	34				
	SB330H		3079081	—	—	9	617	136			G 2 1/2	125	90	30	38				
	SB400 ⁴⁾	400	3107393	290	—	9.3	578	101		234	G 2	100	70	15	41				
	SB500 ⁴⁾	500	3130252	—	—	8.8	598		69							241	46		
	SB600	—	—	345	332265														
13	SB330	330	3047173	—	—	12	695	101	56	229	G 2	100	70	15	46				
	SB330N		—	—	—		25	47											
	SB330H		—	—	—		730	136			G 2 1/2	125	90	30	45				
20	SB330	330	3047174	262	3117153	18.4	895	101	56	229	G 2	100	70	15	49				
	SB330N		3162982	—	—									25					
	SB330H		3092659	—	—	17.5	930	136			G 2 1/2	125	90	30	62				
	SB400 ⁴⁾	400	3115007	290	—	18.4	895	101		234	G 2	100	70	15	71				
	SB500 ⁴⁾	500	3118156	—	—	17	913		69						241	75	112		
	SB600	—	—	345	332266														
24	SB330	330	3047175	—	—	23.6	1060	101	56	229	G 2	100	70	15	72				
	SB330N		—	—	—									25	73				
	SB330H		—	—	—	24	1095	136			G 2 1/2	125	90	30	76				
32	SB330	330	3047176	262	3117154	33.9	1410	101	56	229	G 2	100	70	15	80				
	SB330N		3220899	—	—									25	81				
	SB330H		3059515	—	—	32.5	1445	136			G 2 1/2	125	90	30	98				
	SB400 ⁴⁾	400	3125141	290	—	33.9	1410	101		234	G 2	100	70	15	104				
	SB500 ⁴⁾	500	3760577	—	—	33.5	1423		69						241	75	112		
	SB600	—	—	345	332267														
50	SB330	330	3047177	262	362904	47.5	1933	101	69	229	G 2	100	70	15	114				
	SB330N		3185604	—	—									25	115				
	SB330H		3089605	—	—	48.3	1933	101			234	G 2	100	70	15	128			
	SB400 ⁴⁾	400	3114662	290	—					241						167			
	SB500 ⁴⁾	500	3130253	—	—														
	SB600	—	—	345	332268														
60	SB330	330	3341217	—	—	60	1210	138	69	360	G 2 1/2	125	90	30	160				
80	SB330	330	—	—	—	85	1460	138	69	360	G 2 1/2	125	90	30	200				
100	SB330	330	3098489	—	—	105	1710	138	69	360	G 2 1/2	125	90	30	234				
130	SB330	330	—	—	—	133	2030	138	69	360	G 2 1/2	125	90	30	283				
160	SB330	330	—	—	—	170	2059	137	69	410	G 2 1/2	125	90	30	345				
200	SB330	330	—	—	—	201	2359	137	69	410	G 2 1/2	125	90	30	403				

¹⁾ If not specified, please request

²⁾ Under optimum conditions

³⁾ Slimline version, for confined installation spaces

⁴⁾ Material code (MC) = 212 for AC U, see section 3.