

afeage Safes are of fully welded double wall multibend construction making the body an integrated unit. With a commitment to providing enhanced security beyond prescribed norms the thickness of the outer and inner plate is 8mm, more than the BIS prescribed thickness of 7mm. The special barrier material (different formulations for each class) sandwiched between the outer and inner walls define the category of safe as

Class 'C' - TL 30D, TL 10 X 5, FR30, BIS Licensed IS 550 (evaluation done at ARAI)

Class 'BB' - TRTL 15 X 6 BIS Licensed IS 550 (evaluation done at GTH)

Class 'A' - TRTL 30 X 6 BIS Licensed IS 550 (evaluation done at EMTAC)

## Dimensions:

PRODUCT	"C" Class & "BB" Class INTERNAL			"C" CLASS BIS EXTERNAL				"BB" CLASS BIS EXTERNAL			
	26	475	325	292	691	541	567	370	613	463	513
31	590	435	385	806	651	660	550	728	573	606	710
41(S)	840	435	385	1055	651	660	850	978	573	606	1050
41 (L)	844	572	440	1060	786	715	1050	982	710	661	1180
48	1045	572	440	1261	786	715	1150	1183	710	661	1290
60	1350	572	440	1566	786	715	1200	1470	710	684	1650
72	1614	750	601	1830	966	876	1580	1752	888	822	2020
81	1829	750	601	2045	966	876	2240	1967	888	822	2690

Class "A" Dimensions and weights will be provided when required.

Non BIS Custom built safes also manufactured as required.
We reserve the rights to alter specification and sizes without prior notice.

Options of Customisation including fittings like drawers or Safe Deposit Lockers available on request





Security Products Pvt. Ltd.

120-121, 1st Floor, Swastik Disa Corporate Park, Kohinoor Textile Printing Compound, Opp. Shreyas Cinema, L.B.S. Marg, Ghatkopar (W), Mumbai - 400086.

Tel. Nos. +91 22 4015 8060, 4004 9400, 2500 1903

Email ID: safeagesec@gmail.com Web: www.safeage.in



'BB' Class Safe - Open Condition



Safe with Safe Deposit Lockers