



GeM
Government
e Marketplace

ISO : 9001:2015
ISO : 13485:2016

Ambinova TECHNOLOGIES



+91 8595173503
+91 9625922608



sales@ambinova.in



Plot at KH No.9/25/2, 13/5/1 Industrial Area
Nangli Sakrawati, Najafgarh, New Delhi- 110043.

WATER BATH



DESCRIPTION

Precision is an important factor in laboratories – and temperature control is no exception. Exact temperature control can be crucial to successfully conduct an experiment. That's why water baths are an essential piece of equipment in every lab. With its extensive portfolio of Constant temperature equipment, Ambinova meets the high requirements for professional heating and cooling. Our Ambinova Water Bath product line offers reliability and outstanding temperature homogeneity.

KEY FEATURES

- Simple to operate Water Bath.
- LED Display With Push Button.
- Bath Chamber With Drain Valve.
- LID (To Prevent Heat Loss).
- SS Tray.
- Both Continuous & Timer Mode Available.

TECHNICAL SPECIFICATIONS

- Display
LCD
- Switch
Push Switch
- Controller
PID
- Body Material
GI sheet (Powder Coated)
- Operation condition
Ambient
- Inner Chamber
SS 304
- Safety Protection
Thermostat
- Temperature Range
RT+5 to 99°C
- Temperature Accuracy
±0.5°C
- Temperature uniformity
±1°C
- Heat rate (maximum)
3-4°C/min
- Timer
up to 9999 Min
- Power (watt)
500 to 2000
- Voltage & Frequency
220V 50HZ

OPTIONAL FEATURES

- Buzzer(Cycle Complete / Temp. High & Low)
- Low Water Alarm Safety
- Short Circuit Breaker & Over Current / Over Voltage Protection
- Earth Leakage Safety

ORDERING INFORMATION

CAT.NO.	INNER DIMENSION (WxDxH)	OUTER DIMENSION (WxDxH)	CAPACITY
AMBI-WB-500	300 x 150 x 150(mm)	387 x 253 x 371(mm)	5 Lit
AMBI-WB-1000	298 x 150 x 235(mm)	390 x 325 x 368(mm)	10 Lit
AMBI-WB-2000	500 x 150 x 295(mm)	605 x 403 x 372(mm)	20 Lit
AMBI-WB-3000	500 x 150 x 400(mm)	603 x 503 x 369(mm)	30Lit