



POCKET NC V2-10



CAD-MECH

An ISO 9001-2015 Company

SPECIFICATIONS

MAX TRAVEL

X: 4.55 in (115.5mm)
Y: 5.05 in (128.3 mm)
Z: 3.55 in (90.1mm)
A: -25° to 135°
B: Continuous Rotation
(-9999° to 9999°)

▶ Tested on G5 titanium,
6061 aluminum, 303
stainless, machinable
wax, acetal


Accepts standard
G Code. Test G Code
at sim.pocketnc.com

www.pocketnc.com
info@pocketnc.com
Phone: +1.406.451.3799



[pocket_nc](https://www.instagram.com/pocket_nc)

P: +91 72760 32488, 97637 19533
WhatsApp: +91 97637 19531
Email: admin@cadmech.co.in.
Website: www.vrampsystems.com
www.cadmech.co.in



AXIS	MAX TRAVEL	SPEED
X	4.55 in (115.5 mm)	60 in/min (1524 mm/min)
Y	5.05 in (128.3 mm)	60 in/min (1524 mm/min)
Z	3.55 in (90.1 mm)	60 in/min (1524 mm/min)
A	-25° to 135°	40°/second
B	Continuous rotation (-9999° to 9999°)	40°/second

AXIS	BACKLASH
X & Y	0.0005 in (12.7 µm) at tool base
Z	Backlash at 18 pound (8.16 kg) load: 0.0005 in (12.7 µm)
A & B	0.01°

AXIS	RESOLUTION & REPEATABILITY
XYZ	Resolution: 0.00024 in (6.10µm) Homing Repeatability: ±0.0005 in (12.7µm) Repeatability: ±0.002 in (50.8µm) at 0%
A&B	Resolution: 0.01° Homing Repeatability: ±0.05° Repeatability: ±0.05° at 0% load Runout: < 0.002 in (50.8 µm)
Recommended part tolerance ±0.005in (.127mm)	

SPINDLE	
Spindle Speed	2,000-10,000 RPM
Power	200 W (Max Power)
Spindle Motor	BLDC 3 Phase with Hall Feedback
Spindle Runout	~0.0005 in (12.7 µm)
Tool Change	3mm Hex Key ER11 Collet

MACHINE CONTROL	
Texas Instruments Arm Cortex A8 running Machinekit/Rockhopper	
Accepts Standard Gcode	
Features	Spindle Override Feed Override Stop, Start, Pause 5 axis simultaneous movement
Connectivity	Ethernet, USB, and mini USB
Power Source	90-264 VAC, 127-370 VDC, 47-63Hz

COMPONENTS	
6061 Aluminum Frame, ±0.001 in (+/-25.4 µm) squareness in all axes	
Machine Footprint: 17.5 in (444.5 mm) x 12.5 in (279.3 mm)	
5 NEMA 17 Motors	3 linear lead screws with preloaded nuts 2 Rotary Worm Drives
Linear Bearings	9 and 42mm, 10% preload
Integrated angular contact rotary bearings	

PURCHASE INCLUDES:

One extended reach tool holder
1/8 inch ER11 collet and nut
1/8 inch square end mill, single flute
Pocket NC vise and hardware
Pocket NC limited 1-year warranty

Marketed & Serviced by



CAD-MECH
CAD-Mech Engineering Private Limited



P: +91 72760 32488, 97637 19533
WhatsApp: +91 97637 19531
Email: admin@cadmech.co.in.
Website: www.vrampsystems.com
www.cadmech.co.in