



# XCMG

## Equipment Solution Provider

SOLID TO SUCCEED

### Products

- Hoisting Machinery
- Earthmoving Machinery
- Mining Machinery
- Heavy-duty Trucks
- E-truck
- Road Building Machinery
- Sanitation Machinery
- Port Machinery
- Concrete Machinery
- Special Vehicles
- Piling Machinery
- Trenchless Machinery
- Coal Mining Machinery
- Underground Mining Machinery
- Agricultural Machinery
- Powered Industrial Trucks

### XCMG FOR YOUR SUCCESS

Under our policy of continuous product development and improvement, we reserve the right to change specifications and design without prior notice. Featured machines in photos may include additional equipment. Consult your XCMG dealer for available options and attachments.

Machmall focuses on overseas resource sharing and cross-border trade services, providing global customers with comprehensive information on mechanical and electrical products with commercial infrastructure. It is available in different languages like Chinese, English, Russian, Arabic, etc.

For more complete information on XCMG products, dealer services and industry solutions, visit us on the web at [machmall.com](http://machmall.com) or [xcmg.com](http://xcmg.com)

XCMG, XCMG for Your Success and [www.xcmg.com](http://www.xcmg.com), as well as corporate and product identity used herein are trademarks of XCMG and may not be used without permission.

Sophie Xue

Export Sales Manager

XCMG E-COMMERCE.

Mob/What'sapp/wechat: +86 137 7604 7779 (China)

















































Email: [13776047779@163.com](mailto:13776047779@163.com), [xuemingyu@xcmg.com](mailto:xuemingyu@xcmg.com)





# HOISTING MACHINERY






















## ● TRUCK CRANE

 <p><b>XCT8L4_1</b> Max.Total Rated Lifting Load: 8t Max.Load Moment of Base Boom: 318kNm Max. boom length: 25m Dead Weight in Travel State: 13160kg</p>	 <p><b>XCT12_Y</b> Max.Total Rated Lifting Load: 12t Max.Load Moment of Base Boom: 317kNm Max. boom length: 25m Dead Weight in Travel State: 13500kg</p>	 <p><b>XCT16_Y</b> Max.Total Rated Lifting Load: 16t Max.Load Moment of Base Boom: 730kNm Max. boom length: 32m Dead Weight in Travel State: 23300kg</p>	 <p><b>QY25KC</b> Max.Total Rated Lifting Load: 25t Max.Load Moment of Base Boom: 1158kNm Max. boom length: 35m Dead Weight in Travel State: 30200kg</p>	 <p><b>QY25K5D</b> Max.Total Rated Lifting Load: 25t Max.Load Moment of Base Boom: 1005kNm Max. boom length: 41m Dead Weight in Travel State: 32500kg</p>	 <p><b>XCT25L4_S</b> Max.Total Rated Lifting Load: 25t Max.Load Moment of Base Boom: 961kNm Max. boom length: 34m Dead Weight in Travel State: 28000kg</p>	 <p><b>XCT25L5_S</b> Max.Total Rated Lifting Load: 25t Max.Load Moment of Base Boom: 988kNm Max. boom length: 41m Dead Weight in Travel State: 31000kg</p>
 <p><b>XCT25L4_SR</b> Max.Total Rated Lifting Load: 25t Max.Load Moment of Base Boom: 961kNm Max. boom length: 34m Dead Weight in Travel State: 28000kg</p>	 <p><b>XCT25L5_SR</b> Max.Total Rated Lifting Load: 25t Max.Load Moment of Base Boom: 988kNm Max. boom length: 41m Dead Weight in Travel State: 30000kg</p>	 <p><b>XCT25L4_Y</b> Max.Total Rated Lifting Load: 25t Max.Load Moment of Base Boom: 968kNm Max. boom length: 34m Dead Weight in Travel State: 27500kg</p>	 <p><b>XCT25L4_Y (BSIV)</b> Max.Total Rated Lifting Load: 25t Max.Load Moment of Base Boom: 931kNm Max. boom length: 32.5m Dead Weight in Travel State: 26000kg</p>	 <p><b>XCT25L4_AU</b> Max.Total Rated Lifting Load: 25t Max.Load Moment of Base Boom: 965kNm Max. boom length: 34m Dead Weight in Travel State: 27500kg</p>	 <p><b>XCT25L5_Y</b> Max.Total Rated Lifting Load: 25t Max.Load Moment of Base Boom: 968kNm Max. boom length: 40.5m Dead Weight in Travel State: 30600kg</p>	 <p><b>XCT25_E</b> Max.Total Rated Lifting Load: 25t Max.Load Moment of Base Boom: 1132kNm Max. boom length: 42m Dead Weight in Travel State: 33000kg</p>
 <p><b>QY25K5H</b> Max.Total Rated Lifting Load: 25t Max.Load Moment of Base Boom: 1063kNm Max. boom length: 41m Dead Weight in Travel State: 32200kg</p>	 <p><b>XCT30_S</b> Max.Total Rated Lifting Load: 30t Max.Load Moment of Base Boom: 1132kNm Max. boom length: 42m Dead Weight in Travel State: 33000kg</p>	 <p><b>XCT30_Y</b> Max.Total Rated Lifting Load: 30t Max.Load Moment of Base Boom: 968kNm Max. boom length: 34m Dead Weight in Travel State: 28700kg</p>	 <p><b>XCT30_AU</b> Max.Total Rated Lifting Load: 30t Max.Load Moment of Base Boom: 968kNm Max. boom length: 34m Dead Weight in Travel State: 28700kg</p>	 <p><b>QY30K5H</b> Max.Total Rated Lifting Load: 30t Max.Load Moment of Base Boom: 1148kNm Max. boom length: 43m Dead Weight in Travel State: 33000kg</p>	 <p><b>QY30K5C</b> Max.Total Rated Lifting Load: 30t Max.Load Moment of Base Boom: 1148kNm Max. boom length: 43m Dead Weight in Travel State: 33400kg</p>	 <p><b>XCT35_U</b> Max.Total Rated Lifting Load: 35t Max.Load Moment of Base Boom: 51300 b-ft Max. boom length: 120ft Dead Weight in Travel State: 35000kg</p>
 <p><b>XCT35_BR</b> Max.Total Rated Lifting Load: 35t Max.Load Moment of Base Boom: 1158kNm Max. boom length: 43m Dead Weight in Travel State: 33400kg</p>	 <p><b>XCT40_U</b> Max.Total Rated Lifting Load: 40US Max.Load Moment of Base Boom: 70000 b-ft Max. boom length: 142ft Dead Weight in Travel State: 66100 lb</p>	 <p><b>XCT45_E</b> Max.Total Rated Lifting Load: 45t Max.Load Moment of Base Boom: 1388kNm Max. boom length: 35.5m Dead Weight in Travel State: 32000kg</p>	 <p><b>XCT50_Y</b> Max.Total Rated Lifting Load: 50t Max.Load Moment of Base Boom: 2008kNm Max. boom length: 43.5m Dead Weight in Travel State: 40100kg</p>	 <p><b>XCT55_S</b> Max.Total Rated Lifting Load: 55t Max.Load Moment of Base Boom: 2008kNm Max. boom length: 44m Dead Weight in Travel State: 40600kg</p>	 <p><b>QY50KH</b> Max.Total Rated Lifting Load: 50t Max.Load Moment of Base Boom: 1600kNm Max. boom length: 45m Dead Weight in Travel State: 39000kg</p>	 <p><b>QY50KD</b> Max.Total Rated Lifting Load: 50t Max.Load Moment of Base Boom: 2008kNm Max. boom length: 45m Dead Weight in Travel State: 42200kg</p>
 <p><b>XCT60_Y</b> Max.Total Rated Lifting Load: 60t Max.Load Moment of Base Boom: 2008kNm Max. boom length: 44m Dead Weight in Travel State: 41700kg</p>	 <p><b>QY60KH</b> Max.Total Rated Lifting Load: 60t Max.Load Moment of Base Boom: 1988kNm Max. boom length: 45.5m Dead Weight in Travel State: 43600kg</p>	 <p><b>XCT60_U</b> Max.Total Rated Lifting Load: 60US Max.Load Moment of Base Boom: 117200 b-ft Max. boom length: 154ft Dead Weight in Travel State: 79366 lb</p>	 <p><b>XCT70_S</b> Max.Total Rated Lifting Load: 70t Max.Load Moment of Base Boom: 2038kNm Max. boom length: 44.5m Dead Weight in Travel State: 44000kg</p>	 <p><b>XCT75_S</b> Max.Total Rated Lifting Load: 75t Max.Load Moment of Base Boom: 3178kNm Max. boom length: 48m Dead Weight in Travel State: 46000kg</p>	 <p><b>QY70KH</b> Max.Total Rated Lifting Load: 70t Max.Load Moment of Base Boom: 2178kNm Max. boom length: 46.5m Dead Weight in Travel State: 43900kg</p>	 <p><b>XCT70_BR</b> Max.Total Rated Lifting Load: 70t Max.Load Moment of Base Boom: 2178kNm Max. boom length: 46.5m Dead Weight in Travel State: 44600kg</p>
 <p><b>XCT80_E</b> Max.Total Rated Lifting Load: 80t Max.Load Moment of Base Boom: 3352kNm Max. boom length: 50.5m Dead Weight in Travel State: 50000kg</p>	 <p><b>XCT80_S</b> Max.Total Rated Lifting Load: 80t Max.Load Moment of Base Boom: 3178kNm Max. boom length: 48m Dead Weight in Travel State: 48000kg</p>	 <p><b>QY85KH</b> Max.Total Rated Lifting Load: 85t Max.Load Moment of Base Boom: 2921kNm Max. boom length: 50.5m Dead Weight in Travel State: 46000kg</p>	 <p><b>XCT90_Y</b> Max.Total Rated Lifting Load: 90t Max.Load Moment of Base Boom: 3450kNm Max. boom length: 50.5m Dead Weight in Travel State: 54000kg</p>	 <p><b>XCT90_BR</b> Max.Total Rated Lifting Load: 90t Max.Load Moment of Base Boom: 2678kNm Max. boom length: 48m Dead Weight in Travel State: 46000kg</p>	 <p><b>XCT90_BRI</b> Max.Total Rated Lifting Load: 90t Max.Load Moment of Base Boom: 2942kNm Max. boom length: 48m Dead Weight in Travel State: 45000kg</p>	 <p><b>QY95KH</b> Max.Total Rated Lifting Load: 95t Max.Load Moment of Base Boom: 3468kNm Max. boom length: 52m Dead Weight in Travel State: 48800kg</p>
 <p><b>XCT100_S</b> Max.Total Rated Lifting Load: 100t Max.Load Moment of Base Boom: 3040kNm Max. boom length: 70m Dead Weight in Travel State: 48000kg</p>	 <p><b>XCT100_BRI</b> Max.Total Rated Lifting Load: 100t Max.Load Moment of Base Boom: 3108kNm Max. boom length: 50.5m Dead Weight in Travel State: 45000kg</p>	 <p><b>QY110KH</b> Max.Total Rated Lifting Load: 110t Max.Load Moment of Base Boom: 3840kNm Max. boom length: 72m Dead Weight in Travel State: 54600kg</p>	 <p><b>XCT110_BR</b> Max.Total Rated Lifting Load: 110t Max.Load Moment of Base Boom: 3528kNm Max. boom length: 58m Dead Weight in Travel State: 46000kg</p>	 <p><b>XCT110_BRI</b> Max.Total Rated Lifting Load: 110t Max.Load Moment of Base Boom: 3708kNm Max. boom length: 60m Dead Weight in Travel State: 47500kg</p>	 <p><b>QY130KH</b> Max.Total Rated Lifting Load: 130t Max.Load Moment of Base Boom: 4738kNm Max. boom length: 75m Dead Weight in Travel State: 54600kg</p>	













## ● ALL TERRAIN CRANE

 <p><b>XCA2600</b> Max.Total Rated Lifting Load: 2600t Max.Load Moment of Base Boom: 52684kNm Max. boom length: 68.6m Dead Weight in Travel State: 75000kg</p>	 <p><b>XCA40_E</b> Max.Total Rated Lifting Load: 40t Max.Load Moment of Base Boom: 1191kNm Max. boom length: 25m Dead Weight in Travel State: 24000kg</p>	 <p><b>XCA40_AU</b> Max.Total Rated Lifting Load: 40t Max.Load Moment of Base Boom: 1191kNm Max. boom length: 25m Dead Weight in Travel State: 24000kg</p>	 <p><b>XCA60_E</b> Max.Total Rated Lifting Load: 60t Max.Load Moment of Base Boom: 1898kNm Max. boom length: 30m Dead Weight in Travel State: 36000kg</p>	 <p><b>XCA60_S</b> Max.Total Rated Lifting Load: 60t Max.Load Moment of Base Boom: 1898kNm Max. boom length: 30m Dead Weight in Travel State: 36000kg</p>	 <p><b>XCA60_EV</b> Max.Total Rated Lifting Load: 60t Max.Load Moment of Base Boom: 1722kNm Max. boom length: 30m Dead Weight in Travel State: 36000kg</p>	 <p><b>XCA100_H</b> Max.Total Rated Lifting Load: 100t Max.Load Moment of Base Boom: 2888kNm Max. boom length: 35m Dead Weight in Travel State: 48000kg</p>
 <p><b>XCA150_U</b> Max.Total Rated Lifting Load: 150US Max.Load Moment of Base Boom: 3183000 b-ft Max. boom length: 203.4ft Dead Weight in Travel State: 132725 lb</p>	 <p><b>XCA160H</b> Max.Total Rated Lifting Load: 160t Max.Load Moment of Base Boom: 5145kNm Max. boom length: 78m Dead Weight in Travel State: 55000kg</p>	 <p><b>XCA160_AU</b> Max.Total Rated Lifting Load: 160t Max.Load Moment of Base Boom: 5145kNm Max. boom length: 75m Dead Weight in Travel State: 60000kg</p>	 <p><b>XCA160_BRI</b> Max.Total Rated Lifting Load: 160t Max.Load Moment of Base Boom: 5145kNm Max. boom length: 75m Dead Weight in Travel State: 59500kg</p>	 <p><b>XCA160_BRII</b> Max.Total Rated Lifting Load: 160t Max.Load Moment of Base Boom: 5145kNm Max. boom length: 75m Dead Weight in Travel State: 59500kg</p>	 <p><b>XCA160_BRIII</b> Max.Total Rated Lifting Load: 160t Max.Load Moment of Base Boom: 5145kNm Max. boom length: 75m Dead Weight in Travel State: 60000kg</p>	 <p><b>XCA180_S</b> Max.Total Rated Lifting Load: 180t Max.Load Moment of Base Boom: 5988kNm Max. boom length: 84m Dead Weight in Travel State: 60000kg</p>
 <p><b>XCA230_S</b> Max.Total Rated Lifting Load: 230t Max.Load Moment of Base Boom: 7233kNm Max. boom length: 75m Dead Weight in Travel State: 60000kg</p>	 <p><b>XCA250H</b> Max.Total Rated Lifting Load: 250t Max.Load Moment of Base Boom: 7233kNm Max. boom length: 75m Dead Weight in Travel State: 55000kg</p>	 <p><b>XCA250_BRI</b> Max.Total Rated Lifting Load: 250t Max.Load Moment of Base Boom: 7233kNm Max. boom length: 73m Dead Weight in Travel State: 60000kg</p>	 <p><b>XCA250_BRII</b> Max.Total Rated Lifting Load: 250t Max.Load Moment of Base Boom: 7400kNm Max. boom length: 73m Dead Weight in Travel State: 60000kg</p>	 <p><b>XCA250_BRIII</b> Max.Total Rated Lifting Load: 250t Max.Load Moment of Base Boom: 7400kNm Max. boom length: 73m Dead Weight in Travel State: 60000kg</p>	 <p><b>XCA275_U</b> Max.Total Rated Lifting Load: 275US Max.Load Moment of Base Boom: 545000 b-ft Max. boom length: 147.6ft Dead Weight in Travel State: 13225 lb</p>	 <p><b>XCA300H</b> Max.Total Rated Lifting Load: 300t Max.Load Moment of Base Boom: 7978kNm Max. boom length: 82m Dead Weight in Travel State: 55000kg</p>
 <p><b>XCA300_AU</b> Max.Total Rated Lifting Load: 300t Max.Load Moment of Base Boom: 8200kNm Max. boom length: 78m Dead Weight in Travel State: 72000kg</p>	 <p><b>XCA350BR</b> Max.Total Rated Lifting Load: 350t Max.Load Moment of Base Boom: 10500kNm Max. boom length: 82m Dead Weight in Travel State: 75000kg</p>	 <p><b>XCA450_BRI</b> Max.Total Rated Lifting Load: 450t Max.Load Moment of Base Boom: 12740kNm Max. boom length: 82m Dead Weight in Travel State: 72000kg</p>	 <p><b>XCA460</b> Max.Total Rated Lifting Load: 460t Max.Load Moment of Base Boom: 13800kNm Max. boom length: 85m Dead Weight in Travel State: 55000kg</p>			

## ● ROUGH TERRAIN CRANE

 <p><b>XCR25L4</b> Max.Total Rated Lifting Load: 25t Max.Load Moment of Base Boom: 1023kNm Max. boom length: 34m Dead Weight in Travel State: 25600kg</p>	 <p><b>XCR25L5</b> Max.Total Rated Lifting Load: 25t Max.Load Moment of Base Boom: 902kNm Max. boom length: 40m Dead Weight in Travel State: 28400kg</p>	 <p><b>XCR30</b> Max.Total Rated Lifting Load: 30t Max.Load Moment of Base Boom: 989.8kNm Max. boom length: 35m Dead Weight in Travel State: 27490kg</p>			
 <p><b>XCR30_S</b> Max.Total Rated Lifting Load: 30t Max.Load Moment of Base Boom: 989.8kNm Max. boom length: 35m Dead Weight in Travel State: 27490kg</p>	 <p><b>XCR35_S</b> Max.Total Rated Lifting Load: 35t Max.Load Moment of Base Boom: 1396kNm Max. boom length: 35m Dead Weight in Travel State: 30657kg</p>	 <p><b>XCR40</b> Max.Total Rated Lifting Load: 40t Max.Load Moment of Base Boom: 1396kNm Max. boom length: 35m Dead Weight in Travel State: 30657kg</p>	 <p><b>XCR55L4</b> Max.Total Rated Lifting Load: 55t Max.Load Moment of Base Boom: 2033.5kNm Max. boom length: 36.5m Dead Weight in Travel State: 40215kg</p>	 <p><b>XCR55L5</b> Max.Total Rated Lifting Load: 55t Max.Load Moment of Base Boom: 2033.5kNm Max. boom length: 43.6m Dead Weight in Travel State: 41600kg</p>	 <p><b>XCR55L5_S</b> Max.Total Rated Lifting Load: 55t Max.Load Moment of Base Boom: 2033.5kNm Max. boom length: 43.6m Dead Weight in Travel State: 41600kg</p>
 <p><b>XCR55L5_E</b> Max.Total Rated Lifting Load: 55t Max.Load Moment of Base Boom: 2033.5kNm Max. boom length: 43.6m Dead Weight in Travel State: 41800kg</p>	 <p><b>XCR60_U</b> Max.Total Rated Lifting Load: 60US Max.Load Moment of Base Boom: 149932b-ft Max. boom length: 143ft Dead Weight in Travel State: 92152 lb</p>	 <p><b>XCR70</b> Max.Total Rated Lifting Load: 70t Max.Load Moment of Base Boom: 2028.6kNm Max. boom length: 45m Dead Weight in Travel State: 44055kg</p>	 <p><b>XCR70_S</b> Max.Total Rated Lifting Load: 70t Max.Load Moment of Base Boom: 2028.6kNm Max. boom length: 45m Dead Weight in Travel State: 44055kg</p>	 <p><b>XCR70_E</b> Max.Total Rated Lifting Load: 70t Max.Load Moment of Base Boom: 2028.6kNm Max. boom length: 45m Dead Weight in Travel State: 44520kg</p>	 <p><b>XCR75_U</b> Max.Total Rated Lifting Load: 75US Max.Load Moment of Base Boom: 1496218 b-ft Max. boom length: 147.6ft Dead Weight in Travel State: 97125 lb</p>
 <p><b>XCR90</b> Max.Total Rated Lifting Load: 90t Max.Load Moment of Base Boom: 2840kNm Max. boom length: 48m Dead Weight in Travel State: 53498kg</p>	 <p><b>XCR90_E</b> Max.Total Rated Lifting Load: 90t Max.Load Moment of Base Boom: 2840kNm Max. boom length: 48m Dead Weight in Travel State: 53421kg</p>	 <p><b>XCR90_S</b> Max.Total Rated Lifting Load: 90t Max.Load Moment of Base Boom: 2840kNm Max. boom length: 48m Dead Weight in Travel State: 53498kg</p>	 <p><b>XCR100_U</b> Max.Total Rated Lifting Load: 100US Max.Load Moment of Base Boom: 209559 b-ft Max. boom length: 157.4ft Dead Weight in Travel State: 117608 lb</p>	 <p><b>XCR110L5</b> Max.Total Rated Lifting Load: 110t Max.Load Moment of Base Boom: 3057.6kNm Max. boom length: 51m Dead Weight in Travel State: 58910kg</p>	 <p><b>XCR120</b> Max.Total Rated Lifting Load: 120t Max.Load Moment of Base Boom: 3567kNm Max. boom length: 50m Dead Weight in Travel State: 70048kg</p>

## ● CRAWLER CRANE

 <p><b>XGC85</b> rated power: 129kw/2300rpm operating weight: 36.8t max total rated lifting load: 45t max load moment of base boom: 150t.m</p>	 <p><b>XGC55</b> rated power: 199kw/2000rpm operating weight: 46.3t max total rated lifting load: 55t max load moment of base boom: 203.5t.m</p>	 <p><b>XGC65</b> rated power: 199kw/2000rpm operating weight: 45.2t max total rated lifting load: 65t max load moment of base boom: 227.5t.m</p>	 <p><b>XGC75</b> rated power: 199kw/2000rpm operating weight: 61.5t max total rated lifting load: 75t max load moment of base boom: 286t.m</p>	 <p><b>XGC85</b> rated power: 199kw/2000rpm operating weight: 71.5t max total rated lifting load: 85t max load moment of base boom: 341t.m</p>	 <p><b>XGC100A</b> rated power: 199kw/2000rpm operating weight: 81.2t max total rated lifting load: 100t max load moment of base boom: 425t.m</p>
 <p><b>XGC8800(4000t)</b> Rated power: 3 X 641kw/2100rpm Operating weight: 5950t Max total rated lifting load: 3600t Max load moment of base boom: 88000t.m</p>	 <p><b>XLC130</b> rated power: 241kw/2000rpm operating weight: 121t max total rated lifting load: 130t max load moment of base boom: 742.2t.m</p>	 <p><b>XLC150</b> rated power: 247kw/1900rpm operating weight: 128t max total rated lifting load: 150t max load moment of base boom: 874.8t.m</p>	 <p><b>XLC180</b> Rated power: 243kw/2000rpm Operating weight: 153t Max total rated lifting load: 180t Max load moment of base boom: 1050t.m</p>	 <p><b>XLC220</b> Rated power: 243kw/2000rpm Operating weight: 191t Max total rated lifting load: 220t Max load moment of base boom: 1239t.m</p>	
 <p><b>XGC260</b> Rated power: 243kw/2000rpm Operating weight: 274.7t Max total rated lifting load: 260t Max load moment of base boom: 1430t.m</p>					



## CONSTRUCTION HOIST

<b>XGT600E-32S</b> Jib Length:80m Tip Load:3.5t Rated Load Moment:600t.m Max Lifting Capacity:32t	<b>XGT600H-32S</b> Jib Length:80m Tip Load:3.5t Rated Load Moment:600t.m Max Lifting Capacity:32t	<b>XGT800-40S</b> Jib Length:80m Tip Load:7.2t Rated Load Moment:800t.m Max Lifting Capacity:40t	<b>SC200/200MS1</b> Rated Load:2 x 2000kg Lifting Speed:0-63m/min Mast Section Size:650mm x 650mm x 1508mm	<b>SC200JS1</b> Rated Load:2000kg Lifting Speed:0-50m/min Mast Section Size:650mm x 200mm x 1508mm
<b>XGT1050 (E) -50S</b> Jib Length:90m Tip Load:10t Rated Load Moment:1050t.m Max Lifting Capacity:50t	<b>XGT1200 (E) -64S</b> Jib Length:90m Tip Load:13t Rated Load Moment:1200t.m Max Lifting Capacity:64t	<b>XGT2230-100S</b> Jib Length:90m Tip Load:22.3t Rated Load Moment:2230t.m Max Lifting Capacity:100t	<b>SC200/20ES1</b> Rated Load:2 x 2000kg Lifting Speed:0-50m/min Mast Section Size:650mm x 650mm x 1508mm	<b>SC200/20FS1</b> Rated Load:2 x 2000kg Lifting Speed:0-50m/min Mast Section Size:650mm x 650mm x 1508mm
<b>XGT3100-160S</b> Jib Length:95m Tip Load:29t Rated Load Moment:3100t.m Max Lifting Capacity:160t	<b>XGT4300-200S</b> Jib Length:90m Tip Load:46.5t Rated Load Moment:4300t.m Max Lifting Capacity:200t	<b>XGT15000-600S</b> Jib Length:61m Tip Load:207t Rated Load Moment:15000t.m Max Lifting Capacity:600t	<b>SC200/20FS1-E</b> Rated Load:2 x 2000kg Lifting Speed:0-50m/min Mast Section Size:650mm x 650mm x 1508mm	

## LORRY CRANE

<b>SQZ132</b> Max. lifting moment: 13.2t.m Max. lifting capacity: 6300kg Max. hydraulic outreach: 12.2m	<b>SQZ160</b> Max. lifting moment: 16.8t.m Max. lifting capacity: 8000kg Max. hydraulic outreach: 12.75m	<b>SQZ200</b> Max. lifting moment: 21t.m Max. lifting capacity: 10000kg Max. hydraulic outreach: 12.75m	<b>SQZ300</b> Max. lifting moment: 30t.m Max. lifting capacity: 12000kg Max. hydraulic outreach: 9.78m	<b>SQZ330</b> Max. lifting moment: 33t.m Max. lifting capacity: 16500kg Max. hydraulic outreach: 16.3m	<b>SQZ350</b> Max. lifting moment: 35t.m Max. lifting capacity: 17500kg Max. hydraulic outreach: 13.2m	<b>SQZ400</b> Max. lifting moment: 40t.m Max. lifting capacity: 20000kg Max. hydraulic outreach: 11.81m	<b>SQZ460</b> Max. lifting moment: 46t.m Max. lifting capacity: 20000kg Max. hydraulic outreach: 16.8m
<b>SQZ560.8</b> Max. lifting moment: 49t.m Max. lifting capacity: 28000kg Max. hydraulic outreach: 20.8m	<b>SQZ560</b> Max. lifting moment: 51.2t.m Max. lifting capacity: 28000kg Max. hydraulic outreach: 20.8m	<b>SQZ600</b> Max. lifting moment: 56t.m Max. lifting capacity: 30000kg Max. hydraulic outreach: 16.4m	<b>SQZ660</b> Max. lifting moment: 60t.m Max. lifting capacity: 33000kg Max. hydraulic outreach: 20.67m	<b>SQZ760</b> Max. lifting moment: 66.3t.m Max. lifting capacity: 40000kg Max. hydraulic outreach: 20.55m	<b>SQZ860</b> Max. lifting moment: 74t.m Max. lifting capacity: 43000kg Max. hydraulic outreach: 20.13m		

<b>SQZ125-5</b> Max. lifting moment: 12.5t.m Max. lifting capacity: 5000kg Max. hydraulic outreach: 15.7m	<b>SQZ125-6</b> Max. lifting moment: 12.5t.m Max. lifting capacity: 5000kg Max. hydraulic outreach: 18.7m	<b>SQZ157-4</b> Max. lifting moment: 15.7t.m Max. lifting capacity: 6300kg Max. hydraulic outreach: 11.24m	<b>SQZ157-5</b> Max. lifting moment: 15.7t.m Max. lifting capacity: 6300kg Max. hydraulic outreach: 15.7m	<b>SQZ157-6</b> Max. lifting moment: 15.7t.m Max. lifting capacity: 6300kg Max. hydraulic outreach: 19.8m	<b>SQZ200-4</b> Max. lifting moment: 20t.m Max. lifting capacity: 9100kg Max. hydraulic outreach: 15m	<b>SQZ200-5</b> Max. lifting moment: 20t.m Max. lifting capacity: 8000kg Max. hydraulic outreach: 18.6m	<b>SQZ250-4</b> Max. lifting moment: 26t.m Max. lifting capacity: 11000kg Max. hydraulic outreach: 15.5m	<b>SQZ250-5</b> Max. lifting moment: 26t.m Max. lifting capacity: 11000kg Max. hydraulic outreach: 18.6m	<b>SQZ300-4</b> Max. lifting moment: 33t.m Max. lifting capacity: 13000kg Max. hydraulic outreach: 17m	<b>SQZ300-5</b> Max. lifting moment: 33t.m Max. lifting capacity: 13000kg Max. hydraulic outreach: 18.6m	<b>SQZ350-5</b> Max. lifting moment: 36t.m Max. lifting capacity: 14000kg Max. hydraulic outreach: 19.6m	<b>SQZ400-5</b> Max. lifting moment: 43t.m Max. lifting capacity: 16000kg Max. hydraulic outreach: 21.77m	<b>SQZ450-5</b> Max. lifting moment: 47t.m Max. lifting capacity: 18000kg Max. hydraulic outreach: 22.4m
--	--	---	--	--	--	--	---	---	---	---	---	--	---

## TELESCOPING BOOM LORRY CRANE

<b>SQS42-3</b> Max. lifting moment: 4.2t.m Max. lifting capacity: 3200kg Max. hydraulic outreach: 7.73m	<b>SQS68-3</b> Max. lifting moment: 6.8t.m Max. lifting capacity: 4000kg Max. hydraulic outreach: 7.56m	<b>SQS68-4</b> Max. lifting moment: 6.72t.m Max. lifting capacity: 3200kg Max. hydraulic outreach: 9m	<b>SQS100-3</b> Max. lifting moment: 10t.m Max. lifting capacity: 4000kg Max. hydraulic outreach: 7.93m	<b>SQS100-4</b> Max. lifting moment: 8.4t.m Max. lifting capacity: 4000kg Max. hydraulic outreach: 10m	<b>SQS125-4</b> Max. lifting moment: 12.5t.m Max. lifting capacity: 5000kg Max. hydraulic outreach: 11.24m	<b>SQS125TL-4</b> Max. lifting moment: 12.5t.m Max. lifting capacity: 5000kg Max. hydraulic outreach: 11.2m
--	--	--	--	---	---	--

## EARTHMOVING MACHINERY

### WHEEL LOADER

<b>XC9350</b> Bucket Load:18.0m³ Max. Breakout Force: >260kN Rated Power:370kW Overall Dimension(LxWxH): 17290x5695x8520	<b>LW156FV</b> Bucket Capacity:0.7m³ Rated Load:1100KG Operating Weight:5500KG Max. Breakout:44KN Overall Dimension(LxWxH): 6100x2600x2900mm	<b>LW160FV super</b> Bucket Capacity:0.7m³ Rated Load:1100KG Operating Weight:5500KG Max. Breakout:44KN Overall Dimension(LxWxH): 615x2600x2930mm	<b>LW180FV</b> Bucket Capacity:1.0m³ Rated Load:1400KG Operating Weight:6100KG Max. Breakout:44KN Overall Dimension(LxWxH): 6150x2600x2950mm	<b>LW180K(V)</b> Bucket Capacity:1.1m³ Rated Load:1800KG Operating Weight:6500KG Max. Breakout:55KN Overall Dimension(LxWxH): 6045x2600x2950mm	<b>LW200FV super</b> Bucket Capacity:1.0m³ Rated Load:1600KG Operating Weight:6600KG Max. Breakout:55KN Overall Dimension(LxWxH): 6190x2600x2900mm	<b>LW200K(V)</b> Bucket Capacity:1.1m³ Rated Load:2000KG Operating Weight:7800KG Max. Breakout:58KN Overall Dimension(LxWxH): 6045x2600x2950mm	<b>LW300FN</b> Bucket Load:2.1m³ Rated Load:3300KG Operating Weight:10400kg Max. Breakout:130kN Overall Dimension(LxWxH): 7050x4282x3118mm	<b>LW300KN</b> Bucket Load:2.1m³ Rated Load:3500KG Operating Weight:10800kg Max. Breakout:125kN Overall Dimension(LxWxH): 7245x4282x320mm	
<b>LW300KV</b> Bucket Load:1.8m³ Rated Load:3000KG Operating Weight:9700kg Max. Breakout:125kN Overall Dimension(LxWxH): 7445x2540x3320mm	<b>LW400KN</b> Bucket Load:2.4m³ Rated Load:4000KG Operating Weight:12900kg Max. Breakout:14000kg Overall Dimension(LxWxH): 7800x4183x3480mm	<b>XC916</b> Operating Weight: 4500kg Bucket Capacity: 0.7m³ Max. Breakout Force: >38kN Engine Model: YUNNEI DEF20 Overall Dimension(LxWxH): 5184x1837x2540mm	<b>XC918-EV</b> Operating Weight: 6700kg Bucket Capacity: 1.0m³ Max. Breakout Force: >58kN Motor Type: Permanent Magnet Synchronous Motor Overall Dimension(LxWxH): 5740x1952x2750mm	<b>XC938</b> Operating Weight:10500kg Bucket Capacity: 2.1m³ Max. Breakout:120kN Engine Model: Cummins B6.7 Overall Dimension(LxWxH): 7650x2482x3220mm	<b>XC948</b> Operating Weight: 13100kg Bucket Capacity: 2.4m³ Max. Breakout Force: 130kN Engine Model: Cummins B6.7 Overall Dimension(LxWxH): 7850x2482x3300mm	<b>XC958</b> Operating Weight: 17150kg Bucket Capacity: 3.2m³ Max. Breakout Force: 180kN Engine Model: Cummins L3 Overall Dimension(LxWxH): 8380x2996x3455mm	<b>XC968</b> Operating Weight: 19950kg Bucket Capacity: 3.5m³ Max. Breakout Force: 200kN Engine Model: Cummins L3 Overall Dimension(LxWxH): 8535x3200x3455mm	<b>XC978</b> Operating Weight: 25000kg Bucket Capacity: 4.5m³ Max. Breakout Force: 210kN Engine Model: Cummins L3 Overall Dimension(LxWxH): 8850x3230x3620mm	<b>XC998</b> Operating Weight: 31500kg Bucket Capacity: 5.4m³ Max. Breakout Force: >260kN Engine Model: Cummins X12 Overall Dimension(LxWxH): 9500x3500x3770mm
<b>XC998U</b> Operating weight:31500kg Bucket Capacity:5.4m³ Max. Breakout Force: >260kN Engine Model:Cummins X12 Overall dimension(LxWxH): 9500x3500x3770mm	<b>XC9150</b> Bucket Load:7.7m³ Rated Load:15000kg Operating Weight:55000kg Overall Dimension(LxWxH): 12230x3800x4315mm	<b>XC968-EV</b> Bucket Load:3.2m³ Rated Load:6000kg Operating Weight:19100kg Overall Dimension(LxWxH): 8610x2996x3455mm	<b>LW550FN</b> Bucket Load:3.0m³ Rated Load:5300kg Operating Weight:17100kg Overall Dimension(LxWxH): 8180x2996x3515mm	<b>ZL50GN</b> Bucket Load:3.2m³ Rated Load:5500kg Operating Weight:17150kg Overall Dimension(LxWxH): 8300x2996x3515mm	<b>LW600KN</b> Bucket Load:3.5m³ Rated Load:6000kg Operating Weight:19100kg Overall Dimension(LxWxH): 8505x3220x3515mm	<b>LW700HV</b> Bucket Load:4.2m³ Rated Load:7000kg Operating Weight:23500kg Overall Dimension(LxWxH): 8900x3200x3620mm	<b>LW700KN</b> Bucket Load:4.2m³ Rated Load:7000kg Operating Weight:23800kg Overall Dimension(LxWxH): 8900x3200x3620mm	<b>LW700FV</b> Bucket Load:4.4m³ Rated Load:7000kg Operating Weight:23910kg Overall Dimension(LxWxH): 9000x3230x3620mm	<b>LW800HV</b> Bucket Load:4.8m³ Rated Load:8000kg Operating Weight:25500kg Overall Dimension(LxWxH): 9100x3430x3620mm

<b>LW800KN</b> Bucket Load:4.8m³ Rated Load:8000kg Operating Weight:2770kg Max. Breakout:2800kg Overall Dimension(LxWxH): 9300x3430x3770mm	<b>LW900KN</b> Bucket Load:5.5m³ Rated Load:9000kg Operating Weight:30500kg Max. Breakout:3000kg Overall Dimension(LxWxH): 9400x3430x3770mm	<b>LW1200KN</b> Bucket Load:6.5m³ Rated Load:12000kg Operating Weight:3700kg Max. Breakout:3940kg Overall Dimension(LxWxH): 12337x3875x4319mm	<b>LW1400KN</b> Bucket Load:7.7m³ Rated Load:14000kg Operating Weight:4400kg Max. Breakout:3940kg Overall Dimension(LxWxH): 12337x3875x4319mm	<b>LW180K(V)</b> Min. Clamping Diameter: 800mm Rated Load:1800kg Operating Weight:58.5kW Overall Dimension(LxWxH): 6415x1960x2950mm	<b>LW200K(V)</b> Min. Clamping Diameter: 800mm Rated Load:1600kg Operating Weight:66.2kW Overall Dimension(LxWxH): 6415x1960x2950mm	<b>LW300KN</b> Min. Clamping Diameter: 830mm Rated Load:3000kg Operating Weight:92kW Overall Dimension(LxWxH): 7455x2482x3320mm	<b>LW550FN</b> Min. Clamping Diameter: 1000mm Rated Load:5000kg Operating Weight:162kW Overall Dimension(LxWxH): 8565x2850x3515mm	<b>ZL50GN</b> Min. Clamping Diameter: 1000mm Rated Load:5000kg Operating Weight:162kW Overall Dimension(LxWxH): 8880x2850x3515mm	<b>LW600KN</b> Min. Clamping Diameter: 900mm Rated Load:6000kg Operating Weight:17800kg Overall Dimension(LxWxH): 8805x2860x3515mm
---	--	--	--	---	---	---	---	--	--

<b>LW700K(V)</b> Min. Clamping Diameter: 1000mm Rated Load:7000kg Operating Weight:226kW Overall Dimension(LxWxH): 9233x3200x3620mm	<b>LW800K(V)</b> Min. Clamping Diameter: 1000mm Rated Load:8000kg Operating Weight:277kW Overall Dimension(LxWxH): 9233x3200x3620mm	<b>XC360</b> Shovel Capacity:178kW Operating Weight:19700kg Max. Tractor:171kN Logging Winch Diameter (Cable Type): 273mm Buckle Cutting Depth: 456mm Overall Dimension(LxWxH): 7840x3220x3550mm	<b>LW500K-V-LNG</b> Bucket Load:3m³ Rated Load:5000kg Operating Weight:17500kg Max. Breakout:170kN Overall Dimension(LxWxH): 8322x2996x3515mm	<b>LW600K-V-LNG</b> Bucket Load:3.5m³ Rated Load:6000kg Operating Weight:21500kg Max. Breakout:205kN Overall Dimension(LxWxH): 8780x3220x3515mm	<b>ZL20E</b> Bucket Load:1.0m³ Rated Load:2000kg Operating Weight:66.2kW Max. Breakout:55kN Overall Dimension(LxWxH): 5950x1960x2550mm	<b>ZL30E</b> Bucket Load:1.8m³ Rated Load:3000kg Operating Weight:10800kg Max. Breakout:130kN Overall Dimension(LxWxH): 7470x2482x2965mm	<b>ZL50E</b> Bucket Load:2.5m³ Rated Load:5000kg Operating Weight:162kW Overall Dimension(LxWxH): 8190x3000x2875mm	<b>ZL50GN</b> Bucket Load:2.5m³ Rated Load:5000kg Operating Weight:162kW Overall Dimension(LxWxH): 8515x3000x2875mm
---	---	--	--	--	---	---	--	---

<b>LW500K-V-T18</b> Bucket Load: 1800L at 1400mm height Rated Load:21900kg Operating Weight:162kW Attachment Dimension(LxWxH): 1840x1540x1260mm Max. Dump angle:35° Overall Dimension(LxWxH): 8260x2945x3515mm	<b>LW600K-V-T25</b> Bucket Load: 2500L at 1500mm height Rated Load:29500kg Operating Weight:178kW Attachment Dimension(LxWxH): 1890x1637x1440mm Max. Dump angle:22.5° Overall Dimension(LxWxH): 8750x3290x3585mm	<b>LW700K-V-T33</b> Bucket Load: 3300L at 1800mm height Rated Load:35800 kg Operating Weight:270kW Attachment Dimension(LxWxH): 1500x250x145mm Max. Dump angle:20° Overall Dimension(LxWxH): 9310x3275x3650mm	<b>LW440FN</b> Bucket Load:2.4m³ Rated Load:4000kg Operating Weight:129kW Max. Breakout:14000kg Overall Dimension(LxWxH): 7800x2718x3480mm	<b>ZL50GN</b> Bucket Load:2.5m³ Rated Load:5000kg Operating Weight:162kW Max. Breakout:170kN Overall Dimension(LxWxH): 8290x3000x3515mm	<b>XC6-3007K</b> Max. Lift Capacity:300kg Lifting Height:695mm Rated Load:90kg Operating Weight:7450kg Max. Traction(without load): >=55kN Overall Dimension(LxWxH): 4820x2355x2460mm Fork Length:1000mm	<b>XC6-3514K</b> Max. Lift Capacity:3500kg Lifting Height:13700mm Rated Load:174.9kW Operating Weight:7450kg Max. Traction(without load): >=55kN Overall Dimension(LxWxH): 6380x2500x2740mm Fork Length:1200mm	<b>XC6-4517K</b> Max. Lift Capacity:4500kg Lifting Height:16700mm Rated Load:82.74.9kW Operating Weight:13500kg Max. Traction(without load): >=70/70kN Overall Dimension(LxWxH): 6960x2500x2850mm Fork Length:1200mm	<b>WZ30-25</b> Bucket Load:1.5m³ Rated Load:2500kg Operating Weight:63/73.5kW Overall Dimension(LxWxH): 8000x2383x3450mm
--	--	---	---	--	---	---	---	--

<b>XC7-SR07</b> Bucket Load:0.45m³ Rated Load:890kg Operating Weight:35.5kW Overall Dimension(LxWxH): xxm3410x1800x1960	<b>XC7-SR08</b> Bucket Load:0.45m³ Rated Load:955kg Operating Weight:50.2kW Overall Dimension(LxWxH): xxm3410x1800x1960	<b>XC7-SR10</b> Bucket Load:0.6m³ Rated Load:1100kg Operating Weight:61.3kW Overall Dimension(LxWxH): xxm3760x2000x2040	<b>XC7-SR12</b> Bucket Load:0.6m³ Rated Load:1260kg Operating Weight:61.3kW Overall Dimension(LxWxH): xxm3760x2000x2040	<b>XC7-SV12</b> Bucket Load:0.6m³ Rated Load:1360kg Operating Weight:53.7kW Overall Dimension(LxWxH): xxm3800x2000x2100	<b>XC7-TV12</b> Bucket Load:0.6m³ Rated Load:1250kg Operating Weight:53.7kW Overall Dimension(LxWxH): xxm3760x2000x2100	<b>XC8-2570</b> Bucket Load:1.0m³ Rated Load:2500kg Operating Weight:74.5kW Overall Dimension(LxWxH): 6050x2508x3682mm	<b>XC8-3570</b> Bucket Load:1.3m³ Rated Load:3500kg Operating Weight:74.5kW Overall Dimension(LxWxH): 6013x2587x3716mm	<b>XC8-3580</b> Bucket Load:1.3m³ Rated Load:3500kg Operating Weight:82/81kW Overall Dimension(LxWxH): 6013x2587x3716mm	<b>XC8-0750</b> Bucket Load:0.36m³ Rated Load:700kg Operating Weight:45kW Overall Dimension(LxWxH): 3760x1612x2000mm
---	---	---	---	---	---	--	--	---	--

<b>TY130</b> Rated Power: 95.5kW Operating Weight: 31,310kg Blade Width x Height: 3.275m x 1.149mm Dimensions(L x W x H): 5.820m x 3.275m x 2.974mm (with straight tilt blade and three-shank ripper)	<b>TY160</b> Rated Power: 131kW 178HP 1,850rpm Operating Weight: 28,600kg 63,051lb Blade Width x Height: 3.416m x 1.149mm Dimensions(L x W x H): 6.430m x 3.416m x 3.015mm (with straight tilt blade and three-shank ripper)	<b>TY230</b> Rated Power: 169kW 2,000rpm Operating Weight: 28,600kg 63,051lb Blade Width x Height: 3.725m x 1.391mm Dimensions(L x W x H): 12.3" x 4.7" 6.790m x 3.725m x 3.472mm 22.4" x 4.7" x 11.5" (with straight tilt blade and three-shank ripper and ROPS)	<b>TY320</b> Rated Power: 235kW 315HP 2,000rpm Operating Weight: 36,800kg 85,538lb Blade Width x Height: 4.130m x 1.560mm Dimensions(L x W x H): 13.7" x 5.3" 8.916m x 4.130m x 3.602mm 23.3" x 13.7" x 11.6" (with straight tilt blade and three-shank ripper and ROPS)	<b>TY420</b> Rated Power: 310kW 418HP 2,000rpm Operating Weight: 55,000kg 121,252lb Blade Width x Height: 4.314m x 1.941mm Dimensions(L x W x H): 14.2" x 6.1" 9.630m x 4.314m x 3.827mm 31.7" x 14.2" x 12.7" (with straight tilt blade and three-shank ripper and ROPS)	<b>DL210</b> Shovel Capacity:3.9m³ Rated Power:162kW Operating Weight:16300kg Overall Dimension(LxWxH): 7430x3354x3515mm	<b>DL350</b> Shovel Capacity:6.88m³ Rated Power:277kW Operating Weight:25900kg Overall Dimension(LxWxH): 7950x4434x3805mm	<b>DL560</b> Shovel Capacity:10.0m³ Rated Power:418kW Operating Weight:47000kg Overall Dimension(LxWxH): 10333x5200x4315mm
--	---	--	---	--	--	---	--

<b>XE135B</b> Operating weight: 13800kg Bucket capacity: 0.52m³ Rated power: 72.7/2200kw/rpm	<b>XE215C</b> Operating weight: 21500kg Bucket capacity: 1.0m³ Rated power: 128.5/2100kw/rpm	<b>XE215C (Long chassis)</b> Operating weight: 21900kg Bucket capacity: 1.2m³ Rated power: 128.5/2100kw/rpm	<b>XE17U (Canopy)</b> Operating weight: 1795kg Bucket capacity: 0.04m³ Rated power: 11.8/2300kw/rpm	<b>XE26U (Canopy)</b> Operating weight: 2780kg Bucket capacity: 0.06m³ Rated power: 15.4/2400kw/rpm	<b>XE27U (Cab)</b> Operating weight: 2880kg Bucket capacity: 0.06m³ Rated power: 15.4/2400kw/rpm	<b>XE35U (Canopy/Cab)</b> Operating weight: 4100/4200kg Bucket capacity: 0.12m³ Rated power: 22/2400kw/rpm	<b>XE60DA</b> Operating weight: 6010kg Bucket capacity: 0.23m³ Rated power: 36.2/2100kw/rpm
---	---	--	--	--	---	---	--

<b>XE75DA</b> Operating weight: 7680kg Bucket capacity: 0.33m³ Rated power: 42.4/2000kw/rpm	<b>XE135D</b> Operating weight: 13200kg Bucket capacity: 0.52m³ Rated power: 66/2200kw/rpm	<b>XE155D</b> Operating weight: 14600kg Bucket capacity: 0.61m³ Rated power: 93/2200kw/rpm	<b>XE155DK</b> Operating
--	---	---	-----------------------------



## MATERIAL HANDLER



**XE215SLL**  
 Operating weight: 34900kg  
 Rated power: 128.5/2100kW/rpm  
 Bucket capacity: 1m³  
 Maximum operating radius: 15.43m  
 Maximum working height: 14.48m  
 Working water depth: 1.5m



**XE230M**  
 Operating weight: 23000kg  
 Rated power: 135/2050kW/rpm  
 Bucket capacity: 0.6m³  
 Maximum operating radius: 10.5m  
 Maximum working height: 8.7m



**XE350M**  
 Operating weight: 35000kg  
 Rated power: 169/1850kW/rpm  
 Bucket capacity: 0.8m³  
 Maximum operating radius: 12.5m  
 Maximum working height: 10.5m



**XE450M**  
 Operating weight: 45000kg  
 Rated power: 222/2100kW/rpm  
 Bucket capacity: 1m³  
 Maximum operating radius: 15.4m  
 Maximum working height: 13.2m



**XE480WM**  
 Operating weight: 47000kg  
 Rated power: 222/2100kW/rpm  
 Bucket capacity: 1m³  
 Maximum operating radius: 15.7m  
 Maximum working height: 13.8m

## FORESTRY EXCAVATOR



**XE135F**  
 Operating weight: 13800kg  
 Rated power: 72.7/2200kW/rpm

## DEMOLITION EXCAVATOR



**XE500EHR**  
 Operating weight: 63000kg  
 Rated power: 321/1800kW/rpm

## NEW ENERGY



**XE27U-E**  
 Operating weight: 3300kg  
 Bucket capacity: 0.08m³  
 Rated power: 15.3/2000kW/rpm




**XE35U-E**  
 Operating weight: 4340kg  
 Bucket capacity: 0.12m³  
 Rated power: 22/2400kW/rpm



**XE95E**  
 Operating weight: 8800kg  
 Bucket capacity: 0.4m³  
 Rated power: 55/1485kW/rpm



**XE215E**  
 Operating weight: 23500kg  
 Bucket capacity: 1.1m³  
 Rated power: 140/2200kW/rpm



**XE270E**  
 Operating weight: 27450kg  
 Bucket capacity: 1.4m³  
 Rated power: 140/2200kW/rpm

## MINING MACHINERY

### MINING EXCAVATOR



**XE7000E (Loading Shovel)**  
 Operation Weight: 66000kg  
 Bucket Capacity: 34-44m³  
 Output Power: 2x1250/1489kW/rpm



**XE7000F**  
 Operation Weight: 70000kg  
 Bucket Capacity: 2.4-5.2m³  
 Output Power: 328/2100kW/rpm



**XE7000A**  
 Operation Weight: 69000kg  
 Bucket Capacity: 4.2m³  
 Output Power: 328/2100kW/rpm



**XE7000D**  
 Operation Weight: 69000kg  
 Bucket Capacity: 2.4-4.6m³  
 Output Power: 335/1800kW/rpm



**XE7000GA**  
 Operation Weight: 70000kg  
 Bucket Capacity: 2.4-5.2m³  
 Output Power: 340/2100kW/rpm



**XE7000GK**  
 Operation Weight: 69000kg  
 Bucket Capacity: 4.2m³  
 Output Power: 340/2100kW/rpm



**XE7000GZ**  
 Operation Weight: 72000kg  
 Output Power: 560/1800kW/rpm



**XE750G**  
 Operation Weight: 75000kg  
 Bucket Capacity: 3.8-6.5m³  
 Output Power: 403/2100kW/rpm



**XE800D**  
 Operation weight: 78000kg  
 Bucket Capacity: 3.8-6.5m³  
 Output Power: 403/2100 kW/rpm



**XE1350E (Loading Shovel)**  
 Operation Weight: 124000kg  
 Bucket Capacity: 7-8m³  
 Output Power: 560/1482kW/rpm



**XE1350**  
 Operation Weight: 121000kg  
 Bucket Capacity: 5.2-10m³  
 Output Power: 567/1800kW/rpm



**XE1600 (Backhoe)**  
 Operation Weight: 145000kg  
 Bucket Capacity: 8-12m³  
 Output Power: 634/1800kW/rpm



**XE2000 (Backhoe)**  
 Operation Weight: 152000kg  
 Bucket Capacity: 10-14m³  
 Output Power: 810/1800kW/rpm



**XE2000 (Loading Shovel)**  
 Operation Weight: 152000kg  
 Bucket Capacity: 12m³  
 Output Power: 810/1800kW/rpm



**XE2000E (Loading Shovel)**  
 Operation Weight: 152000kg  
 Bucket Capacity: 10-12m³  
 Output Power: 610/1480kW/rpm



**XE2600 (Loading Shovel)**  
 Operation Weight: 273800kg  
 Bucket Capacity: 15m³  
 Output Power: 1119/1800kW/rpm



**XE3000E**  
 Operation Weight: 285000kg  
 Bucket Capacity: 15m³  
 Output Power: 1200/1490kW/rpm




**XE3000 (Loading Shovel)**  
 Operation Weight: 295000kg  
 Bucket Capacity: 15m³  
 Output Power: 1193/1800kW/rpm



**XE3000 (Backhoe)**  
 Operation Weight: 290000kg  
 Bucket Capacity: 15m³  
 Output Power: 1193/1800kW/rpm



**XE4000 (Backhoe)**  
 Operation Weight: 384000kg  
 Bucket Capacity: 22m³  
 Output Power: 1491/1800kW/rpm



**XE4000 (Loading Shovel)**  
 Operation Weight: 390000kg  
 Bucket Capacity: 20-22m³  
 Output Power: 1491/1800kW/rpm



**XE4000E (Loading Shovel)**  
 Operation Weight: 380000kg  
 Bucket Capacity: 21-23m³  
 Output Power: 1200-1786-1486kW/rpm



**XE5600 (Backhoe)**  
 Operation Weight: 567000kg  
 Bucket Capacity: 25m³  
 Output Power: 2x119/1800kW/rpm



**XE7000 (Loading Shovel)**  
 Operation Weight: 672000kg  
 Bucket Capacity: 34m³  
 Output Power: 2 x 1193/1800kW/rpm



**XE7000 (Backhoe)**  
 Operation Weight: 673000kg  
 Bucket Capacity: 30-38m³  
 Output Power: 2x1193/1800kW/rpm



**XDR80T**  
 Rated power: 353kW  
 Rated load: 8000kg  
 Body capacity/heaped SAE 2:11.30-50m³




**XDR80T-AT**  
 Rated power: 412/1900kW  
 Rated load: 6000kg  
 Body capacity/heaped SAE 2:11.35-53m³



**XDR80TE**  
 Motor rated power: 430kW/550kW  
 Rated load: 7200kg  
 Body capacity (heaped SAE 2:1): 45m³




**XDR9T**  
 Rated power: 412kW  
 Rated load: 8100kg  
 Body capacity (heaped SAE 2:1): 30-50m³



**XDR100T**  
 Rated power: 588kW (800hp)  
 Rated load: 9100kg  
 Body capacity (heaped SAE 2:1): 52-70m³



**XDR100**  
 Rated Power: 783kW  
 Rated Payload: 9100kg  
 Body Capacity: 60m³



**XDE130**  
 Rated Power: 859kW  
 Rated Payload: 12000kg  
 Body Capacity: 73m³



**XDE200**  
 Rated Power: 1492kW  
 Rated Payload: 18600kg  
 Body Capacity: 77m³



**XDE240**  
 Rated Power: 1865kW  
 Rated Payload: 23000kg  
 Body Capacity: 118m³



**XDE260**  
 Rated Power: 1865kW  
 Rated Payload: 23000kg  
 Body Capacity: 118m³




**XDE320**  
 Rated Power: 2014kW  
 Rated Payload: 30000kg  
 Body Capacity: 171m³



**XDE440**  
 Rated Power: 2800kW  
 Rated Payload: 40000kg  
 Body Capacity: 183m³



**XDA30**  
 Rated Power: 290kW  
 Rated Payload: 30000kg  
 Body Capacity: 17.5/18.1m³



**XDA45U (Tier 4/Euro v)**  
 Rated power: 390kW  
 Rated load: 41000kg  
 Body capacity: 25/26m³



**XDA45 (Euro III)**  
 Rated Power: 350kW  
 Rated Payload: 41000kg  
 Body capacity: 25/26m³

## OFF-HIGHWAY DUMP TRUCK



**NXGA570D3T**  
 Rated Power: 340/380HP  
 Transmission: 9+1/6+1(AT)  
 Rated Load: 30t  
 Drive Type: 6 x 4  
 Dump volume: 20m³



**XGA5480D**  
 Rated Power: 380HP  
 Transmission: 9+1/7+1(AT)  
 Rated Load: 30t  
 Drive Type: 6 x 4  
 Dump volume: 21m³



**XGA5650D3T**  
 Rated Power: 380HP  
 Transmission: 9+1/7+1  
 Rated Load: 40t  
 Drive Type: 6 x 4  
 Dump volume: 30m³



**XGA5902D3T**  
 Rated Power: 460/530HP  
 Transmission: 9+1/7+1(AT)  
 Rated Load: 60t  
 Drive Type: 6 x 4  
 Dump volume: 36m³



**XGA105**  
 Rated Power: 530HP  
 Transmission: 8+1/6+1(AT)  
 Rated Load: 70t  
 Drive Type: 6 x 4  
 Dump volume: 43m³



**XGE90**  
 Peak Power: 350-500kW  
 Battery: 422.9kWh  
 Transmission: Auto  
 Rated Load: 60t  
 Drive Type: 6 x 4



**XGA5650D3TS**  
 Rated Power: 460-530HP  
 Transmission: 8+1/7+1  
 Rated Load: 50m³  
 Drive Type: 6 x 4



**XGA5900D3TS**  
 Rated Power: 460-530HP  
 Transmission: 8+1/7+1  
 Rated Load: 50m³  
 Drive Type: 6 x 4



**XGA5470DTS**  
 Rated Power: 380HP  
 Drive type: 4 x 2  
 GVW: 75t  
 Power capacity (kwh) : 281.91  
 Only Charge/Battery swap  
 Rated/Peak Power: 240/360  
 Transmission: 4

## HEAVY-DUTY TRUCK

### DUMP TRUCK



**XGA3160**  
 Drive Type: 4 x 2  
 Engine: 220HP  
 Transmission: 8  
 GCW: 20-25t  
 Overall size: 7 x 2.5 x 3.15m



**XGA3250**  
 Drive Type: 6 x 4  
 Engine: 336/371/375/420/430HP  
 Transmission: 9/10/12  
 GCW: 25t  
 Overall size: 8.6 x 2.5 x 3.5m



**XGA3310**  
 Drive Type: 8 x 4  
 Engine: 371/375/420/550HP  
 Transmission: 9/10/12  
 GCW: 31t  
 Overall size: 10 x 2.5 x 3.4m



**XGA4180**  
 Drive Type: 4 x 2  
 Engine: 350/371/375/460HP  
 Transmission: 9/12/16  
 Traction mass: 60t  
 Overall size: 6.7 x 2.5 x 3.9m



**XGA4250**  
 Drive Type: 6 x 4  
 Engine: 350/371/375/430/460/500/550HP  
 Transmission: 9/12/16  
 Traction mass: 80-120t  
 Overall size: 6.7 x 2.5 x 3.10m

## E-TRUCK

### PURE ELECTRIC TRUCK E-TRACTOR



**XGA4750E/XGA4180E**  
 Drive type: 4 x 2  
 GVW: 75t  
 Power capacity (kwh) : 281.91  
 Only Charge/Battery swap  
 Rated/Peak Power: 240/360  
 Transmission: 4



**XGA4250E**  
 Drive type: 6 x 4  
 GVW: 49t  
 Power capacity (kwh) : 281.91  
 Only Charge/Battery swap  
 Rated/Peak Power: 215/360  
 Transmission: 6



**XGA4750E/XGA4180E**  
 Drive type: 4 x 2  
 GVW: 75t  
 Power capacity (kwh) : 281.91  
 Only Charge/Battery swap  
 Rated/Peak Power: 240/360  
 Transmission: 4

## PURE ELECTRIC TRUCK E-DUMP TRUCK



**XGA4256E/XGA4254E**  
 Drive type: 6 x 4  
 GVW: 49t  
 Power capacity (kwh) : 422.87/281.91  
 Only Charge/Battery swap  
 Rated/Peak Power: 240/360  
 Transmission: 4



**XGA4252E/XGA4254E1**  
 Drive type: 6 x 4  
 GVW: 85t  
 Power capacity (kwh) : 281.91  
 Only Charge/Battery swap  
 Rated/Peak Power: 240/360  
 Transmission: 4



**XGA5250E**  
 Drive type: 6 x 4  
 GVW: 60t  
 Power capacity (kwh) : 281.91  
 Only Charge/Battery swap  
 Rated/Peak Power: 250/360  
 Transmission: 6



**XGA3310E**  
 Drive type: 8 x 4  
 GVW: 31t  
 Power capacity (kwh) : 281.91  
 Only Charge/Battery swap  
 Rated/Peak Power: 215/360  
 Transmission: 6



**XGA5313E/XGA5317E**  
 Drive type: 8 x 4  
 GVW: 45t  
 Power capacity (kwh) : 422.87/281.91  
 Only Charge/Battery swap  
 Rated/Peak Power: 240/360  
 Transmission: 6



**XGA3318E/XGA3312E**  
 Drive type: 8 x 4  
 GVW: 80t  
 Power capacity (kwh) : 422.87/281.91  
 Only Charge/Battery swap  
 Rated/Peak Power: 240/360  
 Transmission: 12/4



**XGA4251E/XGA4251E1/XGA4250E**  
 Drive type: 6 x 4  
 GVW: 49t  
 Power capacity (kwh) : 240/360 198/360  
 Fuel system Rated power: 130.5/117/110kW  
 Hydrogen storage system Capacity: 10X210/10X140L  
 Power capacity (kwh) : 105.3/100.91  
 Transmission: 4/6



**XGA5310E/XGA5310E1/XGA5312E**  
 Drive type: 8 x 4  
 GVW: 45/55t  
 Rated/Peak Power: 1 98/360 198/355  
 Fuel system Rated power: 110/110.5kW  
 Hydrogen storage system Capacity: 7X140L/9X165L  
 Power capacity (kwh) : 100.91/127.7  
 Transmission:



## PAVER

<b>RP305</b> Engine: Kubota 55.4kW stage V Paving Range: 1m - 3.2m Transport Weight: 7800kg maximum laydown rate: 260t/h Size: 4910 x 1450 x 1980	<b>RP355</b> Engine: Cummins 53kW stage II Paving Range: 1.2 - 3.5m Transport Weight: 11200kg maximum laydown rate: 300t/h Size: 4910 x 1450 x 1935	<b>RP453L</b> Engine: ShangChai 73.5kW stage II Paving Range: 1.8m - 4.5m Transport Weight: 17900kg maximum laydown rate: 240t/h Size: 6260 x 1900 x 3750	<b>RP405</b> Engine: ShangChai 95kW stage II Paving Range: 1.8m - 4.5m Transport Weight: 12000kg maximum laydown rate: 350t/h Size: 5860 x 1940 x 3700	<b>RP505</b> Engine: Cummins 104kW stage II Paving Range: 1.8m - 5m Transport Weight: 19200kg maximum laydown rate: 400t/h Size: 5860 x 1940 x 3700	<b>RP603</b> Engine: Cummins 129kW stage II Paving Range: 2.5m - 6m Transport Weight: 19200kg maximum laydown rate: 600t/h Size: 6680 x 2500 x 4000	<b>RP603 (High configuration)</b> Engine: ShangChai 129kW stage II Paving Range: 2.5m - 6m Transport Weight: 19200kg maximum laydown rate: 600t/h Size: 6680 x 2500 x 4000	<b>RP603L</b> Engine: ShangChai 103kW stage II Paving Range: 2.5 - 6m Transport Weight: 16500kg maximum laydown rate: 400t/h Size: 6660 x 2600 x 4000
<b>RP603</b> Engine: Cummins 142kW stage II Paving Range: 2.5m - 8m Transport Weight: 22800kg maximum laydown rate: 800t/h Size: 7080 x 2500 x 4000	<b>RP605</b> Engine: Cummins 119kW stage II Paving Range: 2.5m - 6m Transport Weight: 17000kg maximum laydown rate: 600t/h Size: 6180 x 2300 x 3800	<b>RP705</b> Engine: Cummins 119kW stage II Paving Range: 2.5m - 7.5m Transport Weight: 19000kg maximum laydown rate: 600t/h Size: 6280 x 2550 x 3750	<b>RP705 (C)</b> Engine: Cummins 119kW stage II Paving Range: 2.5m - 7.25m Transport Weight: 19000kg maximum laydown rate: 600t/h Size: 6200 x 2550 x 3750	<b>RP705 (CE)</b> Engine: Cummins 115kW stage V Paving Range: 2.5m - 7.5m Transport Weight: 19000kg maximum laydown rate: 600t/h Size: 6280 x 2550 x 3750	<b>RP1253T</b> Engine: ShangChai 243kW stage II Paving Range: 3.0m - 12.5m Transport Weight: 36000kg maximum laydown rate: 1200t/h Size: 6980 x 3000 x 4065	<b>COLD PLANNER</b> <b>XM200KII</b> Rated Power: 470kW 630hp Operating Weight: 33000kg Max. Milling Width: 2000mm Max. Milling Depth: 320mm Machine: 14500 x 2750 x 3100mm	

<b>XM405S</b> Rated Power: 81kW 109hp Operating Weight: 5200kg Max. Milling Width: 400mm Max. Milling Depth: 120mm Machine: 2850 x 1470 x 2000mm	<b>XM503K</b> Rated Power: 103kW 137hp Operating Weight: 7500kg Max. Milling Width: 500mm Max. Milling Depth: 210mm Machine: 3275 x 1828 x 2600mm	<b>XM505</b> Rated Power: 52kW 122hp Operating Weight: 6100kg Max. Milling Width: 500mm Max. Milling Depth: 210mm Machine: 3125 x 1715 x 2200mm	<b>XM505K</b> Rated Power: 115kW 156hp Operating Weight: 10000kg Max. Milling Width: 500mm Max. Milling Depth: 210mm Machine: 3660 x 1740 x 3250mm	<b>XM1005H</b> Rated Power: 164kW 220hp Operating Weight: 13900kg Max. Milling Width: 1000mm Max. Milling Depth: 320mm Machine: 4800 x 2225 x 2600mm	<b>XM1005K</b> Rated Power: 177kW 240hp Operating Weight: 14700kg Max. Milling Width: 1000mm Max. Milling Depth: 300mm Machine: 980 x 2295 x 2890mm	<b>XM1005F (tire)</b> Rated Power: 177kW 240hp Operating Weight: 17200kg Max. Milling Width: 1000mm Max. Milling Depth: 300mm Machine: 9100 x 2010 x 2900mm	<b>XM1005F (crawler)</b> Rated Power: 177kW 240hp Operating Weight: 18200kg Max. Milling Width: 1000mm Max. Milling Depth: 300mm Machine: 9100 x 2010 x 2900mm	<b>XM1205F</b> Rated Power: 81kW 109hp Operating Weight: 5200kg Max. Milling Width: 500mm Max. Milling Depth: 120mm Machine: 2850 x 1470 x 2000mm
<b>XM1305K</b> Rated Power: 177kW 240hp Operating Weight: 15400kg Max. Milling Width: 1300mm Max. Milling Depth: 300mm Size: 9580 x 2595 x 2690mm	<b>XM1305F</b> Rated Power: 206kW 280hp Operating Weight: 16500kg Max. Milling Width: 1200mm Max. Milling Depth: 320mm Machine: 9950 x 2280 x 3000mm	<b>XM2005</b> Rated Power: 412kW 560hp Operating Weight: 33500kg Max. Milling Width: 2000mm Max. Milling Depth: 330mm Machine: 12597 x 2500 x 3000mm	<b>XM2005K</b> Rated Power: 447kW 600hp Operating Weight: 33500kg Max. Milling Width: 2000mm Max. Milling Depth: 330mm Machine: 12597 x 2500 x 3000mm	<b>XM2005S</b> Rated Power: 485kW 630hp Operating Weight: 31900kg Max. Milling Width: 2000mm Max. Milling Depth: 330mm Size: 12597 x 2500 x 3000mm	<b>XLZ2103S</b> Rated Power: 353kW 480hp 2100rpm Operating Weight: 21000kg Max. Milling Width: 2100mm/2300mm Max. Milling Depth: 400mm Size: 9232 x 3162 x 3450mm	<b>XLZ2103SP</b> Rated Power: 390kW 530hp 2100rpm Operating Weight: 21000kg Max. Milling Width: 2300mm Max. Milling Depth: 400mm Size: 9232 x 3262 x 3450mm	<b>XLZ2303SP</b> Rated Power: 390kW 530hp 2100rpm Operating Weight: 21000kg Max. Milling Width: 2300mm Max. Milling Depth: 400mm Size: 9230x3263x3450mm	

<b>XL2103</b> Engine: 294kW 394hp 1900rpm Operating Weight: 15400kg Max. Milling Width: 2100mm Max. Milling Depth: 400mm Size: 8740 x 2785 x 3450mm	<b>XL2503</b> Engine: 316kW 423hp 1900rpm Operating Weight: 16500kg Max. Milling Width: 2500mm Max. Milling Depth: 300mm Size: 8740 x 3060 x 3450mm	<b>XLZ2303K</b> Engine: 515kW 710hp Operating Weight: 33500kg Max. Milling Width: 2300mm Max. Milling Depth: 330mm Size: 9340 x 3218 x 3197mm	<b>XLZ2305K</b> Engine: 570.5kW 765hp Operating Weight: 33500kg Max. Milling Width: 2300mm Max. Milling Depth: 430mm Size: 9340 x 3218 x 3197mm	<b>XLS303P</b> Rated Power: 73kW 100HP 3200rpm Asphalt Spraying Width: 2100 Dimensions(L x W x H): 5760 x 2050 x 2300	<b>XLS403P</b> Rated Power: 88kW 120HP 3200rpm Asphalt Spraying Width: 2100 Dimensions(L x W x H): 7240 x 2350 x 2500	<b>XLS503P</b> Rated Power: 125kW 170HP 3200rpm Asphalt Spraying Width: 5500 Dimensions(L x W x H): 7240 x 2350 x 2500	<b>XLS603P</b> Rated Power: 125kW 170HP 3200rpm Asphalt Spraying Width: 5500 Dimensions(L x W x H): 7740 x 2350 x 2500	<b>XLS803P</b> Rated Power: 162kW 220HP 2500rpm Asphalt Spraying Width: 5500 Dimensions(L x W x H): 8520 x 2500 x 2950
--	--	--	--	---	---	--	--	--

<b>XL51003P</b> Rated Power: 162kW 220HP 2500rpm Asphalt Spraying Width: 5500 Dimensions(L x W x H): 8520 x 2500 x 3050	<b>XLS1203P</b> Rated Power: 273kW 370HP 2200rpm Asphalt Spraying Width: 5500 Dimensions(L x W x H): 10950 x 2500 x 3300	<b>XLS403</b> Rated Power: 115kW 154HP 2800rpm Transport Weight: 7300kg Asphalt Spraying Width: 4000mm Dimensions(L x W x H): 7010 x 2100 x 2515mm	<b>XLS603</b> Rated Power: 125kW 170HP 2600rpm Transport Weight: 9010kg Asphalt Spraying Width: 4500-6000mm Dimensions(L x W x H): 8050x2350x2900mm	<b>XLS803</b> Rated Power: 208kW 276HP 2300rpm Transport Weight: 12800kg Asphalt Spraying Width: 6000mm Dimensions(L x W x H): 9270x2490x3350mm	<b>XLS1203</b> Rated Power: 228kW 306HP 1900rpm Transport Weight: 17700kg Asphalt Spraying Width: 6000mm Dimensions(L x W x H): 10330 x 2500 x 3220mm	<b>XF1003</b> Rated Power: 228kW 306HP 1900rpm Carrier: 228kW 306HP 1900rpm Transport Weight: 20500kg Paving Range(maximum): 2400-4200mm Transport Width: 3-15mm Dimensions(L x W x H): 11850 x 2496 x 3490mm	<b>XLV053TB</b> Rated Power: 115kW Generator: 22kW Transport Weight: 8250kg Dimensions(L x W x H): 6600 x 2340 x 2950mm	<b>XLV103TB</b> Rated Power: 165kW Superstructure: 48kW Carrier: 205kW 276HP Generator: 12kW Transport Weight: 13750kg Dimensions(L x W x H): 8175 x 2495 x 3440mm
---	--	---	--	--	--	---	--	---

<b>XTF1003</b> Rated Power: 228kW 306HP 1900rpm Transport Weight: 19500kg Max. Seal Width: 4000mm Dimensions(L x W x H): 9920 x 2500 x 3790mm	<b>XTF1403</b> Rated Power: 276kW 370HP 2000rpm Transport Weight: 24800kg Spraying Width: 4000mm Dimensions(L x W x H): 11980 x 2500 x 3890mm	<b>XTF1403R</b> Rated Power: 2100rpm Transport Weight: 22300kg Spraying Width: 4000mm Dimensions(L x W x H): 11300 x 2500 x 3965	<b>XKC163</b> Rated Power: 570.5kW 765hp Transport Weight: 33500kg Dimensions(L x W x H): 9550 x 2500 x 3360mm	<b>XKC203</b> Rated Power: 228kW 306HP 1900rpm Spraying Width: 2400mm Dimensions(L x W x H): 9550 x 2500 x 3610mm	<b>XLQ1005</b> Rated Power: 125kW 170HP 2600rpm working Width: 2550mm Dimensions(L x W x H): 9000 x 2450 x 3190mm	<b>XLV245B</b> Rated Power: 338kW 460HP 1900rpm material silo capacity: 23m³ Dimensions(L x W x H): 9000 x 2550 x 3550
--	--	---	--	---	---	--

<b>XC300</b> Total Installed Power: 90kW Production Capacity: 300t/h Area: 44 x 14m²	<b>XC400</b> Total Installed Power: 107kW Production Capacity: 400t/h Area: 48 x 14m²	<b>XC500</b> Total Installed Power: 139kW Production Capacity: 500t/h Area: 48 x 14m²	<b>XC600</b> Total Installed Power: 151kW Production Capacity: 600t/h Area: 51 x 14m²	<b>XC700</b> Total Installed Power: 164kW Production Capacity: 700t/h Area: 51 x 14m²	<b>XC800</b> Total Installed Power: 222kW Production Capacity: 800t/h Area: 53 x 14m²	<b>XC600S</b> Total Installed Power: 243kW Production Capacity: 600t/h Area: 55 x 14m²	<b>XC700S</b> Total Installed Power: 247kW Production Capacity: 700t/h Area: 55 x 14m²	<b>XC800S</b> Total Installed Power: 300kW Production Capacity: 800t/h Area: 60 x 14m²	<b>XC1000S</b> Total Installed Power: 369kW Production Capacity: 1000t/h Area: 64 x 18m²
---	--	--	--	--	--	---	---	---	---

<b>XFP20</b> Total Installed Power: 6kW 8hp Production Capacity: 20t/h	<b>XFP30</b> Total Installed Power: 10kW 13hp Production Capacity: 30t/h	<b>XAP50</b> Total Installed Power: 153kW, 208hp Production Capacity: 50t/h Area: 448m²	<b>XAP125M</b> Total Installed Power: 302kW, 411hp Production Capacity: 120t/h Area: 1131m²	<b>XAP205</b> Total Installed Power: 431kW, 588hp Production Capacity: 200t/h Area: 1085m²	<b>XAP258</b> Total Installed Power: 442kW, 604hp Production Capacity: 200t/h Area: 1085m²	<b>XAP405</b> Total Installed Power: 1247HP 930kw Production Capacity: 400t/h Area: 2091m²	<b>XAP405H</b> Total Installed Power: 1096kW 1469hp Production Capacity: 400t/h Area: 2624m²	<b>XAP245H</b> Total Installed Power: 927kW 1243hp Production Capacity: 310t/h Area: 2068m²	<b>XRP130</b> Total Installed Power: 252kW 338hp Production Capacity: 130t/h Area: 890m²	<b>XRP163</b> Total Installed Power: 284kW 381hp Production Capacity: 160t/h Area: 890m²	<b>XR65</b> Total Installed Power: 30kW, 41hp Production Capacity: 8t/h Area: 15.4m²	<b>XR105</b> Total Installed Power: 48kW, 65hp Production Capacity: 10t/h Area: 15.4m²
--	--	--	--	---	---	---	---	--	---	---	---	---

## SANITARY ENGINEERING EQUIPMENT

### COMPLETE SET OF GARBAGE COLLECTION AND TRANSFER EQUIPMENT

<b>XGH5070ZYSQ6</b> Curb Weight: 5300/5200kg Rated Payload: 1870/1920kg Dustbin Volume: 6m³ Vehicle Model: 6950/6620x1920x2315mm	<b>XGH5120ZYSQ6</b> Curb Weight: 8900kg Rated Payload: 3395/3460kg Dustbin Volume: 10m³ Vehicle Model: 8150/7780/7930x2500x2990mm	<b>XGH5180ZYSQ6</b> Curb Weight: 10000kg Rated Payload: 3785kg Dustbin Volume: 12.5m³ Vehicle Model: 8890/8375/8570x2500x3000mm	<b>XZJ5250ZYSQ6</b> Curb Weight: 14450kg Rated Payload: 10420/10355kg Dustbin Volume: 19m³ Vehicle Model: 10575/10285x2530x3380mm	<b>XGH5031ZXXA6</b> Curb Weight: 1480kg Rated Payload: 1885kg Max. Lifting Capacity: 1500kg Vehicle Model: 4525x1600x1535mm	<b>XGH5070ZXXQ6</b> Curb Weight: 2320/2760kg Rated Payload: 3670/3830kg Max. Lifting Capacity: 3000kg Vehicle Model: 4850x1920x2200mm	<b>XGH5180ZXXD6</b> Curb Weight: 7020kg Rated Payload: 10270/10205kg Max. Lifting Capacity: 14000kg Vehicle Model: 7340/7370x2480x3070mm
<b>XGH520ZXXD6</b> Curb Weight: 11100kg Rated Payload: 13770/13705kg Max. Lifting Capacity: 20000kg Vehicle Model: 8480x2525x3170mm	<b>XGH5120ZJD6</b> Curb Weight: 7250/7400kg Rated Payload: 5110/5045/4860/4895kg Dustbin Volume: 14.4/13.5m³ Vehicle Model: 6520/6550x2590/2530x3060mm	<b>XGH5070TCAQ6</b> Curb Weight: 5250/4950/5000/4700kg Rated Payload: 1920/2220/2170/2470kg Water Tank Volume: 5.2m³ Vehicle Model: 5840x2030x2800mm	<b>XGH5160TSD6</b> Curb Weight: 8880kg Dustbin Volume: 8m³ Water Tank Volume: 4m³ Vehicle Model: 7270x2500x3220mm	<b>XGA5250D2WCSS</b> Drive Type: 4 x 2/6 x 4 Engine: 90-430HP Transmission: 9 Tank Volume: 5/10/15/20m³	<b>XGA5250D3WCSS</b> Drive Type: 4 x 2/6 x 4 Engine: 90-430HP Transmission: 9 Tank Volume: 5/10/15/20m³	<b>XGA5250D5WCSS</b> Drive Type: 4 x 2/6 x 4 Engine: 90-430HP Transmission: 9 Tank Volume: 5/10/15/20m³
<b>XGH5070TXXQ6</b> Curb Weight: 5520kg Dustbin Volume: 2m³ Water Tank Volume: 4m³ Vehicle Model: 6220x2100x2720mm	<b>SJDH700A</b> Curb Weight: 1800kg Dustbin Volume: 700L Water Tank Volume: 180L Vehicle Model: 3729x1200x2050mm	<b>XGH5160TSD6</b> Curb Weight: 8780kg Dustbin Volume: 4.5m³ Water Tank Volume: 8m³ Vehicle Model: 7845x2510x3170mm	<b>XGH5030TTHA6</b> Curb Weight: 1700kg Rated Payload: 1010kg Water Tank Volume: 1.7m³ Vehicle Model: 5050x1580x2050mm	<b>DXA5251TDYD6</b> Curb Weight: 13650/13110/14160kg Rated Payload: 1882m 11155/11695/10645/11220/11760/11710kg Water Tank Volume: 11.18m³ Vehicle Model: 10805/10925 x 2525 x 3730/3830mm	<b>DXA5161GSD6</b> Curb Weight: 6130kg Rated Payload: 9675kg Water Tank Volume: 10.3m³ Vehicle Model: 7430x2520x2860mm	<b>DXA5183GQXD6</b> Curb Weight: 8300/8470kg Spray Water Cleaning Width: 2.5-3.5m Water Tank Volume: 9.8m³ Vehicle Model: 8223/8823/9240x2530x2920mm

### COMPLETE SET OF ICE BREAKING AND SNOW REMOVAL EQUIPMENT

<b>DXA5250GXD6</b> Curb Weight: 12560kg Spray Water Cleaning Width: 2.5-3.5m Water Tank Volume: 12.8m³ Vehicle Model: 10520x2550x3190mm	<b>XSR36G</b> Cleaning Snow Thickness: ≤ 180mm Vehicle Model: 4000x2395x1385mm	<b>XSR36G</b> Cleaning Snow Thickness: ≤ 180mm Vehicle Model: 3730x2395x1385mm	<b>SRC36</b> Max. Snow Pushing Width: 3660mm Total Weight: 930kg Vehicle Model: 3755 x 2500 x 1845mm	<b>XCD32</b> Max. Snow Pushing Width: 3200mm Total Weight: 1050kg Vehicle Model: 3295x1905x1065mm	<b>SBJ12B</b> Bin Volume: 12m³ Max. Operating Speed: 40km/h Total Weight: 2400kg Vehicle Model: 6370x2130x2200mm	<b>PX90Z</b> Max. Snow Dumping Thickness: 1000mm Max. Snow Throwing Distance: 35m Total Weight: 4500kg Vehicle Model: 2920x2700x4280mm
---	--	--	---	--	--	--

### COMPLETE SET OF UNDERGROUND PIPE NETWORK MAINTENANCE EQUIPMENT

<b>XGH5250TCXD6</b> Curb Weight: 7250/7400kg Vehicle Model: 10607/9786/11259/10896x2500/2530x3710mm	<b>XGH5251TCXZ6</b> Curb Weight: 18050kg Vehicle Model: 10955/10240/11775/11540x2520x3430/3510/3580/3880mm	<b>DXA5120GKWD6</b> Curb Weight: 5610kg Rated Payload: 819kg Tank Volume: 8.1m³ Vehicle Model: 6590x2165x3070mm	<b>DXA5180GKWD6</b> Curb Weight: 8950kg Rated Payload: 8855kg Tank Volume: 11.5m³ Vehicle Model: 7855x2490x3425mm	<b>XZJ5250TWXZ6</b> Curb Weight: 5610kg Rated Payload: 4830kg Tank Volume: 5.7m³ Vehicle Model: 10500x2520x3850mm
---	--	---	---	---

## PORT MACHINERY

<b>CONTAINER REACH STACKER</b> <b>XC51009K</b> Max. lifting capacity: 10t Max. lifting height: 16.2m No. of stacking: 6 <b>XC570S</b> Max. lifting capacity: 70t Max. lifting height: 9m	<b>XC54531K</b> Max. lifting capacity: 45t Max. lifting height: 15.1m No. of stacking: 5 <b>XC5150S</b> Max. lifting capacity: 150t Max. lifting height: 15.1m	<b>XC54535K</b> Max. lifting capacity: 45t Max. lifting height: 15.1m No. of stacking: 5 <b>XC5180S</b> Max. lifting capacity: 180t Max. lifting height: 13.295m	<b>XC54541K</b> Max. lifting capacity: 45t Max. lifting height: 15.1m No. of stacking: 5 <b>XC531W</b> Max. lifting capacity: 31t Max. lifting height: 9.5m	<b>XC54545K</b> Max. lifting capacity: 45t Max. lifting height: 15.1m No. of stacking: 5 <b>XRS400K</b> Max. lifting capacity: 40t Max. lifting height: 6m	<b>EMPTY CONTAINER HANDLER</b> <b>XCH906K</b> Max. lifting capacity: 9t Max. lifting height: 16.2m No. of stacking: 6 ( 8' 6" / 9' 6" ) <b>XCH908K</b> Max. lifting capacity: 9t Max. lifting height: 21.25m No. of stacking: 8 ( 8' 6" / 17' 9" / 6" )	<b>XCH907K</b> Max. lifting capacity: 9t Max. lifting height: 18.78m No. of stacking: 8 ( 8' 6" / 19' 6" ) <b>XCH1006K</b> Max. lifting capacity: 10t Max. lifting height: 21.19m No. of stacking: 8 ( 8' 6" / 19' 6" )	<b>XCH1007K</b> Max. lifting capacity: 10t Max. lifting height: 18.82m No. of stacking: 7 ( 8' 6" / 19' 6" )	<b>XCH1008K</b> Max. lifting capacity: 10t Max. lifting height: 18.75m No. of stacking: 7 ( 8' 6" / 19' 6" )	<b>XCH1009K</b> Max. lifting capacity: 10t Max. lifting height: 21.19m No. of stacking: 8 ( 8' 6" / 19' 6" )
<b>CONTAINER REACH STACKER</b> <b>XC54531K-6S</b> Max. lifting capacity: 45t Max. lifting height: 16.2m No. of stacking: 6 <b>XC541T</b> Max. lifting capacity: 41t Max. lifting height: 10.85m No. of stacking: 3	<b>XC54531T</b> Max. lifting capacity: 45t Max. lifting height: 9.2m No. of stacking: 3 <b>XC555S</b> Max. lifting capacity: 55t Max. lifting height: 15.1m 								



# CONCRETE MACHINERY

## ● TRUCK-MOUNTED CONCRETE BOOM PUMP

### ● V7 DURABLE SERIES

<b>HB30V</b> Chassis: SINOTRUK Drive Type: 4x2 Vertical Reach: 29.6m Theor. Concrete Output: 100m³/h	<b>HB37V</b> Chassis: SINOTRUK Drive Type: 4x2/8x4 Vertical Reach: 36.5m Theor. Concrete Output: 120m³/h	<b>HB40V</b> Chassis: SINOTRUK Drive Type: 6x4 Vertical Reach: 39.1m Theor. Concrete Output: 120m³/h	<b>HB43V</b> Chassis: SINOTRUK/BENZ Drive Type: 6x4/8x4 Vertical Reach: 42.1m Theor. Concrete Output: 180m³/h	<b>HB47V</b> Chassis: SINOTRUK/BENZ Drive Type: 6x4/8x4 Vertical Reach: 46.1m Theor. Concrete Output: 180m³/h	<b>HB50V</b> Chassis: SINOTRUK/BENZ Drive Type: 6x4/8x4 Vertical Reach: 49.1m Theor. Concrete Output: 180m³/h	<b>HB52V</b> Chassis: SINOTRUK/BENZ Drive Type: 6x4/8x4 Vertical Reach: 51.2m Theor. Concrete Output: 180m³/h	<b>HB58V</b> Chassis: SINOTRUK/BENZ Drive Type: 8x4 Vertical Reach: 57.5m Theor. Concrete Output: 180m³/h
--	--	--	---	---	---	---	---

## ● TRAILER-MOUNTED CONCRETE LINE PUMP

<b>HB62V</b> Chassis: SINOTRUK/BENZ Drive Type: 8x4 Vertical Reach: 61.1m Theor. Concrete Output: 180m³/h	<b>HB69V</b> Chassis: SINOTRUK Drive Type: 10x4 Vertical Reach: 68.1m Theor. Concrete Output: 180m³/h
---	---

<b>HBT5008V</b> Work height: 20.5m Max. Pump Pressure: 8MPa	<b>HBT6013V</b> Theor. Concrete Output: 40/65m³/h Max. Pump Pressure: 8/13MPa	<b>HBT8018VD</b> Theor. Concrete Output: 45/90m³/h Max. Pump Pressure: 9/18MPa	<b>HBT10022V</b> Theor. Concrete Output: 55/100m³/h Max. Pump Pressure: 12/22MPa
---	---	--	--

## ● TRUCK-MOUNTED CONCRETE SPRAYING MACHINE

<b>HPS30VI</b> Chassis: Made by XCMG Drive Type: 4x4 Max. Spraying Height: 17m Theor. Concrete Output: 30m³/h
---

### ● VEHICLE-MOUNTED CONCRETE LINE PUMP

<b>HBC10022V</b> Chassis: SINOTRUK Drive Type: 8x4 Theor. Concrete Output: 55/100m³/h Max. Pump Pressure: 12/22MPa
--

### ● SELF-LOADING CONCRETE MIXER

<b>SLM4V</b> Drive Type: 4x4 Mixing Capacity: 4m³ Discharging Type: Front
--

### ● TRUCK-MOUNTED CONCRETE MIXER

<b>G04V</b> Chassis: XCMG/SINOTRUK Drive Type: 4x2 Agitating Volume: 4m³	<b>G06V</b> Chassis: XCMG/SINOTRUK Drive Type: 4x2/6x4 Agitating Volume: 6m³	<b>G08V</b> Chassis: XCMG/SINOTRUK Drive Type: 6x4 Agitating Volume: 8m³	<b>G10V</b> Chassis: XCMG/SINOTRUK Drive Type: 6x4/8x4 Agitating Volume: 10m³	<b>G12V</b> Chassis: XCMG/SINOTRUK Drive Type: 6x4/8x4 Agitating Volume: 12m³
---	---	---	--	--

## ● CONCRETE BATCHING PLANTS

### ● STANDARD

<b>HZS90V</b> Central Mixer Capacity: 1.5m³ Theor. Continuous Production Rate: 90m³/h	<b>HZS120V</b> Central Mixer Capacity: 2m³ Theor. Continuous Production Rate: 120m³/h
<b>HZS180V</b> Central Mixer Capacity: 3m³ Theor. Continuous Production Rate: 180m³/h	<b>HZS270V</b> Central Mixer Capacity: 4.5m³ Theor. Continuous Production Rate: 270m³/h

### ● PROJECT

<b>HZS60VG</b> Central Mixer Capacity: 1m³ Theor. Continuous Production Rate: 60m³/h	<b>HZS90VG</b> Central Mixer Capacity: 1.5m³ Theor. Continuous Production Rate: 90m³/h	<b>HZS120VG</b> Central Mixer Capacity: 2m³ Theor. Continuous Production Rate: 120m³/h	<b>HZS180VG</b> Central Mixer Capacity: 3m³ Theor. Continuous Production Rate: 180m³/h
--	--	--	--

### ● MOBILE

<b>HZS40VY</b> Central Mixer Capacity: 0.75m³ Theor. Continuous Production Rate: 40m³/h	<b>HZS60VY</b> Central Mixer Capacity: 1m³ Theor. Continuous Production Rate: 60m³/h	<b>HZS75VY</b> Central Mixer Capacity: 1.5m³ Theor. Continuous Production Rate: 75m³/h
---	--	--

## ● CONCRETE PLACING BOOM

<b>HGP28</b> Max. Placing Radius: 28m Max. Freestanding Height: 21m Motor Power: 22kW	<b>HGP32</b> Max. Placing Radius: 32m Max. Freestanding Height: 21m Motor Power: 22kW	<b>HGP38</b> Max. Placing Radius: 37.5m Max. Freestanding Height: 21m Motor Power: 22kW
--	--	--

# SPECIAL VEHICLE

## ● MOBILE ELEVATING WORK PLATFORM

### ● OIL FREE SCISSOR LIFT

<b>XG0807AEW</b> Work height: 7.2m Load capacity: 280/115kg Weight: 1600kg	<b>XG0607DC/XG1330DC</b> Work height: 10.5m Load capacity: 240/100kg Weight: 900kg	<b>XG0608DC/XG1330DC</b> Work height: 10.5m Load capacity: 240/120kg Weight: 1050kg	<b>XG0708DC</b> Work height: 7.2m Load capacity: 240/120kg Weight: 1200kg
---	---	--	--

### ● DC SCISSOR LIFTS

<b>XG1212AC/XG3246AC</b> Work height: 12m Load capacity: 320/115kg Weight: 3000kg	<b>XG1412AC/XG44047AC</b> Work height: 13.8m Load capacity: 320/115kg Weight: 3150kg	<b>XG1614AC/XG4555AC</b> Work height: 15.8m Load capacity: 350/115kg Weight: 3500kg
--	---	--

### ● AC SCISSOR LIFTS

<b>XG1523RT/XG4390RT</b> Work height: 15m Load capacity: 680/230kg Weight: 7250kg	<b>XG1823RT/XG5390RT</b> Work height: 18m Load capacity: 680/230kg Weight: 8000kg
--	--

### ● RT SCISSOR LIFTS

<b>XGA16AC/XGA46J</b> Work height: 16.32m Load capacity: 258kg/115kg/350kg/limited Weight: 7600kg	<b>XGA16AC/XGA45ACJ</b> Work height: 16.5m Load capacity: 258kg/115kg/350kg/limited Weight: 7400kg	<b>XGA18E</b> Work height: 18.01m Load capacity: 450/115kg/350kg/limited Weight: 8700kg
--	---	--

### ● ARTICULATED BOOM LIFTS

<b>XGA16AC/XGA25ACJ</b> Work height: 16m Load capacity: 258kg/115kg/350kg/limited Weight: 8600kg	<b>XGA20E/XGA60J</b> Work height: 20.63m Load capacity: 258kg/115kg/350kg/limited Weight: 9900kg	<b>XGA20AC/XGA60ACJ</b> Work height: 20.5m Load capacity: 258kg/115kg/350kg/limited Weight: 9100kg	<b>XGA22AC</b> Work height: 22.21m Load capacity: 258kg/115kg/350kg/limited Weight: 10100kg	<b>XGA26K/XGA80J</b> Work height: 26.8m Load capacity: 256kg/115kg/350kg/limited Weight: 18100kg
---	---	---	--	---

### ● ARTICULATED BOOM LIFTS

<b>XGS16K/XGS46J</b> Work height: 16m Load capacity: 272kg/115kg/350kg/limited Weight: 8050kg	<b>XGS20K/XGS60J</b> Work height: 20.5m Load capacity: 300kg/115kg/350kg/limited Weight: 8500kg	<b>XGS20AC</b> Work height: 20.5m Load capacity: 300kg/115kg/350kg/limited Weight: 8350kg	<b>XGS22E/XGS65J</b> Work height: 22m Load capacity: 272kg/115kg/350kg/limited Weight: 12460kg	<b>XGS25K</b> Work height: 25m Load capacity: 272kg/115kg/350kg/limited Weight: 12750kg	<b>XGS25AC</b> Work height: 25m Load capacity: 272kg/115kg/350kg/limited Weight: 13500kg	<b>XGS28E/XGS85J</b> Work height: 28.2m Load capacity: 272kg/115kg/350kg/limited Weight: 18300kg	<b>XGS28E1/XGS85J1</b> Work height: 28.2m Load capacity: 272kg/115kg/350kg/limited Weight: 15900kg	<b>XGS28AC</b> Work height: 28.2m Load capacity: 272kg/115kg/350kg/limited Weight: 16600kg	<b>XGS32K</b> Work height: 32.6m Load capacity: 272kg/115kg/350kg/limited Weight: 18500kg	<b>XGS32AC</b> Work height: 32.6m Load capacity: 272kg/115kg/350kg/limited Weight: 17900kg
--	--	--	---	--	---	---	---	---	--	---

### ● FIRE TRUCK

<b>DG100</b> Rated Working Height: 100m Rated load on platform: 400kg	<b>DG88C1</b> Rated Working Height: 88m Rated load on platform: 400kg	<b>DG54K3</b> Rated Working Height: 54m Rated load on platform: 500kg	<b>DG34G1</b> Rated Working Height: 34m Rated load on platform: 500kg	<b>JP62G1</b> Rated Working Height: 62m Rated Capacity: 7500kg
<b>JP35C1</b> Rated Working Height: 35m Container Capacity: 8400kg	<b>JP20G1</b> Rated Working Height: 20m Container Capacity: 2000kg	<b>YT60K1</b> Rated Working Height: 60m Rated load on platform: 270kg	<b>YT53G1</b> Rated Working Height: 53m Rated load on platform: 300kg	<b>YT32G1</b> Rated Working Height: 32m Rated load on platform: 450kg
<b>PM180G1</b> rated reach: ≥ 95m Container Capacity: 18100kg	<b>PM120G2</b> rated reach: ≥ 75m Container Capacity: 12000kg	<b>PM80G2</b> rated reach: ≥ 65m Container Capacity: 7800kg	<b>AP50F5</b> rated reach: ≥ 65m Container Capacity: 4200kg	<b>AP50G1</b> Container load: 4260kg rated reach: ≥ 60m
<b>JY120G1</b> Winch rated tension: 70kN Maximum work range: 8m				

## ● INTELLIGENT EMERGENCY RESCUE PLATFORM

<b>RXR-JM400L</b> Water flow: 80L (±1%) Overall working height: 8.7m Max. gradeability: 45°	<b>RXR-M40L</b> Water flow: 0.8MPa, 40L/s Total dynamic head: 15m Wireless remote control distance: 200m	<b>ET112</b> Max. obstacle clearing capability: 2200mm Max. fording depth: 1800mm Max. walking gradeability: 45° Max. ditch width: 3500mm	<b>ET120</b> Max. obstacle clearing capability: 2400mm Max. fording depth: 2000mm Max. walking gradeability: 45° Max. ditch width: 4000mm
--	---	---	---

# PILING MACHINERY

## ● ROTARY DRILLING RIG

<b>XR60E</b> Power: 42.4 kW Drilling diameter: φ 1000 mm Drilling depth: 15 m Overall working weight: 14 t Torque of rotary drive: 95 kN.m	<b>XR80E</b> Power: 115 kW Drilling diameter: φ 1200 mm Drilling depth: 24 m Overall working weight: 29 t Torque of rotary drive: 82 kN.m	<b>XR130E</b> Power: 169 kW Drilling diameter: φ 1500 mm Drilling depth: 50 m Overall working weight: 43 t Torque of rotary drive: 130 kN.m	<b>XR160E</b> Power: 150 kW Drilling diameter: φ 1500 mm Drilling depth: 56 m Overall working weight: 53 t Torque of rotary drive: 160 kN.m	<b>XR168E</b> Power: 169 kW Drilling diameter: φ 1500 mm Drilling depth: 56 m Overall working weight: 50 t Torque of rotary drive: 168 kN.m	<b>XR200E</b> Power: 212 kW Drilling diameter: φ 1800 mm Drilling depth: 65 m Overall working weight: 70 t Torque of rotary drive: 220 kN.m
<b>XR240E Pro</b> Power: 270 kW Drilling diameter: φ 2200 mm Drilling depth: 80 m Overall working weight: 85 t Torque of rotary drive: 280 kN.m	<b>XR280E</b> Power: 315 kW Drilling diameter: φ 2500 mm Drilling depth: 94 m Overall working weight: 106 t Torque of rotary drive: 300 kN.m	<b>XR330E</b> Power: 315 kW Drilling diameter: φ 2500 mm Drilling depth: 100 m Overall working weight: 110 t Torque of rotary drive: 350 kN.m	<b>XR360E</b> Power: 345 kW Drilling diameter: φ 2600 mm Drilling depth: 103 m Overall working weight: 115 t Torque of rotary drive: 380 kN.m	<b>XR400E</b> Power: 373 kW Drilling diameter: φ 2800 mm Drilling depth: 103 m Overall working weight: 118 t Torque of rotary drive: 400 kN.m	<b>XR420E</b> Power: 389 kW Drilling diameter: φ 2800 mm Drilling depth: 106 m Overall working weight: 136 t Torque of rotary drive: 430 kN.m
<b>XR1600E</b> Power: 1130 kW Drilling diameter: φ 7500 mm Drilling depth: 190 m Overall working weight: 1620 kN.m Torque of rotary drive: 560 kN.m	<b>XR450E</b> Power: 399 kW Drilling diameter: φ 3000 mm Drilling depth: 116 m Overall working weight: 165 t Torque of rotary drive: 450 kN.m	<b>XR460E</b> Power: 447 kW Drilling diameter: φ 3000 mm Drilling depth: 110 m Overall working weight: 142 t Torque of rotary drive: 490 kN.m	<b>XR500E</b> Power: 447 kW Drilling diameter: φ 3500 mm Drilling depth: 126 m Overall working weight: 190 t Torque of rotary drive: 500 kN.m	<b>XR600E</b> Power: 567 kW Drilling diameter: φ 3500 mm Drilling depth: 150 m Overall working weight: 225 t Torque of rotary drive: 600 kN.m	<b>XR700E</b> Power: 567 kW Drilling diameter: φ 3500 mm Drilling depth: 160 m Overall working weight: 240 t Torque of rotary drive: 700 kN.m
<b>XR800E</b> Power: 641 kW Drilling diameter: φ 4600 mm Drilling depth: 150 m Overall working weight: 320 t Torque of rotary drive: 783 kN.m	<b>XR1200E</b> Power: 708 kW Drilling diameter: φ 4600 mm Drilling depth: 150 m Overall working weight: 368 t Torque of rotary drive: 1200 kN.m	<b>XR130ES</b> Power: 121 kW Drilling diameter: φ 1500 mm Drilling depth: 48 m Overall working weight: 38 t Torque of rotary drive: 140 kN.m	<b>XR160ES</b> Power: 169 kW Drilling diameter: φ 1500 mm Drilling depth: 56 m Overall working weight: 53 t Torque of rotary drive: 160 kN.m	<b>XR168ES</b> Power: 169 kW Drilling diameter: φ 1500 mm Drilling depth: 56 m Overall working weight: 50 t Torque of rotary drive: 168 kN.m	<b>XR280ES</b> Power: 270 kW Drilling diameter: φ 2200 mm Drilling depth: 94 m Overall working weight: 100 t Torque of rotary drive: 280 kN.m
<b>XR360ES</b> Power: 336 kW Drilling diameter: φ 2500 mm Drilling depth: 102 m Overall working weight: 105 t Torque of rotary drive: 360 kN.m					

### ● TRENCH CUTTER

<b>XTC100M</b> Power: 567 kW Wall thickness: 800-1500 mm Wall depth: 60 m Max. lifting force: 630 kN Overall working weight: 125 t Torque of cutter wheel: 2 x 100 kN.m	<b>XTC120</b> Power: 571 kW Wall thickness: 800-1800 mm Wall depth: 125 m Max. lifting force: 630 kN Overall working weight: 185 t Torque of cutter wheel: 2 x 120 kN.m	<b>XTC180</b> Power: 571-315 kW Wall thickness: 1000-2000 mm Wall depth: 150 m Max. lifting force: 1200 kN Overall working weight: 205 t Torque of cutter wheel: 2 x 180 kN.m
---	---	---

### ● UNDERGROUND DIAPHRAGM WALL HYDRAULIC GRAB

<b>XG500E</b> Power: 298 kW Wall thickness: 300-1500 mm Wall depth: 75 m Max. lifting force: 500 kN Overall working weight: 105 t	<b>XG65S</b> Power: 315 kW Wall thickness: 300-1500 mm Wall depth: 70 m Max. lifting force: 550 kN Overall working weight: 110 t	<b>XG700E</b> Power: 315 kW Wall thickness: 800-1500 mm Wall depth: 80 m Max. lifting force: 700 kN Overall working weight: 133 t	<b>XG85S</b> Power: 345 kW Wall thickness: 800-1800 mm Wall depth: 80 m Max. lifting force: 750 kN Overall working weight: 135 t
--	---	--	---

## ● CUTTING AND MIXING RIG

<b>XCM40</b> Power: 447 kW Wall thickness: 640-1200 mm Wall depth: 40 m Max. lifting force: 630 kN Overall working weight: 142 t Torque of cutter wheel: 2 x 80 kN.m	<b>XCM80</b> Power: 399 kW Wall thickness: 640-1200 mm Wall depth: 85 m Max. lifting force: 1200 kN Overall working weight: 166 t Torque of cutter wheel: 2 x 100 kN.m
--	--

## ● MULTIFUNCTIONAL HYDRAULIC STATIC PILE DRIVER

<b>XJY280</b> Max. pile driving force: 280 kN Max. circular pile specification: φ 500 mm Max. square pile specification: 500 x 500 mm Total power: 90 kW Max. lifting capacity: 120 kN Overall weight: 94 t	<b>XJY480</b> Max. pile driving force: 480 kN Max. circular pile specification: φ 600 mm Max. square pile specification: 600 x 600 mm Total power: 147 kW Max. lifting capacity: 200 kN Overall weight: 134 t	<b>XJY1080</b> Max. pile driving force: 1080 kN Max. circular pile specification: φ 800 mm Max. square pile specification: 800 x 800 mm Total power: 210 kW Max. lifting capacity: 350 kN Overall weight: 260 t
---	---	---

## ● CASING ROTATOR

<b>XRT1600</b> Drilling diameter: 800-1600 mm Rotation torque: 1525/906/512 kN.m Rotation speed: 1.8/2.7/4 rpm Max. pushing force of casing: 560 kN Pulling force of casing: transient: 2440 kN/2690 kN Engine power: 201 kW/2000 rpm	<b>XRT2100</b> Drilling diameter: 1000-2100 mm Rotation torque: 3091/1831/1034 kN.m Rotation speed: 1.3/2.2/3.6 rpm Max. pushing force of casing: 600 kN Pulling force of casing: transient: 3760 kN/4300 kN Engine power: 285 kW/1900 rpm	<b>XRT2600</b> Drilling diameter: 1500-2600 mm Rotation torque: 5300/3150/1790 kN.m Rotation speed: 0.8/1.3/2.3 rpm Max. pushing force of casing: 630 kN Pulling force of casing: transient: 4600 kN/5200 kN Engine power: 441 kW/1800 rpm	<b>XRT3200</b> Drilling diameter: 2000-3200 mm Rotation torque: 9405/4702/2140 kN.m Rotation speed: 0.7/1.4/2.1 rpm Max. pushing force of casing: 1100 kN Pulling force of casing: transient: 7675 kN/8498 kN Engine power: 410 kW/1900rpm+242 kW/2100 rpm
---	--	--	--

## ● MULTIFUNCTIONAL DRILLING RIG

<b>XMZ120A</b> Engine power: 119 kW Clamping range: 60-415 mm Max. horizontal hole forming height: 4650 mm	<b>XMZ150T</b> Engine power-motor power: 53-90 kW Clamping range: 65-225 mm Max. horizontal hole forming height: 4100 mm	<b>XMZ130T</b> Engine power-motor power: 53-75 kW Clamping range: 65-225 mm Max. horizontal hole forming height: 4100 mm	<b>XMZ200</b> Engine power: 194 kW Clamping range: 60-415 mm Max. horizontal hole forming height: 6000 mm
---	---	---	--

## ● SPIRAL PIPE JACKING MACHINE

<b>XDL500 (DN300)</b> OD x length: φ 450 x 1100 mm Cutting torque: 19.5 kN.m Rotation speed of cutterhead: 14 r/min Mud discharging torque: 4.7 kN.m Mud discharging rotation speed: 50 r/min	<b>XDL500 (DN500)</b> OD x length: φ 700 x 1100 mm Cutting torque: 25.4 kN.m Rotation speed of cutterhead: 10 r/min Mud discharging torque: 6.7 kN.m Mud discharging rotation speed: 37 r/min
--	--

## ● CASING OSCILLATOR

<b>XDC2600</b> Drilling diameter: 2600/2100 mm Max. Rotation torque: 1650 kN.m Clamping force: 630 kN Dimension: 6530 x 3370 x 2050 mm Overall weight: 15 t	<b>XDC3600</b> Drilling diameter: 3600/3100 mm Max. Rotation torque: 3500 kN.m Clamping force: 900 kN Dimension: 8250 x 4600 x 2270 mm Overall weight: 30 t
--	--

## ● TRENCHER

<b>XMT550</b> Engine power: 54 kW Cutting depth: 560 mm Max. cutting width: 152 Traveling speed: 10 km/h Overall weight: 5500 kg
---



# TRENCHLESS MACHINERY

## PIPE JACKING MACHINE

	XDN300H	XDN400H	XDN500H	XDN600H	XDN800H	XDN1000H	XDN1200H	XDN400H-R	XDN500H-R	XDN600H-R	XDN800H-R	XDN1000H-R	XDN1200H-R
Max. torque of cutterhead:	7.5 kN·m	19 kN·m	19 kN·m	22 kN·m	54 kN·m	68 kN·m	195 kN·m	19 kN·m	19 kN·m	22 kN·m	80 kN·m	133 kN·m	220 kN·m
Cutterhead power:	18.5 kW	30 kW	30 kW	30 kW	45 kW	45 kW	45 kW	30 kW	30 kW	30 kW	45 kW	45 kW	45 kW
Rotation speed of cutterhead:	13 r/min	7 r/min	7 r/min	6 r/min	4.7 r/min	3.7 r/min	6 r/min	15 r/min	15 r/min	14 r/min	14 r/min	8 r/min	5.2 r/min
OD x length:	φ 435 x 2500 mm	φ 560 x 2530 mm	φ 695 x 2400 mm	φ 795 x 2410 mm	φ 960 x 3010 mm	φ 1220 x 3025 mm	φ 1470 x 3570 mm	φ 560 x 2640 mm	φ 695 x 2530 mm	φ 795 x 2590 mm	φ 980 x 3160 mm	φ 1220 x 3150 mm	φ 1470 x 3570 mm
Weight:	1.3 t	1.7 t	2.1 t	2.5 t	4.2 t	5.5 t	9 t	2 t	2.5 t	2.8 t	4.5 t	6 t	9.5 t

	XDN800-S	XDN1000-S	XDN1200-S	XDN1350-S	XDN1500-S	XDN1650-S	XDN1800-S	XDN2000-S	XDN2200-S	XDN2400-S	XDN2600-S	XDN2800-S	XDN3000-S	XDN3200-S
Max. torque of cutterhead:	50 kN·m	50 kN·m	188 kN·m	188 kN·m	275 kN·m	275 kN·m	412 kN·m	412 kN·m	698 kN·m	698 kN·m	872 kN·m	872 kN·m	1429 kN·m	1429 kN·m
Cutterhead power:	30 x 8 kW	30 x 1 kW	22 x 2 kW	22 x 2 kW	30 x 2 kW	30 x 2 kW	30 x 3 kW	30 x 3 kW	30 x 4 kW	30 x 4 kW	30 x 5 kW	30 x 5 kW	30 x 6 kW	30 x 6 kW
Rotation speed of cutterhead:	5.7 r/min	5.7 r/min	4.4 r/min	4.4 r/min	4.2 r/min	4.2 r/min	4.2 r/min	4.2 r/min	3.3 r/min	3.3 r/min	3.3 r/min	3.3 r/min	2.4 r/min	2.4 r/min
OD x length:	φ 980 x 3000 mm	φ 1220 x 3000 mm	φ 1460 x 3900 mm	φ 1640 x 3900 mm	φ 1820 x 4500 mm	φ 2000 x 4500 mm	φ 2180 x 4500 mm	φ 2420 x 4500 mm	φ 2670 x 4700 mm	φ 2910 x 4700 mm	φ 3100 x 4700 mm	φ 3380 x 4700 mm	φ 3630 x 5350 mm	φ 3380 x 5350 mm
Weight:	5 t	6 t	10 t	10 t	14 t	16 t	22 t	22 t	28 t	31 t	34 t	42 t	60 t	60 t

	XDN3500-S	XDN4000-S	XDN1200-R	XDN1350-R	XDN1500-R	XDN1650-R	XDN1800-R	XDN2000-R	XDN2200-R	XDN2400-R	XDN2600-R	XDN2800-R	XDN3000-R	XDN3200-R
Max. torque of cutterhead:	1905 kN·m	1905 kN·m	188 kN·m	188 kN·m	294 kN·m	294 kN·m	441 kN·m	441 kN·m	588 kN·m	588 kN·m	746 kN·m	746 kN·m	1199 kN·m	1199 kN·m
Cutterhead power:	30 x 8 kW	30 x 8 kW	22 x 2 kW	22 x 2 kW	37 x 2 kW	37 x 2 kW	37 x 3 kW	37 x 3 kW	37 x 4 kW	37 x 4 kW	37 x 5 kW	37 x 5 kW	30 x 6 kW	30 x 6 kW
Rotation speed of cutterhead:	2.4 r/min	2.4 r/min	4.4 r/min	4.4 r/min	4.8 r/min	4.8 r/min	4.8 r/min	4.8 r/min	3.8 r/min	3.8 r/min	3.8 r/min	3.8 r/min	2.4 r/min	2.4 r/min
OD x length:	φ 4140 x 5500 mm	φ 4840 x 5500 mm	φ 1470 x 4670 mm	φ 1650 x 4670 mm	φ 1830 x 5135 mm	φ 2010 x 5135 mm	φ 2190 x 5135 mm	φ 2430 x 5135 mm	φ 2680 x 5500 mm	φ 2920 x 5500 mm	φ 3110 x 5500 mm	φ 3390 x 5500 mm	φ 3630 x 5900 mm	φ 3630 x 5900 mm
Weight:	72 t	88 t	14 t	15 t	20.5 t	22.5 t	25 t	30 t	40 t	46 t	49 t	53 t	65 t	85 t

## HORIZONTAL DIRECTIONAL DRILLING RIG

	XZ120E	XZ150E	XZ200	XZ2055	XZ4055	XZ230E	XZ280E	XZ320D
Rated power:	81 kW	81 kW	113 kW	113 kW	115 kW	113 kW	133 kW	154 kW
Max. push-pull force:	130 kN	165 kN	225 kN	225 kN	200 kN	220/270 kN	260/320 kN	320 kN
Rotation torque:	3000 N·m	3000 N·m	3500 N·m	3500 N·m	3000 N·m	3500 N·m	3000 N·m	3200 N·m
Overall weight:	5 t	5.1 t	8.5 t	8.5 t	10.3 t	9 t	9.5 t	10 t
Dimension:	4500 x 1850 x 2170 mm	5900 x 1850 x 2100 mm	5900 x 2250 x 2400 mm	5700 x 1430 x 1900 mm	6200 x 2240 x 2600 mm	6100 x 2230 x 2300 mm	6100 x 2250 x 2300 mm	6500 x 2250 x 2450 mm

	XZ320E	XZ360E	XZ430E	XZ450P	XZ520E	XZ720E	XZ1000E	XZ1350E	XZ1800E	XZ2600E
Rated power:	154 kW	154 kW	179 kW	194 kW	194 kW	220 kW	264 kW	268 kW	294 kW	264 kW
Max. push-pull force:	345 kN	370 kN	450/520 kN	450/500 kN	530/1000 kN	730/1000 kN	1000/1350 kN	1700 kN	1850 kN	2600 kN
Rotation torque:	12600 N·m	13200 N·m	16500 N·m	16500 N·m	27000 N·m	35000 N·m	48000 N·m	50000 N·m	50000 N·m	60000 N·m
Overall weight:	10 t	10.5 t	15 t	15 t	15 t	15 t	25 t	25 t	26 t	35 t
Dimension:	6200 x 2280 x 2450 mm	6200 x 2280 x 2450 mm	6500 x 2250 x 2450 mm	6500 x 2280 x 2610 mm	9000 x 2280 x 2640 mm	9150 x 2450 x 2600 mm	11880 x 2710 x 3300 mm	11700 x 2760 x 3550 mm	11700 x 2760 x 3550 mm	13700 x 3230 x 3450 mm

	XZ3600	XZ4200	XZ5060	XZ6600	XZ11000	XZ13600
Rated power:	2 x 264 kW	2 x 298 kW	2 x 354 kW	2 x 565 kW	3 x 410 kW	4 x 410 kW
Max. push-pull force:	3600 kN	4200 kN	5000 kN	6600 kN	11000 kN	13600 kN
Rotation torque:	120000 N·m	140000 N·m	160000 N·m	210000 N·m	240000 N·m	360000 N·m
Overall weight:	48 t	52 t	59 t	81 t	81 t	135 t
Dimension:	17500 x 3200 x 3550 mm	17500 x 3200 x 3550 mm	20000 x 3400 x 3770 mm	19000 x 3200 x 3900 mm	20400 x 3200 x 3600 mm	20000 x 3400 x 4700 mm

# COAL MINING MACHINERY

## EBZ SERIES ROADHEADER

	EBZ75	EBZ135L	EBZ160	EBZ160E	EBZ160L	EBZ200A	EBZ200E
Dimension (L x W x H):	8700 x 2300 x 1700 mm	8932 x 2800 x 1668 mm	9460 x 2900 x 1740 mm	9460 x 2900 x 1740 mm	9460 x 2900 x 1740 mm	10440 x 3200 x 2265 mm	10700 x 3200 x 2200 mm
Cutting range (H x W):	4200 x 2300 mm	4000 x 2300 mm	4800 x 2300 mm	4800 x 2300 mm	4800 x 2300 mm	5037 x 6222 mm	4700 x 5700 mm
Power of cutting motor:	75 kW	135 kW	160/100 kW	160/100 kW	160/100 kW	200/110 kW	200/110 kW
Carrying capacity: star wheel/4.3 m <sup>3</sup> /min	31 t	42 t	49 t	49 t	45 t	58 t	58 t
Overall weight:	21 t	21 t	21 t	21 t	21 t	25 t	25 t

	EBZ2200L	EBZ2200R	EBZ2230	EBZ260	EBZ2600	EBZ2600L	EBZ2600R	EBZ320	EBZ320L
Dimension (L x W x H):	10440 x 3200 x 1600 mm	11470 x 3200 x 2345 mm	11470 x 3200 x 2345 mm	11677 x 3900 x 2650 mm	12200 x 2300 x 2250 mm	11700 x 3200 x 2200 mm	11700 x 3200 x 2200 mm	13000 x 3800 x 2885 mm	13000 x 3800 x 2800 mm
Cutting range (H x W):	4570 x 5670 mm	4800 x 6040 mm	4800 x 6040 mm	5630 x 5950 mm	4520 x 4970 mm	5000 x 6000 mm	5000 x 6000 mm	5700 x 7100 mm	5200 x 6200 mm
Power of cutting motor:	200 kW	200/150 kW	230/150 kW	280/200 kW	280/200 kW	280 kW	280 kW	320/240 kW	320/240 kW
Carrying capacity: star wheel/4.3 m <sup>3</sup> /min	63 t	81 t	81 t	81 t	81 t	81 t	81 t	120 t	120 t
Overall weight:	53 t	51 t	51 t	51 t	51 t	51 t	51 t	51 t	51 t

	EBZ200M-2H	EBZ200M-2L	EBZ230M-2H	EBZ230M-4H	EBZ260M-2H	EBZ260M-4H
Height of positioning cutting:	2900-4700 mm	3100-4570 mm	3100-5000 mm	3100-5000 mm	3500-5150 mm	3500-5150 mm
Width of positioning cutting:	3800-5700 mm	3800-5700 mm	3600-6200 mm	3600-6200 mm	4000-6000 mm	4000-6000 mm
Power of cutting motor:	200/110 kW	200/110 kW	230/160 kW	230/160 kW	260/200 kW	260/200 kW
Number of drilling rigs:	2	2	2	2	2	2
Suitable roadway width:	3200-4800 mm	3200-4800 mm	3100-5000 mm	3100-5000 mm	3500-5000 mm	3500-5000 mm
Suitable roadway height:	3200-5700 mm	3200-5700 mm	3600-6500 mm	3600-6500 mm	4000-6500 mm	4000-6500 mm

## XTR SERIES TUNNEL ROADHEADER

	XTR4/160	XTR4/230	XTR4/260	XTR6/260	XTR6/280	XTR6/320	XTR7/360A	XTR6/500
Dimension (L x W x H):	11970 x 1900 x 2030 mm	13470 x 2200 x 2200 mm	13470 x 2200 x 2250 mm	15590 x 3200 x 3380 mm	15590 x 3200 x 3518 mm	16500 x 3800 x 3650 mm	17600 x 3000 x 3700 mm	18900 x 5400 x 4270 mm
Cutting range (H x W):	4200 x 1600 mm	4600 x 2300 mm	4600 x 2300 mm	6200 x 4800 mm	6200 x 4800 mm	6600 x 7900 mm	7450 x 8000 mm	8510 x 9400 mm
Power of cutting motor:	200 kW	230/150 kW	230/150 kW	280/200 kW	280/200 kW	320/240 kW	360/280 kW	500 kW (frequency conversion)
Carrying capacity: star wheel/3.0 m <sup>3</sup> /min	49 t	61 t	61 t	81 t	81 t	81 t	81 t	110 t
Overall weight:	49 t	61 t	61 t	81 t	81 t	81 t	81 t	110 t

## DEEP ( WATER ) WELL DRILLING RIG ( ENERGY EXPLORATION MACHINERY )

	XSL3/160A	XSL5/280A	XSL7/360A	XSL10/520	XSL12/600	XSL15/680	XSL20/1000
Drilling depth:	300 m (φ 89 mm)	500 m (φ 89 mm)	700 m (φ 102 mm)	1000 m (φ 102 mm)	1200 m (φ 102 mm)	1500 m (φ 114 mm)	2000 m (φ 114 mm)
Max. diameter of working floor:	φ 330 mm	φ 400 mm	φ 500 mm	φ 500 mm	φ 500 mm	φ 500 mm	φ 610 mm
Max. lifting force:	200 kN	280 kN	360 kN	520 kN	520 kN	540 kN	610 kN
Max. torque of top drive:	8300 N·m	9200 N·m	15000 N·m	21000 N·m	21000 N·m	20000 N·m	31500 N·m
Overall weight:	9 t	12 t	13.7 t	17.6 t	17.6 t	22 t	47.5 t

## CORE DRILL

	XDY1000	XDY1500	XDY2000
Max. drilling depth (BO):	1000 m	1500 m	2000 m
Max. reaming diameter:	4000 mm	5200 mm	5600 mm
Max. rotation speed of power head:	1250 r/min	1250 r/min	1250 r/min
Max. pulling force of main winch:	68 kN	48 kN	48 kN
Max. pulling speed of main winch:	60 m/min	48 m/min	35/60 m/min

# UNDERGROUND MINING MACHINERY

## EXCAVATION DRILLING RIG

	XUD125	XUD135	XUD235
Coverage area:	5000 x 5000 mm	6600 x 6630 mm	9052 x 6775 mm
Borehole diameter:	45-102 mm/333-64 mm	45-102 mm/333-64 mm	45-102 mm
Weight:	10 t	21 t	21 t

## RAISE BORING MACHINE

	XUR5000
Max. reaming diameter:	5 m
Max. reaming torque:	90°
Max. lifting force:	4500 kN

## MINING LONGHOLE DRILL JUMBO

	XUM135
Coverage area:	7500 x 5000 mm
Borehole diameter:	61-102 mm
Weight:	17.5 t

## BOLT SUPPORT DRILL RIG

	XUB135
Coverage area:	8800 x 7100 mm
Borehole diameter:	32-51 mm
Weight:	13.7 t

## TUNNEL DRILL JUMBO

	XTD275	XTD295	XTD3130	XTD3133C
Suitable section:	4 x 4m-11.2 x 7.6 m	4 x 4m-13.5 x 9.2 m	5 x 5m-15.7 x 13 m	5 x 5m-17.4 x 13.3 m
Dimension:	14.2 x 2.4 x 2.5 m	16 x 2.5 x 2.5 m	16 x 2.95 x 3.4 m	17.5 x 2.9 x 3.6 m
Engine power:	103 kW	119 kW	200 kW	191 kW
Overall weight:	25 t	35 t	47.5 t	53.5 t

## TUNNEL BOLTING RIG

	XTB180	XTB1140C	XTB194
Suitable section:	6 x 6m-14 x 11 m	5 x 5m-19 x 14 m	5.9 x 5.9m-13.2 x 9.4 m
Dimension:	18.7 x 2.4 x 3.26 m	19.3 x 2.5 x 3.1 m	12.2 x 2.1 x 3.1 m
Engine power:	111 kW	145 kW	60 kW
Overall weight:	29.5 t	32 t	13.6 t

## DOWN-THE-HOLE DRILL RIG





# XCMG BRIEFING

Founded in 1943, XCMG is the largest enterprise in the Chinese construction machinery industry. We offer the most diverse product line and the highest technological standards. We provide a comprehensive set of construction solutions, and we are the most internationally competitive firm in the industry. On KHL Yellow Table, we rank No. 1 in China and No.3 globally.

Across our offices in China, the US, Germany, India, and Brazil, XCMG has established a global collaborative research platform including national-level R&D facilities focused on advanced smart manufacturing technology. Our R&D team consists of top talents from around the globe. They are researching cutting-edge technologies such as new energy, unmanned driving and high-end parts. Our work has earned us numerous international patents and awards.

XCMG has the most comprehensive product line, meaning we can offer fully comprehensive solutions in 12 areas: hoisting, earthwork, road building & maintenance, mining, concrete & paving, tunnel-building & underground construction, high-altitude firefighting equipment & special-purpose vehicles, railway & bridge construction, sanitation engineering, agricultural machinery, powered industrial trucks, Port Machinery. All these solutions can be customized to suit our customers' needs.

At XCMG, our five-continent sales network gives our products worldwide visibility. We have 330 overseas distributors, over 10 overseas manufacturing bases and KD factories, and products in more than 190 countries and regions. We supply our global customers with pre-sales, mid-sales and after-sales service, and a convenient, efficient one-stop financing and leasing service. XCMG's total annual exports and overseas income consistently come top of the industry in China.

We care deeply for the welfare of the people. We support numerous charitable causes, and are quick to the scene during disaster relief efforts.

XCMG is all set to become an eternal brand with our feet on the ground and eyes on the horizon. XCMG's ambition leads us forever forwards. XCMG is scaling its Everest, and is determined to reach the top.

## XCMG FOR YOUR SUCCESS



## XUZHOU CITY JIANGSU PROVINCE, CHINA

