



TM

India's First
Solar Ceiling Fan Manufacturer



BLDC CEILING FAN

- Solar Compatible ▶
- Power Saver ▶
- Remote Controlled ▶
- Long Life ▶



9625350897
9899991715



Sector-1, M-254, Bawana Industrial
Area, Delhi-110039

Order Now



TM

3 BLADE



**BLDC CEILING
FAN**



MODEL :
ABS HIGH



**SAVE UPTO
₹1800 / YEAR**

- RF Remote
- Forward & Reverse
- Over/Under Voltage Protection
- Output Power Limit Protection
- Blade Blocking Protection
- Phase Loss Protection

**LED
92 TRI
COLOUR**



**LED
9 WATT**



60% TO 70%

ENERGY SAVING
TECHNOLOGY



EXCELLENT 220
CMM AIR DELIVERY



HI-SPEED
380 RPM



DYNAMICALLY
BALANCED



ECO
FRIENDLY



LOW
NOISE



SPEED
BOOST

TECHNICAL SPECIFICATION

Rated Power	25 W
Max. Power	40 W
Standby power	≤ 0.5 W
Input voltage range	90-305Vac
Operating temperature range	20~55 C
PF	> 0.99 (@32W)
THD	<5% (@32W)
Surge Voltage	4.5 KV
Power Saving	60% to 70%
LED	9 Watt



TM

3 BLADE**BLDC CEILING
FAN****SAVE UPTO
₹1800 / YEAR****MODEL :
ABS NEW**

- RF Remote
- Forward & Reverse
- Over/Under Voltage Protection
- Output Power Limit Protection
- Blade Blocking Protection
- Phase Loss Protection

**ENERGY SAVING
TECHNOLOGY****EXCELLENT 220
CMM AIR DELIVERY****HI-SPEED
320 RPM****DYNAMICALLY
BALANCED****ECO
FRIENDLY****LOW
NOISE****SPEED
BOOST****TECHNICAL SPECIFICATION**

Rated Power	25 W
Max. Power	40 W
Standby power	≤ 0.5 W
Input voltage range	90-305Vac
Operating temperature range	20~55 C
PF	> 0.99 (@32W)
THD	<5% (@32W)
Surge Voltage	4.5 KV
Power Saving	60% to 70%



TM

6 BLADE**BLDC CEILING
FAN****SAVE UPTO
₹1800 / YEAR****MODEL :
71****LED
92 TRI
COLOUR****LED
9 WATT**

- RF Remote
- Forward & Reverse
- Over/Under Voltage Protection
- Output Power Limit Protection
- Blade Blocking Protection
- Phase Loss Protection

60% TO 70%
ENERGY SAVING
TECHNOLOGY

EXCELLENT 220
CMM AIR DELIVERY

HI-SPEED
350 RPM

DYNAMICALLY
BALANCED

ECO
FRIENDLY

LOW
NOISE

SPEED
BOOST

TECHNICAL SPECIFICATION

Rated Power	25 W
Max. Power	40 W
Standby power	≤ 0.5 W
Input voltage range	90-305Vac
Operating temperature range	20~55 C
PF	> 0.99 (@32W)
THD	<5% (@32W)
Surge Voltage	4.5 KV
Power Saving	60% to 70%
LED	9 Watt



TM

3 BLADE**BLDC CEILING
FAN****SAVE UPTO
₹1800 / YEAR****MODEL :
72****7
LED**

- RF Remote
- Forward & Reverse
- Over/Under Voltage Protection
- Output Power Limit Protection
- Blade Blocking Protection
- Phase Loss Protection

**ENERGY SAVING
TECHNOLOGY****EXCELLENT 220
CMM AIR DELIVERY****HI-SPEED
380 RPM****DYNAMICALLY
BALANCED****ECO
FRIENDLY****LOW
NOISE****SPEED
BOOST****TECHNICAL SPECIFICATION**

Rated Power	25 W
Max. Power	35 W
Standby power	≤ 0.5 W
Input voltage range	90-305Vac
Operating temperature range	20~55 C
PF	> 0.99 (@32W)
THD	<5% (@32W)
Surge Voltage	4.5 KV
Power Saving	60% to 70%
LED	7



TM

3 **BLADE**
WOODEN
COLOUR

**BLDC CEILING
FAN**



**SAVE UPTO
₹1800 / YEAR**

**MODEL :
72**



- RF Remote
- Forward & Reverse
- Over/Under Voltage Protection
- Output Power Limit Protection
- Blade Blocking Protection
- Phase Loss Protection

**LED
92 TRI
COLOUR**



**LED
9 WATT**



60% TO 70%
ENERGY SAVING
TECHNOLOGY

EXCELLENT 220
CMM AIR DELIVERY

HI-SPEED
380 RPM

DYNAMICALLY
BALANCED

ECO
FRIENDLY

LOW
NOISE

SPEED
BOOST

TECHNICAL SPECIFICATION

Rated Power	25 W
Max. Power	40 W
Standby power	≤ 0.5 W
Input voltage range	90-305Vac
Operating temperature range	20~55 C
PF	> 0.99 (@32W)
THD	<5% (@32W)
Surge Voltage	4.5 KV
Power Saving	60% to 70%
LED	9 Watt



TM

3 BLADE**BLDC CEILING
FAN****SAVE UPTO
₹1800 / YEAR****MODEL :
84**

- RF Remote
- Forward & Reverse
- Over/Under Voltage Protection
- Output Power Limit Protection
- Blade Blocking Protection
- Phase Loss Protection

60% TO 70%**ENERGY SAVING
TECHNOLOGY****EXCELLENT 220
CMM AIR DELIVERY****HI-SPEED
380 RPM****DYNAMICALLY
BALANCED****ECO
FRIENDLY****LOW
NOISE****SPEED
BOOST****TECHNICAL SPECIFICATION**

Rated Power	25 W
Max. Power	35 W
Standby power	≤ 0.5 W
Input voltage range	90-305Vac
Operating temperature range	20~55 C
PF	> 0.99 (@32W)
THD	<5% (@32W)
Surge Voltage	4.5 KV
Power Saving	60% to 70%



TM

3 BLADE

BLDC CEILING FAN



**SAVE UPTO
₹1800 / YEAR**



**MODEL :
73**

- RF Remote
- Forward & Reverse
- Over/Under Voltage Protection
- Output Power Limit Protection
- Blade Blocking Protection
- Phase Loss Protection

60% TO 70%

ENERGY SAVING
TECHNOLOGY



EXCELLENT 220
CMM AIR DELIVERY



HI-SPEED
380 RPM



DYNAMICALLY
BALANCED



ECO
FRIENDLY



LOW
NOISE



SPEED
BOOST

TECHNICAL SPECIFICATION

Rated Power	25 W
Max. Power	35 W
Standby power	≤ 0.5 W
Input voltage range	90-305Vac
Operating temperature range	20~55 C
PF	> 0.99 (@32W)
THD	<5% (@32W)
Surge Voltage	4.5 KV
Power Saving	60% to 70%



TM

3 BLADE**BLDC CEILING
FAN****MODEL :
79****SAVE UPTO
₹1800 / YEAR**

- RF Remote
- Forward & Reverse
- Over/Under Voltage Protection
- Output Power Limit Protection
- Blade Blocking Protection
- Phase Loss Protection

60% TO 70%**ENERGY SAVING
TECHNOLOGY****EXCELLENT 220
CMM AIR DELIVERY****HI-SPEED
380 RPM****DYNAMICALLY
BALANCED****ECO
FRIENDLY****LOW
NOISE****SPEED
BOOST****TECHNICAL SPECIFICATION**

Rated Power	25 W
Max. Power	35 W
Standby power	≤ 0.5 W
Input voltage range	90-305Vac
Operating temperature range	20~55 C
PF	> 0.99 (@32W)
THD	<5% (@32W)
Surge Voltage	4.5 KV
Power Saving	60% to 70%